#### MICROPROCESSOR BASED SYSTEM DESIGN LAB

### Lab #04



# Spring 2021 CSE307L MBSD Lab

Submitted by: Shah Raza

Registration No.: 18PWCSE1658

Class Section: **B** 

"On my honor, as student of University of Engineering and Technology, I have neither given nor received unauthorized assistance on this academic work."

S	tudent	Signature:	
v	tuucnt	Dizmature.	

Submitted to:

Engr. Amaad Khalil

Saturday, May 29, 2021

Department of Computer Systems Engineering
University of Engineering and Technology, Peshawar

# Task 1:

Interface Push buttons to 8051 microcontroller and blink even and odd LEDs using input buttons.

# **Code:**

ORG 0000H

MOV P2,#00H

Start:

JB P2.0,Even

Check:

JB P2.1,Odd

SJMP Start

#### Even:

**CLR P2.1** 

MOV R1,#0AAH

MOV P1,R1

SJMP Check

## Odd:

**CLR P2.0** 

MOV R2,#55H


MOV P1,R2

SJMP Start


END

# **Output / Graphs / Plots / Results:**

Pressing the button at P2.0:



# Pressing the button at P2.1:



# Task 2:

Interface Push buttons to 8051 microcontroller and display up counting and down counting using seven segment display using input buttons.

## **Code:**

ORG 0

MOV P2,#00H START: JB P2.0,UP JB P2.1,DOWN

SJMP START

#### UP:

MOV R1,#3FH ACALL DISPLAY

MOV R1,#06H ACALL DISPLAY

MOV R1,#5BH ACALL DISPLAY

MOV R1,#4FH ACALL DISPLAY

MOV R1,#66H ACALL DISPLAY

MOV R1,#6DH ACALL DISPLAY

MOV R1,#7DH ACALL DISPLAY

MOV R1,#07H ACALL DISPLAY

MOV R1,#7FH ACALL DISPLAY

MOV R1,#6FH ACALL DISPLAY

SJMP START

DOWN:

MOV R1,#6FH ACALL DISPLAY

MOV R1,#7FH ACALL DISPLAY

MOV R1,#07H ACALL DISPLAY

MOV R1,#7DH ACALL DISPLAY

MOV R1,#6DH ACALL DISPLAY

MOV R1,#66H ACALL DISPLAY

MOV R1,#4FH ACALL DISPLAY

MOV R1,#5BH ACALL DISPLAY

MOV R1,#06H ACALL DISPLAY

MOV R1,#3FH ACALL DISPLAY

SJMP START

DISPLAY:

MOV P1,R1 ACALL DELAY RET

DELAY:

MOV R2,#255

AGAIN:

MOV R3,#255


HERE:

NOP

NOP DJNZ R3,HERE DJNZ R2,AGAIN RET

# **END**

# Output / Graphs / Plots / Results: Upcounting(Pressing button at P2.0):



# Downcounting(Pressing button at P2.1):

