Create database Info

Choose a database creation method

- Standard create — You set all of the configuration options, including ones for availability, security, backups, and maintenance.
- Easy create — Use recommended best-practice configurations. Some configuration options can be changed after the database is created.

Engine options

Engine type Info

- Aurora (MySQL Compatible)
- Aurora (PostgreSQL Compatible)
- MySQL
- MariaDB
- PostgreSQL
- Oracle
- Microsoft SQL Server
- IBM Db2

Engine version Info
View the engine versions that support the following database features.

Hide filters

Show only versions that support the Multi-AZ DB cluster Info
Create a Multi-AZ DB cluster with one primary DB instance and two readable standby DB instances. Multi-AZ DB clusters provide up to 2x faster transaction commit latency and automatic failover in typically under 35 seconds.

Engine version

PostgreSQL 13.16-R1

Enable RDS Extended Support Info
Amazon RDS Extended Support is a paid offering. By selecting this option, you consent to being charged for this offering if you are running your database version past the end of the standard support date for that version. Check the end of standard support date for your major version in the RDS for PostgreSQL documentation

Templates

Choose a sample template to meet your use case.

- Production — Use defaults for high availability and fast, consistent performance.
- Dev/Test — This instance is intended for development use outside of a production environment.
- Free tier — Use RDS Free Tier to develop new applications, test existing applications, or gain hands-on experience with Amazon RDS. Info

Availability and durability

Deployment options Info
The deployment options below are limited to those supported by the engine you selected above.

- Multi-AZ DB Cluster — Creates a DB cluster with a primary DB instance and two readable standby DB instances, with each DB instance in a different Availability Zone (AZ). Provides high availability, data redundancy and increases capacity to serve read workloads.
- Multi-AZ DB instance (not supported for Multi-AZ DB cluster snapshot) — Creates a primary DB instance and a standby DB instance in a different AZ. Provides high availability and data redundancy, but the standby DB instance doesn't support connections for read workloads.
- Single DB instance (not supported for Multi-AZ DB cluster snapshot) — Creates a single DB instance with no standby DB instances.

Settings

DB instance identifier Info
Type a name for your DB instance. The name must be unique across all DB instances owned by your AWS account in the current AWS Region.

PostgreSQL-13-6-R1-Prayer-Server

The DB instance identifier is case-insensitive, but is stored as all lowercase (as in "mydbinstance"). Constraints: 1 to 60 alphanumeric characters or hyphens. First character must be a letter. Can't contain two consecutive hyphens. Can't end with a hyphen.

Credentials Settings

Master username Info
Type a login ID for the master user of your DB instance.

postgres

1 to 16 alphanumeric characters. The first character must be a letter.

Credentials management
You can use AWS Secrets Manager or manage your master user credentials.

- Managed in AWS Secrets Manager - most secure — RDS generates a password and manages it in Secrets Manager throughout its lifecycle using AWS Secrets Manager.
- Self managed — Enter your own password or have RDS create a password that you manage.

Auto generate password
Amazon RDS can generate a password for you, or you can specify your own password.

Master password Info

Password strength Very strong

Minimum constraints: At least 8 printable ASCII characters. Can't contain any of the following symbols: / ' " @

Confirm master password Info

Instance configuration

The DB instance configuration options below are limited to those supported by the engine that you selected above.

DB instance class Info

Hide filters

Include previous generation classes

- Standard classes (includes m classes)
- Memory optimized classes (includes r and x classes)
- Burstable classes (includes t classes)

db.t3.micro
2 vCPUs 1 GiB RAM Network: Up to 2,085 Mbps

Storage

Storage type Info
Provisioned IOPS SSD (io2) storage volumes are now available.

General Purpose SSD (gp3)
Performance scales independently from storage

Allocated storage 20 GiB
Minimum: 20 GiB. Maximum: 6,144 GiB

After you modify the storage for a DB instance, the status of the DB instance will be in storage-optimization. Your instance will remain available as the storage-optimization operation completes. Learn more

Advanced settings
Baseline IOPS of 3,000 IOPS and storage throughput of 125 MiBps are included for allocated storage less than 400 GiB.

To provision additional IOPS and throughput, increase the allocated storage to 400 GiB or greater.

Provisioned IOPS Info
3000 IOPS

Storage throughput Info
125 MiBps

Storage autoscaling

Storage autoscaling Info
Provides dynamic scaling support for your database's storage based on your application's needs.

Enable storage autoscaling
Enabling this feature will allow the storage to increase after the specified threshold is exceeded.

Connectivity Info

Compute resource
Choose whether to set up a connection to a compute resource for this database. Setting up a connection will automatically change connectivity settings so that the compute resource can connect to this database.

- Don't connect to an EC2 compute resource — Don't set up a connection to a compute resource for this database. You can manually set up a connection to a compute resource later.
- Connect to an EC2 compute resource — Set up a connection to an EC2 compute resource for this database.

Network type Info
To use dual-stack mode, make sure that you associate an IPv6 CIDR block with a subnet in the VPC you specify.

- IPv4 — Your resources can communicate only over the IPv4 addressing protocol.
- Dual-stack mode — Your resources can communicate over IPv4, IPv6, or both.

Virtual private cloud (VPC) Info
Choose the VPC. The VPC defines the virtual networking environment for this DB instance.

Default VPC (vpc-0b05018b3f56502ee)
6 Subnets, 6 Availability Zones

Only VPCs with a corresponding DB subnet group are listed.

After a database is created, you can't change its VPC.

DB subnet group Info
Choose the DB subnet group. The DB subnet group defines which subnets and IP ranges the DB instance can use in the VPC that you selected.

default-vpc-0b05018b3f56502ee
6 Subnets, 6 Availability Zones

Public access Info

- Yes — RDS assigns a public IP address to the database. Amazon EC2 instances and other resources outside of the VPC can connect to your database. Resources inside the VPC can also connect to the database. Choose one or more VPC security groups that specify which resources can connect to the database.
- No — RDS doesn't assign a public IP address to the database. Only Amazon EC2 instances and other resources inside the VPC can connect to your database. Choose one or more VPC security groups that specify which resources can connect to the database.

VPC security group (firewall) Info
Choose one or more VPC security groups to allow access to your database. Make sure that the security group rules allow the appropriate incoming traffic.

- Choose existing — Choose existing VPC security groups
- Create new — Create new VPC security group

Existing VPC security groups

Choose one or more options

postgres-SG default

Availability Zone Info

No preference

RDS Proxy
RDS Proxy is a fully managed, highly available database proxy that improves application scalability, resiliency, and security.

Create an RDS Proxy Info
RDS automatically creates an IAM role and a Secrets Manager secret for the proxy. RDS Proxy has additional costs. For more information, see Amazon RDS Proxy pricing

Certificate authority - optional Info
Using a server certificate provides an extra layer of security by validating that the connection is being made to an Amazon database. It does so by checking the server certificate that is automatically installed on all databases that you provision.

rds-ca-rsa2048-g1 (default)
Expiry: May 26, 2061

If you don't select a certificate authority, RDS chooses one for you.

Additional configuration

Database port Info
TCP/IP port that the database will use for application connections.

5432

Tags - optional

A tag consists of a case-sensitive key-value pair.

No tags associated with the resource.

Add new tag
You can add up to 50 more tags.

Database authentication

Database authentication options Info

- Password authentication — Authenticates using database passwords.
- Password and IAM database authentication — Authenticates using the database password and user credentials through AWS IAM users and roles.
- Password and Kerberos authentication — Choose a directory in which you want to allow authorized users to authenticate with this DB instance using Kerberos Authentication.

Monitoring

Turn on Performance Insights

Additional configuration
Enhanced Monitoring

Additional configuration

Database options, encryption turned off, backup turned off, backtrack turned off, maintenance, CloudWatch Logs, delete protection turned off.

Database options

Initial database name Info

PrayerAppDB

If you do not specify a database name, Amazon RDS does not create a database.

DB parameter group Info

default.postgres13

Option group Info

default:postgres-13

Backup

Enable automated backups
Creates a point-in-time snapshot of your database

Encryption

Enable encryption
Choose to encrypt the given instance. Master key IDs and aliases appear in the list after they have been created using the AWS Key Management Service console. Info

Log exports

Select the log types to publish to Amazon CloudWatch Logs

PostgreSQL log
Upgrade log

IAM role
The following service-linked role is used for publishing logs to CloudWatch Logs.

RDS service-linked role

Maintenance

Auto minor version upgrade Info

Enable auto minor version upgrade
Enabling auto minor version upgrade will automatically upgrade to new minor versions as they are released. The automatic upgrades occur during the maintenance window for the database.

Maintenance window Info
Select the period you want pending modifications or maintenance applied to the database by Amazon RDS.

- Choose a window
- No preference

Deletion protection

Enable deletion protection
Protects the database from being deleted accidentally. While this option is enabled, you can't delete the database.

Estimated monthly costs

The Amazon RDS Free Tier is available to you for 12 months. Each calendar month, the free tier will allow you to use the Amazon RDS resources listed below for free:

- 750 hrs of Amazon RDS in a Single-AZ db.t2.micro, db.t3.micro or db.t4g.micro Instance.
- 20 GB of General Purpose Storage (SSD).
- 20 GB for automated backup storage and any user-initiated DB Snapshots.

Learn more about AWS Free Tier

When your free usage expires or if your application use exceeds the free usage tiers, you simply pay standard, pay-as-you-go service rates as described in the Amazon RDS Pricing page

You are responsible for ensuring that you have all of the necessary rights for any third-party products or services that you use with AWS services.

Cancel Create database

PostgreSQL

PostgreSQL is a powerful, open-source object-relational database system with a strong reputation of reliability, stability, and correctness.

- High reliability and stability in a variety of workloads.
- Advanced features to perform in high-volume environments.
- Vibrant open-source community that releases new features multiple times per year.
- Supports multiple extensions that add even more functionality to the database.
- Supports up to 15 Read Replicas per instance, within a single Region or 5 read replicas cross-region.
- Supports General Purpose, Memory Optimized, and Burstable Performance instance classes.
- The most Oracle-compatible open-source database.

© 2024, Amazon Web Services, Inc. or its affiliates. Privacy Terms Cookie preferences