

◆ Partial Class

- Allows splitting a class definition across multiple files.
 - Useful in large projects or when working with auto-generated code (e.g., WinForms Designer, EF models).
-

◆ Private Constructor

- Used to prevent direct instantiation of a class.
 - Core part of the Singleton Design Pattern → ensures only one instance exists.
-

◆ Record (C# 9.0)

- New reference type for immutable data models.
 - Provides value-based equality, concise syntax, and with expressions.
 - Great for DTOs and read-only models.
-

◆ Default Constructor of a Class

- If you don't define a constructor, the CLR automatically provides a parameterless constructor.
 - Initializes fields with default values (0 for int, null for refs...).
 - If you define any constructor yourself, the CLR does not add a default one.
-

◆ Performance: Struct vs Class

- Struct (Value Type) → stored on the stack, faster in many cases, but causes overhead with boxing/unboxing.
 - Class (Reference Type) → stored on the heap, requires garbage collection, more flexible (supports inheritance).
 - Rule of thumb:
 - Use struct for small, lightweight data.
 - Use class for complex/large objects or when inheritance is required.
-

◆ Save Memory Indirectly

- Structs can save memory when small.
 - But large structs can hurt performance → because copying passes the entire struct by value.
-

◆ Dependency Inversion Principle (SOLID - D)

- Depend on Abstractions, not on Concrete implementations.
 - Example: Code against IRepository instead of SqlRepository.
 - This makes the code more flexible, testable, and maintainable.
-

◆ Couple Operators (Operator Overloading)

- In C#, you can overload operators like +, -, ==.
 - Example: Override == for comparing object values instead of just references.
-

◆ Source Browser (Reference Source)

- Tool/website for browsing .NET BCL (Base Class Library) source code.
 - Helps in studying how .NET classes and overrides are implemented.
-

◆ Override in BCL

- Most .NET base classes override methods like:
 - ToString() → to return meaningful output.
 - Equals() → for logical equality comparison.
 - GetHashCode() → for dictionary/hash usage.