
Rob J Hyndman George Athanasopoulos

FORECASTING PRINCIPLES AND PRACTICE



10. Dynamic regression models


10.3 Forecasting

OTexts.org/fpp3/


Forecasting

- To forecast a regression model with ARIMA errors, we need to forecast the regression part of the model and the ARIMA part of the model and combine the results.
- Some predictors are known into the future (e.g., time, dummies).
- Separate forecasting models may be needed for other predictors.
- Forecast intervals ignore the uncertainty in forecasting the predictors.

US personal consumption and income




```
vic_elec_daily |>
  ggplot(aes(x = Temperature, y = Demand, colour = Day_Type)) +
  geom_point() +
  labs(x = "Maximum temperature", y = "Electricity demand (GW)")
```



```
vic_elec_daily |>
  pivot_longer(c(Demand, Temperature)) |>
  ggplot(aes(x = Date, y = value)) +
  geom_line() + facet_grid(name ~ ., scales = "free_y") +
  labs(v = "")
350 -
300 -
250 -
200 -
 40 -
 30 -
 20 -
 10 -
                       Apr 2014
                                           Jul 2014
    Jan 2014
                                                                                  Jan 2015
                                            Date
```

```
fit <- vic elec dailv |>
  model(arima = ARIMA(Demand ~ Temperature + I(Temperature^2) +
    (Day Type == "Weekday")))
report(fit)
## Series: Demand
## Model: LM w/ ARIMA(2,1,2)(2,0,0)[7] errors
##
## Coefficients:
##
           ar1
               ar2 ma1
                                  ma2 sar1 sar2 Temperature
  -0.1093 0.7226 -0.0182 -0.9381 0.1958 0.417 -7.614
##
## s.e. 0.0779 0.0739 0.0494 0.0493 0.0525 0.057 0.448
   I(Temperature^2) Day Type == "Weekday"TRUE
##
##
                0.1810
                                          30.40
## s.e.
                0.0085
                                          1.33
##
## sigma^2 estimated as 44.91: log likelihood=-1206
## ATC=2432 ATCc=2433
                       BTC=2471
```




```
augment(fit) |>
features(.resid, ljung_box, dof = 6, lag = 14)
```

Daily electricity demand - revised

```
fit <- vic elec dailv |>
  model(arima = ARIMA(log(Demand) ~ Temperature + I(Temperature^2) +
                         (Day Type == "Weekday"), stepwise = FALSE,
                     order constraint = (p+q \le 8 \& P+0 \le 5))
report(fit)
## Series: Demand
## Model: LM w/ ARIMA(5,1,3)(2,0,0)[7] errors
## Transformation: log(Demand)
##
  Coefficients:
##
                 ar2 ar3 ar4 ar5
                                            ma1
                                                          ma3 sar1
          ar1
                                                   ma2
  0.0262 -0.029 0.539 -0.087 0.185 -0.212 -0.141 -0.622 0.3217
##
## s.e. 0.2311 0.148 0.117 0.061 0.071 0.230 0.179 0.128 0.0594
##
         sar2 Temperature I(Temperature^2) Day Type == "Weekday"TRUE
  0.3866
                 -0.0311
                                    86-04
                                                           0.1396
##
## s.e. 0.0593 0.0004
                                    0e+00
                                                           0.0061
##
```

Daily electricity demand - revised



```
# Forecast one day ahead
vic next day <- new data(vic elec daily, 1) |>
 mutate(Temperature = 26, Day_Type = "Holiday")
forecast(fit, vic_next_day)
## # A fable: 1 x 6 [1D]
## # Key: .model [1]
##
    .model Date
                                 Demand .mean Temperature Day_Type
## <chr> <date>
                                 <dist> <dbl> <dbl> <chr>
## 1 arima 2015-01-01 t(N(5.1, 0.00087)) 163.
                                                     26 Holiday
```

```
vic_elec_future <- new_data(vic_elec_daily, 14) |>
mutate(
   Temperature = 26,
   Holiday = c(TRUE, rep(FALSE, 13)),
   Day_Type = case_when(
    Holiday ~ "Holiday",
    wday(Date) %in% 2:6 ~ "Weekday",
    TRUE ~ "Weekend"
   )
)
)
```

