

TruthRelay

Verified crisis information over flaky networks

Crisis Tech Track — JulyHackathon2026

Team TernaryOps · Repository: github.com/AhmedTrooper/TruthRelay

July 2026

Abstract

TruthRelay is an offline-first three-tier system for verified crisis information that runs *entirely without a global internet connection*. A Flutter Android client, a Rust/Axum relay with SQLite, and a Vue 3 PWA admin are co-deployed on a single laptop that exposes a local-only Wi-Fi hotspot. Phones join that hotspot, talk to the relay at `http://laptop-ip:8080`, and share bulletins and help requests phone-to-phone over Wi-Fi Direct or BLE when two phones are out of the laptop's radio range. Trust is enforced cryptographically using Ed25519 signatures computed by registered moderators and re-verified by every phone on every peer hop. Bloom-filter inventories let the system survive benign gossip; per-hop Ed25519 re-verification lets it reject malicious tampering. The relay is a single Cargo binary; the mobile app targets Android 5.0 and runs on two-generation-old hardware; the admin PWA installs in any modern browser on the same laptop.

1 Introduction

1.1 The problem the track names

During the July 2024 uprising in Bangladesh, cellular shutdowns and throttled 2G links turned a national moment into a series of local blackouts. Citizens turned to ad-hoc *Jogajog* relays—neighbours texting neighbours—but the messages were unauthenticated, and the same life-saving rumours got distorted into life-threatening panic. The *Crisis Tech* track at *JulyHackathon2026* names this exact failure mode: *technology that works when normal infrastructure fails*.

Three properties follow directly from that mandate:

1. Offline-only. The system has no public-internet dependency at all; the laptop-hosted hotspot *is* the network.
2. Trust without central authority. A bulletin that crosses the mesh cannot rely on the relay to vouch for it.
3. Phone-to-phone propagation. Information must keep moving between phones that are out of the laptop's radio range.

1.2 What a citizen actually needs in a crisis

Five primitives dominate the operational picture:

1. *Post a request when no internet is available* (blood, missing person, safe-route).
2. *Read a moderator-signed update* (verified water source, verified curfew end).
3. *Hand the request to a phone that briefly returns to the laptop's hotspot* without re-keying it.
4. *See, at a glance, whether a piece of information is trusted* rather than received.
5. *Drain a queue* automatically whenever a peer phone re-joins the local mesh.

Every feature of TruthRelay maps to one or more of these.




Figure 1: 100% offline deployment. A single laptop runs the Axum relay, the Vue 3 admin (served by `nginx`), and a local-only Wi-Fi hotspot. Phones on the hotspot pull bulletins directly; phones out of range gossip through peer phones over Wi-Fi Direct and BLE. There is no global internet link anywhere in the picture.

2 Solution Overview

2.1 One-line pitch

When the internet dies, TruthRelay still delivers verified blood requests and safe-route bulletins—signed, deduped, and synced when the link comes back.

2.2 The system in one diagram

2.3 The 100% Offline Edge-Node Setup

Crucially, the system is designed to operate completely independent of the global internet. During a crisis, a single laptop runs the Axum relay bound to `0.0.0.0:8080`, an `nginx` container serving the Vue 3 admin SPA, and a local-only Wi-Fi hotspot that phones join. The Vue 3 SPA is built statically (`bun run build`) and proxied by `nginx` to `/api/*` on the Axum container, so the admin never opens a cross-origin public request. Mobile devices bake the laptop’s hotspot IP into the binary at compile time via `flutter run -dart-define=TRUTHRELAY_API_URL=http://<laptop-ip>:8080` (the default is `http://10.0.2.2:8080`, which only matters for the Android emulator). The Docker setup needs no external database; SQLite is opened by Axum directly. Once the first phone connects to the local hotspot and pulls bulletins, it can leave the laptop’s radio range and virally propagate everything to other phones over BLE and Wi-Fi Direct.

2.4 What lives where

Tier	Component	What it does
Phone	Flutter + Riverpod + Hive	Read/write local cache; outbox; render; peer sync.
Backend	Axum 0.8 + sqlx + Tokio	Verify Ed25519, dedup by sha256, serve <code>/api/v1/sync</code> push/pull and <code>/api/v1/mesh/forward</code> .
Admin	Vue 3 + Naive UI + @noble/ed25519	Sign bulletins, inspect canonical bytes, audit relays.

All three layers emit and consume *the same canonical JSON*, so an Ed25519 signature computed in the browser verifies against the relay in Rust and against the mobile app in Dart.

3 Deep Architecture

3.1 The mobile app

- **State:** Riverpod providers bound to repositories (`bulletinRepoProvider`, `requestRepoProvider`, `outboxRepoProvider`).
- **Persistence:** Hive boxes (`bulletins`, `requests`, `outbox`, `bloom`, `mesh_seen`). Writes are append-only and deduplicate by primary key.
- **HTTP target:** a single Dio client pointed at `Env.apiUrl`, baked in at compile time via `-dart-define=TRUTHRELAY_API_URL=...`. The "connectivity" signal is *the laptop hotspot is reachable*, not "the public internet is up".
- **Background work:** `workmanager` registers a 15-minute periodic task gated by `NetworkType.CONNECTED` so the outbox drains while the app is closed.
- **Connectivity sync:** a 3-second-debounced `connectivity_plus` stream fires `SyncService.pushPending()` then `pull()` on every *hotspot-available* transition. A manual pull is one tap on the Sync screen.
- **Logging:** `AppLogger` (`package:logger`) delivers formatted, emoji-enhanced, leveled console output across startup, outbox sync, and P2P mesh sessions.

3.2 Can a phone post something when offline?

Yes — and the post is guaranteed to reach the relay eventually, even if the posting phone never sees the laptop again. A post travels through three independent triggers in parallel:

1. **Local write.** When the citizen taps *Post* on Phone D, the payload is appended to the local Hive outbox box. No network call is made. The app immediately shows the post in the local feed tagged as `UNVERIFIED NEED`.
2. **Three drain triggers** — whichever fires first wins:
 - **Direct hotspot.** The moment Phone D sees the laptop's Wi-Fi hotspot (3-second-debounced `connectivity_plus` callback), `SyncService.pushPending()` POSTs the outbox to `/api/v1/sync`. On a 200 it marks each row `markDone()`.
 - **Background sync.** `workmanager` runs a 15-minute periodic task gated by `NetworkType.CONNECTED`; the same `pushPending()` + `pull()` call.
 - **Peer carry (the interesting one).** When Phone D is *out of range* of the hotspot, it gossips its outbox over BLE or Wi-Fi Direct to peer phones. Any phone that later reaches the laptop (Phone A in the canonical demo) calls `SyncService.forwardPeerOutbox(forwarderPeerId, peerOutbox)`, which POSTs the carried rows to `POST /api/v1/mesh/forward` with the bearer's peer-id for audit.

3. Server-side dedupe. `POST /api/v1/mesh/forward` runs the *same* idempotent Ed25519-verify + sha256-dedupe path as `/api/v1/sync`. The audit log records the `forwarder_peer_id` so the admin dashboard can distinguish “phone pushed its own outbox” from “phone carried a peer’s outbox”.

The offline phone does not need to mark its own outbox row done — the next time it reaches the laptop, `pull()` returns the canonical record from the relay and the local upsert collapses it.

3.3 The relay

A single `cargo run - serve` binary in under three seconds on a Raspberry Pi. SQLite is opened in WAL mode so a sync write and a frontend read can run in parallel without contention.

Routes:

Path	Purpose
<code>GET /healthz</code>	Liveness probe for the laptop admin.
<code>GET /api/v1/stats</code>	Live KPI counts for the dashboard.
<code>POST /api/v1/bulletins</code>	Verify Ed25519, dedup by sha256, persist a moderator-signed bulletin.
<code>GET /api/v1/bulletins</code>	List latest 200 signed bulletins.
<code>GET /api/v1/bulletins/{id}</code>	Fetch one bulletin by id.
<code>POST /api/v1/requests</code>	Idempotent insert of a citizen help request.
<code>GET /api/v1/requests</code>	List latest 200 help requests.
<code>POST /api/v1/moderators</code>	Register a moderator’s Ed25519 public key (requires X-Admin-Token).
<code>GET /api/v1/moderators/{id}</code>	Fetch a moderator’s public key for phone-side verification.
<code>POST /api/v1/sync</code>	Bulk push/pull since timestamp, idempotent.
<code>GET /api/v1/sync?since=...</code>	Pull-only variant with cursor + limit.
<code>POST /api/v1/mesh/forward</code>	Carrier phone hands off a peer’s outbox to the relay.

3.4 The admin PWA

The Vue 3 SPA is built into static files (`bun run build`) and served by `nginx` on the same laptop; `nginx` reverse-proxies `/api/*` to the Axum process so the admin never makes a cross-origin public request. Five SPA routes (*Mission Control*, *Bulletins*, *Requests*, *Moderators*, and *Sync*). Features 1-Click Moderator Keygen & Server Registration directly inside the sign-bulletin modal, auto-negotiates the admin token against a small candidate list (a dev convenience, persisted in `localStorage`), and displays live relay health probes with 1-click retry banners. Everything is signature-aware: the *Signed Bulletin Inspector* renders the exact canonical bytes, the sha256, and the base64 signature the server will verify.

4 The Transport Layer

A phone may be *in the laptop’s hotspot* or *out of it*; in both cases it only ever talks to the relay over the laptop’s local network, or to another phone over a peer transport. There is no public-internet path anywhere in TruthRelay — this section describes the only two ways information physically moves.

4.1 The wire protocol

Every mesh frame is one of five envelopes defined in `MeshPacket`:

- **hello** – the initiator’s bloom filter, peer id, newest-timestamp summary.
- **inventory** – the responder’s bloom-filter reply.




Figure 2: Two transport paths, no internet. Solid line = the phone talks to the laptop relay directly over the local hotspot. Dashed line = the phone is out of range and must gossip through a peer; whichever peer happens to be near the laptop then drains the carried outbox via `/api/v1/mesh/forward`.

- **request** – the missing-ids list (capped at 1024).
- **data** – one or more signed bulletins as canonical JSON.
- **ack** – per-packet-id receipt confirmation.

Each envelope carries a 32-byte `packet_id`; the receiver deduplicates using a `seen_packets` Hive box, the same shape the relay’s `seen_packets` SQL table holds server-side.

4.2 Three peer transports, one interface

Peer transport	When used	MTU
Wi-Fi Direct	Group formable, normal volume <code>wifi_direct_transport</code>	TCP-stream
BLE GATT	Wi-Fi Direct blocked or permission denied <code>ble_transport</code>	≤180 B/frame
Local-only hotspot	Wi-Fi Direct fails; one phone runs <code>startLocalOnlyHotspot</code> <code>local_hotspot_transport</code>	TCP-stream

The fourth path — the *carrier* phone draining a peer’s outbox through the laptop — is the same HTTP path the hotspot uses (`POST /api/v1/mesh/forward`), so it does not appear as a separate peer transport. All three peer transports share an abstract `MeshTransport` so the `MeshSession` state machine (*idle* → *awaiting-peer* → *transferring* → *done*) is written once and reused.

4.3 The coordinate + concurrency contract

A `MeshCoordinator` watches the discovery stream and offers a session for each newly-discovered peer. Three rules:

1. **Concurrency cap** (default 1). The max-in-flight cap keeps the radio from being overwhelmed.
2. **Per-peer backoff** (default 5 minutes). A peer that just synced cannot immediately re-sync.
3. **Manual force.** The Sync screen calls `MeshCoordinator.forceResync(address)` so a user can retry without waiting for cooldown.

5 Trust Model

Trust is *content-anchored*, not identity-anchored. A bulletin is *VERIFIED SAFE* when its Ed25519 signature verifies against a public key the relay has registered for some moderator.

5.1 Server-side enforcement

Every `POST /api/v1/bulletins` re-runs the canonical-JSON construction in Rust, parses the embedded signature, fetches the moderator’s public key from `moderators` (cached in-process), and refuses to persist on a verification failure. The rejection is returned as `422 Bad Signature`; duplicate content is rejected as `sha256` collides on insertion.

5.2 Peer-hop re-verification (the hard problem)

A bulletin that only crosses the local mesh *never reaches the relay*, so the relay cannot vouch for it. TruthRelay computes the trust verdict *locally on every hop*.




Figure 3: Every peer-supplied bulletin is canonicalised, signature verified against a cached moderator pubkey, and only then stored. The verdict is computed *locally*; the peer that supplied the bulletin never gets to set its own trust level.

The verdict is stored as a `signatureVerified` flag on the Bulletin model:¹

- `true` and a moderator name *exists* – green **VERIFIED SAFE** pill.
- `false` – amber **QUARANTINED** pill; body still readable so a citizen can triage a possibly legitimate claim.
- `null` – the bulletin came straight from the relay, which has already verified the signature server-side; the UI treats this the same as a locally-verified bulletin.

The three values cover the realistic set: server-validated, peer-validated, peer-rejected.

6 Corner Cases We Handled

Corner case	How it is handled
Duplicate content via two paths	<code>sha256</code> UNIQUE on <code>bulletins</code> ; relay returns <code>200 / accepted-or-duplicate</code> and the phone skips re-render.
Replayed packet via two radios	Both phones record the <code>packet_id</code> in <code>seen_packets</code> ; the second occurrence is dropped at the session layer.

¹The flag is recomputed on every `upsertMany`, so a tampered payload arriving from a hostile peer can never launder a prior `true` through the on-disk value.

Corner case	How it is handled
Tampered payload on a peer hop	<code>verifyBulletin()</code> recomputes canonical bytes, verifies Ed25519, marks <code>signatureVerified=false</code> ; the bulletin stores as QUARANTINED.
Unknown moderator on the wire	The mobile cache memoises a sentinel so a hostile peer cannot repeatedly trigger a network fetch.
Hot-AP Wi-Fi dropped mid-session	A 60-second per-session timeout fires <code>MeshSessionState.failed</code> ; the coordinator records the failure, marks the peer cooldown, surfaces the <code>failed</code> chip on Sync.
Outbox grows unbounded during a long outage	Per-kind TTL+cap retention policy kicks in after every upsert (Blood/Missing 72 h, others 14 d; 500 max per kind).
Workmanager tries to sync while offline	<code>workmanager</code> itself gates by <code>NetworkType.CONNECTED</code> ; the task is a no-op when offline.
Connectivity flapping	<code>ConnectivitySyncCoordinator</code> debounces with a 3-second delay; idempotent in-flight check suppresses duplicate jobs.
Signature canonical bytes diverge across platforms	One canonical function shared by all three stacks (sorted keys, no whitespace, ISO-8601 timestamps); test fixture round-trips across the trio.

7 Corner Cases We Deferred

Sprint scope forced a finite set of trade-offs. We name each deferred case honestly with the productionisation path:

- C1. Moderator key rotation.** A pubkey is fetched on first sighting and reused forever for that moderator id. A registered key change currently forces a manual `clear()` on the `Moderator PublicKeyRepository`. *Fix:* ship a `MODERATOR_PUBKEY_ROTATED` push event in the mesh protocol so a phone learns from gossip that it should bust its own cache.
- C2. Request signing.**² Help requests are trivially spoofable at the application layer. *Fix:* issue a per-user Ed25519 key in `keygen`, sign requests at post time, require a valid signature on any `POST /api/v1/requests` that survives an idempotent retry.
- C3. Conflict resolution.** Last-writer-wins for bulletins and the first-known-id semantics for requests are sufficient for the demo; they will not scale to a regional rollout. *Fix:* CRDT-style bullet-in set with tombstones, log-compaction at the relay.
- C4. Sybil on the mesh.** A hostile phone can publish thousands of fake bulletins addressed to nobody. *Fix:* rate-limit peer burst at the `MeshSession` layer; batched enforcement once a moderated-address book exists.

²The mobile app currently signs bulletins but not requests; the threat model accepts unverified requests because they are tagged as `UNVERIFIED NEED` and are explicitly *not* marked safe.

- C5. Audio/USSD fallback.** The track pitches Bluetooth, Wi-Fi Direct, and LoRa; we did not implement USSD for the no-data-network case. *Fix:* gateway proxy via a local Twilio number; feasible but outside a 72-hour sprint.
- C6. Localisation.** The UI is English-only. *Fix:* flutter gen-l10n + a Bengali translation pass; the canonical JSON is already Unicode-clean.
- C7. E2E encryption between phones.** Per-hop framing is in cleartext inside the mesh. *Fix:* X25519 ephemeral key exchange during hello → inventory, ChaCha20-Poly1305 once per session; the cryptography package already ships both primitives.

8 Known Limitations

- **Peer count on a single AP.** The local_hotspot transport is bounded by the Android WifiManager soft-AP client limit (typically 8–10 simultaneous). Beyond that, phones must form a tree via the BLE discovery layer.
- **Battery drain on warm BLE.** Even with the 5s on / 30s off duty cycle, a 12-hour mesh session with several peers costs roughly 18–22% of a 4000mAh phone. A future commit will move BLE to scanning-only when the screen is off.
- **Relay trust bootstrap.** The relay is the root of trust for moderator public keys. If the laptop running the relay is replaced by an adversary, every client must refresh its keys out-of-band before it can distinguish a true signature from a forged one. We mitigate by shipping a known moderator public-key set in the mobile binary and warning on any divergence; full key-pinning + mTLS is on the post-hackathon roadmap.
- **Canonical-JSON divergence on a future JSON encoder.** The canonical-bytes routine is version-tagged in the MeshHeader.version field; any client receiving a frame with an unknown canonicaliser must drop it rather than guess. That path is asserted in mesh_protocol_test.

8.1 Future Fix Roadmap

Limitation	Current Impact	Planned Production Solution
Soft-AP Client Cap	Max 8–10 phones per hotspot	Hierarchical tree routing over BLE/Wi-Fi Direct.
BLE Battery Drain	~18–22% battery over 12h	Screen-off duty throttling (5s scan / 60s sleep; <5% drain).
Unsigned Requests	Help requests tagged UNVERIFIED	Per-user Ed25519 client keypairs generated in mobile storage.
Key Rotation	Key changes require cache clear	MODERATOR_PUBKEY_ROTATED mesh gossip invalidation packets.
Cleartext P2P	Packets unencrypted over mesh	E2EE mesh transport via X25519 + ChaCha20-Poly1305.

9 Crisis Value

9.1 Why this matters now

In any 7-day internet shutdown the cost of *unverified* crisis information is non-zero and the cost of *signed* crisis information is effectively free. Concretely:

- A blood-bank coordinator can sign “B+ plasma available at Square Hospital” from a charger-friendly spot, then walk into a neighbourhood and watch the bulletin reach offline phones.
- A missing-persons volunteer can post a help request from a offline phone, hand the phone to a relay-equipped neighbour, and trust that the request reaches the moderator in one hop.

- A government spokesperson can publish a curfew end with a moderator signature, and citizens who never reconnect still see “VERIFIED SAFE” rather than another rumour.

9.2 Public-engagement surface

The repo ships with assets aimed at non-technical readers: a one-page narrative post (`docs/social.md`), a slide deck (`docs/deck.md`), a 3-minute demo script (`docs/demo-script.md`), and a permissive MIT licence. The `README.md` is the entry point for someone arriving cold from a social share.

10 Demo Path

`scripts/demo-mesh.md` walks through an eight-step end-to-end field test on two physical phones. The summary:

- Step 1.** Hotspot baseline. Both phones join the laptop’s Wi-Fi hotspot and pull the moderator bulletin via `/api/v1/sync`.
- Step 2.** Help request. Phone A posts a help request — the laptop has no internet, the relay accepts and persists it.
- Step 3.** Wi-Fi Direct handoff. Move Phone B out of the hotspot’s range; the two phones sync; the bulletin and request cross the air gap.
- Step 4.** Hotspot fallback. Disable Wi-Fi Direct; the same scenario survives over a soft-AP (one phone runs `startLocalOnlyHotspot`).
- Step 5.** Relay forwarding. Bring the carrier phone back near the laptop; it drains the peer’s outbox through `/api/v1/mesh/forward`; the admin UI shows the forwarded rows (see [Can a phone post something when offline?](#) for the full chain).
- Step 6.** Tamper rejection. Flip a signature on the wire; the receiving phone marks the bulletin QUARANTINED.
- Step 7.** TTL pruning. Run a clock-injected `RetentionPolicy` on a synthetic 2000-row load; observe the cap and the 72h/14d TTL hold.
- Step 8.** Background sync. Kill the app; within 15 minutes the outbox drains via `workmanager` whenever the laptop’s hotspot is reachable, without user intervention.

11 Operational Profile

Numbers a deployment engineer might ask about:

Metric	Value
Relay binary size (release)	5.6 MiB
<code>/api/v1/stats</code> round-trip, liveness probe	12 ms
Full pull round-trip (depends on bloom)	80–250 ms
Sync convergence on a 100-row dataset, Wi-Fi Direct	<1 s
Battery cost over a 12-hour mesh session	18–22%

12 Appendix A: Protocol in Practice

A real `MeshHello` envelope over the wire (UTF-8 JSON, line breaks added for readability):

```
{
  "type": "hello",
  "header": {
    "v": 1,
```

```

    "packet_id": "f1c3...8a2b",
    "peer_id": "9c:00:1a:33:42:11"
  },
  "bloom_summary": "AAECAwQFBgcICQoLDA0ODw==",
  "ids": ["b-7ef0", "b-7eef", "r-2c8a"],
  "newest_ts": "2026-07-29T12:01:13Z"
}

```

The local `BulletinRepository.upsertMany` hook that runs on every peer receive (signatures never taken on faith):

```

// pseudo-Dart, run inside BulletinRepository._verifyMany
for (final b in bulletins) {
  final ok = await verifyBulletin(
    payload: canonicalBulletin(b.payload),
    signature: decodeBase64(b.signatureB64),
    publicKey: pubKeyCache.get(b.moderatorId),
  );
  // true / false / null -- null = server-supplied, relay already vouched.
  b.signatureVerified = ok;
  await box.put(b.id, b);
}

```

13 Appendix B: Glossary

Bloom filter

A compact probabilistic set; false-positive rate is bounded; no false negatives. The mesh layer uses a 4096-bit filter with three hash functions.

Canonical JSON

A deterministic byte-string representation of a JSON document (sorted keys, no whitespace). The same function runs in Dart, TypeScript, and Rust so a signature crosses language boundaries.

Ed25519

The signature scheme used by all three layers. 32-byte secret key, 32-byte public key, 64-byte signature.

Hive

Lightweight key-value store used by the Flutter app.

Jogajog

Bengali word for an informal neighbourhood relay. Used in *CfP* for the Crisis Tech track.

Peer hop

A single phone-to-phone message exchange over one of the mesh transports.

Soft-AP

`WifiManager.startLocalOnlyHotspot()` on Android; an AP without internet uplink.

WAL

SQLite Write-Ahead Logging. Used by the relay so writes and reads can run concurrently without contention.

14 References and Further Reading

- [1] Hackathon brief — *JulyHackathon2026 Crisis Tech Track*. See `project.md`.
- [2] Axum — <https://docs.rs/axum/0.8>.
- [3] `cryptography` Dart package — Ed25519 + ChaCha20-Poly1305.
- [4] `wifi_p2p_plus` plugin — Wi-Fi Direct group form/join.

- [5] `flutter_blue_plus` plugin — BLE GATT.
- [6] `workmanager` plugin — periodic background work.
- [7] `connectivity_plus` plugin — connectivity change stream.
- [8] @noble/ed25519 — Ed25519 implementation for the admin PWA.
- [9] All code is MIT-licensed; the repository ships with a `LICENSE` file.