Business glossary

Telecom data platform: CRM, billing, network, mobile app and partner data

Version 1.0 | October 2026 | Status: draft for review

What this document is. One agreed definition for every business term used in the project, with the source column, the quality rule and the owner for each. It also includes a data dictionary of every table and a catalogue of quality rules.

Contents. 1 How to read this glossary | 2 Sources and owners | 3 Glossary by domain (CRM, billing, network, mobile app, partner, data platform, data quality, governance) | 4 Data dictionary by table | 5 Quality rule catalogue | 6 Open items

1. How to read this glossary

Each entry has five fields. **Term** is the business word. **Definition** is the one agreed meaning. **Source / column** shows where the term lives in the data. **Quality rule** says what makes the value valid. **Owner** is the team that answers questions about the term and approves changes.

The glossary explains business meaning. The data dictionary in section 4 explains technical columns. The glossary points to the dictionary, and the dictionary points back to the glossary term.

Why it matters here: the word *customer* means a person in CRM, an account in billing and a phone number in the network data. Only the MSISDN joins them. Without one definition, two dashboards can show different customer counts.

Owners are suggested team names for this project. Replace them with real names before the document is approved.

2. Sources and owners

Source	What it holds	Where it lives	How it arrives	Key fields	Owner
CRM	Customers, plans and devices.	Postgres schema crm	Streaming (CDC)	customer_id, msisdn	CRM team
Billing	Accounts, invoices, invoice lines and payments. Also monthly file copies.	Postgres schema billing; monthly CSV	Streaming (CDC) and batch	account_id, invoice_id, msisdn	Billing team
Network	Calls, messages and data sessions (CDR).	Daily CSV files	Batch	cdr_id, msisdn	Network operations
Mobile app	Customer actions in the app.	JSON events on Kafka	Streaming	event_id, customer_id	Digital team
Partner	Roaming and international usage charged by a partner.	Monthly CSV	Batch	partner_record_id, msisdn	Partnerships team

3. Glossary by domain

3.1 CRM: customers, plans and devices

Term	Definition	Source / column	Quality rule	Owner
Customer	A person or company that holds at least one plan with the company, as recorded in CRM.	crm.customers.customer_id	Unique. One row per person; duplicates are rejected.	CRM team
Customer status	The lifecycle state of a customer: ACTIVE, SUSPENDED or CHURNED.	crm.customers.status	Value must be one of the three allowed values.	CRM team
Active customer	A customer whose status is ACTIVE and who can use the service.	crm.customers.status = ACTIVE	Counted once per customer in all dashboards.	CRM team
Suspended customer	A customer whose service is temporarily restricted but who has not left.	crm.customers.status = SUSPENDED	Needs a status change date (SCD2 history).	CRM team
Churned customer	A customer who has left the company.	crm.customers.status = CHURNED	Needs a change date. Basis for the churn rate.	CRM team
MSISDN	The mobile phone number that identifies a subscriber. It is the only key shared by CRM, billing, network and partner data.	msisdn in CRM, billing, CDR, partner	Format +316 followed by 8 digits. Local format 06xxxxxxxx is auto-fixed in quarantine.	Data governance
Plan	A product with a monthly fee and an allowance of data and voice minutes.	crm.plans.plan_id	Plan must exist for every customer.	Product team
Monthly fee	The price of a plan per month, before any overage.	crm.plans.monthly_fee	Greater than 0. Must equal the billed plan fee.	Product team
Data allowance	The amount of mobile data in GB included in a plan each month.	crm.plans.data_gb	Zero or more.	Product team
Voice allowance	The number of call minutes included in a plan each month.	crm.plans.voice_minutes	Zero or more.	Product team
Plan change	A customer moves from one plan to another. Each change creates a new history row.	crm.customers.plan_id	Tracked with SCD2 (valid_from, valid_to, is_current).	CRM team
Device	The handset a customer uses, recorded once per customer.	crm.devices	Customer must exist.	CRM team
IMEI	A 15-digit identifier of the physical handset.	crm.devices.imei	Exactly 15 digits.	CRM team
Customer 360	A single combined view of a customer: profile, plan history, devices, billing, usage and app activity.	gold.dim_customer and related facts	Built only from rows that passed the quality gate.	Analytics team

3.2 Billing and revenue

Term	Definition	Source / column	Quality rule	Owner
Billing account	The account that receives invoices. It has its own ID and is linked to the CRM customer only by MSISDN.	billing.accounts.account_id	Every account maps to exactly one CRM customer.	Billing team
Account reference	The readable reference of a billing account, in the form ACC followed by 8 digits.	billing.accounts.account_ref	Unique. Format ACC-########.	Billing team
Invoice	A monthly bill sent to a billing account.	billing.invoices.invoice_id	Total equals the sum of its lines.	Billing team
Billing period	The date range an invoice covers, normally one calendar month.	billing.invoices.period_start, period_end	Start date is not after end date.	Billing team
Invoice total	The full amount charged on an invoice.	billing.invoices.total_amount	Not negative. Within the normal range (outliers raise an alert).	Billing team
Invoice line	One charge on an invoice, such as the plan fee or a data overage.	billing.invoice_lines	Invoice must exist. Amount is not negative.	Billing team
Plan fee (PLAN_FEE)	The invoice line that charges the monthly price of the plan.	invoice_lines.line_type = PLAN_FEE	Equals the CRM plan monthly fee.	Billing team
Data overage (DATA_OVERAGE)	The invoice line that charges data used beyond the plan allowance.	invoice_lines.line_type = DATA_OVERAGE	Not negative. Compared with usage in network CDRs.	Billing team
Payment	Money received against an invoice.	billing.payments.payment_id	Invoice must exist. Amount equals the invoice total.	Finance team
Payment method	How the customer paid: CARD, SEPA or IDEAL.	billing.payments.method	Not empty. Value in the allowed list.	Finance team
Unpaid invoice	An invoice with no matching payment.	invoices without a payment row	Counted in the unpaid balance of Customer 360.	Finance team
ARPU	Average revenue per user: invoiced revenue in a period divided by the number of active customers in that period.	gold.fact_invoice	Defined once and used by every dashboard.	Finance team
Revenue leakage	Revenue the company should have billed or collected but did not.	monitoring.recon_results, incidents	Measured in EUR at risk per mismatch type.	Revenue assurance
Revenue assurance	The practice of checking that what customers used equals what they were billed.	Recon models and dashboard 2	Every mismatch becomes an incident.	Revenue assurance

3.3 Network and usage

Term	Definition	Source / column	Quality rule	Owner
CDR	Call detail record: one row for each call, SMS or data session on the network.	network cdr_id	Unique. A repeated cdr_id is a duplicate.	Network operations
Event type	The kind of network event: VOICE, SMS or DATA.	network event_type	Value must be one of the three allowed values.	Network operations
Event timestamp	The date and time the network event started.	network event_ts	Valid timestamp, not in the future.	Network operations
Call duration	The length of a call or data session in seconds.	network duration_sec	A number, zero or more. Text values break the schema.	Network operations
Data volume	The amount of data transferred in a session, in megabytes.	network data_mb	Zero or more. Sudden spikes raise a distribution alert.	Network operations
Cell	A radio tower that served the event, identified by a cell ID.	network cell_id	Not empty. Format CELL-###.	Network operations
Call result	How a voice call ended: COMPLETED or DROPPED.	network call_result	Value must be COMPLETED or DROPPED.	Network operations
Dropped call	A voice call that ended without being completed normally.	call_result = DROPPED	Normal drop rate is about 5 percent; a jump raises an alert.	Network operations
Usage	What a customer consumed: calls, messages and data, matched to the customer by MSISDN.	gold.fact_usage	MSISDN must exist in CRM, or the row becomes an incident.	Network operations

3.4 Mobile app

Term	Definition	Source / column	Quality rule	Owner
App event	One action a customer performs in the mobile app, sent as a message.	app.events event_id	Unique. A repeated event_id is a duplicate.	Digital team
App event type	The kind of action: login, view_bill, topup, crash or plan_change.	app.events event_type	Value must be in the allowed list.	Digital team
App version	The release of the mobile app that sent the event.	app.events app_version	Not empty.	Digital team
Top-up	A customer adds credit to the account through the app.	event_type = topup	Linked to a customer.	Digital team
App crash	The app stops unexpectedly. Used to judge app quality per version.	event_type = crash	Crash rate per version is monitored.	Digital team
Customer ID in events	Links an app event to a CRM customer.	app.events customer_id	Not empty. Customer must exist in CRM.	Digital team

3.5 Partner

Term	Definition	Source / column	Quality rule	Owner
Partner usage record	One charge from a partner operator for usage by one of our customers.	partner_record_id	Unique. A repeated ID is a duplicate.	Partnerships team
Roaming	Customer use of the service on a foreign network, billed to us by the partner.	partner service = ROAMING	Compared with roaming billed to the customer.	Partnerships team
International call	A call to a number in another country that uses a partner network.	partner service = INTL_CALL	Compared with international charges billed.	Partnerships team
Partner amount	The amount the partner charges for the record.	partner amount	Not negative.	Partnerships team
Currency	The currency of a partner amount. The project uses EUR.	partner currency	Value must be EUR.	Partnerships team

3.6 Data platform and architecture

Term	Definition	Source / column	Quality rule	Owner
Source system	A system that produces data: CRM, billing, network, mobile app or partner.	Source column in the architecture	Each source has a data contract.	Data platform
Ingestion	Moving data from a source into the platform, either as a stream or as batch files.	Ingestion layer	Every record keeps its source and load time.	Data platform
Streaming ingestion	Changes and events flow continuously: Postgres to Debezium to Kafka to the bridge, then into Databricks.	Streaming path	Runs every 1 to 2 minutes as a Databricks Job.	Data platform
Batch ingestion	Files arrive on a schedule (daily or monthly) and are loaded together.	Network, partner and billing files	File must arrive within its freshness SLA.	Data platform
CDC	Change data capture: reading every insert, update and delete from a database log.	Debezium on Postgres	Needs full before and after images (REPLICA IDENTITY FULL).	Data platform
Debezium	The tool that reads the Postgres log and publishes change events to Kafka.	debezium/connector-postgres.json	Connector status must be RUNNING.	Data platform
Kafka	The message broker that holds change events and app events until they are read.	Topics cdc.* and app.events	Topics exist before the connector starts.	Data platform
Bridge	A script on the laptop that reads Kafka and uploads small files to the Databricks Volume.	generators/bridge.py	Commits offsets only after a successful upload.	Data platform
Volume (landing zone)	The Databricks storage folder where raw files land before Bronze.	/Volumes/telecom/landing/raw	Folders per source: stream/ and batch/.	Data platform
Auto Loader	The Databricks feature that picks up new files in a folder and loads only the new ones.	01_bronze notebooks	Reads as strings so bad types do not crash the load.	Data platform
Delta table	The table format used in Databricks. It supports MERGE and history.	All telecom.* tables	Not applicable.	Data platform
Unity Catalog	The Databricks catalog that holds schemas, tables, tags, comments and lineage.	catalog telecom	Every table has an owner tag and a comment.	Data governance
Bronze	The raw layer: data exactly as received, never changed, with audit columns.	telecom.bronze.*	Immutable and auditable.	Data platform
Audit columns	Extra columns added in Bronze: ingested_at, source_system, source_file, row_hash, contract_version.	telecom.bronze.*	Always filled.	Data platform
Silver	The cleaned layer: parsed, deduplicated, standardized, PII masked and history tracked.	telecom.silver.*	Only rows that passed the quality gate.	Data platform
Gold	The business layer: star schema and monitoring tables used by dashboards.	telecom.gold.*	Only built from Silver. Certified tables.	Analytics team
Standardization	Making values follow one format, such as one phone format and trimmed lowercase emails.	Silver notebooks	Same format in every system.	Data platform

Term	Definition	Source / column	Quality rule	Owner
PII masking	Hiding personal data, such as email and phone, so analysts do not see the real values.	silver.dim_customer	PII columns tagged and masked.	Data governance
Deduplication	Keeping one row when the same record arrives more than once.	Silver notebooks	By Kafka offset or business key.	Data platform
SCD2	Slowly changing dimension type 2: keep the full history of changes with valid_from, valid_to and is_current.	dim_customer, dim_plan	Applied with MERGE in change-time order.	Data platform
customer_xref	A mapping table that links the CRM customer ID to the billing account ID through MSISDN.	silver.customer_xref	One row per customer. No orphans.	Data platform
Star schema	Gold layout with fact tables (events and amounts) surrounded by dimension tables (who, what, when).	dim_* and fact_* tables	Facts reference valid dimensions.	Analytics team
Dimension table	A table that describes something: customer, plan, device or date.	dim_customer, dim_plan, dim_device, dim_date	Unique key per row version.	Analytics team
Fact table	A table of measured events or amounts: invoices, payments, usage, app events.	fact_invoice, fact_payment, fact_usage, fact_app_events	Every key exists in its dimension.	Analytics team
Backfill and replay	Re-running the pipeline on old or corrected files without breaking history.	Replay Job	Result is the same on repeat runs.	Data platform

3.7 Data quality

Term	Definition	Source / column	Quality rule	Owner
Data contract	The agreed schema, types, rules, SLA and version for one source.	contract/*.yaml	Versioned. A change creates a new version.	Data governance
Quality gate	The check between Bronze and Silver that tests every row against the contract.	02_quality_gate notebook	Pass goes to Silver, fail goes to Quarantine.	Data quality
Quarantine	The holding area for rows that failed the gate.	telecom.quarantine.*	Each row has a reason code and a failed rule.	Data quality
Auto-fix	An automatic repair of a known, safe defect, such as a 06 phone number or an uppercase email.	Quarantine step	Only fixes that are certain.	Data quality
Reject	A row that cannot be repaired is kept in quarantine with a reason and not used.	Quarantine step	Reason code is mandatory.	Data quality
Revalidate	Running the same gate again on repaired rows. Passing rows move on to Silver.	03_quarantine notebook	Same rules as the first pass.	Data quality
Reconciliation (recon)	Comparing the same facts across systems, such as CRM, billing and network.	dbt recon models	A mismatch creates an incident.	Revenue assurance
Incident	A recorded problem found by a monitor or by recon, with severity, status and time to resolve.	monitoring.incidents	Has an owner and a status.	Data quality
Severity	How serious an incident is: for example low, medium, high.	monitoring.incidents.severity	Set from the money or rows at risk.	Data quality
Freshness	Did the data arrive on time? One of the five pillars of data observability.	monitoring.dq_results	Compared with the SLA in the contract.	Data quality
Volume	Is the number of rows in the normal range? One of the five pillars.	monitoring.dq_results	Compared with contract bounds.	Data quality
Distribution	Are values in the normal range? One of the five pillars.	monitoring.dq_results	For example data_mb, invoice totals, drop rate.	Data quality
Schema	Did columns or types change? One of the five pillars.	monitoring.dq_results	Compared with the contract schema.	Data quality
Lineage	Which tables feed which. Shows what a failure affects. One of the five pillars.	Unity Catalog lineage	Recorded automatically.	Data governance
Schema drift	A source starts sending a new or changed column without notice.	Auto Loader rescued data	Raises an alert and a new contract version.	Data quality
Completeness	Required values are present.	Quality gate rule	For example email, cell_id, payment method.	Data quality
Validity	Values are in a legal format or range.	Quality gate rule	For example MSISDN format, amounts not negative.	Data quality

Term	Definition	Source / column	Quality rule	Owner
Uniqueness	Each record appears once.	Quality gate rule	For example customer_id, cdr_id, event_id.	Data quality
Domain values	Values come from an allowed list.	Quality gate rule	For example status, currency, event type.	Data quality
Accuracy and consistency	Values are correct and systems agree with each other.	Recon models	For example invoice total equals sum of lines.	Revenue assurance
Timeliness	Timestamps make sense and data is not late or from the future.	Quality gate rule	event_ts and created_at not in the future.	Data quality
SLA, SLI, SLO	SLA: the promise (for example file by 06:00). SLI: what is measured. SLO: the target for the measure.	contract/*.yaml	Each source has at least a freshness SLA.	Data governance
Pass rate	Share of rows that passed the gate: passed rows divided by all rows checked.	monitoring.dq_results	Reported per source and per rule.	Data quality
Circuit breaker	Stopping a batch from moving on when it fails badly, to protect downstream tables.	Quality gate	A missing column blocks the whole file.	Data quality

3.8 Data governance

Term	Definition	Source / column	Quality rule	Owner
Data governance	The rules, roles and processes that keep data trusted, secure and used consistently.	This document and Unity Catalog	Owners named for every dataset.	Data governance
Business glossary	A shared dictionary of business terms with one agreed definition, an owner and a link to the data.	This document	Reviewed when a term changes.	Data governance
Data dictionary	Technical description of tables and columns: names, types and rules.	Section 4 of this document	Matches the real tables.	Data governance
Data owner	The person accountable for a dataset and its definitions.	Owner tag in Unity Catalog	Every table has one.	Data governance
Data steward	The person who looks after daily quality and answers questions about a dataset.	Steward tag in Unity Catalog	Named per source.	Data governance
PII	Personally identifiable information: name, email, phone number, IMEI.	Tag pii = true	Masked outside the secure layer.	Data governance
Certified table	A table whose definition, owner and quality are checked and approved for dashboards.	Gold tables	Only certified tables feed dashboards.	Data governance

4. Data dictionary by table

Technical view of every table and file. Types follow the Postgres definitions; file fields are shown with their expected type.

crm.plans | CRM, one row per plan, 20 plans

Column	Type	Business meaning	Rule
plan_id	SERIAL	Unique ID of the plan.	Primary key.
plan_name	TEXT	Commercial name of the plan.	Not empty.
monthly_fee	NUMERIC(8,2)	Monthly price in EUR.	Greater than 0.
data_gb	INT	Data allowance in GB per month.	Zero or more.
voice_minutes	INT	Voice allowance in minutes per month.	Zero or more.

crm.customers | CRM, one row per customer

Column	Type	Business meaning	Rule
customer_id	BIGSERIAL	Unique ID of the customer in CRM.	Primary key. No duplicates.
first_name, last_name	TEXT	Name of the customer.	PII. Masked in Silver.
email	TEXT	Contact email.	PII. Not empty. Trimmed and lowercase.
msisdn	TEXT	Mobile number, the cross-system key.	Format +316 and 8 digits.
city, country	TEXT, CHAR(2)	Home city and country code.	Country NL.
status	TEXT	Customer lifecycle state.	ACTIVE, SUSPENDED or CHURNED.
plan_id	INT	Current plan of the customer.	Must exist in crm.plans.
created_at, updated_at	TIMESTAMPTZ	When the row was created and last changed.	Not in the future.

crm.devices | CRM, one row per device

Column	Type	Business meaning	Rule
device_id	BIGSERIAL	Unique ID of the device row.	Primary key.
customer_id	BIGINT	Owner of the device.	Must exist in crm.customers.
imei	TEXT	15-digit handset identifier.	15 digits. PII.
model	TEXT	Handset model.	Not empty.
created_at	TIMESTAMPTZ	When the device was recorded.	Not in the future.

billing.accounts | Billing, one row per billing account

Column	Type	Business meaning	Rule
account_id	BIGSERIAL	Billing ID of the account. Differs from the CRM ID on purpose.	Primary key.
msisdn	TEXT	Mobile number linking the account to CRM.	Must match one CRM customer.
account_ref	TEXT	Readable account reference.	Format ACC-########.
status	TEXT	Account state, for example OPEN.	Not empty.
created_at, updated_at	TIMESTAMPTZ	When the row was created and last changed.	Not in the future.

billing.invoices | Billing, three monthly invoices per account

Column	Type	Business meaning	Rule
invoice_id	BIGSERIAL	Unique ID of the invoice.	Primary key.
account_id	BIGINT	Account that is billed.	Must exist in billing.accounts.
period_start, period_end	DATE	First and last day covered.	Start not after end.
total_amount	NUMERIC(10,2)	Total charged in EUR.	Not negative. Equals sum of lines.
status	TEXT	Invoice state, for example ISSUED.	Not empty.
issued_at	TIMESTAMPTZ	When the invoice was issued.	Not in the future.

billing.invoice_lines | Billing, charges on each invoice

Column	Type	Business meaning	Rule
line_id	BIGSERIAL	Unique ID of the line.	Primary key.
invoice_id	BIGINT	Invoice the line belongs to.	Must exist in billing.invoices.
line_type	TEXT	Kind of charge: PLAN_FEE, DATA_OVERAGE, VOICE or ROAMING.	Value in the allowed list.
description	TEXT	Readable text of the charge.	Not empty.
amount	NUMERIC(10,2)	Amount of the charge in EUR.	Not negative.

billing.payments | Billing, payments received

Column	Type	Business meaning	Rule
payment_id	BIGSERIAL	Unique ID of the payment.	Primary key.
invoice_id	BIGINT	Invoice that was paid.	Must exist in billing.invoices.
amount	NUMERIC(10,2)	Amount paid in EUR.	Equals the invoice total.
method	TEXT	CARD, SEPA or IDEAL.	Not empty.
status	TEXT	Payment state, for example PAID.	Not empty.
paid_at	TIMESTAMPTZ	When the payment was received.	Not in the future.

network cdr_YYYYMMDD.csv | Network, one file per day, about 5000 rows

Column	Type	Business meaning	Rule
cdr_id	TEXT	Unique ID of the event.	Unique.
msisdn	TEXT	Subscriber that used the service.	Must exist in CRM.
event_type	TEXT	VOICE, SMS or DATA.	One of the three values.
event_ts	TIMESTAMP	When the event started.	Not in the future.
duration_sec	INT	Length in seconds.	Number, zero or more.
data_mb	DECIMAL	Data volume in MB.	Zero or more.
cell_id	TEXT	Radio tower that served the event.	Not empty.
call_result	TEXT	COMPLETED or DROPPED.	One of the two values.

app.events (JSON) | Mobile app, streamed through Kafka

Column	Type	Business meaning	Rule
event_id	TEXT	Unique ID of the event.	Unique.
customer_id	BIGINT	Customer who did the action.	Not empty. Must exist in CRM.
event_type	TEXT	login, view_bill, topup, crash or plan_change.	Value in the allowed list.
app_version	TEXT	App release that sent the event.	Not empty.
event_ts	TIMESTAMP	When the action happened.	Not in the future.

partner_usage_YYYYMM.csv | Partner, one file per month

Column	Type	Business meaning	Rule
partner_record_id	TEXT	Unique ID of the partner record.	Unique.
msisdn	TEXT	Subscriber that used the partner network.	Must exist in CRM.
service	TEXT	ROAMING or INTL_CALL.	One of the two values.
amount	DECIMAL	Amount charged by the partner.	Not negative.
currency	TEXT	Currency of the amount.	EUR.
period_start	DATE	First day of the billing month.	Valid date.

5. Quality rule catalogue

Rule	Dataset	Rule statement	Dimension	Action on failure
R01	crm.customers	MSISDN matches +316 plus 8 digits	Validity	Auto-fix 06xxxxxxx; reject others
R02	crm.customers	Email is present	Completeness	Flag or reject
R03	crm.customers	Email is trimmed and lowercase	Validity	Auto-fix
R04	crm.customers	Status is ACTIVE, SUSPENDED or CHURNED	Domain values	Reject
R05	crm.customers	created_at is not in the future	Timeliness	Reject
R06	crm.customers	No two customers share the same MSISDN and email	Uniqueness	Deduplicate in Silver
R07	billing.invoices	Total amount is not negative	Validity	Reject
R08	billing.invoices	Total is within the normal range	Distribution	Alert
R09	billing.payments	Method is present	Completeness	Flag
R10	network cdr	cdr_id is unique	Uniqueness	Deduplicate
R11	network cdr	duration_sec is a number and not negative	Validity and schema	Quarantine or reject
R12	network cdr	cell_id is present	Completeness	Flag
R13	network cdr	event_ts is not in the future	Timeliness	Reject
R14	network cdr file	Daily file arrives on time	Freshness	Incident
R15	network cdr file	Row count is within normal bounds	Volume	Incident
R16	network cdr file	Columns match the contract	Schema	Block file or alert on new column
R17	app.events	customer_id is present and exists in CRM	Completeness and consistency	Reject or incident
R18	app.events	event_type is in the allowed list; event_id is unique	Domain values and uniqueness	Reject or deduplicate
R19	partner usage	Amount is not negative; currency is EUR; record ID is unique	Validity, domain, uniqueness	Reject or deduplicate
R20	CRM vs billing	Every customer has one billing account and the reverse	Consistency	Incident
R21	invoices vs lines	Invoice total equals the sum of its lines	Accuracy	Incident
R22	invoices vs plans	Billed plan fee equals the CRM monthly fee	Accuracy	Incident
R23	payments vs invoices	Every payment has an invoice and equals its total	Accuracy and consistency	Incident
R24	network and partner vs CRM	Every MSISDN in usage files exists in CRM	Consistency	Incident

6. Open items

1. Replace the suggested team names with real owners and stewards.
2. Confirm the ARPU formula and the period used with Finance.
3. Confirm the freshness SLA time for each daily and monthly file.
4. Copy the definitions into Unity Catalog as table and column comments, and tag PII and owners.
5. Review the glossary whenever a data contract changes version.