

ROOM FINISH SCHEDULE

309		ΙI		101		MARK	
FAN LOFT	PENTHOUSE	UPPER LEVEL	CONTAINMENT CELLS	LAB 101	LOWER LEVEL		BUYN MOON
CONC	CONC		CONC	CONC		MATERIAL	<u> </u>
CONC	CONC		SEAL	_		FINISH	100 R0
1	1			RB		WALL BASE	
PANELS	WALL PANELS		CMU	CMU		MATERIAL	W A
1	ı		PT	PT		FINISH	BALLS
EXP	EXP		EXP	SAC		MATERIAL	
1	1		PI	ı		FINISH	
1	1		1	8'-6"		HEIGHT	
1	1		SEAL EXPOSED CONCRETE FLOOR PAINT EXPOSED CONC. LID TO MATCH CMU WALLS	PAINT ALL CMU WALLS			REMARKS

EX100 3'-0" x 7' EX101 3'-0" x 7' EX102 1'-8" x 7' EX104 3'-0" x 7' EX104 3'-0" x 7' EX200 3'-0" x 7' EX202 3'-0" x 7' EX202 3'-0" x 7' EX202 3'-0" x 7' 300 4'-6" x 8' 309 3'-0" x 7' 310 3'-0" x 7' MARK

DOOR

AND FRAME

SCHEDULE

				2		8		4)3		<u> </u>		ŏ	Ш		
3'-0" × 7'-0"	3'-0" × 7'-0"	4'-6" x 8'-0" PAIR	FAN LOFT AND PENTHOUSE	3'-0" × 7'-0"	3'-0" × 7'-0"	3'-0" × 7'-0" PAIR	UPPER LEVEL	3'-0" x 7'-0" PAIR	3'-0" x 7'-0" PAIR	× 7.	×	3'-0" x 6'-8"	3'-0" x 7'-0" PAIR	LOWER LEVEL		DOOR SIZE
-	I	ı		1	ı	ı		ı	ı	ı	ı	ı	ı		TYPE	<u></u>
¥	¥	¥		MH	MH	MH		MH	НМ	MH	MH	MH	HM		MATERIAL	
٦	₽	₽		Р	Р	Р		Р	Ρ	Р	Р	Р	Ρ		FINISH	
ı	ı	ı		-	-	١		١	-	١	١	-	-		TYPE	$\left\ \mathbf{C} \right\ $
¥	M	₹		MH	¥	¥		¥	НМ	¥	¥	ΗM	HM		MATERIAL	DOOR
Ъ	₽	₽		Р	ס	P		٦	Р	٦	٦	ס	Р		FINISH	
_	ı	_		-	_	ı		ı	1	ı	ı	_	ı		HARDWARE	
ı	ı	ı		١	ı	ı		ı	ı	ı	ı	ı	-		HEAD	
ı	ı	ı		-	-	-		-	-	-	-	-	_		JAMB	STALB
ı	I	ı		-	-	-		-	-	-	-	-	_		THRESHOLD	
1	I	ı		_	_	_		1HR	1HR	_	1HR	_	_		FIRE RATING	
I	FIELD VERIFY LOCATION	4 PAIR HINGES AND REMOVABLE MULLION		EXISTING DOOR AND HARDWARE	SIGN	EXG. DOOR AND HARDWARE, ADD 1-HR. DOOR LABEL		EXG. DOOR AND HARDWARE, ADD 1-HR. DOOR LABEL	EXG. DOOR AND HARDWARE, ADD 1-HR. DOOR LABEL	EXISTING DOOR AND HARDWARE	EXG. DOOR AND HARDWARE, ADD 1-HR. DOOR LABEL	1	EXISTING DOOR AND HARDWARE			REMARKS

6'-8", 7'-0" OR 8'-0" FRAME/DOOR TYPE LOW METAI / PAINT 6'-8", 7'-0" OR 8'-0" METAL / PAINT

HARDWARE SET NUMBERS
DOORS 101 AND 201

1 CLOSER
EXIT DEVICE
THRESHOLD
WEATHER STRIPPING
PULL HANDLE
DOOR CONTACT TO SECURITY
LOCKSET

ALL DOORS SCHEDULED SHALL HAVE A TACTILE SIGN, INCLUDING RAISED LETTERS AND BRAILLE, SIGN SHALL BE 4" CLEAR FROM EDGE OF DOOR JAMB AND 48" A.F.F., BRAILLE DESIGNATION AT THESE DOORS SHALL NOT EXCEED 42" A.F.F.

PROVIDE SIGN ABOVE DOOR EX100 AND EX200 WITH 1" HIGH BLACK LETTERS ON WHITE BACKGROUND TO READ "THIS DOOR TO REMAIN UNLOCKED WHEN BUILDING IS OCCUPIED" IBC 1008.1.8.3. THESE DOORS SHALL BE OPENABLE FROM THE INSIDE WITHOUT THE USE OF KEY OR SPECIAL KNOWLEDGE OR EFFORT. THE UNLATCHING OF ANY DOOR SHALL NOT REQUIRE MORE THAN ONE OPERATION PER IFC SECTION 1003.3.1.8

COORDINATE ALARM REQUIREMENTS WITH OWNER

COORDINATE HARDWARE TYPE AND FINISH WITH OWNER

DOOR JAMB ANCHOR CLIPS SHALL BE BOLTED OR SCREWED TO STUDS: THREE PER FRAME.

ROOM FINISH NOTES

PAINTING CONTRACTOR SHALL EXAMINE ALL SURFACES AFTER COMPLETION OF WORK OF ALL TRADES AND PROVIDE NECESSARY "TOUCH UP" PAINTING AND PATCHING. HE SHALL IMMEDIATELY REMOVE ANY PAINT SPILLAGE OR SPLATTER.

ALL PAINTING WORK SHALL BE DONE BY SKILLED MECHANICS USING EITHER BRUSHES OR ROLLERS. POOR WORKMANSHIP WILL NOT BE ACCEPTED. ALL MATERIALS SHALL BE EVENLY SPREAD, SMOOTHLY FLOWED ON AND FREE FROM RUNS, SACS, CRAWLINGS OR OTHER DEFECTS. FINISHED SURFACES SHALL BE UNIFORM IN COLOR, GLOSS, SHEEN AND MATTE FINISH AND FREE FROM BRUSH MARKS, BRISTLES, LINT OR DUST PIMPLES.

VINYL TILE AREAS SHALL HAVE 4" RESILIENT COVE BASE

FRAMING AND GYPSUM BOARD NOTES PRIME AND PAINT ALL WALLS AS SPECIFIED.

FURR-OUT AROUND THE STRUCTURAL COLUMNS AS REQUIRED AND NOTED.

PROVIDE SOLID BLOCKING FOR DOORS, WINDOWS, TOILET PARTITION, ACCESSORIES, HANDRAILS, LAVATORY BRACES, ETC. AS REQUIRED BY MANUFACTURER AND ALL WORK DONE BY CARPENTRY AND MILLWORK TRADES. ALL WOOD REQUIRED BY BUILDING CODES SHALL MEET ALL REQUIREMENTS TO THE CODE OF UNDERWRITERS LABORATORIES, INC. VERIFY THE DEPTH OF WALLS PRIOR TO INSTALLING RECESSED FIXTURES.

ALL EXPOSED EDGES AND / OR CORNER ON ALL GYPSUM WALL BOARD CONSTRUCTION SHALL HAVE A METAL CORNER TRIM, TAPED AND SPACKLED. GYPSUM BOARD CONSTRUCTION AND ACCESSORIES SHALL BE LEFT IN A CLEAN AND SATISFACTORY CONDITION SUITABLE FOR PAINTING.

ALL NEW GYPSUM BOARD PARTITIONS TO BE PROPERLY PREPARED, PATCHED, SPACKLED AND SANDED, ETC., TO PROVIDE A SMOOTH FINISH AND AS REQUIRED TO RECEIVE NEW FINISHES.

CG Ction

DWG. FILE:

DATE:

TIME: LAYOUT:

ACAD VERSION:

PLATFORM:

A/E APPROVED BY

ВΥ

ral Integrity

ENGINEER

CHECKED BY



sst Research Institute • Battelle • Bechtel ##### NREL PROJECT NO. EX2010034	Department of Energy Table Table	Energy Laboratory		THERMO-CHE
---	---	-------------------	--	------------

REVISION NO.	DRAWING NO. A-02	PRAWING NO. PREFIX FTLB—135—
Ξ	TASK ORDER 13 LAB 269 UPPER LEVEL	LAE
ARC 101 CONVERSION	LABORATORY 101	THERMO-CHEM LABORATORY