



Handling Keyboard Inputs and Mouse Inputs

Window Properites

- `glutFullScreen();`
 - To Put window into full screen.
- `glutReshapeWindow(windowWidth, windowHeight);`
 - To change the width and height of the window.
- `glutPositionWindow(windowPosX, windowPosY);`
 - To change window position.

Handling Keyboard Inputs

- We can register callback functions to handle keyboard inputs for **normal and special keys**.
- **glutKeyboardFunc**: registers callback handler for keyboard event.
- **glutSpecialFunc**: registers callback handler for special key (such as arrow keys and function keys).

Handling Keyboard Inputs

glutKeyboardFunc

- glutSpecialFunc(**specialKeys**);
- void specialKeys(int key, int x, int y)
 - **key** : GLUT_KEY_* (* for LEFT, RIGHT, UP, DOWN, HOME, END, PAGE_UP, PAGE_DOWN, F1,...F12).
 - (**x, y**) is the mouse location in Windows' coordinates

Handling Keyboard Inputs

glutSpecialFunc

- glutKeyboardFunc(**keyboard**);
- void keyboard(unsigned char key, int x, int y) .
 - **key** is the char pressed, e.g., 'a' or 27 for ESC
 - **(x, y)** is the mouse location in Windows' coordinates

Handling Mouse Inputs

- we can register callback function to handle **mouse-click** and **mouse-motion**.
- **glutMouseFunc**: registers callback handler for mouse click..
- **glutMotionFunc**: registers callback handler for mouse motion (**when the mouse is clicked and moved**).

Handling Mouse Inputs

glutMouseFunc

- glutMouseFunc(mouse);
- void mouse(int button, int state, int x, int y)
 - button : GLUT_LEFT_BUTTON, GLUT_RIGHT_BUTTON, GLUT_MIDDLE_BUTTON.
 - state : GLUT_UP, GLUT_DOWN.
 - (x, y) is the mouse-click location.

Handling Mouse Inputs

glutMotionFunc

- glutMotionFunc(motion);
- void motion(int x, int y)
 - (x, y) is the mouse location in Window's coordinate.