

AI 3000 : REINFORCEMENT LEARNING

ASSIGNMENT No 1

DUE DATE : 10/09/2025

Easwar Subramanian, IIT Hyderabad

25/08/2025

Problem 1 : Markov Reward Process

Consider the following snake and ladders game as depicted in the figure below.




Figure 1: A Simple Snake and Ladder Problem

- Initial state is S and a fair four sided dice is used to decide the next state at each time
- Player must land exactly on state W to win
- Dice throw that take you further than state W leave the state unchanged

- (a) Identify the states, transition matrix of this Markov process. (2 points)
- (b) Construct a suitable reward function, discount factor and use the Bellman equation for the Markov reward process to compute how long does it take "on average" (the expected number of dice throws) to reach the state W from any other state. (3 points)

Problem 2 : Effect of Noise and Discounting

Consider the grid world problem shown in Figure 2. The grid has two terminal states with positive payoff (+1 and +10). The bottom row is a cliff where each state is a terminal state with negative payoff (-10). The greyed squares in the grid are walls. The agent starts from the yellow state S . As usual, the agent has four actions $\mathcal{A} = (\text{Left, Right, Up, Down})$ to choose from any non-terminal state and the actions that take the agent off the grid leaves the state unchanged. Notice that, if agent follows the dashed path, it needs to be careful not to step into any terminal state at the bottom row that has negative payoff. There are four possible (optimal) paths that an agent can take.

- Prefer the close exit (state with reward +1) but risk the cliff (dashed path to +1)

- (a) Let $\hat{M} = \langle \mathcal{S}, \mathcal{A}, \mathcal{P}, \hat{\mathcal{R}}, \gamma \rangle$ be another infinite horizon MDP with a modified reward function $\hat{\mathcal{R}}$ such that

$$\mathcal{R}(s, a, s') - \hat{\mathcal{R}}(s, a, s') = \varepsilon$$

where ε is a constant independent of $s \in \mathcal{S}$ or $a \in \mathcal{A}$. Given a policy π , let V^π and \hat{V}^π be value functions of policy π for MDPs M and \hat{M} respectively. Derive an expression that relates $V^\pi(s)$ to $\hat{V}^\pi(s)$ for any state $s \in \mathcal{S}$ of the MDP. (3 Points)

- (b) Does M and \hat{M} have the same optimal policy ? Explain. (3 Points)
- (c) State and prove an analogous result for the sub-question (a) for the case when M and \hat{M} are finite horizon MDPs with horizon length $H < \infty$. (4 Points)
- (d) Now, consider an indefinite MDP or a stochastic shortest path MDP where the horizon length H can vary. A subset of the state space $S_{\text{term}} \subset \mathcal{S}$ is considered terminal if a trajectory of the form $s_0, a_0, r_1, s_1, a_1, r_2, \dots$, keeps rolling out until a terminal state $S_H \in S_{\text{term}}$ is visited. In general, the length of the episode H is a random variable. Does the analogous result of sub-question (a) hold when M and \hat{M} are indefinite MDPs ? Explain. (4 Points)
- (e) For this sub-question let $\hat{M} = \langle \mathcal{S}, \mathcal{A}, \mathcal{P}, \hat{\mathcal{R}}, \gamma \rangle$ be a infinite horizon MDP with a modified reward function $\hat{\mathcal{R}}$ such that

$$\left| \mathcal{R}(s, a, s') - \hat{\mathcal{R}}(s, a, s') \right| \leq \varepsilon$$

where ε is a constant independent of s and a . Derive an expression that relates the optimal value functions $V_*(s)$ and $\hat{V}_*(s)$. Would M and \hat{M} have the same optimal policy ? Explain. (6 Points)

Problem 4 : Programming Value and Policy Iteration

Implement value and policy iteration algorithm and test it on '**Frozen Lake**' environment in openAI gym. '**Frozen Lake**' is a grid-world like environment available in gym. The purpose of this exercise is to help you get hands on with using gym and to understand the implementation details of value and policy iteration algorithm(s)

This question will not be graded but will still come in handy for future assignments.

ALL THE BEST