



DODO Learning: Domain-Demographic Transfer in Language Models for Detecting Abuse Targeted at Public Figures

Hannah Rose Kirk^{*1,2}, Angus R. Williams^{*1}, Liam Burke¹, Yi-Ling Chung¹, Ivan Debono¹, Pica Johansson¹, Francesca Stevens¹, Jonathan Bright¹, and Scott A. Hale^{1,2}

¹The Alan Turing Institute, London, UK

²Oxford Internet Institute, University of Oxford, Oxford, UK

Abstract

Public figures receive a disproportionate amount of abuse on social media, impacting their active participation in public life. Automated systems can identify abuse at scale but labelling training data is expensive, complex and potentially harmful. So, it is desirable that systems are efficient and generalisable, handling both shared and specific aspects of online abuse. We explore the dynamics of cross-group text classification in order to understand how well classifiers trained on one domain or demographic can transfer to others, with a view to building more generalisable abuse classifiers. We fine-tune language models to classify tweets targeted at public figures across Domains (sport and politics) and Demographics (women and men) using our novel DODO dataset, containing 28,000 labelled entries, split equally across four domain-demographic pairs. We find that (i) small amounts of diverse data are hugely beneficial to generalisation and model adaptation; (ii) models transfer more easily across demographics but models trained on cross-domain data are more generalisable; (iii) some groups contribute more to generalisability than others; and (iv) dataset similarity is a signal of transferability.

Content Warning: We include some synthetic examples of the dataset schema to illustrate its contents.

Data Release Statement: Due to institutional guidelines concerning privacy issues surrounding the release of Twitter data, we are unable to release the DODO dataset.

1 Introduction

Civil discussion between public figures and citizens is a key component of a well-functioning democratic society (Dewey, 1927; Rowe, 2015; Papacharissi, 2004). Social media has opened

new channels of communication and permitted greater access between users and public figures (Doidge, 2015; Ward and McLoughlin, 2020); becoming an important tool for self-promotion, message spreading and maintaining a dialogue with fans, followers or the electorate (Farrington et al., 2014), beyond traditional media gatekeeping (Coleman, 1999, 2005; Coleman and Spiller, 2003; Williamson, 2009). However, there is a cost: the immediacy, ease and anonymity of online interactions has routinised the problem of abuse (Suler, 2004; Shulman, 2009; Brown, 2009; Joinson et al., 2009; Rowe, 2015; Ward and McLoughlin, 2020). Public figures attract more intrusive and abusive attention than average users of online platforms (Mullen et al., 2009; Meloy et al., 2008), and abuse directed towards them is both highly-public yet often grounded in highly-personal attacks (Erikson et al., 2021). There are detrimental effects both to individual victims’ mental health, which can ultimately result in their withdrawal from public life (Vidgen et al., 2021a; Delisle et al., 2019), and to society as a whole from normalising a culture of abuse and hate (Ingle, 2021). Disengagement is particularly worrisome for the functioning of democracy and political representation as it might be spread unevenly across different groups (Theocharis et al., 2016; Greenwood et al., 2019; Ward and McLoughlin, 2020), for example female representatives being more likely to give up on politics than their male counterparts (Manning and Kemp, 2019).

Tackling abuse against public figures is a pressing issue, but the volume of social media posts makes manual investigations challenging, and conclusions drawn from anecdotal self-reporting or small sample size surveys offer limited and potentially biased coverage of the problem (Ward and McLoughlin, 2020). Automated systems based on machine learning or language models can be used to classify text at scale, but depend on la-

^{*}Equal contribution.

labelling training data which is complex, expensive to collect and potentially psychologically harmful to annotators (Kirk et al., 2022c).

In this context, it is highly desirable to develop general abuse classifiers that can perform well across a range of different abuse types whilst being trained on a minimal ‘labelling budget’. However, this may be technically challenging because, while some properties of abuse are shared across settings, different *domains* (e.g., sport, politics or journalism) introduce linguistic and distributional shifts. Furthermore, previous reports reveal that the nature of online abuse is heavily influenced by the identity attributes of its targets, for example gendered abuse against female politicians (Bardall, 2013; Stambolieva, 2017; Erikson et al., 2021; Delisle et al., 2019); so, learnings from different *demographics* may also not transfer.

Despite the promise of generalisable abuse models for protecting more groups from harm, only a limited amount of research has addressed the extent to which models trained in one context can transfer to another. In this paper, we ask how well classifiers trained on one domain or demographic transfer to others, with a view to building more generalisable models that achieve high performance on areas they have been exposed to during training but also perform well on those they have not seen until inference time. Our novel DoDo dataset is collected from Twitter and contains tweets targeted at public figures across two Domains (UK members of parliament or “MPs” and professional footballer players) and Demographic groups (women and men). Tweets are annotated with four fine-grained labels to disambiguate abuse from other sentiments like criticism. We present results from experiments exploring the impacts of data diversity and quantity on domain-demographic transfer and generalisability.

2 Dataset

2.1 Data Collection

Our data is collected from Twitter. While generally over-researched (Vidgen and Derczynski, 2020), Twitter is a dominant source for interactions between public figures and the general public in the United Kingdom. Most MPs have Twitter accounts and Twitter activity may even have a small impact on elections (Bright et al., 2020).

We compile lists of accounts for UK MPs (590 accounts, 384 men, 206 women) and for players

from England’s top football divisions (808 from the Men’s Premier League, 216 from the Women’s Super League). We use the streaming endpoint of v1.1 Twitter API to collect all tweets directed at these accounts (which we label as “audience contact” tweets) in real-time into an unlabelled pool (see Table 1). We define “audience contact” as i) replies directly to a public figure, or ii) top-level tweets that mention a public figure.¹ For women footballers, we also use the full-archive search endpoint due to insufficient real-time data. We only retain tweets in English that contain some text content aside from URLs and tagged mentions of Twitter users.

2.2 Data Sampling

Levels of abusive content ‘in-the-wild’ are relatively low (Vidgen et al., 2019). In order to evaluate classifiers on realistic distributions while maximising the ability of those classifiers to detect abusive content, we randomly sample the test and validation datasets (preserving real-world class imbalance) but apply boosted sampling for the training dataset (ensuring the model sees enough instances of the rarer abusive class). For each domain-demographic pair, starting with our unlabelled pool, we randomly sample (and remove) 3,000 entries for the test set and 1,000 entries for the validation set. We then randomly sample (and remove) 1,500 entries for training and concatenate these with a further 1,500 entries containing a keyword from a list of 731 abusive and hateful keywords (750 entries with at least one profanity keyword and 750 with at least one identity keyword).² Each training set has 3,000 entries in total.

2.3 Data Annotation

We employ crowdworkers and expert annotators to label the sampled datasets.³ There are 4 classes of sentiment expressed towards public figures: Positive, Neutral, Critical, or Abusive, as defined below.⁴ Figure 1 contains synthetic example tweets across domain-demographic pairs and classes.

¹A similar approach is adopted in prior work that tracks public figure abuse (Gorrell et al., 2020; Ward and McLoughlin, 2020; Rheault et al., 2019).

²Compiled from Davidson et al. (2017); ElSherief et al. (2018); Vidgen et al. (2021b); Kirk et al. (2022b), available at github.com/Turing-Online-Safety-Codebase/dodo-learning.

³A data statement (Bender and Friedman, 2018) is available in the [dodo-learning](https://github.com/Turing-Online-Safety-Codebase/dodo-learning) repository.

⁴Labels are assigned based on the use of language, not the target of sentiment expressed.

Domain	Demographic	Pool Size	Collection Dates		Collection Method	
			Start	End	Streaming	Search
Footballers	Men	1,008,399	12/08/2021	02/02/2022	✓	
	Women	226,689	13/08/2021	28/11/2022	✓	✓
MPs	Men	1,000,000	13/01/2022	19/09/2022	✓	
	Women	1,000,000	13/01/2022	19/09/2022	✓	

Table 1: Dates and pool sizes for each domain-demographic pair.

	Positive	Neutral	Critical	Abusive
Footballers Men	[PLAYER] [USER] CR7 GOAT!!	[PLAYER] puts [CLUB] 1-0 up against [CLUB] [URL] #goal	It wouldn't be so hard to watch [CLUB] if [PLAYER] didn't bottle it every time #coys	[PLAYER] get out of my club shithhead
Footballers Women	Love you you absolute beast [PLAYER]	[PLAYER] You'll get used to the cold eventually!	[PLAYER] who keeps telling you you should be taking pens, it's painful to watch	[PLAYER] fuck off
MPs Men	[MP] great speech sir	Does anyone else think [MP] and [MP] look strangely similar? #doppelganger	[MP] Why should anyone believe you when everything you say gets proven to be a lie?	[MP] Who the fuck voted you in scumbag #corrupt
MPs Women	[MP] you're one of the good ones	[MP] [USER] Take a look at the report shared by [MP], pretty stark numbers	[MP] good one, talk about dignity when you and your colleagues spent it all on filling your own pockets...	[MP] Turns out this bitch is blind as well as stupid

Figure 1: Synthetic example tweets for each class label, loosely based on topics and sentiment of content in the dataset. Entries from the dataset are presented to annotators as shown, with special tokens to represent tagged mentions of public figures, accounts representing affiliations (e.g., football clubs), and other users.

1. **Positive:** Language that expresses support, praise, respect or encouragement towards an individual or group. It can praise specific skills, behaviours, or achievements, as well as encourage diversity and the representation of identities.
2. **Neutral:** Language with an unemotive tone or that does not fit the criteria of the other three categories, including factual statements, event descriptions, questions or objective remarks.
3. **Critical:** Language that makes a substantive negative assessment or claim about an individual or group. Negative assessment can be based on factors such as behaviour, performance, responsibilities, or actions, without being abusive.⁵
4. **Abusive:** Language containing threats, insults, derogatory remarks (e.g., hateful use of slurs and negative stereotypes), dehumanisation (e.g., comparing individuals to insects, animals, or trash), mockery, or belittlement towards an individual, group, or protected identity attribute.

We use two different sets of annotators across the two domains, as we annotated the sets sequentially, and found high rates of annotator disagreement in initial annotation rounds, with a large

⁵The annotator guidelines focused on distinguishing between abuse and criticism. Criticism must include a rationale for negative opinions on an individual's actions (not their identity)—it is not a form of “soft” abuse.

number of entries requiring expert annotation as a result. We use the same label schema for all domain and demographic pairs but use specific example tweets in the guidelines. We only employ annotators who pass a test of gold questions.

We employed 3,375 crowdworkers for male footballers and 3,513 for female footballers. Each entry was annotated by 3 crowdworkers, with an additional two annotations required if no majority agreement ($\frac{2}{3}$) was reached, then sent for expert annotation if still no majority agreement ($\frac{3}{5}$) was reached. The average annotator agreement per entry was 68%, and the Cohen's kappa was 0.50.⁶

We employed 23 high-quality annotators for both MP datasets. Each entry received 3 annotations, then was sent for expert annotation if no majority agreement was reached ($\frac{2}{3}$). The average entry-wise agreement was 82% and the Cohen's kappa was 0.67.

2.4 Analysis

Terminology We abbreviate pairs of domain-demographic data as: fb-m (footballers-men), fb-w (footballers-women), mp-m (MPs-men), mp-w (MPs-women). We refer to any given domain-demographic pair as a *dodo*. We refer to groups of models that we train by the number of *dodos*

⁶Calculated using the generalised formula from [Gwet \(2014\)](#) to account for variable # of annotations per entry.

Split	Stance	dodo			
		fb-m	fb-w	mp-m	mp-w
Train	Abusive	867 29%	481 16%	1007 34%	870 29%
	Critical	475 16%	282 9%	1283 43%	1353 45%
	Neutral	647 21%	719 24%	605 20%	628 21%
	Positive	1011 34%	1518 51%	105 3%	149 5%
Test	Abusive	103 3%	43 1%	392 13%	373 12%
	Critical	377 13%	89 3%	1467 49%	1471 49%
	Neutral	811 27%	767 26%	985 33%	927 31%
	Positive	1709 57%	2101 70%	156 5%	229 8%
Validation	Abusive	33 3%	14 1%	140 14%	135 13%
	Critical	93 9%	45 5%	484 48%	459 46%
	Neutral	335 34%	267 27%	332 33%	337 34%
	Positive	539 54%	674 67%	44 4%	69 7%
Random	Abusive	181 3%	75 1%	744 13%	661 12%
	Critical	642 12%	197 4%	2676 49%	2676 49%
	Neutral	1677 30%	1466 27%	1788 33%	1741 32%
	Positive	3000 55%	3762 68%	292 5%	422 7%

Table 2: Tweet counts across splits, dodos, and stances, with percentages within the dodo split. Includes counts and percentages for tweets from all splits selected by random sampling before annotation (5,500 tweets total per dodo).

included in the training data: dodo1 for models trained using one domain-demographic pair, dodo2 for models trained using two pairs, etc.

Overview The total dataset has 28,000 annotated entries, 7,000 for each dodo pair, with 3K/3K/1K test/train/validation splits. Table 2 shows class distributions across splits and counts of tweets sampled randomly pre-annotation.

Class Distributions The last row of Table 2 contains the randomly sampled entries across each dataset (ignoring keyword sampled entries which would skew the distributions). The majority of tweets in the MPs datasets are either abusive or critical, in contrast to the footballers datasets where the majority class is positive, especially for fb-w. We also see slightly higher proportions of abusive tweets targeted at male demographic groups (fb-m, mp-m). Investigating these differences is outside the scope of this paper, but it is notable how levels of abuse vary.

Tweet Length The MPs data contains longer tweets on average than the footballers data (125 vs. 84 characters), and has over twice as many tweets ≥ 250 characters (1,632 vs. 556 tweets). Many of these longer tweets for MPs are critical, implying the presence of detailed political debate.

3 Experiments

We conduct experiments to study how well model performance transfers across domains and demographics, and how the quantity and diversity of

training data affects model generalisability. To reflect the focus on generalisability, we evaluate models on: (i) “seen” dodos (dodos used in training); (ii) “unseen” dodos (dodos not used in training)⁷; and (iii) the total evaluation set (including evaluation splits from all dodos). We train models on data from combinations of dodo pairs, and experiment with continued fine-tuning on the resulting models. We repeat experiments across 3 random seeds and 2 labelling budgets. We make predictions using the total test set (12,000), and calculate mean and standard deviation of Macro-F1 across the seeds. The Macro-F1 score represents a macro-average of per class F1 scores, accounting for class imbalance. We also investigate the correlation of Macro-F1 with dataset similarity.

Models We fine-tune deBERTa-v3 (deBERT, He et al., 2021) on a Tesla K80 GPU for 5 epochs with an early stopping patience of 2 epochs using Macro-F1 on the validation set.⁸

Dodo Combinations Our dataset has four dodo pairs, each with 3,000 training entries. There are 15 combinations of these pairs (if order does not matter): four single pairs (dodo1), six ways to pick two pairs (dodo2), four ways to pick three pairs (dodo3) and all pairs (dodo4). For all combinations, we randomly shuffle the concatenated training data before any training commences.

Labelling Budget For each model and training combination, we make two budget assumptions. In the **full budget** condition, we just concatenate the training sets: 3,000 training entries for dodo1 experiments; 6,000 for dodo2 experiments; 9,000 for dodo3; and 12,000 for dodo4. In the **fixed budget** condition, we assume the train budget is fixed at 3,000 entries and allocate ratios according to the dodo combinations: each included dodo makes up 100% of the budget for dodo1 experiments; 50% for dodo2; 33% for dodo3; and 25% for dodo4. This allows us to test the effects of training data composition without confounding effects of its size.

⁷All test sets are fully held out from training—by “seen” and “unseen” we only mean the domain or demographic.

⁸We also ran experiments on distilBERT (Sanh et al., 2019), but deBERTa-v3 had consistently higher performance, therefore we only present results for deBERTa-v3.




Figure 2: Performance of models trained on different `dodo` combinations and evaluated on the total test set (Macro-F1 averaged across seeds). We show both the fixed (train size = 3,000) and full budget (train size = 3,000 · number of `dodos`). The lines indicate which `dodo` is added at each step. Starting from the initial `dodo1` models, the progression of fixed budget models goes to the left, and full budget models to the right. To get from a `dodo1` model to a `dodo4` model requires an additional `dodo` to be added 3 times, meaning a line representing a journey from `dodo1` to `dodo4` will consist of 3 different coloured/patterned lines.

4 Results

4.1 Small amounts of diverse data are hugely beneficial to generalisable performance.

Figure 2 provides an overview of the performance of models trained on all combinations of `dodo` data. It illustrates that the increase in performance from adding data from new domains or demographics is not linear: the full budget `dodo2` models only attain a one percentage point (pp) average increase in Macro-F1 Score for an additional 3,000 training entries. We also see the two `dodo4` models are only separated by 3pp despite the full budget version being exposed to 4 times the amount of training data as the fixed budget version. This shows that gains from data diversity outweigh those from significantly greater quantities of data in training generalisable models.

4.2 Cross-demographic transfer is more effective than cross-domain.

Table 3 shows the comparisons for domain transfer and demographic transfer by Macro-F1 score on the seen and unseen portions of the test set, using

Train on	Test on			
	Seen		Unseen	
fb-m; fb-w	Footballers	0.67	MPs	0.59
mp-m; mp-w	MPs	0.68	Footballers	0.56
fb-m; mp-m	Men	0.72	Women	0.72
fb-w; mp-w	Women	0.74	Men	0.70

Table 3: Cross-domain and cross-demographic transfer with mean Macro-F1 for `dodo2` models. We train on two `dodos` and evaluate on concatenated portions of the test set, e.g., we train *fb-w*; *fb-m* then test on *fb-w*; *fb-m* (seen) and *mp-m*, *mp-w* (unseen).

the `dodo2` models. For domain transfer, training on footballers gives a 0.65 F1 on the footballers dataset and 0.58 F1 on the MPs dataset. This is symmetric with training on MPs and testing on footballers. For demographic transfer, training on the male pairs and testing on female pairs faces no drop in performance. In contrast, training on women and testing on men leads to a small reduction in performance on the male data. In general, this demonstrates that transferring across domains is more challenging than transferring across demographics while keeping the domain fixed.




Figure 3: Mean and std-dev Macro-F1 across seeds for models trained on dodo combos, for fixed and full budgets, on test sets from seen and unseen dodos. *We removed one degenerate training seed ($s=2$).

4.3 Cross-domain within-demographic training produces more generalisable models than cross-demographic.

Figure 3 shows that, as expected, performance on test sets from seen dodo is generally higher than on those from unseen dodos. Within the dodo2 models, cross-demographic within-domain models (e.g., fb-m; fb-w) perform 10pp better on average on seen dodo evaluation sets than unseen ones, compared to a much narrower gap of 1pp on average for cross-demographic models (e.g., fb-w; mp-w). We also see from Figure 2 that cross-domain within-demographic dodo2 models outperform all cross-demographic within-domain dodo2 models on the total test set. These findings provide evidence that models trained on a single domain (e.g., just football data) struggle to deal with out-of-domain examples, and that cross-domain models are more generalisable.

4.4 Not all dodos contribute equally to generalisable performance.

The average Macro-F1 increase provided by including each dodo in training is summarised in Figure 4. We see that fb-m provides the biggest boost in a fixed budget scenario, and mp-w in a full budget scenario. In some cases, including fb-w data during training can detract from overall performance across both budget scenarios. A dodo1




Figure 4: Violin plot displaying distribution of change in Macro-F1 score when adding a dodo to the training data ($N=7$), with mean represented by red marker.

model trained only on fb-m also outperforms all other dodo1 models on the total test set (see Figure 2), and fb-m data is included in the training dataset for the top ranking model for each dodo size across both labelling budgets. These findings suggest that training with fb-m is more important for good model generalisation than other dodos.

We now consider the situation of leaving out one dodo pair during training. We compare this left out case (dodo3) to training on all pairs (dodo4) in Table 4. We show the change in Macro-F1 on the total test set and change in number of training entries. For the full budget, leaving out mp-w from training leads to the largest reduction in performance. In contrast, removing all fb-w or mp-m entries does not significantly degrade performance even with 3,000 fewer training entries. For the fixed budget setting (with no confounding by training size), leaving out the two male pairs leads to a larger drop in performance, than leaving out two female pairs.

	Raw size		Fixed size	
	$\Delta F1$	ΔN	$\Delta F1$	ΔN
all dodos	0.731	12,000	0.701	3,000
leave out fb-m	-0.006	-3,000	-0.001	0
leave out fb-w	-0.004	-3,000	0.007	0
leave out mp-m	-0.007	-3,000	0.005	0
leave out mp-w	-0.029	-3,000	-0.006	0

Table 4: Comparing model trained on all pairs (dodo4) with models trained on 3 pairs (dodo3). Shows relative change in mean Macro-F1 on total test set, and relative change in N of training entries.




Figure 5: Learning curves for starting with a dodo1 model trained on a single dodo pair and adding increments from the training set of a new dodo pair. We show mean and std-dev Macro-F1 (across 3 seeds) on the new adapt dodo and source start dodo at each increment.

	dodo1: fb_m				dodo1: fb_w				dodo1: mp_m				dodo1: mp_w				dodo4: all (fixed)				dodo4: all (full)											
True Stance	Positive	Neutral	Critical	Abusive	Positive	Neutral	Critical	Abusive	Positive	Neutral	Critical	Abusive	Positive	Neutral	Critical	Abusive	Positive	Neutral	Critical	Abusive	Positive	Neutral	Critical	Abusive								
Positive	3726	352	99	18	3756	397	22	20	2489	1419	193	94	2579	1220	268	128	3591	474	107	23	3713	379	82	21								
Neutral	476	2415	564	35	471	2791	183	45	156	2541	701	92	115	2511	757	107	330	2324	779	57	321	2471	646	52								
Critical	197	963	2067	177	319	1786	1069	230	62	628	2475	239	45	605	2525	229	86	560	2522	236	104	574	2526	200								
Abusive	32	133	277	469	80	217	143	471	3	87	226	595	5	62	274	570	16	82	269	544	19	82	233	577								
	Positive	Neutral	Critical	Abusive	Positive	Neutral	Critical	Abusive	Positive	Neutral	Critical	Abusive	Positive	Neutral	Critical	Abusive	Positive	Neutral	Critical	Abusive	Positive	Neutral	Critical	Abusive								
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive				Neutral				Critical				Abusive			
	Positive				Neutral				Critical				Abusive				Positive															

isting models generalise. The importance of data composition over data quantity aligns with the fixed/full budget findings from §4.1. On catastrophic forgetting, we generally do not find major performance drops. In some cases, adapting models to new data even helps classification in the source pair (e.g., mp-w to mp-m). Future work can explore where adaptation helps or hurts performance in source domains or demographics.




Figure 7: Jaccard similarity and mean 0-shot Macro-F1 for dodo1 deBERT models with line of best fit. On graph annotations represent evaluation dodo. Shows positive correlation ($\rho = 0.7$) and effectiveness of cross-demographic vs. cross-domain transfer.

4.6 Dataset similarity is a signal of transferability.

Using the specialist dodo1 models, we examine if dataset similarity signals transferability, i.e., the Macro-F1 score that a dodo1 model can achieve on unseen dodos. We compute three classical text distance metrics with unigram bag-of-words approaches: Jaccard and Sørensen-Dice similarity, and Kullback-Leibler divergence. In Figure 7, we plot Macro-F1 scores (of unseen single dodos) against Jaccard similarity for each pair of dodos. The correlation coefficient is 0.7, demonstrating a positive relationship between dataset similarity and unseen dodo performance.¹⁰ Greater similarity between demographic pairs versus domain pairs results in better cross-demographic transfer versus cross-domain transfer. Using these metrics could help estimate transfer potential before investing in an expensive labelling process.

¹⁰Correlation coefficients are 0.7 for Dice Similarity and -0.66 for KL Divergence, confirming Jaccard robustness.

4.7 Error Analysis

Analysing errors made by each dodo1 model reveals that the fb-m model performs best on positive tweets and less well on abusive tweets, with a similar pattern for the fb-w model (see Figure 6). The mp-m model performs best on critical tweets and less well on positive and neutral tweets, with a similar pattern for the mp-w model.

These errors reflect the class imbalance outlined in §2.4, as well as some inherent similarity between classes which border one another i.e., positive vs. neutral, neutral vs. critical, and critical vs. abusive, demonstrating the value of fine-grained labels for identifying model weaknesses. Recurring errors reveal several types of tweet that are challenging to classify: tweets that (i) contain a mixture of both positive and critical language; (ii) use positive or sarcastic language to mock; (iii) rely on emoji to convey abuse; (iv) contain niche insults; or (v) short, ambiguous tweets that lack context.

5 Discussion

5.1 Limitations

Targets of Abuse It is sometimes hard to disentangle the target of sentiment in tweets directed at public figures—some tweets praise public figures while simultaneously criticising another figure or even abusing identity groups (such as an praising an MP’s anti-immigration policy while abusing immigrants). Our label schema does not tag target-specific spans nor flag when it is a non-public figure account or abstract group is being abused. We also do not use further conversational context during annotation. Furthermore, we are limited by gender distinctions in UK MPs statistics and football leagues—the dataset does not cover non-binary identities or other identity attributes.

Types of Abuse While our dataset is more diverse than most abuse datasets in including four class labels, it does not disaggregate abusive content into further subcategories such as identity attacks. Our preliminary keyword analysis suggested that identity attacks comprise a relatively small proportion of all abuse (especially for female footballers) but can nonetheless cause significant harm. Further investigation on abuse across demographic groups is needed to understand how women and men are targeted differently, and to assess distributional shifts of specific homophobic,

racist, sexist or otherwise identity-based abuse.

Language and Platform Focus Our dataset contains English language tweets associated with UK MPs and the top football leagues in England (though players come from a variety of nationalities). Prior studies suggest politicians face online abuse in other countries (Theocharis et al., 2016; Ezeibe and Ikeanyibe, 2017; Rheault et al., 2019; Fuchs and Schäfer, 2020; Erikson et al., 2021); and that the English football social media audience is a global one (Kilvington and Price, 2019). However, shifting national or cultural context will introduce further distributional and linguistic shifts. Furthermore, our data is only collected from Twitter though abuse towards public figures exists on a variety of social media platforms (Agarwal et al., 2021) such as YouTube (Esposito and Zollo, 2021) or WhatsApp (Saha et al., 2021).

Evaluation Robustness Aggregate evaluation metrics may obscure per `dodo` and per class weaknesses (Röttger et al., 2021). The Macro-F1 score across the combined test set from all `dodos` does not equal the averaged Macro-F1 across each `dodo` test set (the former is 4.7pp higher on average). This is due to different class distributions across `dodos` skewing the total Macro-F1 calculation. The ranking of models was consistent across these two metrics. We have not investigated the relative dataset difficulty (Ethayarajh et al., 2022) of individual `dodo` test sets, which may influence measures of generalisability.

5.2 Areas of Future Work

Despite these limitations and the challenging nature of annotating social media content, our study provides ample opportunity for areas of future work. Expanding demographics and adding more complexity to the labelling schema would provide a broader basis for understanding generalisability in abuse classification. Other promising avenues include investigating whether active learning techniques (Vidgen et al., 2022; Kirk et al., 2022c) aid more efficient cross-domain/demographic transfer, or whether architectures better suited for continual learning can assist in the addition of new groups without forgetting those previously trained-on (Hu et al., 2020; Qian et al., 2021; Li et al., 2022). We shuffled entries during training and used all four class labels but future work could assess whether performance is affected by

order of training on different groups, and the impact of training on binary versus multi-class labels on transfer performance. Finally, our experiments only use fine-tuning on labelled data, but in-domain continued pre-training could be explored as a budget-efficient way to boost performance (Gururangan et al., 2020; Kirk et al., 2023).

6 Related Works

Abuse Against MPs Academics and journalists account abuse against politicians, which may cause politicians to withdraw from their posts (Parliament, 2023; Manning and Kemp, 2019; James et al., 2016). Empirical work commonly studies Twitter (Binns and Bateman, 2018; Gorrell et al., 2020; Ward and McLoughlin, 2020; Agarwal et al., 2021), including across national contexts such as European Parliament elections (Theocharis et al., 2016), Canadian and US politicians (Rheault et al., 2019) and members of the UK parliament (Gorrell et al., 2020). Other studies focus on gender differences in abuse (Rheault et al., 2019; Erikson et al., 2021) though some datasets only contain abuse against women (Stambolieva, 2017; Delisle et al., 2019) which limits comparison across genders (unlike `DODO`). Various techniques are employed to identify abusive tweets including rules-based or lexicon approaches and topic analysis (Gorrell et al., 2018, 2020; Greenwood et al., 2019); traditional machine learning classifiers (Stambolieva, 2017; Rheault et al., 2019; Agarwal et al., 2021) or pre-trained language models and off-the-shelf classifiers like Perspective API (Delisle et al., 2019).

Abuse Against Footballers Sport presents a good case for studying public figure abuse due to the influence of athletes (Carrington, 2012), as well as the heightened symbolic focus on in-out groups and race-nation relations (Bromberger, 1995; Back et al., 2001; King, 2003; Burdsey, 2011; Doidge, 2015). Several studies track the change from racist chants at football stadiums, to the more pernicious and harder to control online abuse (King, 2004; Cleland, 2013; Cleland and Cashmore, 2014; Kilvington and Price, 2019). Civil society organisations track social media abuse as far back as the 2012/2013 season, but are limited by a focus on manual case-by-case resolution and suffer from chronic underreporting (Bennett and Jönsson, 2017). The most similar work to our large-scale automated analysis is Vid-

gen et al. (2022), who use some of the same data as the male footballers portion in DODO but also label additional data using active learning.

Abuse Datasets and Detection Developing robust abuse classifiers is challenging (Zhang and Luo, 2019). Surveys on abuse detection cover various aspects such as algorithms (Schmidt and Wiegand, 2017; Mishra et al., 2019), model generalisability (Yin and Zubiaga, 2021), and data desiderata (Vidgen and Derczynski, 2020). Many studies curate data from mainstream platforms, focusing on abuse against different identities such as women (Fersini et al., 2018; Pamungkas et al., 2020) and immigrants (Basile et al., 2019). Recent approaches to developing abuse classifiers predominately fine-tune large language models on labelled datasets directly (Fortuna et al., 2021) (our approach) or in a multi-task setting (Talat et al., 2018; Yuan and Rizoïu, 2022), as well as incorporate contextual information (Chiril et al., 2022). Abuse detection datasets mostly focus on binary classification, and few cast the predictions as a multi-class problem. Similarly, cross-domain classification is under-explored to address generalisability (Glavaš et al., 2020; Yadav et al., 2023). The dataset we use in this paper rectifies some of these issues, as a cross-domain and demographic dataset with fine-grained labels.

Domain Adaptation Several NLP techniques have been explored for model generalisation in abuse detection, including feature-based domain alignment (Bashar et al., 2021; Ludwig et al., 2022), regularisation methods (Ludwig et al., 2022), and adaptive pre-training (Faal et al., 2021). Systematic evaluation of model generalisability is limited, focusing on dataset features (Fortuna et al., 2021) and multilinguality (Pamungkas et al., 2020; Yadav et al., 2023). To our knowledge, no prior work has quantified the effects of cross-domain *and* cross-demographic transfer.

7 Conclusion

Using our new DODO dataset, we trained language models to detect abuse against public figures for two domains (sports, politics) and two demographics (women, men). We found that (i) even small amounts of diverse data provide significant benefits to generalisable performance and model adaptation; (ii) cross-demographic transfer (from women to men, or vice-versa) is more

effective than cross-domain transfer (from footballers to MPs, or vice-versa) but models trained on data from one domain are less generalisable than models trained on cross-domain data; (iii) not all domains and demographics contribute equally to training generalisable models; and (iv) dataset similarity is a signal of transferability.

There are broader policy implications of our work. Online harms are in constant evolution, both in terms of the targets and nature of abuse. Policymakers, NGOs and others with an interest in independently monitoring harms face a constant challenge in terms of building models that are both broad enough to capture a wide range of harms but also specific enough to capture the distinctive nature of abuse (e.g., the difference between hate speech targeted at male and female MPs), all whilst remaining within the tight resource constraints typical of policy settings. Our work contributes to the policy landscape by providing fresh perspective on the feasibility of transferring models created to detect harm for one target to other targets. It thus gives a roadmap and resources for developing automated systems that are cost-effective, generalisable and performative across domains and demographics of interest.

Ethics and Harm Statement

We present our limitations section in §5.1. In addition to these limitations, engaging with a subject such as online abuse raises ethical concerns. Here we set out the nature of those concerns, and how we managed them. Creation and annotation of a dataset focusing on abuse risks harming the annotators and researchers constructing the dataset, as repeated exposure to such material can be detrimental towards their mental health (Kirk et al., 2022a). Mitigating these risks is easier with a small trained team of annotators (like those we used for the MPs dataset) and harder with crowdworkers (like those we used for the FBs dataset). With the trained group of annotators, we maintained an open annotator forum where they could discuss such issues during the labelling process, and seek welfare support. For crowdworkers, we had very limited contact with them but include on our guidelines and task description extensive content warnings and links to publicly-available resources on vicarious trauma.

Acknowledgements

We would like to thank Dr Bertie Vidgen for prior direction and data annotation support, and Eirini Koutsouroupa for invaluable project management support. This work was supported by the Ecosystem Leadership Award under the EPSRC Grant EPX03870X1 & The Alan Turing Institute.

References

- Pushkal Agarwal, Oliver Hawkins, Margarita Amaxopoulou, Noel Dempsey, Nishanth Sastry, and Edward Wood. 2021. [Hate Speech in Political Discourse: A Case Study of UK MPs on Twitter](#). *Proceedings of the 32nd ACM Conference on Hypertext and Social Media*, pages 5–16. Publisher: ACM.
- Les Back, Tim Crabbe, John, and John Solomos Solomos. 2001. *The Changing Face of Football. Racism, Identity and Multiculturc in the English Game*. Berg Publishers.
- Gabrielle Bardall. 2013. [Gender-Specific Election Violence: The Role of Information and Communication Technologies](#). *Stability: International Journal of Security & Development*, 2(3):60.
- Md Abul Bashar, Richi Nayak, Khanh Luong, and Thirunavukarasu Balasubramaniam. 2021. Progressive domain adaptation for detecting hate speech on social media with small training set and its application to covid-19 concerned posts. *Social Network Analysis and Mining*, 11:1–18.
- Valerio Basile, Cristina Bosco, Elisabetta Fersini, Debora Nozza, Viviana Patti, Francisco Manuel Rangel Pardo, Paolo Rosso, and Manuela Sanguinetti. 2019. [SemEval-2019 task 5: Multilingual detection of hate speech against immigrants and women in Twitter](#). In *Proceedings of the 13th International Workshop on Semantic Evaluation*, pages 54–63, Minneapolis, Minnesota, USA. Association for Computational Linguistics.
- Emily M. Bender and Batya Friedman. 2018. [Data statements for natural language processing: Toward mitigating system bias and enabling better science](#). *Transactions of the Association for Computational Linguistics*, 6:587–604.
- Hayley Bennett and Anna Jönsson. 2017. Klick it out: tackling online discrimination in football. In *Sport and Discrimination*, page 12. Routledge.
- Amy Binns and Martin Bateman. 2018. [And they thought Papers were Rude](#). *British Journalism Review*, 29(4):39–44.
- Jonathan Bright, Scott Hale, Bharath Ganesh, Andrew Bulovsky, Helen Margetts, and Phil Howard. 2020. [Does campaigning on social media make a difference? Evidence from candidate use of Twitter during the 2015 and 2017 U.K. elections](#). *Communication Research*, 47(7):988–1009.
- Christian Bromberger. 1995. [Football as world-view and as ritual](#). *French Cultural Studies*, 6(18):293–311.
- Christopher Brown. 2009. [WWW.HATE.COM: White Supremacist Discourse on the Internet and the Construction of Whiteness Ideology](#). *Howard Journal of Communications*, 20(2):189–208.
- Daniel Burdsey. 2011. *Race, Ethnicity and Football*. Routledge.
- Ben Carrington. 2012. [Introduction: sport matters](#). *Ethnic and Racial Studies*, 35(6):961–970.
- Patricia Chiril, Endang Wahyu Pamungkas, Farah Benamara, Véronique Moriceau, and Viviana Patti. 2022. Emotionally informed hate speech detection: a multi-target perspective. *Cognitive Computation*, pages 1–31.
- Jamie Cleland. 2013. [Racism, Football Fans, and Online Message Boards](#). *Journal of Sport and Social Issues*, 38(5):415–431. Publisher: SAGE PublicationsSage CA: Los Angeles, CA.
- Jamie Cleland and Ellis Cashmore. 2014. [Fans, Racism and British Football in the Twenty-First Century: The Existence of a ‘Colour-Blind’ Ideology](#). *Journal of Ethnic and Migration Studies*, 40(4):638–654.
- Stephen Coleman. 1999. [Can the New Media Invigorate Democracy?](#) *The Political Quarterly*, 70(1):16–22.

- Stephen Coleman. 2005. [New mediation and direct representation: reconceptualizing representation in the digital age](#). *New Media & Society*, 7(2):177–198.
- Stephen Coleman and Josephine Spiller. 2003. [Exploring new media effects on representative democracy](#). *The Journal of Legislative Studies*, 9(3):1–16.
- Thomas Davidson, Dana Warmusley, Michael Macy, and Ingmar Weber. 2017. [Automated Hate Speech Detection and the Problem of Offensive Language](#). *Proceedings of the 11th International Conference on Web and Social Media, ICWSM 2017*, pages 512–515. Publisher: AAAI Press.
- Laure Delisle, Alfredo Kalaitzis, Krzysztof Majewski, Archy de Berker, Milena Marin, and Julien Cornebise. 2019. [A large-scale crowd-sourced analysis of abuse against women journalists and politicians on twitter](#).
- John Dewey. 1927. *The public and its problem*. Henry Holt.
- Mark Doidge. 2015. [‘If you jump up and down, Balotelli dies’: Racism and player abuse in Italian football](#). *International Review for the Sociology of Sport*, 50(3):249–264. Publisher: SAGE PublicationsSage UK: London, England.
- Mai ElSherief, Vivek Kulkarni, Dana Nguyen, William Yang Wang, and Elizabeth Belding. 2018. [Hate lingo: A target-based linguistic analysis of hate speech in social media](#). In *Proceedings of the International AAAI Conference on Web and Social Media*, pages 42–51.
- Josefina Erikson, Sandra Håkansson, and Cecilia Josefsson. 2021. [Three Dimensions of Gendered Online Abuse: Analyzing Swedish MPs’ Experiences of Social Media](#). *Perspectives on Politics*, pages 1–17. Publisher: Cambridge University Press.
- Eleonora Esposito and Sole Alba Zollo. 2021. [“How dare you call her a pig, I know several pigs who would be upset if they knew”*](#). *Journal of Language Aggression and Conflict*, 9(1):47–75.
- Kawin Ethayarajh, Yejin Choi, and Swabha Swayamdipta. 2022. [Understanding Dataset Difficulty with \$\mathcal{V}\$ -Usable Information](#). In *Proceedings of the 39th International Conference on Machine Learning*, pages 5988–6008. PMLR. ISSN: 2640-3498.
- Christian Chukwuebuka Ezeibe and Okey Marcellus Ikeanyibe. 2017. [Ethnic Politics, Hate Speech, and Access to Political Power in Nigeria](#). *Africa Today*, 63(4):65.
- Farshid Faal, Jia Yuan Yu, and Ketra A. Schmitt. 2021. [Domain adaptation multi-task deep neural network for mitigating unintended bias in toxic language detection](#). In *Proceedings of the 13th International Conference on Agents and Artificial Intelligence, ICAART 2021, Volume 2, Online Streaming, February 4-6, 2021*, pages 932–940. SCITEPRESS.
- N. Farrington, L. Hall, D. Kilvington, J. Price, and A. Saeed. 2014. *Sport, racism and social media*. Routledge.
- Elisabetta Fersini, Debora Nozza, Paolo Rosso, et al. 2018. [Overview of the evalita 2018 task on automatic misogyny identification \(ami\)](#). In *EVALITA Evaluation of NLP and Speech Tools for Italian Proceedings of the Final Workshop 12-13 December 2018, Naples*. Accademia University Press.
- Paula Fortuna, Juan Soler-Company, and Leo Wanner. 2021. [How well do hate speech, toxicity, abusive and offensive language classification models generalize across datasets?](#) *Information Processing & Management*, 58(3):102524.
- Tamara Fuchs and Fabian Schäfer. 2020. [Normalizing misogyny: hate speech and verbal abuse of female politicians on Japanese Twitter](#). *Japan Forum*, pages 1–27.
- Goran Glavaš, Mladen Karan, and Ivan Vulić. 2020. [XHate-999: Analyzing and Detecting Abusive Language Across Domains and Languages](#). In *Proceedings of the 28th International Conference on Computational Linguistics*, pages 6350–6365, Barcelona, Spain (Online). International Committee on Computational Linguistics.
- Genevieve Gorrell, Tracie Farrell, and Kalina Bontcheva. 2020. [Mp twitter abuse in the age of covid-19: White paper](#).

- Genevieve Gorrell, Mark Greenwood, Ian Roberts, Diana Maynard, and Kalina Bontcheva. 2018. [Twits, Twats and Twaddle: Trends in Online Abuse towards UK Politicians and twaddle: Trends in online abuse towards UK politicians](#). *Proceedings of the International AAAI Conference on Web and Social Media*, 12(1).
- Mark A. Greenwood, Mehmet E. Bakir, Genevieve Gorrell, Xingyi Song, Ian Roberts, and Kalina Bontcheva. 2019. [Online abuse of uk mps from 2015 to 2019: Working paper](#).
- Suchin Gururangan, Ana Marasović, Swabha Swayamdipta, Kyle Lo, Iz Beltagy, Doug Downey, and Noah A Smith. 2020. Don't stop pretraining: Adapt language models to domains and tasks. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 8342–8360.
- Kilem L. Gwet. 2014. *Handbook of inter-rater reliability: The definitive guide to measuring the extent of agreement among raters*. Advanced Analytics, LLC.
- Pengcheng He, Jianfeng Gao, and Weizhu Chen. 2021. Debertav3: Improving deberta using electra-style pre-training with gradient-disentangled embedding sharing. *arXiv preprint arXiv:2111.09543*.
- Hexiang Hu, Ozan Sener, Fei Sha, and Vladlen Koltun. 2020. [Drinking from a firehose: Continual learning with web-scale natural language](#). Version: 2.
- Sean Ingle. 2021. [Sports bodies to boycott social media for bank holiday weekend over abuse](#). *The Guardian*.
- David V. James, Frank R. Farnham, Seema Sukhwai, Katherine Jones, Josephine Carlisle, and Sara Henley. 2016. [Aggressive/intrusive behaviours, harassment and stalking of members of the United Kingdom parliament: a prevalence study and cross-national comparison](#). *The Journal of Forensic Psychiatry & Psychology*, 27(2):177–197.
- Adam Joinson, Katelyn Y. A. McKenna, Tom Postmes, and Ulf-Dietrich Reips. 2009. *Oxford Handbook of Internet Psychology*. Oxford University Press.
- Daniel Kilvington and John Price. 2019. [Tackling Social Media Abuse? Critically Assessing English Football's Response to Online Racism](#). *Communication & Sport*, 7(1):64–79. Publisher: SAGE PublicationsSage CA: Los Angeles, CA.
- Anthony King. 2003. *The European Ritual: Football in the New Europe*. Ashgate Publishing Ltd.
- Colin King. 2004. *Offside racism: Playing the white man*. Routledge.
- Hannah Kirk, Abeba Birhane, Bertie Vidgen, and Leon Derczynski. 2022a. [Handling and Presenting Harmful Text in NLP Research](#). In *Findings of the Association for Computational Linguistics: EMNLP 2022*, pages 497–510, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.
- Hannah Kirk, Bertie Vidgen, Paul Röttger, Tristan Thrush, and Scott Hale. 2022b. Hatemoji: A test suite and adversarially-generated dataset for benchmarking and detecting emoji-based hate. In *Proceedings of the 2022 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 1352–1368.
- Hannah Rose Kirk, Bertie Vidgen, and Scott A. Hale. 2022c. [Is More Data Better? Using Transformers-Based Active Learning for Efficient and Effective Detection of Abusive Language](#). In *Proceedings of the 3rd workshop on Threat, Aggression and Cyberbullying (COLING 2022)*. Association for Computational Linguistics.
- Hannah Rose Kirk, Wenjie Yin, Bertie Vidgen, and Paul Röttger. 2023. [SemEval-2023 Task 10: Explainable Detection of Online Sexism](#). In *Proceedings of the 17th International Workshop on Semantic Evaluation*, Toronto, Canada. Association for Computational Linguistics.
- Dingcheng Li, Zheng Chen, Eunah Cho, Jie Hao, Xiaohu Liu, Fan Xing, Chenlei Guo, and Yang Liu. 2022. [Overcoming catastrophic forgetting during domain adaptation of seq2seq language generation](#). In *Proceedings of the 2022 Conference of the North American Chapter of the*

- Association for Computational Linguistics: Human Language Technologies*, pages 5441–5454. Association for Computational Linguistics.
- Florian Ludwig, Klara Dolos, Torsten Zesch, and Eleanor Hobley. 2022. [Improving Generalization of Hate Speech Detection Systems to Novel Target Groups via Domain Adaptation](#). In *Proceedings of the Sixth Workshop on Online Abuse and Harms (WOAH)*, pages 29–39, Seattle, Washington (Hybrid). Association for Computational Linguistics.
- Lucy Manning and Phillip Kemp. 2019. [MPs describe threats, abuse and safety fears](#). *BBC News*.
- J. Reid Meloy, Lorraine Sheridan, and Jens Hoffmann, editors. 2008. *Stalking, Threatening, and Attacking Public Figures*. Oxford University Press.
- Pushkar Mishra, Helen Yannakoudakis, and Ekaterina Shutova. 2019. Tackling online abuse: A survey of automated abuse detection methods. *arXiv preprint arXiv:1908.06024*.
- Paul E. Mullen, David V. James, J. Reid Meloy, Michele T. Pathé, Frank R. Farnham, Lulu Preston, Brian Darnley, and Jeremy Berman. 2009. [The fixated and the pursuit of public figures](#). *Journal of Forensic Psychiatry & Psychology*, 20(1):33–47. Publisher: Routledge.
- Endang Wahyu Pamungkas, Valerio Basile, and Viviana Patti. 2020. [Misogyny detection in twitter: a multilingual and cross-domain study](#). *Information Processing & Management*, 57(6):102360.
- Zizi Papacharissi. 2004. Democracy online: Civility, politeness, and the democratic potential of online political discussion groups. *New media & society*, 6(2):259–283.
- UK Parliament. 2023. [Women in Parliament Today](#). Technical report, UK Parliament.
- Jing Qian, Hong Wang, Mai ElSherief, and Xifeng Yan. 2021. [Lifelong Learning of Hate Speech Classification on Social Media](#). ArXiv:2106.02821 [cs].
- Ludovic Rheault, Erica Rayment, and Andreea Musulan. 2019. [Politicians in the line of fire: Incivility and the treatment of women on social media](#). *Research & Politics*, 6(1).
- Ian Rowe. 2015. [Civility 2.0: a comparative analysis of incivility in online political discussion](#). *Information, Communication & Society*, 18(2):121–138.
- Paul Röttger, Bertie Vidgen, Dong Nguyen, Zeerak Waseem, Helen Margetts, and Janet Pierrehumbert. 2021. [HateCheck: Functional Tests for Hate Speech Detection Models](#). In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 41–58, Online. Association for Computational Linguistics.
- Punyajoy Saha, Binny Mathew, Kiran Garimella, and Animesh Mukherjee. 2021. [“Short is the Road that Leads from Fear to Hate”: Fear Speech in Indian WhatsApp Groups](#). In *Proceedings of the Web Conference 2021*, pages 1110–1121. ACM.
- Victor Sanh, Lysandre Debut, Julien Chaumond, and Thomas Wolf. 2019. Distilbert, a distilled version of bert: smaller, faster, cheaper and lighter. *arXiv preprint arXiv:1910.01108*.
- Anna Schmidt and Michael Wiegand. 2017. [A survey on hate speech detection using natural language processing](#). In *Proceedings of the Fifth International Workshop on Natural Language Processing for Social Media*, pages 1–10, Valencia, Spain. Association for Computational Linguistics.
- Stuart W. Shulman. 2009. [The Case Against Mass E-mails: Perverse Incentives and Low Quality Public Participation in U.S. Federal Rulemaking](#). *Policy & Internet*, 1(1):22–52.
- Ekaterina Stambolieva. 2017. Methodology : Detecting Online Abuse against Women MPs on Twitter. Technical Report Amnesty International, Amnesty International.
- John Suler. 2004. [The Online Disinhibition Effect](#). *CyberPsychology & Behavior*, 7(3):321–326.
- Zeerak Talat, James Thorne, and Joachim Bingel. 2018. Bridging the gaps: Multi task learning for domain transfer of hate speech detection. *Online harassment*, pages 29–55.

- Yannis Theocharis, Pablo Barberá, Zoltán Fazekas, Sebastian Adrian Popa, and Olivier Parnet. 2016. [A Bad Workman Blames His Tweets: The Consequences of Citizens' Uncivil Twitter Use When Interacting With Party Candidates](#). *Journal of Communication*, 66(6):1007–1031.
- Bertie Vidgen, Yi-Ling Chung, Pica Johansson, Hannah Rose Kirk, Angus Williams, Scott A. Hale, Helen Zerlina Margetts, Paul Röttger, and Laila Sprejer. 2022. [Tracking Abuse on Twitter Against Football Players in the 2021 – 22 Premier League Season](#).
- Bertie Vidgen and Leon Derczynski. 2020. [Directions in abusive language training data, a systematic review: Garbage in, garbage out](#). *PLOS ONE*, 15(12):e0243300. Publisher: Public Library of Science.
- Bertie Vidgen, Alex Harris, Dong Nguyen, Rebekah Tromble, Scott Hale, and Helen Margetts. 2019. Challenges and frontiers in abusive content detection. In *Proceedings of the Third Workshop on Abusive Language Online*, pages 80–93.
- Bertie Vidgen, Dong Nguyen, Helen Margetts, Patricia Rossini, and Rebekah Tromble. 2021a. [Introducing CAD: the contextual abuse dataset](#). In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 2289–2303, Online. Association for Computational Linguistics.
- Bertie Vidgen, Tristan Thrush, Zeerak Waseem, and Douwe Kiela. 2021b. Learning from the worst: Dynamically generated datasets to improve online hate detection. In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 1667–1682.
- Stephen Ward and Liam McLoughlin. 2020. [Turds, traitors and tossers: the abuse of UK MPs via Twitter](#). *The Journal of Legislative Studies*, 26(1):47–73.
- Andy Williamson. 2009. [The Effect of Digital Media on MPs' Communication with Constituents](#). *Parliamentary Affairs*, 62(3):514–527.
- Ankit Yadav, Shubham Chandel, Sushant Chatufale, and Anil Bandhakavi. 2023. Lahm: Large annotated dataset for multi-domain and multilingual hate speech identification. *arXiv preprint arXiv:2304.00913*.
- Wenjie Yin and Arkaitz Zubiaga. 2021. Towards generalisable hate speech detection: a review on obstacles and solutions. *PeerJ Computer Science*, 7:e598.
- Lanqin Yuan and Marian-Andrei Rizoiu. 2022. Detect hate speech in unseen domains using multi-task learning: A case study of political public figures. *arXiv preprint arXiv:2208.10598*.
- Ziqi Zhang and Lei Luo. 2019. Hate speech detection: A solved problem? the challenging case of long tail on twitter. *Semantic Web*, 10(5):925–945.