

```
/* Thanks to former CS 31 TA Kung-Hua Chang for the set of practice problems and solutions.
```

```
Ref: Practice Problems for C++ Beginners: Moving Beyond the Basics,  
by Dr. Kung-Hua Chang. */
```

```
/*
```

```
Q1: What is the output of the program below given the inputs?
```

```
123456
```

```
105000
```

```
Software Engineer
```

```
*/
```

```
#include <iostream>
```

```
#include <string>
```

```
using namespace std;
```

```
struct employee // we can replace struct by class, but...
```

```
{
```

```
    int ID;
```

```
    double salary;
```

```
    string jobtitle;
```

```
}; // Remember to put semicolon here...
```

```
int main()
```

```
{
```

```
    employee emp;
```

```
    cout << "Please enter employee information:\n";
```

```
    cout << "ID Number: ";
```

```
    cin >> emp.ID;
```

```
    cout << "Salary: ";
```

```
    cin >> emp.salary; cin.ignore(1000, '\n');
```

```
    cout << "Job title: ";
```

```
    getline(cin, emp.jobtitle);
```

```
    cout << "There is one employee:\n";
```

```
    cout << "ID Number: " << emp.ID << endl;
```

```
    cout << "Salary: " << emp.salary << endl;
```

```
    cout << "Job Title: " << emp.jobtitle << endl;
```

```
}
```

```

/*
Q2: What is the output of the program below given the inputs?
123456
105000
Software Engineer
*/

#include <iostream>
#include <string>
using namespace std;

struct employee // we can replace struct by class, but...
{
    int ID;
    double salary;
    string jobtitle;
}; // Remember to put semicolon here...

int main()
{
    employee emp_a;
    employee *emp = &emp_a;

    // The arrow, ->, is used with a pointer to access the members of a
    struct/class. emp->ID is equivalent to (*emp).ID

    cout << "ID Number: ";
    cin >> emp->ID;

    cout << "Salary: ";
    cin >> (*emp).salary;

    cin.ignore(1000, '\n');
    cout << "Job title: ";
    getline(cin, emp->jobtitle);

    cout << "There is one employee:\n";
    cout << "ID Number: " << emp->ID << endl;
    cout << "Salary: " << emp->salary << endl;
    cout << "Job Title: " << emp->jobtitle << endl;
}

/*

```

Q3: What is the output of the program below given the inputs?

123456

105000

Software Engineer

*/

```
#include <iostream>
```

```
#include <string>
```

```
using namespace std;
```

```
struct employee // we can replace struct by class, but...
```

```
{
```

```
    int ID;
```

```
    double salary;
```

```
    string jobtitle;
```

```
}; // Remember to put semicolon here...
```

```
void getInput(employee emp) //
```

```
{
```

```
    cout << "ID Number: ";
```

```
    cin >> emp.ID;
```

```
    cout << "Salary: ";
```

```
    cin >> emp.salary;
```

```
    cin.ignore(1000, '\n');
```

```
    cout << "Job title: ";
```

```
    getline(cin, emp.jobtitle);
```

```
}
```

```
int main()
```

```
{
```

```
    employee emp = {0, 0, ""}; // initialization
```

```
    // same as: emp.ID = 0; emp.salary = 0; emp.jobtitle = "";
```

```
    getInput(emp);
```

```
    cout << "There is one employee:\n";
```

```
    cout << "ID Number: " << emp.ID << endl;
```

```
    cout << "Salary: " << emp.salary << endl;
```

```
    cout << "Job Title: " << emp.jobtitle << endl;
```

```
}
```

```
/*
```

Q4: What is the output of the program below given the inputs?

123456

105000

Software Engineer

246802

130000

Senior Software Engineer

*/

```
#include <iostream>
```

```
#include <string>
```

```
using namespace std;
```

```
struct employee // we can replace struct by class, but...
```

```
{
```

```
    int ID;
```

```
    double salary;
```

```
    string jobtitle;
```

```
}; // Remember to put semicolon here...
```

```
int main()
```

```
{
```

```
    employee emp[2];
```

```
    // employee *emp = new employee[2];
```

```
    for (int i = 0; i < 2; i++)
```

```
    {
```

```
        cout << "ID Number: ";    cin >> emp[i].ID;
```

```
        cout << "Salary: ";    cin >> emp[i].salary;    cin.ignore(1000, '\n');
```

```
        cout << "Job title: ";    getline(cin, emp[i].jobtitle);
```

```
    }
```

```
    cout << "There are 2 employees:\n";
```

```
    for (int i = 0; i < 2; i++)
```

```
    {
```

```
        cout << "Employee #" << i + 1 << ":" << endl;
```

```
        cout << "ID Number: " << emp[i].ID << endl;
```

```
        cout << "Salary: " << emp[i].salary << endl;
```

```
        cout << "Job Title: " << emp[i].jobtitle << endl;
```

```
    }
```

```
}
```

```

/*
Q5: What is the output of the program below given the inputs?
123456
105000
Software Engineer
246802
130000
Senior Software Engineer
*/

#include <iostream>
#include <string>
using namespace std;

struct employee // we can replace struct by class, but...
{
    int ID;
    double salary;
    string jobtitle;
}; // Remember to put semicolon here...

// same as employee *emp or employee emp[]
void getInput(employee emp[2])
{
    for (int i = 0; i < 2; i++)
    {
        cout << "ID Number: ";   cin >> emp[i].ID;
        cout << "Salary: ";      cin >> emp[i].salary;    cin.ignore(1000,
'\n');
        cout << "Job title: ";    getline(cin, emp[i].jobtitle);
    }
}

int main()
{
    employee emp[2];

    getInput(emp);

    cout << "There are 2 employees:\n";

    for (int i = 0; i < 2; i++)
    {
        cout << "Employee #" << i + 1 << ":" << endl;
    }
}

```

```

        cout << "ID Number: " << emp[i].ID << endl;
        cout << "Salary: " << emp[i].salary << endl;
        cout << "Job Title: " << emp[i].jobtitle << endl;
    }
}

```

/*

Q6: What is the output of the program below given the inputs?

*/

```

#include <iostream>
#include <string>
using namespace std;

```

```

struct employee // we can replace struct by class, but...
{
public:
    void outputID() { cout << ID << endl;}
    int ID;
    double salary;
}; // Remember to put semicolon here...

```

```

int main()
{
    employee emp[5];

```

// Before we rotate left at the first position

```

for (int i = 0; i < 5; i++)
{
    emp[i].ID = i;
    emp[i].salary = 10000 * i + 50000;
    emp[i].outputID();
}

```

```

cout << "=====" << endl;

```

// Now we want to rotate left at the first position

```

employee temp = emp[0];
for (int i = 0; i < 4; i++)
    emp[i] = emp[i+1];
emp[4] = temp;

```

```

    for (int i = 0; i < 5; i++)
        emp[i].outputID();
}

```

```

/*

```

Q7: What is the output of the program below given the inputs?

123456

105000

Software Engineer

```

*/

```

```

#include <iostream>
#include <string>
using namespace std;

```

```

class employee

```

```

{

```

```

public:

```

```

    void input();           // public member function

```

```

    void output();          // public member function

```

```

private:

```

```

    int ID;                 // private data member

```

```

    double salary;          // private data member

```

```

    string jobtitle;        // private data member

```

```

};

```

```

void employee::input()

```

```

{

```

```

    cout << "ID Number: ";   cin >> ID;

```

```

    cout << "Salary: ";      cin >> salary;    cin.ignore(1000, '\n');

```

```

    cout << "Job title: ";   getline(cin, jobtitle);

```

```

}

```

```

void employee::output()

```

```

{

```

```

    cout << "There is one employee:\n";

```

```

    cout << "ID Number: " << ID << endl;

```

```

    cout << "Salary: " << salary << endl;

```

```

    cout << "Job Title: " << jobtitle << endl;

```

```

}

```

```

int main()

```

```

{

```

```

    employee emp;

    emp.input();
    emp.output();
}

```

```

/*
Q8: If the following program doesn't compile, why not? If it does
compile, what is the output of the program below given the inputs?
123456
105000
Software Engineer
*/

```

```

#include <iostream>
#include <string>
using namespace std;

class employee
{
    int ID;
    double salary;
    string jobtitle;
};

int main()
{
    employee *emp = new employee;
    // This also works: employee *emp = new employee();

    cout << "ID Number: ";
    cin >> emp->ID;
    cout << "Salary: ";
    cin >> (*emp).salary;
    cin.ignore(1000, '\n');
    cout << "Job title: ";
    getline(cin, emp->jobtitle);

    cout << "There is one employee:\n";

    cout << "ID Number: " << emp->ID << endl;
    cout << "Salary: " << emp->salary << endl;
    cout << "Job Title: " << emp->jobtitle << endl;
}

```



```
}
```

```
/*
```

```
Q9: What is the output of the program below?
```

```
*/
```

```
#include <iostream>
#include <string>
using namespace std;
```

```
struct employee
{
    int ID;
    double salary;
    string jobtitle;
};
```

```
int main()
{
    employee emp1[2];
    // An employee struct array with 2 cells.
    // Each cell is an employee object.

    employee *emp2 = new employee[2];
    // An employee* pointer points to the starting address of the
    // employee struct array with 2 cells.

    employee *emp3[2];
    // emp3[0] stores an employee struct pointer (points to a random
    place)
    // emp3[1] also points to a random place.

    cout << "Static array: size = " << sizeof(emp1[0]) << endl;

    cout << "Dynamic array: size = " << sizeof(emp2[0]) << endl;

    cout << "Array storing only pointers: size = " << sizeof(emp3[0]) <<
    endl;
}
```

```
/* Q10: If the following program doesn't compile, why not? If it does
compile, what is the output when it is run?
```

```

*/

#include <iostream>
#include <string>
using namespace std;

class employee
{
public:
    employee()
    {
        ID = 0;
        salary = 0;
        jobtitle = "";
    }
    employee(int ID, double salary, string jobtitle)
    {
        this -> ID = ID;
        this -> salary = salary;
        this -> jobtitle = jobtitle;
    }
    ~employee()
    {
        cout << "This is destructor!!" << endl;
    }
    void Output();
private:
    int ID;
    double salary;
    string jobtitle;
};

void employee::Output()
{
    cout << "ID Number: " << ID << endl;
    cout << "Salary: " << salary << endl;
    cout << "Job Title: " << jobtitle << endl;
}

int main()
{
    employee A; // (1)
    employee B(); // (2)
    employee C = {0, 0, ""}; // (3)
    employee D(1234, 90000.0, "Software Engineer"); // (4)
    employee *E = new employee; // (5)
}

```

```

    employee *F = new employee(); // (6)
    employee *G = new employee(5432, 95000.0, "Manager"); // (7)
    A.Output(); // (8)
    B.Output(); // (9)
    C.Output(); // (10)
    D.Output(); // (11)
    E->Output(); // (12)
    F->Output(); // (13)
    G->Output(); // (14)
}

```

/* Q11: What is the output of the program below?

The general way to code a class is to

- (1) Hide information: leave data member in private section
- (2) Declare accessor and mutator functions to access private members.
 - Accessor: only read the private data members out.
 - Mutator: change the private data members.

*/

```

#include <iostream>
#include <string>
using namespace std;

```

```

class employee
{

```

```

public:
    // Is it okay NOT to declare your own constructor and destructor?

```

```

    void setValue(int theID, double theSalary)
    {
        // This is a mutator function
        ID = theID; salary = theSalary;
    }

```

//These two member function below are accessor functions

```

int getID()
{
    return ID;
}
double getSalary();

```

```

private:
    int ID;
    double salary;

```

```

};

double employee::getSalary()
{
    return salary;
}

int main()
{
    employee emp[2];

    emp[0].setValue(1, 100000.0);
    emp[1].setValue(2, 110000.0);

    cout << "ID1: " << emp[0].getID()
          << " Salary1 = " << emp[0].getSalary() << endl;

    cout << "ID2: " << emp[1].getID()
          << " Salary2 = " << emp[1].getSalary() << endl;
}

```

/*
Q12: What is the output of the program below?
*/

```

#include <iostream>
#include <string>
using namespace std;
class employee
{
public:
    employee()
    {
        ID = 0;
        salary = 0;
        jobtitle = "";
    }

    void setData(int ID, double salary, string jobtitle)
    {
        this -> ID = ID;
        this -> salary = salary;
        this -> jobtitle = jobtitle;
    }
}

```

```

    }

    int getID() const { return ID; }

    ~employee()
    {
        cout << ID << " got laid off!!" << endl;
    }

    void Output()
    {
        cout << "ID number: " << ID << endl;
        cout << "Salary: " << salary << endl;
        cout << "Job Title: " << jobtitle << endl;
    }

private:
    int ID;
    double salary;
    string jobtitle;
};

class company
{
public:
    company() {}
    company(string name, int numEmp)
    {
        this -> name = name;
        emp = new employee[numEmp];
        for (int i = 0; i < numEmp; i++)
        {
            emp[i].setData(i+1, 80000, "Software Engineer");
            cout << emp[i].getID()
                << " got hired to join the company" << endl;
        }
    }
    ~company()
    {
        cout << this -> name << " company goes bankrupt!!" << endl;
        delete [] emp;
    }
private:
    employee *emp;
    string name;

```

```
};
```

```
int main()  
{  
    company comp("ABC", 2);  
}
```