
CS 35L- Software Construction Laboratory

Fall 18

TA: Guangyu Zhou

Lab 3

Announcement

- Signup for Assignment 10 Presentation (No later than Oct 21, 11:55pm)
 - Use **UCLA** account to register at the following link
 - <https://docs.google.com/spreadsheets/d/1L2leP7WRbCmAygSPN5pq7SU2pTddKNooUteBGetde2M/edit?usp=sharing>
 - Topic on recent research in computer science
 - **Technical** content is required
 - 1 or 2 people
 - ~10 minutes talk in class (~12 min for teams)
 - Use slides and upload to CCLE before presentation
 - Participation in Q&A
 - Brief Research report (due in the last week)
-

Week 2 Review

- Unix wildcards, basic regular expressions
 - More advanced commands (e.g., grep, find)
 - Text editing tools (tr, sed)
 - Pipelines and redirection
 - Simple shell scripting
-

Some Useful Exercises for HW2

- How to write script to see if file1 and file2 are same?
 - `cmp file1 file2`
 - How to obtain the return value or exist status of previous command?
 - `output=$(cmp file1 file2); echo "$output"`
 - `cmp file1 file2; echo $?`
 - What's the difference between `'`, `"`, and ```:
 - `date=20021226`
 - `echo '$date'`
 - `echo "$date"`
 - `echo "`date`"`
-

Regular expression exercises

- Which one would match “Gogle”, “Google” and “Gooogle” but not “Ggle”?
 - – Answer: “Go+gle”

 - Which regular expression would match any version of the word “Google” that has an even number of o’s?
 - – Answer: “G(oo)+gle”
-

Regular expression exercises

- Which line(s) would this regular expression match? “^T.+e\$”
 - A. The ; B. Te ; C. Three ; D. Then
 - Answer: The, Three (ERE)
-
- Which regular expression(s) would match the words “Ted”, “Ned” and “Sed”?
 - A. (T|N|S)ed ; B. [T N S]ed ; C. .ed ; D. [L-U]?ed ; E. *ed
 - Answer:
 - A., B., C.,
 - D., E. (ERE)
-

Some regular expression examples

- Credit card matching:
 - All Visa card numbers start with a 4. New cards have 16 digits. Old cards have 13.

`^4[0-9]{12}(?:[0-9]{3})?.$`

awk command

- awk [options] [program file]
 - **-F fs** To specify a file separator.
 - **-f file** To specify a file that contains awk script.
 - **-v var=value** To declare a variable.
 - Tasks:
 - Define variables.
 - Use string and arithmetic operators.
 - Use control flow and loops.
 - Generate formatted reports.
-

tr vs sed vs awk

- sed is a **stream** editor. It works with streams of characters on a per-line basis.
 - It has a primitive programming language that includes goto-style loops and simple conditionals (in addition to pattern matching and address matching).
 - There are essentially only two "variables": pattern space and hold space. Readability of scripts can be difficult. Mathematical operations are extraordinarily awkward at best.
 - tr perform character based transformation but sed perform string based transformation.
 - `echo I am a good boy | tr 'good' 'test'`
 - `echo I am a good boy | sed 's/good/best/g'`
 - awk is oriented toward **delimited** fields on a per-line basis.
 - It has much more robust programming constructs including if/else, while, do/while and for (C-style and array iteration).
 - Mathematical operations resemble those in C.
 - It has printf and functions.
-

Awk basic usage

- With awk, you can process text files. Awk assigns some variables for each data field found:
 - \$0 for the whole line.
 - \$1 for the first field.
 - \$2 for the second field.
 - \$n for the nth field.
- The whitespace character like space or tab is the default separator between fields in awk.
- `$ awk '{print $1}' myfile`

```
likegeeks@likegeeks-VirtualBox ~/Desktop $ cat myfile
This is a test.
This is the second test.
This is the thrid test.
This is the fourth test.
likegeeks@likegeeks-VirtualBox ~/Desktop $ awk '{print $1}' myfile
This
This
This
This
likegeeks@likegeeks-VirtualBox ~/Desktop $
```

Awk basic usage

- Sometimes the separator in some files is not space nor tab but something else. You can specify it using `-F` option:
- `awk -F: '{print $0}' /etc/passwd`

```
nobody:*:-2:-2:Unprivileged User:/var/empty:/usr/bin/false---> nobody
root:*:0:0:System Administrator:/var/root:/bin/sh---> root
daemon:*:1:1:System Services:/var/root:/usr/bin/false---> daemon
_uucp:*:4:4:Unix to Unix Copy Protocol:/var/spool/uucp:/usr/sbin/uucico---> _uucp
_taskgated:*:13:13:Task Gate Daemon:/var/empty:/usr/bin/false---> _taskgated
_networkd:*:24:24:Network Services:/var/networkd:/usr/bin/false---> _networkd
_installassistant:*:25:25:Install Assistant:/var/empty:/usr/bin/false---> _installassistant
_lp:*:26:26:Printing Services:/var/spool/cups:/usr/bin/false---> _lp
_postfix:*:27:27:Postfix Mail Server:/var/spool/postfix:/usr/bin/false---> _postfix
_scsd:*:31:31:Service Configuration Service:/var/empty:/usr/bin/false---> _scsd
_ces:*:32:32:Certificate Enrollment Service:/var/empty:/usr/bin/false---> _ces
```

Awk basic usage

- `echo "Hello Eggert" | awk '{$2="Guangyu"; print $0}'`
 - => Hello Guangyu
- Create your awk script then run.
- `awk -f myscript /etc/passwd`

```
BEGIN {  
  print "Users and thier corresponding home"  
  print " UserName \t HomePath"  
  print " _____ \t _____ "  
  FS=":"  
}  
{  
  print $1 " " \t " $6  
}  
END {  
  print "The end"
```

```
Users and thier corresponding shells  
UserName      HomePath  
_____  
root           /root  
daemon         /usr/sbin  
bin            /bin  
sys            /dev  
sync           /bin  
games          /usr/games  
man            /var/cache/man  
lp             /var/spool/lpd  
mail           /var/mail  
news           /var/spool/news  
uucp           /var/spool/uucp  
proxy          /bin
```

Modify and Rewrite Software

Week 3

Outline

- **Build from source & Bug Fixing**
 - **Compile using makefile**
 - **File patching**
 - Introduction to Python
-

How to Install Software

- Windows
 - Microsoft/Windows Installer
 - OS X
 - Drag and drop from .dmg mount -> Applications folder
 - Linux
 - rpm(Redhat Package Management)
 - RedHat Linux (.rpm)
 - apt-get(Advanced Package Tool)
 - Debian Linux, Ubuntu Linux (.deb) –
 - **Good old build process**
 - **configure, make, make install**
-

How to decompose files

- Generally, you receive Linux software in the tarball format (.tgz) or (.gz)
 - Decompress file in current directory:
 - `$ tar -xzvf filename.tar.gz`
 - Option `-x`: --extract
 - Option `-z`: --gzip
 - Option `-v`: --verbose
 - Option `-f`: --file
-

Compilation Process

Compilation

1

source code
file

prog1.cpp

C++
preprocessor

#included header
files

expanded
source code
file

temporary file; can be
printed on stdout

2

compiler

assembler
file

prog1.s

3

assembler

object code
file

prog1.o

4

linker

object code for
library functions

executable
file

prog1

Command-Line Compilation

- shop.cpp
 - #includes shoppingList.h and item.h
 - shoppingList.cpp
 - #includes shoppingList.h
 - item.cpp
 - #includes item.h
 - How to compile?
 - **g++ -Wall shoppingList.cpp item.cpp shop.cpp -o shop**
-

What if...

- **We change one of the header or source files?**
 - Rerun command to generate new executable
 - **We only made a small change to item.cpp?**
 - not efficient to recompile shoppinglist.cpp and shop.cpp
 - Solution: avoid waste by producing a separate object code file for each source file
 - g++ -Wall -c item.cpp... (for each source file)
 - g++ item.o shoppingList.o shop.o -o shop (combine)
 - Less work for compiler, saves time but more commands
-

What if...

- **We change item.h?**

- Need to recompile every source file that includes it & every source file that includes a header that includes it. Here: item.cpp and shop.cpp
- Difficult to keep track of files when project is large
 - Windows 7 ~40 million lines of code
 - Google ~2 billion lines of code

=> Make

Make

- Utility for managing large software projects
 - Compiles files and keeps them up-to-date
 - Efficient Compilation (only files that need to be recompiled)
-

Makefile Example

Makefile - A Basic Example

all : shop #usually first

shop : item.o shoppingList.o shop.o

g++ -g -Wall -o shop item.o shoppingList.o shop.o

item.o : item.cpp item.h

g++ -g -Wall -c item.cpp

shoppingList.o : shoppingList.cpp shoppingList.h

g++ -g -Wall -c shoppingList.cpp

shop.o : shop.cpp item.h shoppingList.h

g++ -g -Wall -c shop.cpp

clean :

rm -f item.o shoppingList.o shop.o shop

} Rule

■ Comments
■ Targets
■ Prerequisites
■ Commands

} Dependency Line

Build Process

- **configure**
 - Script that checks details about the machine before installation
 - Dependency between packages
 - Creates 'Makefile'
 - **make**
 - Requires 'Makefile' to run
 - Compiles all the program code and creates executables in current temporary directory
 - **make install**
 - make utility searches for a label named install within the Makefile, and executes only that section of it
 - executables are copied into the final directories (system directories)
-

Task: Fixing a bug

- On a certain computer (not necessarily seasnet), the command `ls -l /bin/bash` displays:

```
$ ls -l /bin/bash
```

```
-rwxr-xr-x 1 root root 729040 2009-03-02 06:22 /bin/bash
```

- But this is a bug, you want it to display traditional Linux format:

```
$ ls -l /bin/bash
```

```
-rwxr-xr-x 1 root root 729040 Mar 2 2009 /bin/bash
```

Steps for fixing bugs

- Outputs the 'buggy result'
 - `ls -l --time-style=long-iso /bin/bash`
 - Login to Seasnet
 - Download coreutils to a temporary directory
 - How to download file (wget)
 - Untar\Unzip it
 - How to unzip a file
 - `man tar`
 - `cd` to the newly created coreutils folder
-

The tar command

- Usage of tar
 - `tar -cvf <tarfilename.tar> <target directories>` # creates tar file.
 - `tar -tvf <tarfilename.tar>` # list tar file contents
 - `tar -xvf <tarfilename.tar>` # extracts tar file
 - -z option: generate .gz files
 - Tips
 - Always create tarfile in target directory (relative file/directory names)
 - Always list tarfile before extracting (insure relative file names)
 - Always extact tarfile in target directory (relative file/directory names)
 - Example
 - `tar -tvf a2.tar`
 - `tar -xzvf filename.tar.gz`
-

Compile using makefile

- Download a utility from the internet to your Linux machine
 - There are no binaries, but source code and makefile is available
 - Compile and build to install it
 - Reading text files(e.g. README) in the program folder gives clues how to install the program
-

Compile using makefile

- The order of compilation is usually:
 - `./configure`
 - `make`
 - `make install`
 - Usage: `man make`
 - View makefile in the programs folder for details
 - Configure
 - Setup the path for make and install
 - Should use **absolute path** here
 - Demo
-

Makefile and make

- Function of makefile: Instruct how to compile and link a program
 - The make program allows you to use **macros**, which are similar to variables to codify how to compile a set of source code
 - Macros are assigned as BASH variable:
 - CFLAGS= -O -systype bsd43
 - LIBS = "-lncurses -lm -lsdl"
 - Makefile is invoked with **make <target_name>**
-

Standard “targets”

- People have come to expect certain targets in Makefiles. You should always browse first, but it's reasonable to expect that the targets `all` (or just `make`), `install`, and `clean` will be found
 - **make**: compile the default target
 - **make all**: compile everything so that you can do local testing before installing
 - **make install**: install things in the right places. But watch out that things are installed in the right place for your system
 - **make clean**: clean things up. Get rid of the executables, any temporary files, object files, etc.
 - Details: see supplement materials [GCC and Make]
-

Apply a patch

- Read the patch bug report

<http://lists.gnu.org/archive/html/bug-coreutils/2009-09/msg00410.html>


- Understand what part of the code is being fixed
-

Patching

- A patch is a piece of software designed to fix problems with or update a computer program
 - It's a *.diff* file that includes the changes made to a file
 - A person who has the original (buggy) file can use the patch command with the *diff* file to add the changes to their original file
 - Patch Command
 - Usage: patch [options] [originalfile] [patchfile]
 - **-pnum**: strip the smallest prefix containing num leading slashes from each file name found in the patch file
 - Examples: see supplement materials [Patch command]
-

Applying a patch

Source Files



diff Unified Format

- `--- path/to/original_file`
 - `+++ path/to/modified_file`
 - `@@ -l,s +l,s @@`
 - `@@`: beginning and end of a hunk
 - `l`: beginning line number
 - `s`: number of lines the change hunk applies to for each file
 - A line with:
 - `-` sign was deleted from the original
 - `+` sign was added in the new file
 - `'` stayed the same
-

Applying the Patch

```
diff --git a/src/ls.c b/src/ls.c
```

```
index 1bb6873..4531b94 100644
```

```
--- a/src/ls.c
```

```
+++ b/src/ls.c
```

```
@@ -2014,7 +2014,6 @@ decode_switches (int argc, char **argv)
```

```
    break;
```

```
    case long_iso_time_style:
```

```
-    case_long_iso_time_style:
```

```
    long_time_format[0] = long_time_format[1] = "%Y-%m-%d %H:%M";
```

```
    break;
```

```
@@ -2030,13 +2029,8 @@ decode_switches (int argc, char **argv)
```

```
    formats.  If not, fall back on long-iso format.  */
```

```
    int i;
```

```
    for (i = 0; i < 2; i++)
```

```
-    {
```

```
        char const *locale_format =
```

```
            dcgettext (NULL, long_time_format[i], LC_TIME);
```

```
        if (locale_format == long_time_format[i])
```

```
            goto case_long_iso_time_style;
```

```
        long_time_format[i] = locale_format;
```

```
-    }
```

```
+    long_time_format[i] =
```

```
+    dcgettext (NULL, long_time_format[i], LC_TIME);
```

```
    }
```

```
}
```

```
/* Note we leave %5b etc. alone so user widths/flags are honored.  */
```

Additional Resource

- Guide: Building and Installing Software Packages for Linux
<https://www.tldp.org/HOWTO/pdf/Software-Building-HOWTO.pdf>
-