

CS35L – Winter ‘19

Slide set:	5.2
Slide topics:	System call programming
Assignment:	5



Laboratory

- Write `tr2b` and `tr2u` programs in 'C' that transliterate bytes. They take two arguments *from* and *to*. The programs will transliterate every byte in *from* to the corresponding byte in *to*

```
./tr2b 'abcd' 'wxyz' < bigfile.txt
```

```
./tr2b 'mno' 'pqr' < bigfile.txt
```

- `tr2u` uses **getchar** and **putchar** to read from STDIN and write to STDOUT.
 - `tr2b` uses **read** and **write** to read and write each byte, instead of using `getchar` and `putchar`. The `nbyte` argument should be `1` so it reads/writes a single byte at a time.
 - Test it on a big file with 5,000,000 bytes

```
$ head --bytes=# /dev/urandom > output.txt
```
-

time and strace

- **time** [*options*] *command* [*arguments...*]
 - Output:
 - real 0m4.866s: elapsed time as read from a wall clock
 - user 0m0.001s: the CPU time used by your process
 - sys 0m0.021s: the CPU time used by the system on behalf of your process (to make system calls etc)
 - **strace**: intercepts and prints out system calls to stderr or to an output file
 - \$ strace -c ./tr2b 'AB' 'XY' < input.txt
 - \$ strace -c ./tr2u 'AB' 'XY' < input.txt
-

Homework

5

(sfrobu.c)

- Rewrite `sfrob` using system calls (`sfrobu`)
- `sfrobu` should behave like `sfrob` except:
 - If `stdin` is a regular file, it should initially allocate enough memory to hold all data in the file all at once
 - `-f` option, your program should ignore case while sorting (use the standard `toupper` function to upper-case each byte after decrypting and before comparing the byte)
- Functions you'll need: `read`, `write`, and `fstat` (read the man pages)
- Measure differences in performance between `sfrob` and `sfrobu` using the `time` command

Homework

5(sfrobs)



Write a shell script “sfrobs” that uses `tr` and the `sort` utility to perform the same overall operation as `sfrobu` (support `-f` option as well)



Use pipelines (create no temporary files)



Encrypted input -> `tr` (decrypt) -> `sort` (sort decrypted text) -> `tr` (encrypt) -> encrypted output

Homework 5(sfrob.txt)

Measure

Measure any differences in performance between sfrob and sfrobu using the time command.

Run

Run your program on inputs of varying numbers of input lines, and estimate the number of comparisons as a function of the number of input lines.

Compare

Use the time command to compare the overall performance of sfrob, sfrobu, sfrobs, sfrobu -f, and sfrobs -f.

01

Run your program on inputs of varying numbers of input lines, and estimate the number of comparisons as a function of the number of input lines.

02

Varying number of input lines => number of words

03

Number of comparisons => keep a counter in the `frobcmp()` function to check how many times it is being called

Homework 5
