

AiFinPay Merchant Integration Guide

Document: AIFP Merchant Integration Guide **Audience:** Backend engineers **Status:** Stable **Version:** 1.0.0 **Date:** June 28, 2026 **Contact:** developers@aifinpay.io · <https://docs.aifinpay.io>

This is **Document 2 of 4** in the official AiFinPay documentation set:

1. [AIFP-1 — Payment Protocol Specification](#) — the normative standard
2. **Merchant Integration Guide** (*this document*)
3. [AI Agent SDK Specification](#)
4. [Security & Cryptography Specification](#)

This guide is **self-contained** for integration purposes. It conforms to AIFP-1; where protocol details are summarized here, the [AIFP-1 specification](#) governs.

Copyright Notice

Copyright © 2026 AiFinPay, Inc. Licensed under CC BY 4.0. Code samples are licensed Apache-2.0/MIT and may be used without attribution.

Table of Contents

1. [Overview & Mental Model](#)
 2. [Core Concepts You Must Internalize](#)
 3. [The Integration Checklist](#)
 4. [Pricing Engine & Free Quota](#)
 5. [Receipt Verification \(the one thing you must get right\)](#)
 6. [Framework Integrations - Express - Fastify - NestJS - Next.js - FastAPI - Django - Laravel - Spring Boot - ASP.NET Core - Go \(net/http + chi\) - Rust \(Axum\) - Cloudflare Workers - NGINX - Apache - WordPress](#)
 7. [Error Handling & Retry](#)
 8. [Production Best Practices](#)
 9. [Security](#)
 10. [Scaling](#)
 11. [Benchmarks](#)
 12. [Glossary](#)
 13. [References](#)
-

1. Overview & Mental Model

You are a backend engineer. You have an API or content endpoint that AI agents hit. Today you either give it away free or block the bots. **AiFinPay lets you charge them, per request, automatically.**

Integration is one piece of middleware that does four things on every request:

1. **Identify** the agent (`AIFP-Agent-ID` header or fingerprint).
2. **Count** against a free quota (default 100 requests).
3. When quota is gone, **challenge** with `402 Payment Required` + a machine-readable payment challenge.
4. When the agent retries with a `Payment-Receipt` , **verify it locally** (Ed25519 signature — no network call) and serve the resource.

```
flowchart LR
    R[Request] --> ID[Identify agent]
    ID --> Q{Quota left?}
    Q -- yes --> SERVE[Serve + decrement]
    Q -- no --> REC{Receipt present?}
    REC -- no --> CH[402 + Challenge]
    REC -- yes --> V{Valid?}
    V -- yes --> SERVE
    V -- replay --> C409[409]
    V -- invalid --> C422[422]
```

The crucial property: **the AiFinPay backend is never in your request hot path.** Quota lives in your cache; receipt verification is a local signature check. Your latency overhead is microseconds, and you keep serving even if AiFinPay is down (see [§8 degraded mode](#)).

2. Core Concepts You Must Internalize

Concept	What it means for you
Payment Challenge	The JSON/ <code>402</code> you return when quota is exhausted. Must include <code>nonce</code> + <code>expires_at</code> .
Receipt Token	An EdDSA-signed JWT the agent sends on retry. You verify it locally.
Stateless verification	Verify by signature + claims (<code>aud</code> , <code>resource</code> , <code>exp</code> , <code>amount</code> , <code>nonce</code>). No call to AiFinPay.
Nonce store	A short-TTL set (Redis/in-memory) preventing receipt replay. TTL = receipt TTL (~600s).
Pricing Tier tier	You tag each route <code>standard</code> / <code>complex</code> / <code>premium</code> → price.
Free quota	First N requests per agent are free (default 100).

Concept	What it means for you
JWKS	AiFinPay's public keys. Cache them; refresh on unknown <code>kid</code> .

Pricing defaults (override per route): **standard USD 0.00001** · **complex USD 0.00006** · **premium USD 0.00010**.

JWKS endpoint: `https://api.aifinpay.io/.well-known/jwks.json` — **cache it** (e.g., 1h), refresh on cache-miss of a `kid`.

3. The Integration Checklist

```
[ ] Install the AiFinPay merchant SDK (or implement verification directly).
[ ] Set AIFP_MERCHANT_ID and AIFP_API_KEY from env.
[ ] Configure free quota (default 100) + per-route pricing_tier tiers.
[ ] Wire middleware: identify → quota → challenge / verify.
[ ] Cache JWKS; handle key rotation by kid.
[ ] Add a nonce store (Redis) for replay protection.
[ ] Map verification failures to 402 / 409 / 422 correctly.
[ ] Verify webhook signatures (HMAC-SHA256) if you consume webhooks.
[ ] Load-test; confirm degraded-mode behavior when AiFinPay is unreachable.
[ ] Ship behind TLS 1.3.
```

4. Pricing Engine & Free Quota

A merchant maps a request to a **pricing_tier tier**, which maps to a **price**. The simplest engine is a static route table; advanced setups use rules (method, path, query weight, payload size) and may consult the Dynamic Pricing Engine.

```
// pricing.ts – framework-agnostic
export type PricingTier = "standard" | "complex" | "premium";

const PRICE: Record<PricingTier, string> = {
  standard: "0.00001", complex: "0.00006", premium: "0.00010",
};

const ROUTE_TIER: { test: RegExp; tier: PricingTier }[] = [
  { test: /^\/api\/lookup\/$/, tier: "standard" },
  { test: /^\/api\/search/, tier: "complex" },
  { test: /^\/api\/infer/, tier: "premium" },
];

export function tierFor(path: string): PricingTier {
  return ROUTE_TIER.find(r => r.test.test(path))?.tier ?? "standard";
}
```

```
export function priceFor(path: string): string { return PRICE[tierFor(path)]; }

export const FREE_QUOTA = Number(process.env.AIFP_FREE_QUOTA ?? 100);
```

Free quota is a per-agent counter in your cache. Atomic decrement (Redis `INCR / DECR`) avoids race conditions under concurrency:

```
async function quotaRemaining(redis, agentId: string): Promise<number> {
  const used = await redis.incr(`aifp:quota:${agentId}`);
  if (used === 1) await redis.expire(`aifp:quota:${agentId}`, 60 * 60 * 24 * 30); // mo
  return FREE_QUOTA - used;
}
```

5. Receipt Verification (the one thing you must get right)

Every integration below ultimately calls one function. Get this right and the rest is glue. The canonical algorithm (AIFP-1 §7.4):

```
// verify.ts – the heart of every merchant integration
import { jwtVerify, createRemoteJWKSet } from "jose";

const JWKS = createRemoteJWKSet(new URL("https://api.aifinpay.io/.well-known/jwks.json"));
const ISSUER = "https://api.aifinpay.io";

// Compare decimal USD strings as integer minor units (×10^8) – never use float.
function toMinorUnits(s: string): bigint {
  const [int, frac = ""] = s.split(".");
  return BigInt(int) * 10n ** 8n + BigInt(frac.padEnd(8, "0").slice(0, 8));
}

function amountGte(a: string, b: string): boolean { return toMinorUnits(a) >= toMinorUnits(b); }

export type VerifyResult =
  | { ok: true; receiptId: string; nonce: string; exp: number }
  | { ok: false; status: 402 | 409 | 422; reason: string };

export async function verifyReceipt(opts: {
  token: string; merchantId: string; resource: string; requiredAmount: string;
  nonceSeen: (n: string) => Promise<boolean>; // returns true if replay
  markNonce: (n: string, ttl: number) => Promise<void>;
}): Promise<VerifyResult> {
  let payload: any;
  try {
    ({ payload } = await jwtVerify(opts.token, JWKS, {
      issuer: ISSUER, audience: opts.merchantId, algorithms: ["EdDSA"],
      clockTolerance: 30, // seconds
    }));
  } catch {
    return { ok: false, status: 402, reason: "Invalid token" };
  }
  const nonce = payload.nonce;
  if (opts.nonceSeen(nonce) === true) return { ok: false, status: 409, reason: "Nonce seen" };
  if (!amountGte(payload.amount, opts.requiredAmount)) return { ok: false, status: 422, reason: "Amount too low" };
  return { ok: true, receiptId: payload.receiptId, nonce, exp: payload.exp };
}
```

```

} catch { return { ok: false, status: 422, reason: "signature/exp/aud invalid" }; }

if (payload.resource !== opts.resource)
  return { ok: false, status: 422, reason: "resource mismatch" };
if (!amountGte(payload.amount, opts.requiredAmount))
  return { ok: false, status: 422, reason: "amount below price" };

if (await opts.nonceSeen(payload.nonce))
  return { ok: false, status: 409, reason: "receipt replay" };

const ttl = Math.max(1, payload.exp - Math.floor(Date.now() / 1000));
await opts.markNonce(payload.nonce, ttl);
return { ok: true, receiptId: payload.receipt_id, nonce: payload.nonce, exp: payload.exp };
}

```

Why local? Ed25519 verifies at ~50k ops/s/core. Verifying on your side means AiFinPay availability never gates your traffic, and you add only microseconds per request. This is non-negotiable for scale (AIFP-1 §4.2).

The Python equivalent (used by FastAPI/Django) and others mirror this exactly. Each framework section below shows the framework glue; the verification logic is always this algorithm.

6. Framework Integrations

Every example: installs the SDK, configures env, adds middleware, returns a conformant 402 challenge, and verifies receipts locally. Replace `mrch_...` and keys with your own. All snippets are production-shaped (error handling, headers, nonce store).

6.1. Express (Node.js)

Install

```
npm install @aifinpay/merchant jose ioredis
```

Middleware

```

import express from "express";
import Redis from "ioredis";
import { verifyReceipt } from "../verify";
import { priceFor, tierFor, FREE_QUOTA } from "../pricing";
import crypto from "crypto";

const app = express();

```

```

const redis = new Redis(process.env.REDIS_URL!);
const MERCHANT_ID = process.env.AIFP_MERCHANT_ID!;

function challenge(res, resource: string) {
  const nonce = crypto.randomBytes(16).toString("hex");
  res.status(402)
    .set("AIFP-Payment-Required", "true")
    .set("Accept-Payment", "aifp/1.0")
    .json({
      error: { type: "payment_required", code: "AIFP-402", message: "Free quota exhausted" },
      payment_challenge: {
        version: "1.0", scheme: "aifp",
        quote_endpoint: "https://api.aifinpay.io/v1/quote",
        merchant_id: MERCHANT_ID, resource, pricing_tier: tierFor(resource),
        estimated_amount: priceFor(resource), currency: "USD",
        accepted_assets: ["USDC", "USDT", "PYUSD"],
        accepted_chains: ["polygon", "base", "solana"],
        nonce, expires_at: new Date(Date.now() + 300_000).toISOString(),
      },
    });
}

export async function aifp(req, res, next) {
  const resource = req.path;
  const agentId = req.header("AIFP-Agent-ID") || req.ip;

  const used = await redis.incr(`q:${agentId}`);
  if (used === 1) await redis.expire(`q:${agentId}`, 2592000);
  if (used <= FREE_QUOTA) return next(); // free tier

  const token = req.header("Payment-Receipt");
  if (!token) return challenge(res, resource);

  const r = await verifyReceipt({
    token, merchantId: MERCHANT_ID, resource, requiredAmount: priceFor(resource),
    nonceSeen: n => redis.exists(`n:${n}`).then(Boolean),
    markNonce: (n, ttl) => redis.set(`n:${n}`, "1", "EX", ttl).then(() => {}),
  });
  if (!r.ok) {
    if (r.status === 402) return challenge(res, resource);
    return res.status(r.status).json({ error: { code: `AIFP-${r.status}`, message: r.reason } });
  }
  next();
}

app.use(aifp);
app.get("/api/data", (_req, res) => res.json({ data: "premium content" }));
app.listen(3000);

```

6.2. Fastify (Node.js)

```
npm install fastify @aifinpay/merchant jose ioredis
```

```

import Fastify from "fastify";
import Redis from "ioredis";
import { verifyReceipt } from "../verify";
import { priceFor, tierFor, FREE_QUOTA } from "../pricing";
import crypto from "crypto";

const app = Fastify();
const redis = new Redis(process.env.REDIS_URL!);
const MERCHANT_ID = process.env.AIFP_MERCHANT_ID!;

app.addHook("onRequest", async (req, reply) => {
  const resource = req.url.split("?")[0];
  const agentId = (req.headers["aifp-agent-id"] as string) || req.ip;
  const used = await redis.incr(`q:${agentId}`);
  if (used === 1) await redis.expire(`q:${agentId}`, 2592000);
  if (used <= FREE_QUOTA) return;

  const token = req.headers["payment-receipt"] as string | undefined;
  const send402 = () => {
    const nonce = crypto.randomBytes(16).toString("hex");
    reply.code(402).headers({ "AIFP-Payment-Required": "true", "Accept-Payment": "aifp/"
      error: { type: "payment_required", code: "AIFP-402", message: "Free quota exhaust
      payment_challenge: {
        version: "1.0", scheme: "aifp", quote_endpoint: "https://api.aifinpay.io/v1/qu
        merchant_id: MERCHANT_ID, resource, pricing_tier: tierFor(resource),
        estimated_amount: priceFor(resource), currency: "USD", nonce,
        expires_at: new Date(Date.now() + 300_000).toISOString(),
      },
    });
  };
  if (!token) return send402();

  const r = await verifyReceipt({
    token, merchantId: MERCHANT_ID, resource, requiredAmount: priceFor(resource),
    nonceSeen: n => redis.exists(`n:${n}`).then(Boolean),
    markNonce: (n, ttl) => redis.set(`n:${n}`, "1", "EX", ttl).then(() => {}),
  });
  if (!r.ok) return r.status === 402 ? send402()
    : reply.code(r.status).send({ error: { code: `AIFP-${r.status}`, message: r.reason
  });

  app.get("/api/data", async () => ({ data: "premium content" }));
  app.listen({ port: 3000 });

```

6.3. NestJS

```
npm install @nestjs/common @aifinpay/merchant jose ioredis
```

```

// aifp.guard.ts
import { CanActivate, ExecutionContext, Injectable } from "@nestjs/common";

```

```

import Redis from "ioredis";
import crypto from "crypto";
import { verifyReceipt } from "../verify";
import { priceFor, tierFor, FREE_QUOTA } from "../pricing";

@Injectable()
export class AifpGuard implements CanActivate {
  private redis = new Redis(process.env.REDIS_URL!);
  private MERCHANT_ID = process.env.AIFP_MERCHANT_ID!;

  async canActivate(ctx: ExecutionContext): Promise<boolean> {
    const req = ctx.switchToHttp().getRequest();
    const res = ctx.switchToHttp().getResponse();
    const resource = req.path;
    const agentId = req.headers["aifp-agent-id"] || req.ip;

    const used = await this.redis.incr(`q:${agentId}`);
    if (used === 1) await this.redis.expire(`q:${agentId}`, 2592000);
    if (used <= FREE_QUOTA) return true;

    const token = req.headers["payment-receipt"];
    const challenge = () => {
      const nonce = crypto.randomBytes(16).toString("hex");
      res.status(402).set("Accept-Payment", "aifp/1.0").json({
        error: { code: "AIFP-402", message: "Free quota exhausted." },
        payment_challenge: { version: "1.0", scheme: "aifp", merchant_id: this.MERCHANT_ID,
          resource, pricing_tier: tierFor(resource), estimated_amount: priceFor(resource),
          quote_endpoint: "https://api.aifinpay.io/v1/quote", nonce,
          expires_at: new Date(Date.now() + 300_000).toISOString() } });
      return false;
    };
    if (!token) return challenge();

    const r = await verifyReceipt({
      token, merchantId: this.MERCHANT_ID, resource, requiredAmount: priceFor(resource),
      nonceSeen: n => this.redis.exists(`n:${n}`).then(Boolean),
      markNonce: (n, ttl) => this.redis.set(`n:${n}`, "1", "EX", ttl).then(() => {}),
    });
    if (r.ok) return true;
    if (r.status === 402) return challenge();
    res.status(r.status).json({ error: { code: `AIFP-${r.status}`, message: r.reason } });
    return false;
  }
}

// usage: @UseGuards(AifpGuard) on a controller/route

```

6.4. Next.js

Use Edge Middleware so the check runs before the route. Receipt verification works at the edge (Web Crypto / `jose`).


```
// middleware.ts
import { NextRequest, NextResponse } from "next/server";
import { jwtVerify, createRemoteJWKSet } from "jose";

const JWKS = createRemoteJWKSet(new URL("https://api.aifinpay.io/.well-known/jwks.json"));
const MERCHANT_ID = process.env.AIFP_MERCHANT_ID!;
const PRICE = { standard: "0.00001", complex: "0.00006", premium: "0.00010" } as const;

export async function middleware(req: NextRequest) {
  const resource = req.nextUrl.pathname;
  if (!resource.startsWith("/api/")) return NextResponse.next();

  const token = req.headers.get("payment-receipt");
  const challenge = () => NextResponse.json({
    error: { code: "AIFP-402", message: "Payment required." },
    payment_challenge: { version: "1.0", scheme: "aifp", merchant_id: MERCHANT_ID, resource: resource, pricing_tier: "standard", estimated_amount: PRICE.standard, quote_endpoint: "https://api.aifinpay.io/v1/quote", nonce: crypto.randomUUID(), expires_at: new Date(Date.now() + 300_000).toISOString() },
    { status: 402, headers: { "Accept-Payment": "aifp/1.0" } }
  });

  // (quota check omitted for brevity – use Upstash Redis at edge)
  if (!token) return challenge();
  try {
    const { payload } = await jwtVerify(token, JWKS, {
      issuer: "https://api.aifinpay.io", audience: MERCHANT_ID, algorithms: ["EdDSA"],
    });
    const toUnits = (s: string) => { const [i, f = ""] = s.split("."); return BigInt(i) + (f ? BigInt(f.padEnd(10, '0')) : 0); };
    if (payload.resource !== resource || toUnits(payload.amount) < toUnits(PRICE.standard))
      return NextResponse.json({ error: { code: "AIFP-422" } }, { status: 422 });
    return NextResponse.next();
  } catch { return challenge(); }
}

export const config = { matcher: "/api/:path*" };

```

6.5. FastAPI (Python)

```
pip install fastapi uvicorn "python-jose[cryptography]" httpx redis
```

```
# aifp.py
import time, secrets, httpx
from decimal import Decimal
from fastapi import Request, HTTPException
from fastapi.responses import JSONResponse
from jose import jwt
from functools import lru_cache
import redis.asyncio as redis

MERCHANT_ID = "mrch_9f3a1c2b"
ISSUER = "https://api.aifinpay.io"

```

```

JWKS_URL = "https://api.aifinpay.io/.well-known/jwks.json"
PRICE = {"standard": "0.00001", "complex": "0.00006", "premium": "0.00010"}
FREE_QUOTA = 100
r = redis.from_url("redis://localhost")

@lru_cache(maxsize=1)
def _jwks():
    return httpx.get(JWKS_URL, timeout=5).json()

def tier_for(path): return "standard"

def challenge(resource):
    return JSONResponse(status_code=402, headers={"Accept-Payment": "aifp/1.0"}, content={
        "error": {"code": "AIFP-402", "message": "Free quota exhausted."},
        "payment_challenge": {
            "version": "1.0", "scheme": "aifp", "merchant_id": MERCHANT_ID,
            "resource": resource, "pricing_tier": tier_for(resource),
            "estimated_amount": PRICE[tier_for(resource)],
            "quote_endpoint": f"{ISSUER}/v1/quote",
            "nonce": secrets.token_hex(16),
            "expires_at": time.strftime("%Y-%m-%dT%H:%M:%SZ", time.gmtime(time.time() +
        )))

async def aifp_middleware(request: Request, call_next):
    resource = request.url.path
    if not resource.startswith("/api/"):
        return await call_next(request)

    agent = request.headers.get("aifp-agent-id") or request.client.host
    used = await r.incr(f"q:{agent}")
    if used == 1: await r.expire(f"q:{agent}", 2592000)
    if used <= FREE_QUOTA:
        return await call_next(request)

    token = request.headers.get("payment-receipt")
    if not token:
        return challenge(resource)
    try:
        payload = jwt.decode(token, _jwks(), algorithms=["EdDSA"],
                               audience=MERCHANT_ID, issuer=ISSUER)
    except Exception:
        return challenge(resource)
    if payload.get("resource") != resource:
        return JSONResponse({"error": {"code": "AIFP-422"}}, status_code=422)
    if Decimal(payload["amount"]) < Decimal(PRICE[tier_for(resource)]):
        return JSONResponse({"error": {"code": "AIFP-422-AMOUNT"}}, status_code=422)
    if await r.exists(f"n:{payload['nonce']}"):
        return JSONResponse({"error": {"code": "AIFP-409"}}, status_code=409)
    await r.set(f"n:{payload['nonce']}", "1", ex=max(1, int(payload['exp'] - time.time())))
    return await call_next(request)

```

```

# main.py
from fastapi import FastAPI

```

```

from aifp import aifp_middleware
app = FastAPI()
app.middleware("http")(aifp_middleware)

@app.get("/api/data")
async def data(): return {"data": "premium content"}

```

6.6. Django (Python)

```

pip install django "python-jose[cryptography]" httpx redis

```

```

# aifp_middleware.py
import time, secrets, httpx
from decimal import Decimal
from django.http import JsonResponse
from jose import jwt
import redis

MERCHANT_ID = "mrch_9f3a1c2b"; ISSUER = "https://api.aifinpay.io"
JWKS = httpx.get("https://api.aifinpay.io/.well-known/jwks.json", timeout=5).json()
PRICE = {"standard": "0.00001"}; FREE_QUOTA = 100
R = redis.from_url("redis://localhost")

class AifpMiddleware:
    def __init__(self, get_response): self.get_response = get_response
    def __call__(self, request):
        resource = request.path
        if not resource.startswith("/api/"):
            return self.get_response(request)
        agent = request.headers.get("AIFP-Agent-ID") or request.META["REMOTE_ADDR"]
        used = R.incr(f"q:{agent}")
        if used == 1: R.expire(f"q:{agent}", 2592000)
        if used <= FREE_QUOTA:
            return self.get_response(request)
        token = request.headers.get("Payment-Receipt")
        if not token: return self._challenge(resource)
        try:
            p = jwt.decode(token, JWKS, algorithms=["EdDSA"], audience=MERCHANT_ID, iss
        except Exception:
            return self._challenge(resource)
        if p.get("resource") != resource or Decimal(p["amount"]) < Decimal(PRICE["stand
            return JsonResponse({"error": {"code": "AIFP-422"}}, status=422)
        if R.exists(f"n:{p['nonce']}"):
            return JsonResponse({"error": {"code": "AIFP-409"}}, status=409)
        R.set(f"n:{p['nonce']}", "1", ex=max(1, int(p["exp"] - time.time())))
        return self.get_response(request)

    def _challenge(self, resource):
        return JsonResponse(status=402, headers={"Accept-Payment": "aifp/1.0"}, data={
            "error": {"code": "AIFP-402", "message": "Payment required."},
            "payment_challenge": {"version": "1.0", "scheme": "aifp", "merchant_id": ME

```

```

        "resource": resource, "pricing_tier": "standard", "estimated_amount": P
        "quote_endpoint": f"{ISSUER}/v1/quote", "nonce": secrets.token_hex(16),
        "expires_at": time.strftime("%Y-%m-%dT%H:%M:%SZ", time.gmtime(time.time
# settings.py: MIDDLEWARE = [..., "aifp_middleware.AifpMiddleware"]

```

6.7. Laravel (PHP)

```
composer require firebase/php-jwt predis/predis guzzlehttp/guzzle
```

```

<?php // app/Http/Middleware/Aifp.php
namespace App\Http\Middleware;
use Closure; use Illuminate\Http\Request;
use Firebase\JWT\JWT; use Firebase\JWT\JWK;
use Predis\Client as Redis;

class Aifp {
    private string $merchant = 'mrch_9f3alc2b';
    private string $issuer = 'https://api.aifinpay.io';
    private array $price = ['standard' => '0.00001'];
    private int $quota = 100;

    public function handle(Request $req, Closure $next) {
        $resource = $req->getPathInfo();
        if (!str_starts_with($resource, '/api/')) return $next($req);
        $redis = new Redis();
        $agent = $req->header('AIFP-Agent-ID') ?? $req->ip();
        $used = $redis->incr("q:$agent");
        if ($used === 1) $redis->expire("q:$agent", 2592000);
        if ($used <= $this->quota) return $next($req);

        $token = $req->header('Payment-Receipt');
        if (!$token) return $this->challenge($resource);
        try {
            $jwks = json_decode(file_get_contents("$this->issuer/.well-known/jwks.json"));
            $p = (array) JWT::decode($token, JWK::parseKeySet($jwks));
        } catch (\Throwable $e) { return $this->challenge($resource); }
        if (($p['aud'] ?? '') !== $this->merchant || ($p['resource'] ?? '') !== $resource)
            return response()->json(['error' => ['code' => 'AIFP-422']], 422);
        if (bccomp($p['amount'] ?? '0', $this->price['standard'], 8) < 0)
            return response()->json(['error' => ['code' => 'AIFP-422-AMOUNT']], 422);
        if ($redis->exists("n:{$p['nonce']}"))
            return response()->json(['error' => ['code' => 'AIFP-409']], 409);
        $redis->setex("n:{$p['nonce']}", max(1, $p['exp'] - time()), '1');
        return $next($req);
    }

    private function challenge(string $resource) {
        return response()->json([
            'error' => ['code' => 'AIFP-402', 'message' => 'Payment required.'],
            'payment_challenge' => ['version' => '1.0', 'scheme' => 'aifp',

```

```

        'merchant_id' => $this->merchant, 'resource' => $resource, 'pricing_tie
        'estimated_amount' => $this->price['standard'],
        'quote_endpoint' => "$this->issuer/v1/quote", 'nonce' => bin2hex(random
        'expires_at' => gmdate('Y-m-d\TH:i:s\Z', time() + 300)],
    ], 402)->header('Accept-Payment', 'aifp/1.0');
    }
}

```

6.8. Spring Boot (Java)

```

<!-- pom.xml -->
<dependency><groupId>com.nimbusds</groupId><artifactId>nimbus-jose-jwt</artifactId><ver
<dependency><groupId>org.springframework.boot</groupId><artifactId>spring-boot-starter-

```

```

// AifpFilter.java
@Component
public class AifpFilter extends OncePerRequestFilter {
    private static final String MERCHANT = "mrch_9f3alc2b";
    private static final String ISSUER = "https://api.aifinpay.io";
    private static final long QUOTA = 100;
    @Autowired StringRedisTemplate redis;
    private final JWKSSource<SecurityContext> jwks =
        JWKSSourceBuilder.create(new URL(ISSUER + "/.well-known/jwks.json")).build();

    @Override protected void doFilterInternal(HttpServletRequest req, HttpServletResponse
        throws ServletException, IOException {
        String resource = req.getRequestURI();
        if (!resource.startsWith("/api/")) { chain.doFilter(req, res); return; }
        String agent = Optional.ofNullable(req.getHeader("AIFP-Agent-ID")).orElse(req.getRe
        Long used = redis.opsForValue().increment("q:" + agent);
        if (used != null && used == 1) redis.expire("q:" + agent, Duration.ofDays(30));
        if (used != null && used <= QUOTA) { chain.doFilter(req, res); return; }

        String token = req.getHeader("Payment-Receipt");
        if (token == null) { challenge(res, resource); return; }
        try {
            ConfigurableJWTProcessor<SecurityContext> p = new DefaultJWTProcessor<>();
            p.setJWSKeySelector(new JWSVerificationKeySelector<>(JWSAlgorithm.EdDSA, jwks));
            JWTClaimsSet c = p.process(token, null);
            if (!MERCHANT.equals(c.getAudience().get(0)) || !resource.equals(c.getStringClaim
                { res.setStatus(422); return; }
            if (new java.math.BigDecimal(c.getStringClaim("amount")).compareTo(new java.math.
            String nonce = c.getStringClaim("nonce");
            if (Boolean.TRUE.equals(redis.hasKey("n:" + nonce))) { res.setStatus(409); return
            long ttl = Math.max(1, c.getExpirationTime().getTime()/1000 - System.currentTimeM
            redis.opsForValue().set("n:" + nonce, "1", Duration.ofSeconds(ttl));
            chain.doFilter(req, res);
        } catch (Exception e) { challenge(res, resource); }
    }
}

```

```

private void challenge(HttpServletResponse res, String resource) throws IOException {
    res.setStatus(402); res.setHeader("Accept-Payment", "aifp/1.0");
    res.setContentType("application/json");
    res.getWriter().write("{\"error\":{\"code\":\"AIFP-402\"},\"payment_challenge\":{\""
        + MERCHANT + "\",\"resource\":\"" + resource + "\",\"pricing_tier\":\"standard\",
        + ISSUER + "/v1/quote\"}}");
    }
}

```

6.9. ASP.NET Core (C#)

```

dotnet add package Microsoft.IdentityModel.Tokens
dotnet add package System.IdentityModel.Tokens.Jwt
dotnet add package StackExchange.Redis

```

```

// AifpMiddleware.cs
public class AifpMiddleware {
    private const string Merchant = "mrch_9f3alc2b";
    private const string Issuer = "https://api.aifinpay.io";
    private const long Quota = 100;
    private readonly RequestDelegate _next;
    private readonly IDatabase _redis;
    public AifpMiddleware(RequestDelegate next, IConnectionMultiplexer mux) { _next = next; }

    public async Task Invoke(HttpContext ctx) {
        var resource = ctx.Request.Path.Value ?? "/";
        if (!resource.StartsWith("/api/")) { await _next(ctx); return; }
        var agent = ctx.Request.Headers["AIFP-Agent-ID"].FirstOrDefault() ?? ctx.ConnectionId;
        var used = await _redis.StringIncrementAsync($"q:{agent}");
        if (used == 1) await _redis.KeyExpireAsync($"q:{agent}", TimeSpan.FromDays(30));
        if (used <= Quota) { await _next(ctx); return; }

        var token = ctx.Request.Headers["Payment-Receipt"].FirstOrDefault();
        if (token is null) { await Challenge(ctx, resource); return; }
        try {
            var jwks = await new HttpClient().GetStringAsync($"{Issuer}/.well-known/jwks.json");
            var keys = new JsonWebKeySet(jwks).GetSigningKeys();
            var handler = new JwtSecurityTokenHandler();
            var principal = handler.ValidateToken(token, new TokenValidationParameters {
                ValidIssuer = Issuer, ValidAudience = Merchant, IssuerSigningKeys = keys,
                ClockSkew = TimeSpan.FromSeconds(30)
            }, out _);
            var claims = principal.Claims.ToDictionary(c => c.Type, c => c.Value);
            if (claims["resource"] != resource || decimal.Parse(claims["amount"]) < 0.01) {
                if (await _redis.KeyExistsAsync($"n:{claims["nonce"]}")) { ctx.Response.StatusCode = 402; }
                await _redis.SetStringAsync($"n:{claims["nonce"]}", "1", TimeSpan.FromSeconds(1));
                await _next(ctx);
            }
        } catch { await Challenge(ctx, resource); }
    }
}

```

```

private static async Task Challenge(HttpContext ctx, string resource) {
    ctx.Response.StatusCode = 402;
    ctx.Response.Headers["Accept-Payment"] = "aifp/1.0";
    await ctx.Response.WriteAsJsonAsync(new {
        error = new { code = "AIFP-402" },
        payment_challenge = new { version = "1.0", scheme = "aifp", merchant_id = M
            resource, pricing_tier = "standard", estimated_amount = "0.00001",
            quote_endpoint = $"{Issuer}/v1/quote" } });
    }
}
// app.UseMiddleware<AifpMiddleware>();

```

6.10. Go (net/http + chi)

```
go get github.com/go-chi/chi/v5 github.com/golang-jwt/jwt/v5 github.com/redis/go-redis/
```

```

package aifp

import (
    "encoding/json"; "net/http"; "strconv"; "time"
    "github.com/golang-jwt/jwt/v5"
    "github.com/redis/go-redis/v9"
)

const (
    merchant = "mrch_9f3a1c2b"
    issuer   = "https://api.aifinpay.io"
    quota    = 100
)

func Middleware(rdb *redis.Client, keyfunc jwt.Keyfunc) func(http.Handler) http.Handler {
    return func(next http.Handler) http.Handler {
        return http.HandlerFunc(func(w http.ResponseWriter, r *http.Request) {
            ctx := r.Context()
            resource := r.URL.Path
            agent := r.Header.Get("AIFP-Agent-ID")
            if agent == "" { agent = r.RemoteAddr }
            used, _ := rdb.Incr(ctx, "q:"+agent).Result()
            if used == 1 { rdb.Expire(ctx, "q:"+agent, 30*24*time.Hour) }
            if used <= quota { next.ServeHTTP(w, r); return }

            token := r.Header.Get("Payment-Receipt")
            if token == "" { challenge(w, resource); return }
            tok, err := jwt.Parse(token, keyfunc, jwt.WithValidMethods([]string{"EdDSA"
                jwt.WithIssuer(issuer), jwt.WithAudience(merchant))
            if err != nil || !tok.Valid { challenge(w, resource); return }
            c := tok.Claims.(jwt.MapClaims)
            if c["resource"] != resource { w.WriteHeader(422); return }
            amt, _ := strconv.ParseFloat(c["amount"].(string), 64) // use shopspring/de
            if amt < 0.00001 { w.WriteHeader(422); return }

```

```

        nonce := c["nonce"].(string)
        if n, _ := rdb.Exists(ctx, "n:"+nonce).Result(); n == 1 { w.WriteHeader(409)
        rdb.Set(ctx, "n:"+nonce, "1", 600*time.Second)
        next.ServeHTTP(w, r)
    })
}
}

func challenge(w http.ResponseWriter, resource string) {
    w.Header().Set("Accept-Payment", "aifp/1.0")
    w.Header().Set("Content-Type", "application/json")
    w.WriteHeader(402)
    json.NewEncoder(w).Encode(map[string]any{
        "error": map[string]string{"code": "AIFP-402"},
        "payment_challenge": map[string]any{"version": "1.0", "scheme": "aifp",
            "merchant_id": merchant, "resource": resource, "pricing_tier": "standard",
            "estimated_amount": "0.00001", "quote_endpoint": issuer + "/v1/quote",
            "expires_at": time.Now().Add(5 * time.Minute).UTC().Format(time.RFC3339)},
    })
}
}

```

6.11. Rust (Axum)

```

# Cargo.toml
axum = "0.7"
jsonwebtoken = "9"
redis = { version = "0.25", features = ["tokio-comp"] }
serde_json = "1"
tokio = { version = "1", features = ["full"] }

```

```

use axum::{extract::Request, http::StatusCode, middleware::Next, response::{IntoResponse, Response}};
use jsonwebtoken::{decode, DecodingKey, Validation, Algorithm};
use serde::Deserialize;
use serde_json::json;

const MERCHANT: &str = "mrch_9f3a1c2b";
const ISSUER: &str = "https://api.aifinpay.io";

#[derive(Deserialize)]
struct Claims { aud: String, resource: String, amount: String, nonce: String, exp: usize }

pub async fn aifp(req: Request, next: Next) -> Response {
    let resource = req.uri().path().to_string();
    if !resource.starts_with("/api/") { return next.run(req).await; }

    // (quota check via Redis omitted for brevity)
    let token = req.headers().get("payment-receipt").and_then(|v| v.to_str().ok());
    let Some(token) = token else { return challenge(&resource); };

    let key = DecodingKey::from_ed_pem(/* fetched JWKS PEM */ b"").unwrap();
}

```



```

let mut v = Validation::new(Algorithm::EdDSA);
v.set_audience(&[MERCHANT]); v.set_issuer(&[ISSUER]); v.leeway = 30;
match decode::<Claims>(token, &key, &v) {
    Ok(data) if data.claims.resource == resource
        && data.claims.amount.parse::<f64>().unwrap_or(0.0) >= 0.00001 => next.run(
    Ok(_) => StatusCode::UNPROCESSABLE_ENTITY.into_response(),
    Err(_) => challenge(&resource),
}
}

fn challenge(resource: &str) -> Response {
    (StatusCode::PAYMENT_REQUIRED, [("Accept-Payment", "aifp/1.0")],
    Json(json!({ "error": { "code": "AIFP-402"},
        "payment_challenge": { "version": "1.0", "scheme": "aifp", "merchant_id": MERCHANT,
            "resource": resource, "pricing_tier": "standard", "estimated_amount": "0.00001",
            "quote_endpoint": format!("{ISSUER}/v1/quote")} }))).into_response()
}

```

6.12. Cloudflare Workers

Verification runs at the edge with Web Crypto; quota via Workers KV / Durable Objects.

```

import { jwtVerify, createRemoteJWKSet } from "jose";
const JWKS = createRemoteJWKSet(new URL("https://api.aifinpay.io/.well-known/jwks.json"));
const MERCHANT = "mrch_9f3alc2b";

export default {
    async fetch(req: Request, env: Env): Promise<Response> {
        const url = new URL(req.url);
        if (!url.pathname.startsWith("/api/")) return fetch(req);

        const agent = req.headers.get("AIFP-Agent-ID") ?? req.headers.get("cf-connecting-ip");
        const used = Number(await env.QUOTA.get(`q:${agent}`) ?? "0") + 1;
        await env.QUOTA.put(`q:${agent}`, String(used), { expirationTtl: 2592000 });
        if (used > 100) return fetch(req);

        const token = req.headers.get("Payment-Receipt");
        const challenge = () => new Response(JSON.stringify({
            error: { code: "AIFP-402" },
            payment_challenge: { version: "1.0", scheme: "aifp", merchant_id: MERCHANT,
                resource: url.pathname, pricing_tier: "standard", estimated_amount: "0.00001",
                quote_endpoint: "https://api.aifinpay.io/v1/quote", nonce: crypto.randomUUID(),
                expires_at: new Date(Date.now() + 300000).toISOString() } })), {
            status: 402, headers: { "Accept-Payment": "aifp/1.0", "Content-Type": "application/json" }
        });
        if (!token) return challenge();
        try {
            const { payload } = await jwtVerify(token, JWKS, {
                issuer: "https://api.aifinpay.io", audience: MERCHANT, algorithms: ["EdDSA"],
            });
            if (payload.resource !== url.pathname) return new Response(null, { status: 422 });
            if (await env.NONCE.get(`n:${payload.nonce}`)) return new Response(null, { status: 422 });
            await env.NONCE.put(`n:${payload.nonce}`, "1", { expirationTtl: 600 });
            return fetch(req);
        } catch {
            return challenge();
        }
    }
}

```

```

    } catch { return challenge(); }
  },
};

```

6.13. NGINX (njs + auth_request)

Offload verification to an internal subrequest handled by an njs module.

```

# nginx.conf
load_module modules/ngx_http_js_module.so;
http {
    js_import aifp from /etc/nginx/aifp.js;
    server {
        location /api/ {
            auth_request /_aifp_verify;
            error_page 402 = @challenge;
            proxy_pass http://backend;
        }
        location = /_aifp_verify { internal; js_content aifp.verify; }
        location @challenge { js_content aifp.challenge; }
    }
}

```

```

// /etc/nginx/aifp.js (njs)
import qs from "querystring";
const MERCHANT = "mrch_9f3alc2b";
// njs has limited crypto; for EdDSA verification, proxy the token to a tiny sidecar
// (e.g. a local Go/Node verifier on 127.0.0.1:8787) that returns 204/402/409/422.
async function verify(r) {
    const token = r.headersIn["Payment-Receipt"];
    if (!token) { r.return(402); return; }
    const resp = await ngx.fetch("http://127.0.0.1:8787/verify", {
        method: "POST",
        headers: { "Content-Type": "application/json" },
        body: JSON.stringify({ token, resource: r.uri, merchant: MERCHANT }),
    });
    r.return(resp.status === 200 ? 204 : resp.status);
}
function challenge(r) {
    r.headersOut["Accept-Payment"] = "aifp/1.0";
    r.headersOut["Content-Type"] = "application/json";
    r.return(402, JSON.stringify({ error: { code: "AIFP-402" },
        payment_challenge: { version: "1.0", scheme: "aifp", merchant_id: MERCHANT,
            resource: r.uri, pricing_tier: "standard", estimated_amount: "0.00001",
            quote_endpoint: "https://api.aifinpay.io/v1/quote" } }));
}
export default { verify, challenge };

```

Pattern: edge proxies (NGINX/Apache) that lack native EdDSA delegate the signature check to a small local **verifier sidecar** (a stripped Go/Node service running §5). This keeps verification local (no AiFinPay round-trip) while staying within the proxy's capabilities.

6.14. Apache (httpd)

Use `mod_auth_request` -style delegation via `mod_rewrite` + a verifier sidecar, or `mod_lua` .

```
# httpd.conf (mod_lua)
LuaHookAuthChecker /etc/httpd/aifp.lua aifp_check
<Location "/api/">
    Require valid-aifp
</Location>
```

```
-- /etc/httpd/aifp.lua
local http = require "socket.http"
local ltn12 = require "ltn12"
local cJSON = require "cjson"
local MERCHANT = "mrch_9f3a1c2b"

function aifp_check(r)
    local token = r.headers_in["Payment-Receipt"]
    if not token then return challenge(r) end
    local body = cJSON.encode({ token = token, resource = r.uri, merchant = MERCHANT })
    local resp = {}
    local _, code = http.request{
        url = "http://127.0.0.1:8787/verify", method = "POST",
        headers = { ["Content-Type"] = "application/json", ["Content-Length"] = #body },
        source = ltn12.source.string(body), sink = ltn12.sink.table(resp),
    }
    if code == 200 then return apache20K else return challenge(r) end
end

function challenge(r)
    r.status = 402
    r.headers_out["Accept-Payment"] = "aifp/1.0"
    r.content_type = "application/json"
    r:write(cJSON.encode({ error = { code = "AIFP-402" },
        payment_challenge = { version = "1.0", scheme = "aifp", merchant_id = MERCHANT,
            resource = r.uri, pricing_tier = "standard", estimated_amount = "0.00001",
            quote_endpoint = "https://api.aifinpay.io/v1/quote" } })
    )
    return 402
end
```

6.15. WordPress (PHP plugin)

```

<?php
/* Plugin Name: AiFinPay Paywall */
add_action('init', function () {
    if (strpos($_SERVER['REQUEST_URI'], '/wp-json/') === false) return;
    require_once __DIR__ . '/vendor/autoload.php';
    use Firebase\JWT\JWT; use Firebase\JWT\JWK;

    $merchant = get_option('aifp_merchant_id', 'mrch_9f3a1c2b');
    $issuer = 'https://api.aifinpay.io';
    $resource = parse_url($_SERVER['REQUEST_URI'], PHP_URL_PATH);

    $agent = $_SERVER['HTTP_AIFP_AGENT_ID'] ?? $_SERVER['REMOTE_ADDR'];
    $key = "aifp_q_" . md5($agent);
    $used = (int) get_transient($key) + 1;
    set_transient($key, $used, MONTH_IN_SECONDS);
    if ($used <= 100) return;

    $token = $_SERVER['HTTP_PAYMENT_RECEIPT'] ?? null;
    $challenge = function () use ($merchant, $issuer, $resource) {
        status_header(402);
        header('Accept-Payment: aifp/1.0');
        header('Content-Type: application/json');
        echo json_encode([
            'error' => [
                'code' => 'AIFP-402',
                'payment_challenge' => [
                    'version' => '1.0',
                    'scheme' => 'aifp',
                    'merchant_id' => $merchant,
                    'resource' => $resource,
                    'pricing_tier' =>
                        'estimated_amount' => '0.00001',
                        'quote_endpoint' => "$issuer/v1/quote",
                    'nonce' => bin2hex(random_bytes(16)),
                    'expires_at' => gmdate('Y-m-d\TH:i:s\Z', time() + 300)]],
            ], true);
        exit;
    };
    if (!$token) $challenge();
    try {
        $jwks = json_decode(file_get_contents("$issuer/.well-known/jwks.json"), true);
        $p = (array) JWT::decode($token, JWK::parseKeySet($jwks));
    } catch (\Throwable $e) { $challenge(); }
    if (($p['aud'] ?? '') !== $merchant || ($p['resource'] ?? '') !== $resource
        || bccomp($p['amount'] ?? '0', '0.00001', 8) < 0) { status_header(422); exit; }
    $nkey = "aifp_n_" . $p['nonce'];
    if (get_transient($nkey)) { status_header(409); exit; }
    set_transient($nkey, 1, max(1, $p['exp'] - time()));
});

```

7. Error Handling & Retry

Map verification outcomes to the correct HTTP code — agents depend on this (AIFP-1 §17):

Outcome	Return	Agent reaction
No receipt, quota gone	402 + challenge	Pay, then retry

Outcome	Return	Agent reaction
Signature/aud/exp invalid	422	Re-quote, re-pay
Amount below price	422 - AMOUNT	Re-quote at correct tier
Nonce reused	409	Get a fresh receipt
Expired receipt	402	Pay again
Settlement not confirmed (high-value)	425 + Retry-After	Wait, retry same receipt
Rate limited	429 + Retry-After	Backoff

Always include a structured body: `{ "error": { "type", "code", "message", "request_id", "doc" } }`. Never leak stack traces.

8. Production Best Practices

- **Cache JWKS** with a TTL (e.g., 1h) and refresh on an unknown `kid` (key rotation). Never fetch JWKS per request.
- **Degraded mode:** if AiFinPay is unreachable, keep honoring valid unexpired receipts. Verification is local — it does not need AiFinPay to be up.
- **Atomic quota:** use Redis `INCR` with a TTL window, never read-modify-write.
- **Nonce store sizing:** TTL = receipt TTL (~600s). At any instant you only store nonces seen in the last ~10 min, so the set stays tiny even at billions/day.
- **Clock skew:** allow ≤ 30 s tolerance on `exp`.
- **Idempotent challenges:** issuing a `402` must never consume quota or mutate state.
- **Observability:** emit `aifp_402_total`, `aifp_verify_fail_total{reason}`, `aifp_receipt_redeemed_total`, p99 verify latency.
- **Webhooks:** verify `AIFP-Signature` (HMAC-SHA256) + 5-min timestamp window before trusting any webhook.

9. Security

- **TLS 1.3 only.** All traffic, including receipt retries.
- **Verify everything by signature.** Never trust a receipt you did not cryptographically verify against the current JWKS.
- **Bind tightly.** Always check `aud == your merchant_id` and `resource == requested path`. A receipt for resource A MUST NOT unlock resource B.
- **Replay-proof.** A nonce store is mandatory; without it, a captured receipt could be reused until expiry.

- **Secrets hygiene.** Keep `sk_live_*` server-side only; rotate on exposure. Use `pk_live_*` for any client-exposed config.
- **Rate limit** the challenge path to blunt nonce-harvesting and DoS.
- Full guidance: [Security & Cryptography Specification](#).

10. Scaling

Concern	Approach
Verification throughput	Local Ed25519 (~50k/s/core); scale horizontally, no backend dependency
Quota counters	Redis cluster / Workers KV; shard by agent id
Nonce store	Short-TTL Redis; memory bounded by TTL window
Edge	Verify at CDN edge (Cloudflare/Next middleware) for single-digit-ms overhead
Hot keys	Consistent hashing; local LRU for JWKS
Multi-region	JWKS is global & cacheable; nonce store can be regional with sticky agent routing

11. Benchmarks

Representative figures on a single modern core (illustrative, your numbers will vary):

Operation	Throughput	p99 latency
Ed25519 receipt verify (warm JWKS)	~50,000 /s/core	< 40 μ s
Quota INCR (local Redis)	~120,000 /s	< 0.4 ms
Nonce check + set (Redis)	~90,000 /s	< 0.6 ms
End-to-end middleware overhead	—	< 1 ms added

The dominant cost is your own business logic, not AIFP. The protocol adds sub-millisecond overhead per request.

12. Glossary

See AIFP-1 [Appendix A](#) for the canonical glossary. Key merchant terms: **Payment Challenge**, **Receipt Token**, **Stateless Verification**, **Free Quota**, **Pricing Tier Tier**, **Nonce Store**, **JWKS**, **kid**, **Degraded Mode**.

13. References

- [AIFP-1 — Payment Protocol Specification](#) (normative).
- [AI Agent SDK Specification](#) — the client side that pays you.
- [Security & Cryptography Specification](#).
- [RFC 7519] JWT · [RFC 8037] EdDSA in JOSE · [RFC 9110] HTTP Semantics.

End of Merchant Integration Guide. © 2026 AiFinPay, Inc. Licensed CC BY 4.0.