

Bielik Student API

Documentation for Students

1. Introduction

Bielik Student API provides access to a local Polish language model

SpeakLeash/bielik-11b-v3.0-instruct:Q4_K_M through an OpenAI-compatible interface. You can use it with the Python `openai` library, the `curl` tool, or any REST HTTP client.

API Address: `http://<server-address>:8080`

2. Authorization

Every request must include an Authorization header with a Bearer token. You will receive your token from your instructor — it looks like this:

```
Authorization: Bearer bsk-a1b2c3d4e5f6...
```

Without a valid token, the API will return **401 Unauthorized**.

3. Limits and Restrictions

Restriction	Value
Maximum prompt length	25,000 characters
Requests per hour	60 requests
Requests per day	240 requests
File/Image uploads	Blocked
Response streaming	Not available

4. Usage Examples

4.1 *curl* (Terminal)

```
curl -X POST http://<server-address>:8080/v1/chat/completions \
  -H "Authorization: Bearer bsk-YOUR-TOKEN" \
  -H "Content-Type: application/json" \
  -d '{
    "messages": [
      {"role": "user", "content": "Explain what entropy is"}
    ]
  }'
```

4.2 *Python* — *openai* Library

```
from openai import OpenAI

client = OpenAI(
    base_url="http://<server-address>:8080/v1",
```

```

    api_key="bsk-YOUR-TOKEN",
)

response = client.chat.completions.create(
    model="SpeakLeash/bielik-11b-v3.0-instruct:Q4_K_M",
    messages=[
        {"role": "user", "content": "Explain what entropy is"}
    ]
)

print(response.choices[0].message.content)

```

4.3 Python — requests Library

```

import requests

API_URL = "http://<server-address>:8080/v1/chat/completions"
TOKEN = "bsk-YOUR-TOKEN"

resp = requests.post(API_URL,
    headers={"Authorization": f"Bearer {TOKEN}"},
    json={"messages": [{"role": "user", "content": "Hello, who are you?"}]}
)

data = resp.json()
print(data["choices"][0]["message"]["content"])

```

4.4 Multi-turn Conversation

```

messages = [
    {"role": "system", "content": "You are a helpful assistant."},
    {"role": "user", "content": "What is the value of pi?"},
]
resp = requests.post(API_URL,
    headers={"Authorization": f"Bearer {TOKEN}"},
    json={"messages": messages}
)
answer = resp.json()["choices"][0]["message"]["content"]
messages.append({"role": "assistant", "content": answer})
messages.append({"role": "user", "content": "What about Euler's number?"})
# ... continue the conversation by adding more messages

```

5. Error Codes

HTTP Code	Meaning	What to Do
200 OK	Success	Read response from choices[0].message.content
400 Bad Request	Prompt too long or file upload attempt	Shorten prompt to max 25,000 characters
401 Unauthorized	Missing or invalid token	Check Authorization: Bearer <token> header
429 Too Many Requests	Rate limit exceeded	Wait — limit: 60/hour, 240/day
503 Service Unavailable	Model temporarily unavailable	Try again in a few minutes

6. FAQ

Q: Can I use the API for homework?

A: Yes, the API is available for educational use. However, keep in mind that independent work provides the best learning outcomes.

Q: Why are responses slow?

A: Bielik-11b is a large language model running locally. Response time depends on server load and prompt length.

Q: Can I upload files or images?

A: No. File and image uploads are blocked. If you want to analyze text from a document, copy its content directly into your message.

Q: What should I do if I get a 503 error?

A: The model is temporarily unavailable. Wait a few minutes and try again. If the problem persists, contact your instructor.

Q: How many requests can I make?

A: Your token allows 60 requests per hour and 240 requests per day. Counters reset automatically.

Q: Is conversation content saved?

A: The API does not store conversation content. Only request timestamps are recorded for rate-limiting purposes.