



 Home / Products / Wine Coolers / BI Series / XBI102DB Pro



XBI102DB Pro Wine Cooler

Share:

XBI102DB Pro [Spec Sheet](#)

Technical Specifications

NO.	SPECIFICATION	VALUE
1	Energy Consumption	F TBC
2	Noise Level (dB(A))	37
3	Installation	Built-in



5	Bottle Capacity (750ml)	32
6	Temp. Zone	Dual Zone
7	Temp Range	Upper: 5-20°C, Lower:5-20°C
8	Compressor	Inverter/Embraco
9	Air Ventilation	3G Self-ventilation System (Patented)
10	Control Panel Location	Control On Door (Patented)
11	Door Open	Touch-open
12	Door Reversible	Yes
13	Outer Cabinet	Black/Metal
14	Cabinet Face Frame	Caramel/HD Moso (Bio-based)
15	Inner Cabinet	Caramel/HD Moso (Bio-based)
16	Door Open Warning	Yes

▼ View All 33 Specifications

Installation

Install PDF XBI102DB Pro

Install Drawing XBI102D

Bottle Loading XBI102D

 Install PDF XBI102DB Pro

Download PDF



5-20/5-20°C
TEMPERATURE RANGE



50-80%RH
HUMIDITY CONTROL



32 bottles
CAPACITY



Cooling Engine

Airflow Layout

Eco Features

Inverter/Embraco Compressor



Sustainability

F

Energy Rating

85%

Recyclable

0

Ozone Depletion



RoHS Compliant

✉ Send Inquiry



XMOSO TECH. CO., LTD.
广东三栖鸟科技有限公司
sales@xmoso.com

QUICK LINKS

- Products
- About



SUSTAINABILITY

Committed to reducing carbon footprint through energy-efficient cooling technology and sustainable manufacturing.

© 2026 DeepCool. All rights reserved.