

Shell Scripting

- Source code vs machine code
 - Source code is the human readable code written in a programming language like python
 - Machine code consists of binary 1s and 0s and is the language a computer's CPU understands
- Compiler: a program used for converting a complete source code into machine code
- Interpreter: a program that converts source code into machine code line by line
- Compiled program vs Interpreted program
 - a compiled is a binary file produced by a compiler
 - an interpreted program is a program that requires an interpreter to interpret and run each instruction
- Shell scripts are examples of interpreted programs, and the interpreter used is the BASH shell

Creating a basic script

- Start vim, enable line numbers, and enter insert mode
- type:
 - `#!/bin/bash`
 - `echo "this is a script that displays information about your linux system"`
 - `uname -a`
- Save the file and name it `script1.sh`
- Type `chmod u+x script1.sh` to make the file executable
- to run the script type `./script1.sh`

Displaying text

- To display a line of text use the echo command
 - Ex. `echo "this is a message"`
- `echo -n` does not output a new line

Working with variables

- Variable: placeholder for data
- Environment variable: is the placeholder for data that can change: typically, it gets its value automatically from the OS startup or the shell being used.
- The HOME environment variable stores the absolute pathname to a user's home directory, so it varies for each user
- The env command allows you to see all environment variables
- You can also use the echo command to see the value of each environment variable
 - `echo $HOME`
 - `echo $HOST`

Exit Status Codes

- Exit Status code: a number sent to the shell when you run a command
- Successful commands usually return the code 0, and failures return a value greater than 0

Using Structured Commands

Conditions

- The if statement is used to carry out certain commands based on testing a condition and the exit status of the command
- if-statement- Starts the condition being tested
- then statement- Starts the portion of code specifying what to do if the condition evaluates to true
- else statement- Starts the portion of code specifying what to do if the condition evaluates to false.
- The fi statement indicates the end of the if statement

Table 5-7 File attribute operators in the BASH shell

File attribute operator	Description
-a	Checks whether the file exists
-d	Checks whether the file is a directory
-f	Checks whether the file is a regular file
-r	Checks whether the user has read permission for the file
-s	Checks whether the file contains data
-w	Checks whether the user has write permission for the file
-x	Checks whether the user has execute permission for the file
-O	Checks whether the user is the owner of the file
-G	Checks whether the user belongs to the group owner of the file
file1 -nt file2	Checks whether file1 is newer than file2
file1 -ot file2	Checks whether file1 is older than file2

Numeric Comparison

Comparison	Description	Example
<code>n1 -eq n2</code>	Checks if n1 is equal to n2	If [<code>\$n1 -eq \$n2</code>]
<code>n1 -ge n2</code>	Checks if n1 is greater than or equal to n2	If [<code>\$n1 -ge \$n2</code>]
<code>n1 -gt n2</code>	Checks if n1 is greater than n2	If [<code>\$n1 -gt \$n2</code>]
<code>n1 -le n2</code>	Checks if n1 is less than or equal to n2	If [<code>\$n1 -le \$n2</code>]
<code>n1 -lt n2</code>	Checks if n1 is less than n2	If [<code>\$n1 -lt \$n2</code>]
<code>n1 -ne n2</code>	Checks if n1 is not equal to n2	If [<code>\$n1 -ne \$n2</code>]

String Comparison

Comparison	Description	Example
<code>str1 = str2</code>	Checks if str1 is the same as string str2	If [<code>\$str1 = \$str2</code>]
<code>str1 != str2</code>	Checks if str1 is not the same as str2	If [<code>\$str1 != \$str2</code>]
<code>str1 < str2</code>	Checks if str1 is less than str2	If [<code>\$str1 < \$str2</code>]
<code>str1 \> str2</code>	Checks if str1 is greater than str2	If [<code>\$str1 > \$str2</code>]
<code>-n str1</code>	Checks if str1 has a length greater than zero	If [<code>\$str1 -n</code>]
<code>-z str1</code>	Checks if str1 has a length of zero	If [<code>\$str1 -z</code>]