

Activity 1.4.3 Arrays and Images

Introduction

Have you ever played with special photo effects on a computer? Now that you know that images are really just zeros and ones, you might wonder: how are those special effects created?

Even very routine computer work involves constant manipulation of images. Every time you move a window on the screen, click on a menu, or even just move the mouse, the pixels on the screen change. What algorithms are used to determine the zeros and ones for the graphics card to send to the monitor?



Ready, set, JPG!

Materials

- Computer with Enthought Canopy distribution of *Python*® programming language
- Source file `woman.jpg`

Procedure

1. Form pairs as directed by your teacher. Meet or greet each other to practice professional skills. Set team norms.
2. Launch Canopy. Open an editor window.

Part I: Using Arrays of Pixels

3. In the previous activity, you created an `ndarray` called `ax`. It was an array of `SubplotAxes` objects. You accessed one `SubplotAxes` by using an index in square brackets: `ax[0]`. You probably recognize that this is the same syntax used to access an element of a list. However, the `ndarray` is different than a list; it is an array. All the elements of an array are of the same type, and as a result the computer can access the elements more quickly. Lists and tuples are slower than arrays, but they can mix different data types, like strings and integers.

How are arrays and lists similar? How are they different?

4. Execute the following code and consider line 14.

```

1  '''
2  JDoe_JSmith_1_4_3: Change pixels in an image.
3  '''
4  import matplotlib.pyplot as plt
5  import os.path
6  import numpy as np          # "as" lets us use standard abbreviations
7
8  '''Read the image data'''
9  # Get the directory of this python script
10 directory = os.path.dirname(os.path.abspath(__file__))
11 # Build an absolute filename from directory + filename
12 filename = os.path.join(directory, 'woman.jpg')
13 # Read the image data into an array
14 img = plt.imread(filename)
15
16 '''Show the image data'''
17 # Create figure with 1 subplot
18 fig, ax = plt.subplots(1, 1)
19 # Show the image data in a subplot
20 ax.imshow(img, interpolation='none')
21 # Show the figure on the screen
22 fig.show()

```

The `imread()` function is not a method being called on an object here; `plt` was the nickname we assigned to the `matplotlib.pyplot` library when we imported it. The `imread()` function takes a string that is the name of the image file. It returns an array object that is an `ndarray`, an object with properties and methods defined in the `numpy` library. Try:

```
| In []: type(img)
```

The authors of the `ndarray` package called it `ndarray` because it supports n-dimensional (i.e., any dimensional) arrays. Image arrays can be 2-dimensional

[row][column]

if each pixel is represented by only one number, as in a black and white image. In an RGB color image, each pixel is a list of three color intensities. Some color images have a fourth number for each pixel called the **alpha channel** that identifies how **opaque** the pixel is. Opaque is the opposite of transparent; you cannot see through an opaque object. Whether the array for each pixel has three or four elements, a color image is a 3-dimensional array:

[row][column][color channel]

Examine the output:

```
| In []: img
```

Each pixel is an array of three numbers—red, green, and blue intensities—each between 0 and 255, inclusive. An array of these pixel arrays forms a row of pixels. An array of the row arrays forms the image. Since `img` is an array of rows,

```
| In []: len(img)
```

tells how many rows there are. Since `img[0]` is an array of the first pixel row,

```
| In []: len(img[0])
```

tells how many pixels wide the image is. Since `img[5]` is the 6th row of pixels (don't forget the first one is indexed with zero!), `img[5][9]` is the 10th pixel in the 6th row. Since the three elements of that pixel's array are RGB intensities, `img[5][9][1]` is the green intensity at (5, 9).

Referring to lines 10-12 of your code, use the IPython session to open the image `woman.jpg`. Determine the values of

the height = the number of rows of pixels = _____

the width = the number of columns = _____

the green intensity at (5,9) = `img[5][9][1]`

the red intensity at (4,10) = _____

the red intensity of the 25th pixel in the 50th row = _____

Part II: Manipulating Pixels

5. You can assign new values to a pixel. Add the following lines of code before the `ax.imshow` and `fig.show()` in your code. Execute the code and examine the figure it creates.

```
22 ###
23 # Make a rectangle of pixels yellow
24 ###
25
26 height = len(img)
27 width = len(img[0])
28 for row in range(200, 220):
29     for column in range(50, 100):
30         img[row][column] = [255, 255, 0] # red + green = yellow
```

The **nested** `for` loops iterate through a rectangle of pixels. The outer loop runs through each row, from row 200 through row 219. For each iteration of that outer loop, the inner loop works across the image from column 50 to column 99. A new list of RGB values is assigned to every one of these pixels.

Change the code to create a green rectangle that covers the woman's earring . Screenshot and post into your turn in file.

6. The assignment in line 30 from the previous step can be placed within an `if` structure so that not all pixels get the new assignment. Try replacing the code for a colored rectangle from the previous step with lines 22-31 of the following code. The conditional in the new line 30 uses the built-in function `sum()` to add together the values of the three RGB pixels. If red + green + blue is more than 500, the pixel was bright and in this image was probably the sky.

```
20 img = plt.imread(filename)
21
22 ###
23 # Change a region if condition is True
```

```

24  ###
25
26  height = len(img)
27  width = len(img[0])
28  for r in range(155):
29      for c in range(width):
30          if sum(img[r][c])>500: # brightness R+G+B goes up to 3*255=765
31              img[r][c]=[255,0,255] # R + B = magenta
32
33  ###
34  # Show the image data
35  ###

```

- a. Explain the algorithm used by lines 28-31 of this code.
- b. Add another section of code to change the color of the woman's earring.
- c. Screenshot your *Python* file in the code editor and add to the file you are going to upload.

Conclusion

1. Describe what the data in a digital image contains, and describe what it means if a digital image has been “altered.”
2. What are some of the differences between a photograph taken with light-sensitive film and a photograph taken with a digital camera? In what ways are they the same?