

Simulating a Particle Detector and Particle Decay in C++

Aidan Hughes

11306492

School of Physics and Astronomy

University of Manchester

Third Year Code Report

May 2026

Abstract

The aim of this project was to utilize object oriented programming practices to create a particle detector and particle decay simulators in C++. It consists of two main inheritance chains, one for the particle classes and another for sub-detector classes. These classes, and their respective container classes ParticleBunch and Detector, practice encapsulation by storing data members as private or protected with access via public member functions. The use of virtual and pure virtual functions in the abstract parent classes of the hierarchy enables polymorphism in the child classes.

1 Introduction

The aim of this project was to create a C++ library that simulates a particle detector and its detecting functionality through the use of object oriented programming. As an addition, this code also aims to simulate particle decays within an accelerator. Particle detectors, such as ATLAS or the CMS, compose of multiple sub-detector types, each of which measure different types of particles.

The tracker, the first sub-detector a particle will pass through, uses magnetic fields to measure particle paths, so can only measure charged particles. Next are the calorimeters, which are split into two, an electromagnetic and a hadronic calorimeter. The electromagnetic calorimeter causes electrons and photons to trigger a particle shower which is measured to find their energy. The hadronic calorimeter does the same but for protons and neutrons. Finally, due to muons high energy, they are not turned into showers by the calorimeters, and pass through to the Muon Spectrometer sub-detector. Using information about which sub-detectors were triggered, the type of particle that passed through can be deduced. These sub-detectors also have a detection efficiency associated with them, which compares the number of particles detected to the number produced during an event, usually represented as a percentage.

Along with the particles mentioned above, tau and Higgs particles are also found in accelerators, but decay quickly to other particles. This project focuses on the decays to muon and neutrinos for tau and di-photon decay for the Higgs. All particles have a four-momentum, which is a relativistically conserved property, akin to conservation of three-momentum in classical mechanics. Many particles also have masses, charges or even type specific conservation numbers like lepton number.

To simulate the sub-detectors and particles in C++, an inheritance chain was established for each.

2 Code Implementation

Object oriented programming (OOP) is built on four pillars: encapsulation, inheritance, polymorphism and abstraction.

2.1 FourMomentum

The FourMomentum class holds the energy and momentum properties of a particle. The four-momentum components were stored as private double member variables within the FourMomentum class, as this is a more readable format than a vector in which the index corresponding to each property is not explicit to anyone extending the class. The components are accessed via getters and setters, returning the value as a double, and the setters taking a double as input and changing the member variable. Using getters and setters along with private variables is an example of encapsulation. In this case the encapsulation allowed for value checking on inputted

energy, Listing 1, to ensure it was positive, throwing an error if not, which would not have been possible if the data member was publicly accessible.

```

30 // Setter
31 void FourMomentum::set_energy(double energy)
32 {
33     if(!validate_energy(energy))
34     {
35         throw std::invalid_argument("negative_energy");
36     }
37     energy_ = energy;
38 }

```

Listing 1: Showing setter for energy private data member in FourMomentum.cpp.

A major benefit of constructing separate class to hold particle four momentum is to be able to overload operators, such as the addition and increment operators shown in Listing 2

```

39 // Addition
40 FourMomentum FourMomentum::operator+(const FourMomentum &vector) const
41 {
42     FourMomentum result(energy_ + vector.energy_, x_momentum_
43         + vector.x_momentum_, y_momentum_ + vector.y_momentum_,
44         z_momentum_ + vector.z_momentum_);
45     return result;
46 }
47 // Increment
48 FourMomentum & FourMomentum::operator+=(const FourMomentum &vector)
49 {
50     *this = *this + vector;
51     return *this;
52 }

```

Listing 2: Code snippet from FourMomentum.cpp showing the overloading of + and += operators to add FourMomentum objects component-wise.

2.2 Particle hierarchy

PLAN OOP EXAMPLES encapsulation - all classes, particle probaly best inheritance - particle hierarchy polymorphism static - overloaded function - constructors dynamic - info() function on particles - detector flags abstraction - particle type enum class

FEATURES USED enum class for particle type - validation in one place - easier to scale switch cases than if enables - re used for Neutrino flavour deque to do particle decay unordered map to do key value pairs rand() for efficiency / misdetection calulation

3 Results

```
1      int main()  
2      {  
3          return 0;  
4      }
```

4 Discussion

errors on detected value. Extra abstraction in detect function.