

# Python CS-521

Eugene Pinsky  
Department of Computer Science  
Metropolitan College, Boston University  
Boston, MA 02215  
email: epinsky@bu.edu

May 2, 2020

## **Abstract**

This course will present an effective approach to help you learn Python. With extensive use of graphical illustrations, we will build understanding of Python and its capabilities by learning through many simple examples and analogies. The class will involve active student participation, discussions, and programming exercises. This approach will help you build a strong foundation in Python that you will be able to effectively apply in real-job situations and future courses.

# SEARCHING

# Searching

- some collections are indexed
- they can be sorted for efficient searching
- can use a bisection search algorithm
- search is done in  $O(\log n)$  steps

# Search in Non-Indexed Collections

- these collections cannot be sorted
- sequential search
- need to examine  $n/2$  items
- sequential vs. bisection:

#items $n$	sequential: $n/2$	bisection: $\log n$
100	50	8
1,000	500	10
1,000,000	500,000	20
1,000,000,000	500,000,000	30
1,000,000,000,000	500,000,000,000	40


# Sequential Search

```
def search_seq(x, target):  
    count = 0  
    for e in x:  
        print('count: ', count, 'element:', e)  
        if e == target:  
            return count  
        count = count + 1  
    return -1
```

```
x_set = {'mon', 'tue', 'wed', 'thu',  
         'fri', 'sat', 'sun'}  
  
target='thu'  
steps = search_seq(x_set, target)  
if steps >=0:  
    print('found target: ', target,  
          'after', steps, ' steps')  
else:  
    print('did not find ', target)
```

# Sequential Search (cont'd)

```
count: 0 element: wed  
count: 1 element: mon  
count: 2 element: thu  
found target:  thu after 2  steps
```



# Recursive Bisection


```
# assume x is sorted in increasing order
def search_rec(x, start, end, target):
    global count
    count = count + 1
    if count > 10:
        return None
    if start == end:
        if x[start] == target:
            return start
        else:
            return None
    else:
        mid_index = (start+end)//2
        if x[mid_index] == target:
            return mid_index
        elif x[mid_index] < target:
            return search_rec(x, mid_index,
                              end, target)
        else:
            return search_rec(x, start,
                              mid_index, target)
```

# Recursive Bisection (cont'd)


```
x_list = ['mon', 'tue', 'wed', 'thu',  
          'fri', 'sat', 'sun']  
  
x_list.sort()  
target = 'thu'  
count = 0  
index = search_rec(x_list, 0,  
                  len(x_list)-1, target)  
if index is not None:  
    print('index=', index, 'steps:', count)  
else:  
    print('target not found, steps:', count)
```



# Recursive Search Step



# Recursive Final Step




# Iterative Bisection

```
# assume x is sorted in increasing order
def search_non_rec(x, start, end, target):
    count = 0
    while count < len(x):
        count = count + 1
        if start == end:
            if x[start] == target:
                return start, count
            else:
                return None, None
        else:
            mid_index = (start+end)//2
            if x[mid_index] == target:
                return mid_index, count
            elif x[mid_index] < target:
                start = mid_index
            else:
                end = mid_index
```

# Iterative Bisection (cont'd)

```
x_list = ['mon', 'tue', 'wed', 'thu',  
          'fri', 'sat', 'sun']  
  
x_list.sort()  
target = 'thu'  
  
index, count = search_non_rec(x_list, 0,  
                              len(x_list)-1, target)  
if index is not None:  
    print('index=', index, 'steps:', count)  
else:  
    print('target not found')
```


# Iterative Bisection Step



# Iterative Bisection

## Final Step

```
index= 4 steps: 2
```



# Bisection Root Computation

- assume  $f(x)$  is continuous
- want root  $r$ :  $f(r) = 0$
- assume  $a < b$ ,  $f(a)f(b) < 0$
- root  $r \in [a, b]$ 
  - (a) compute  $m = (a + b)/2$
  - (b) if  $|f(m)| < \epsilon$  then  $m$  is  $r$
  - (c) else take  $[a, m]$  and  $[m, b]$
  - (d) look for  $r$  in  $[a, m]$  or  $[m, b]$
  - (e) recursively or iteratively


# Recursive Algorithm

```
def f(x):  
    return x**2 - 11*x + 10  
  
def root_recursive(a,b, e):  
    global count  
    count = count + 1  
    m = (a + b)/2.0  
    m_value = f(m)  
    print('count=', count, 'a=', a, 'b=', b,  
          'm=', m, 'f(m)=', round(m_value,2))  
    if abs(m_value) < e:  
        return m  
    else:  
        a_value = f(a)  
        if a_value * m_value < 0:  
            return root_recursive(a, m, e)  
        else:  
            return root_recursive(m, b, e)  
  
a = 2; b = 12; count = 100  
root = root_recursive(2, 12, e=0.5)
```



# Recursive Root Computation

```
count= 1 a= 2 b= 12 m= 7.0 f(m)= -18.0
count= 2 a= 7.0 b= 12 m= 9.5 f(m)= -4.25
count= 3 a= 9.5 b= 12 m= 10.75 f(m)= 7.31
count= 4 a= 9.5 b= 10.75 m= 10.125 f(m)= 1.14
count= 5 a= 9.5 b= 10.125 m= 9.8125 f(m)= -1.65
count= 6 a= 9.8125 b= 10.125 m= 9.96875 f(m)= -0.28
```



# Iterative Method

```
def f(x):
    return x**2 - 11*x + 10

def root_iterative(a,b, e, max_count = 100):
    count = 0;
    while count < max_count:
        count = count + 1
        m = (a + b)/2.0; m_value = f(m)
        print('count=', count, 'a=', a, 'b=', b,
              'm=', m, 'f(m)=', round(m_value,2))
        if abs(m_value) < e:
            return m
        else:
            a_value = f(a)
            if a_value * m_value < 0:
                b = m
            else:
                a = m
    else: # can use else with while in Python
        print('no root after', max_count, 'steps')

a = 2; b = 12;
root = root_iterative(2, 12, e=0.5)
```

# Iterative Root Computation

```
count= 1 a= 2 b= 12 m= 7.0 f(m)= -18.0
count= 2 a= 7.0 b= 12 m= 9.5 f(m)= -4.25
count= 3 a= 9.5 b= 12 m= 10.75 f(m)= 7.31
count= 4 a= 9.5 b= 10.75 m= 10.125 f(m)= 1.14
count= 5 a= 9.5 b= 10.125 m= 9.8125 f(m)= -1.65
count= 6 a= 9.8125 b= 10.125 m= 9.96875 f(m)= -0.28
```

