Chapter 1

Thermoelasticity: Combining the Heat equation and non-linear Solid Mechanics




Figure 1.1 Undeformed configuration of an elastic block.

We consider the uniform steady thermal expansion of an elastic body that is differentially heated. The top surface is heated and the bottom surface is maintained at the reference temperature, which leads to a uniform temperature gradient throughout the material. The material expands more near the upper surface than near the lower surface, deforming the initially rectangular block into an curved configuration.




Figure 1.2 Deformed elastica when the top surface is heated and the lower surface is maintained at the reference temperature. The contours indicate the temperature of the body.

1.1 The driver code

The driver code for this example is given below:

```
//LIC// This file forms part of oomph-lib, the object-oriented,
//LIC// multi-physics finite-element library, available //LIC// at http://www.oomph-lib.org.
//LIC// Copyright (C) 2006-2023 Matthias Heil and Andrew Hazel
//LIC// This library is free software; you can redistribute it and/or
//LIC// modify it under the terms of the GNU Lesser General Public
//LIC// License as published by the Free Software Foundation; either
//\mathrm{LIC}// version 2.1 of the License, or (at your option) any later version.
//LIC/
//LIC// This library is distributed in the hope that it will be useful,
//LIC// but WITHOUT ANY WARRANTY; without even the implied warranty of
//LIC// MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE. See the GNU
//LIC// Lesser General Public License for more details.
//LIC//
//LIC// You should have received a copy of the GNU Lesser General Public
//LIC// License along with this library; if not, write to the Free Software
//LIC// Foundation, Inc., 51 Franklin Street, Fifth Floor, Boston, MA
//LIC// 02110-1301 USA.
//LIC//
//LIC// The authors may be contacted at oomph-lib@maths.man.ac.uk.
//T.TC//
//Driver for a multi-physics problem that couples the
//unsteady heat equation to the equations of large-displacement solid
//mechanics
//Oomph-lib headers, we require the generic, unsteady heat
//and and elements.
#include "generic.h"
#include "solid.h"
#include "unsteady_heat.h"
// The mesh is our standard rectangular quadmesh
#include "meshes/rectangular_quadmesh.h"
// Use the oomph and std namespaces
using namespace oomph;
using namespace std;
/// A class that solves the equations of steady thermoelasticity by
\ensuremath{///} combining the UnsteadyHeat and PVD equations into a single element.
/// A temperature-dependent growth term is added to the PVD equations by
/// overloading the member function get_istotropic_growth()
                     ====class definition===========
template<unsigned DIM>
class QThermalPVDElement : public virtual QPVDElement<DIM, 3>,
                           public virtual QUnsteadyHeatElement<DIM,3>
private:
 /// Pointer to a private data member, the thermal expansion coefficient
 double* Alpha_pt;
 /// The static default value of Alpha
 static double Default_Physical_Constant_Value;
public:
 /// Constructor: call the underlying constructors and
 /// initialise the pointer to Alpha to point
 /// to the default value of 1.0.
 QThermalPVDElement() : QPVDElement<DIM, 3>(),
                         QUnsteadyHeatElement<DIM, 3>()
   Alpha_pt = &Default_Physical_Constant_Value;
 /// The required number of values stored at the nodes is the sum of the
 /// required values of the two single-physics elements. Note that this step is /// generic for any multi-physics element of this type.
 unsigned required_nvalue(const unsigned &n) const
  {return (QUnsteadyHeatElement<DIM, 3>::required_nvalue(n) +
           QPVDElement<DIM, 3>::required_nvalue(n));}
 /// Access function for the thermal expansion coefficient (const version)
 const double &alpha() const {return *Alpha_pt;}
 /// Access function for the pointer to the thermal expansion coefficientr
 double* &alpha_pt() {return Alpha_pt;}
 /// Overload the standard output function with the broken default
 void output(ostream &outfile) {FiniteElement::output(outfile);}
 /// Output function:
 /// Output x, y, u, v, p, theta at Nplot^DIM plot points
```

1.1 The driver code 3

```
// Start of output function
void output(ostream &outfile, const unsigned &nplot)
  //vector of local coordinates
  Vector<double> s(DTM):
  Vector<double> xi(DIM);
  // Tecplot header info
  outfile « this->tecplot_zone_string(nplot);
  // Loop over plot points
  unsigned num_plot_points=this->nplot_points(nplot);
  for (unsigned iplot=0;iplot<num_plot_points;iplot++)</pre>
    // Get local coordinates of plot point
    this->get_s_plot(iplot,nplot,s);
    // Get the Lagrangian coordinate
    this->interpolated_xi(s,xi);
    // Output the position of the plot point
    for (unsigned i=0;i<DIM;i++)</pre>
     {outfile « this->interpolated_x(s,i) « " ";}
    // Output the temperature (the advected variable) at the plot point
    outfile « this->interpolated_u_ust_heat(s) « std::endl;
  outfile « std::endl;
  // Write tecplot footer (e.g. FE connectivity lists)
  this->write_tecplot_zone_footer(outfile,nplot);
 } //End of output function
/// C-style output function: Broken default
void output (FILE* file_pt)
 {FiniteElement::output(file_pt);}
/// C-style output function: Broken default
void output(FILE* file_pt, const unsigned &n_plot)
{FiniteElement::output(file_pt,n_plot);}
/// Output function for an exact solution: Broken default
void output_fct(ostream &outfile, const unsigned &Nplot,
                FiniteElement::SteadyExactSolutionFctPt
                exact soln pt)
 {FiniteElement::output_fct(outfile,Nplot,exact_soln_pt);}
/// Output function for a time-dependent exact solution:
/// Broken default.
void output_fct(ostream &outfile, const unsigned &Nplot,
                const double& time,
                FiniteElement::UnsteadyExactSolutionFctPt
                exact_soln_pt)
  FiniteElement::
  output_fct(outfile,Nplot,time,exact_soln_pt);
/// Compute norm of solution: use the version in the unsteady heat
void compute_norm(double& el_norm)
 OUnsteadyHeatElement<DIM, 3>::compute norm(el norm);
/// Validate against exact solution at given time
/// Solution is provided via function pointer.
/// Plot at a given number of plot points and compute L2 error
/// and L2 norm of velocity solution over element
/// Call the broken default
void compute_error(ostream &outfile,
                   FiniteElement::UnsteadyExactSolutionFctPt exact_soln_pt,
                    const double& time,
                   double& error, double& norm)
 {FiniteElement::compute_error(outfile,exact_soln_pt,
                                time, error, norm);}
/// Validate against exact solution.
/// Solution is provided via function pointer.
/// Plot at a given number of plot points and compute L2 error
/// and L2 norm of velocity solution over element
/// Call the broken default
void compute_error(ostream &outfile,
                   FiniteElement::SteadyExactSolutionFctPt exact_soln_pt,
                   double& error, double& norm)
 {FiniteElement::compute_error(outfile,exact_soln_pt,error,norm);}
/// Overload the growth function in the advection-diffusion equations.
/// to be temperature-dependent.
```

```
void get_isotropic_growth(const unsigned& ipt, const Vector<double> &s,
                        const Vector<double>& xi, double &gamma) const
 //The growth is the undeformed coefficient plus linear thermal
 //expansion
 gamma = 1.0 + (*Alpha_pt)*this->interpolated_u_ust_heat(s);
 /// Calculate the contribution to the residual vector.
 /// We assume that the vector has been initialised to zero
 /// before this function is called.
 void fill_in_contribution_to_residuals(Vector<double> &residuals)
   //Call the residuals of the advection-diffusion eqautions
  UnsteadyHeatEquations<DIM>::
   fill_in_contribution_to_residuals(residuals);
   //Call the residuals of the Navier-Stokes equations
  PVDEquations<DIM>::
   fill_in_contribution_to_residuals(residuals);
 /// Compute the element's residual Vector and the jacobian matrix
 /// We assume that the residuals vector and jacobian matrix have been
 /// initialised to zero before calling this function
void fill_in_contribution_to_jacobian(Vector<double> &residuals,
                                   DenseMatrix<double> &jacobian)
  //Just call standard finite difference for a SolidFiniteElement so
   //that variations in the nodal positions are taken into account
  SolidFiniteElement::fill_in_contribution_to_jacobian(residuals, jacobian);
};
/// Set the default physical value to be one
//=====
template<>
double QThermalPVDElement<2>::Default_Physical_Constant_Value=1.0;
//=====start_of_namespace=======
/// Namespace for the physical parameters in the problem
namespace Global_Physical_Variables
/// Thermal expansion coefficient
double Alpha=0.0;
 /// Young's modulus for solid mechanics
double E = 1.0; // ADJUST
 /// Poisson ratio for solid mechanics
double Nu = 0.3; // ADJUST
 /// We need a constitutive law for the solid mechanics
ConstitutiveLaw* Constitutive_law_pt;
} // end_of_namespace
//===== start_of_problem_class==============
/// 2D Thermoelasticity problem on rectangular domain, discretised
/// with refineable elements. The specific type
/// of element is specified via the template parameter.
template<class ELEMENT>
class ThermalProblem : public Problem
public:
 /// Constructor
ThermalProblem();
 /// Destructor. Empty
~ThermalProblem() {}
 /// Update the problem specs before solve (empty)
 void actions_before_newton_solve() {}
 /// Update the problem after solve (empty)
void actions_after_newton_solve(){}
 /// Actions before adapt: (empty)
 void actions_before_adapt(){}
 /// Doc the solution.
 void doc_solution();
```

1.1 The driver code 5

```
/// Overloaded version of the problem's access function to
 /// the mesh. Recasts the pointer to the base Mesh object to /// the actual mesh type.
ElasticRectangularQuadMesh<ELEMENT>* mesh_pt()
   return dynamic_cast<ElasticRectangularQuadMesh<ELEMENT>*>(
    Problem::mesh_pt());
private:
 /// DocInfo object
DocInfo Doc info;
}; // end of problem class
/// Constructor for Convection problem
template<class ELEMENT>
ThermalProblem < ELEMENT > :: ThermalProblem ()
// Set output directory
Doc_info.set_directory("RESLT");
 // # of elements in x-direction
unsigned n_x=8;
 // # of elements in y-direction
 unsigned n_y=8;
 // Domain length in x-direction
double 1_x=3.0;
 // Domain length in y-direction
 double l_y=1.0;
 // Build a standard rectangular quadmesh
 Problem::mesh_pt() =
  new ElasticRectangularQuadMesh<ELEMENT>(n_x,n_y,l_x,l_y);
 // Set the boundary conditions for this problem: All nodes are
// free by default -- only need to pin the ones that have Dirichlet
 // conditions here
  //The temperature is prescribed on the lower boundary
  unsigned n_boundary_node = mesh_pt()->nboundary_node(0);
  for(unsigned n=0;n<n_boundary_node;n++)</pre>
    //Get the pointer to the node
    Node* nod_pt = mesh_pt()->boundary_node_pt(0,n);
    //Pin the temperature at the node
    nod_pt->pin(0);
    //Set the temperature to 0.0 (cooled) \,
    nod_pt->set_value(0,0.0);
  //The temperature is prescribed on the upper boundary
  n_boundary_node = mesh_pt()->nboundary_node(2);
  for(unsigned n=0;n<n_boundary_node;n++)</pre>
    Node* nod_pt = mesh_pt()->boundary_node_pt(2,n);
    //Pin the temperature at the node
    nod_pt->pin(0);
    //Set the temperature to 1.0 (heated)
    nod_pt->set_value(0,1.0);
  //The horizontal-position is fixed on the vertical boundary (symmetry)
  n_boundary_node = mesh_pt()->nboundary_node(1);
  for(unsigned n=0;n<n_boundary_node;n++)</pre>
    \verb|static_cast| < \verb|SolidNode*| (mesh_pt() -> boundary_node_pt(1,n)) -> pin_position(0); \\
  //We need to completely fix the lower-right corner of the block to
  //prevent vertical rigid-body motions
  static_cast<SolidNode*> (mesh_pt()->boundary_node_pt(1,0))->pin_position(1);
 , // Complete the build of all elements so they are fully functional
 // Loop over the elements to set up element-specific
 // things that cannot be handled by the (argument-free!) ELEMENT
 unsigned n_element = mesh_pt()->nelement();
 for(unsigned int i=0;i<n_element;i++)</pre>
  {
   // Upcast from GeneralsedElement to the present element
   ELEMENT *el_pt = dynamic_cast<ELEMENT*>(mesh_pt()->element_pt(i));
   // Set the coefficient of thermal expansion
   el_pt->alpha_pt() = &Global_Physical_Variables::Alpha;
   // Set a constitutive law
   el_pt->constitutive_law_pt() =
  Global_Physical_Variables::Constitutive_law_pt;
```

```
// Setup equation numbering scheme cout «"Number of equations: " « assign_eqn_numbers() « endl;
} // end of constructor
/// Doc the solution
template<class ELEMENT>
void ThermalProblem<ELEMENT>::doc_solution()
 //Declare an output stream and filename
ofstream some file:
char filename[100];
 // Number of plot points: npts x npts
 unsigned npts=5;
 // Output solution //----
sprintf(filename, "%s/soln%i.dat", Doc_info.directory().c_str(),
         Doc_info.number());
 some_file.open(filename);
mesh_pt()->output(some_file,npts);
 some_file.close();
Doc_info.number()++;
} // end of doc
/// Driver code for 2D Thermoelasticity problem
int main(int argc, char **argv)
 // "Big G" Linear constitutive equations:
Global_Physical_Variables::Constitutive_law_pt = new GeneralisedHookean(&Global_Physical_Variables::Nu,
                           &Global_Physical_Variables::E);
 //{\tt Construct} \ {\tt our} \ {\tt problem}
 ThermalProblem<QThermalPVDElement<2> > problem;
 //Number of quasi-steady steps
 unsigned n_steps = 11;
 //If we have additional command line arguemnts, take fewer steps
 if(argc > 1) {n_steps = 2;}
 for (unsigned i=0;i<n_steps;i++)</pre>
   //Increase the thermal expansion coefficient
   Global_Physical_Variables::Alpha = 0.1*i;
   //Perform a single steady newton solve
   problem.newton_solve();
   //Document the solution
   problem.doc_solution();
```

1.2 Source files for this tutorial

• The source files for this tutorial are located in the directory:

demo_drivers/multi_physics/thermo/

· The driver code is:

demo_drivers/multi_physics/thermo/thermo.cc

1.3 PDF file

A pdf version of this document is available.