

Apply filters to SQL queries

Project description

Our security team recently discovered potential violations involving login attempts and employee machines. My task was to examine the organization's employees and log_in_attempts tables data. I used SQL filters to retrieve records from different company datasets, investigate potential security issues, and update computers.

Retrieve after hours failed login attempts

After being alerted of failed login attempts made after business hours (18:00), my task was to investigate them. I used an SQL query on the log_in_attempts table to retrieve the failed login attempts data. Since they had to meet the two conditions of attempted after business hours and failed I had to use the WHERE clause with the AND operator to get both results. The first condition code is login_time > '18:00', the greater than sign filter for attempts after '18:00'. The second condition code is success = FALSE, which filters for the failed logins.

```
MariaDB [organization]> SELECT * FROM log_in_attempts WHERE login_time > '18:00' AND success = 0;
```

event_id	username	login_date	login_time	country	ip_address	success
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
18	pwashing	2022-05-11	19:28:50	US	192.168.66.142	0
20	tshah	2022-05-12	18:56:36	MEXICO	192.168.109.50	0
28	astrada	2022-05-09	19:28:12	MEXICO	192.168.27.57	0
34	drosas	2022-05-11	21:02:04	US	192.168.45.93	0
42	cgriffin	2022-05-09	23:04:05	US	192.168.4.157	0
52	cjackson	2022-05-10	22:07:07	CAN	192.168.58.57	0
69	wjaffrey	2022-05-11	19:55:15	USA	192.168.100.17	0
82	abernard	2022-05-12	23:38:46	MEX	192.168.234.49	0
87	apatel	2022-05-08	22:38:31	CANADA	192.168.132.153	0
96	ivelasco	2022-05-09	22:36:36	CAN	192.168.84.194	0
104	asundara	2022-05-11	18:38:07	US	192.168.96.200	0
107	bisles	2022-05-12	20:25:57	USA	192.168.116.187	0
111	astrada	2022-05-10	22:00:26	MEXICO	192.168.76.27	0
127	abellmas	2022-05-09	21:20:51	CANADA	192.168.70.122	0
131	bisles	2022-05-09	20:03:55	US	192.168.113.171	0
155	cgriffin	2022-05-12	22:18:42	USA	192.168.236.176	0
160	jclark	2022-05-10	20:49:00	CANADA	192.168.214.49	0
199	yappiah	2022-05-11	19:34:48	MEXICO	192.168.44.232	0

```
19 rows in set (0.020 sec)
```

Retrieve login attempts on specific dates

Our team wanted to investigate a suspicious event that occurred either May 9, 2022 or May 8, 2022. I was tasked to retrieve all login attempts that occurred that day or the day before from the `log_in_attempts` table. To gather that data I used the `WHERE` clause with an `OR` operator in my SQL query to meet those two conditions. The first condition code is `login_date = '2022-05-09'` to gather all login attempts on May 9th. The second condition code is similar, with `login_date = '2022-05-08'` to get the May 8th login attempts.

```
MariaDB [organization]> SELECT * FROM log_in_attempts WHERE login_date = '2022-05-09' OR login_date = '2022-05-08';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	1
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0
8	bisles	2022-05-08	01:30:17	US	192.168.119.173	0
12	dkot	2022-05-08	09:11:34	USA	192.168.100.158	1
15	lyamamot	2022-05-09	17:17:26	USA	192.168.183.51	0
24	arusso	2022-05-09	06:49:39	MEXICO	192.168.171.192	1
25	sbaelish	2022-05-09	07:04:02	US	192.168.33.137	1
26	apatel	2022-05-08	17:27:00	CANADA	192.168.123.105	1
28	aestrada	2022-05-09	19:28:12	MEXICO	192.168.27.57	0
30	yappiah	2022-05-09	03:22:22	MEX	192.168.124.48	1
32	acook	2022-05-09	02:52:02	CANADA	192.168.142.239	0
36	asundara	2022-05-08	09:00:42	US	192.168.78.151	1
38	sbaelish	2022-05-09	14:40:01	USA	192.168.60.42	1
39	yappiah	2022-05-09	07:56:40	MEXICO	192.168.57.115	1
42	cgriffin	2022-05-09	23:04:05	US	192.168.4.157	0
43	mcouliba	2022-05-08	02:35:34	CANADA	192.168.16.208	0
44	daquino	2022-05-08	07:02:35	CANADA	192.168.168.144	0
47	dkot	2022-05-08	05:06:45	US	192.168.233.24	1
49	asundara	2022-05-08	14:00:01	US	192.168.173.213	0
53	nmason	2022-05-08	11:51:38	CAN	192.168.133.188	1
56	acook	2022-05-08	04:56:30	CAN	192.168.209.130	1

Retrieve login attempts outside of Mexico

Our team wanted to investigate all the login attempts made outside of Mexico and I was tasked to find this information in the `log_in_attempts` table. I used the `WHERE` clause with the `NOT` operator to filter login attempts made everywhere but in Mexico. In the country column, Mexico could be categorized as `MEX` and `MEXICO` making it difficult to remove login attempts made in there. To filter it out properly I used `LIKE` with `MEX%` in the condition part because the

wildcard % allows the filtration of both strings.

```
MariaDB [organization]> SELECT * FROM log_in_attempts WHERE NOT country LIKE 'MEX%';
```

event_id	username	login_date	login_time	country	ip_address	success
1	jrafael	2022-05-09	04:56:27	CAN	192.168.243.140	1
2	apatel	2022-05-10	20:27:27	CAN	192.168.205.12	0
3	dkot	2022-05-09	06:47:41	USA	192.168.151.162	1
4	dkot	2022-05-08	02:00:39	USA	192.168.178.71	0
5	jrafael	2022-05-11	03:05:59	CANADA	192.168.86.232	0
7	eraab	2022-05-11	01:45:14	CAN	192.168.170.243	1
8	bisles	2022-05-08	01:30:17	US	192.168.119.173	0
10	jrafael	2022-05-12	09:33:19	CANADA	192.168.228.221	0
11	sgilmore	2022-05-11	10:16:29	CANADA	192.168.140.81	0
12	dkot	2022-05-08	09:11:34	USA	192.168.100.158	1
13	mrah	2022-05-11	09:29:34	USA	192.168.246.135	1
14	sbaelish	2022-05-10	10:20:18	US	192.168.16.99	1
15	lyamamot	2022-05-09	17:17:26	USA	192.168.183.51	0
16	mcouliba	2022-05-11	06:44:22	CAN	192.168.172.189	1
17	pwashing	2022-05-11	02:33:02	USA	192.168.81.89	1
18	pwashing	2022-05-11	19:28:50	US	192.168.66.142	0
19	jhill	2022-05-12	13:09:04	US	192.168.142.245	1
21	iuduike	2022-05-11	17:50:00	US	192.168.131.147	1
25	sbaelish	2022-05-09	07:04:02	US	192.168.33.137	1
26	apatel	2022-05-08	17:27:00	CANADA	192.168.123.105	1

Retrieve employees in Marketing

Our team then needed to update marketing employee computers whose offices are in the east building. I was tasked with finding the marketing employees' computers in the east building from the `employees` table. In the SQL query, I used a `WHERE` clause with an `AND` operator to filter for those two conditions. The first condition code is `department = 'Marketing'` to return employees in the marketing department. The second condition code is `office LIKE 'East%'` because the offices have different buildings and numbers in the string, which wildcard portion `'East%'` helps filter properly for only east ones.

```
MariaDB [organization]> SELECT * FROM employees WHERE department = 'Marketing' AND office LIKE 'East-%';
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1052	a192b174c940	jdarosa	Marketing	East-195
1075	x573y883z772	fbautist	Marketing	East-267
1088	k865l965m233	rgosh	Marketing	East-157
1103	NULL	randerss	Marketing	East-460
1156	a184b775c707	dellery	Marketing	East-417
1163	h679i515j339	cwilliam	Marketing	East-216

7 rows in set (0.095 sec)

Retrieve employees in Finance or Sales

Our team must also update employee computers in the finance or sales departments. I was tasked with finding employee computers from either department in the `employees` table. Since I need to meet two conflicting conditions inside the department column it is best to use a `WHERE` clause with `OR` operator to filter for both in the SQL query. Both conditions' codes will be structured similarly with `department = 'Finance'` to get finance employees and `department = 'Sales'` for sales employees.

```
MariaDB [organization]> SELECT * FROM employees WHERE department = 'Sales' OR department = 'Finance';
```

employee_id	device_id	username	department	office
1003	d394e816f943	sgilmore	Finance	South-153
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170
1009	NULL	lrodriqu	Sales	South-134
1010	k242l212m542	jlansky	Finance	South-109
1011	l748m120n401	drosas	Sales	South-292
1015	p61lq262r945	jsoto	Finance	North-271
1017	r550s824t230	jclark	Finance	North-188
1018	s310t540u653	abellmas	Finance	North-403
1022	w237x430y567	arusso	Finance	West-465
1024	y976z753a267	iuduike	Sales	South-215
1025	z381a365b233	jhill	Sales	North-115
1029	d336e475f676	ivelasco	Finance	East-156
1035	j236k303l245	bisles	Sales	South-171

Retrieve all employees not in IT

Lastly, our team needed to update the security on employee computers except those in the Information Technology (IT) department. I was tasked with finding all employee computers outside of IT from the `employees` table. In my SQL query, I used a `WHERE` clause with `NOT` operator to filter out the IT department, and the condition code was a `department = 'Information Technology'`.

```
MariaDB [organization]> SELECT * FROM employees WHERE NOT department = 'Information Technology';
```

employee_id	device_id	username	department	office
1000	a320b137c219	elarson	Marketing	East-170
1001	b239c825d303	bmoreno	Marketing	Central-276
1002	c116d593e558	tshah	Human Resources	North-434
1003	d394e816f943	sgilmore	Finance	South-153
1004	e218f877g788	eraab	Human Resources	South-127
1005	f551g340h864	gesparza	Human Resources	South-366
1007	h174i497j413	wjaffrey	Finance	North-406
1008	i858j583k571	abernard	Finance	South-170
1009	NULL	lrodriqu	Sales	South-134
1010	k242l212m542	jlansky	Finance	South-109
1011	l748m120n401	drosas	Sales	South-292
1015	p61lq262r945	jsoto	Finance	North-271
1016	q793r736s288	sbaelish	Human Resources	North-229
1017	r550s824t230	jclark	Finance	North-188

Summary

I used SQL queries to filter for information in the `log_in_attempts` and `employees` tables. It reviewed SQL's `WHERE` clause with `AND`, `OR`, `NOT`, `LIKE` operators, and `%` wildcard.