Transport Stream

Related terms:

Synchronization, Multiplexing, Elementary Stream, Video Compression Standard

View all Topics

Learn more about Transport Stream

Video Communication Networks

Dan Schonfeld, in Handbook of Image and Video Processing (Second Edition), 2005

2.4.4 MPEG-2 Transport Stream

A transport stream (TS) permits multiplexing streams (PESs and PSs) that do not necessarily share a common time-base for transmission in noisy environments. The TS is designed for broadcasting over communication networks such as ATM networks. The TS uses small fixed-length packets (188 bytes) that make them more resilient to packet loss or damage during transmission. The TS provides the input to the transport layer in the OSI reference model.[9]

The TS packet is composed of a 4-byte header followed by 184 bytes shared between the variable-length adaptation field and the TS packet payload. An illustration of the TS header is depicted in Fig. 5. The corresponding glossary of the TS header is provided in Table 3. Note that the unshaded box appearing in Fig. 5 is used to represent the optional adaptation field (AF).



FIGURE 5. Transport stream header.

TABLE 3. Transport stream header glossary

Acronym


I Picture
P Picture
P Picture
Elementary Stream (ES)
PES Header
I Picture
PES Header
P Picture
Packetized Elementary Stream (PES)
0
187B
0
187B
0
187B
TS Header
PES Data
TS Header
PES Data
TS Header
PES Data
Stuffing
Transport Stream (TS)



FIGURE 6. Transport stream packets.

FIGURE 6. Transport stream packets.

> Read full chapter

> Read full chapter

MPEG-2 transport stream

MPEG-2 transport stream

MPEG-2 transport stream

In Digital Video and HDTV (Second Edition), 2012

In Digital Video and HDTV (Second Edition), 2012

MPEG-2 transport stream

MPEG-2 transport stream

An MPEG-2 transport stream (TS) is part of the MPEG-2 suite of standards that specifies a relatively complex mechanism for multiplexing video and audio for one or more programs into a data stream, typically having short packets, suitable for transmission through a more or less error-prone medium where relatively powerful forward error-correction (FEC) is required. A TS is not ideal as a suitable format for applications where a player connects to a program (like television), as opposed to reading a file from its beginning. For terrestrial over-the-air (OTA) or cable television, TS packets are expected to be suitably protected; however, specification of the FEC and channel coding lies outside the MPEG standards within the realm of digital television standards (for example, ATSC standards in North America, and DVB standards in Europe).

An MPEG-2 transport stream (TS) is part of the MPEG-2 suite of standards that specifies a relatively complex mechanism for multiplexing video and audio for one or more programs into a data stream, typically having short packets, suitable for transmission through a more or less error-prone medium where relatively powerful forward error-correction (FEC) is required. A TS is not ideal as a suitable format for applications where a player connects to a program (like television), as opposed to reading a file from its beginning. For terrestrial over-the-air (OTA) or cable television, TS packets are expected to be suitably protected; however, specification of the FEC and channel coding lies outside the MPEG standards within the realm of digital television standards (for example, ATSC standards in North America, and DVB standards in Europe).

ATM: Asynchronous transfer mode, a protocol for high performance networking.

ATM: Asynchronous transfer mode, a protocol for high performance networking.

A *transport stream packet* (TSP) is 188 bytes long. A TSP has a 4-byte header (whose first byte has the value 47h), including a 13-bit packet identifier (PID), and 184 bytes of payload. Packet size was designed with ATM in mind. One TSP packet fits into four ATM cells (48 bytes each). Owing to lack of overhead for program streams, a *single program transport stream* (SPTS) may be used for some applications, a *multiple program transport stream* (MPTS) is used.

Transport stream packets with PID 0 contain the *program association table* (PAT), repeated a few times per second. The PAT lists PIDs of subsequent packets containing *program map tables* (PMTs). A PMT lists PIDs of video and audio elementary streams associated with a single program.

ATSC Standard A/65, *Program and System Information Protocol*.

An ATSC DTV transport stream contains a set of packets implementing the *program and system information protocol* (PSIP). PSIP identifies channels and programs, and conveys time-of-day and station call sign information. PSIP enables a receiver to provide an electronic program guide (EPG).

On a computer, 188-byte transport stream packets typically have a 4-byte timecode appended (resulting in 192-byte packets), a sequence of such packets typically has extension *m2ts*, *m2t*, *mts*, or just *ts*.

TOD is reported to be for transport stream on disk.

MPEG-2 transport streams are used in applications such as these:

- The TOD consumer video format (essentially MPEG-2 MP@HL HD transport stream)
- The BDAV container of Blu-ray
- H.264 compressed video
- AVCHD compressed video (HD content, the file extension *mts* is usual)

> Read full chapter

> Read full chapter

SDI and HD-SDI interfaces

In Digital Video and HD (Second Edition), 2012

ASI

ASI

Within a broadcast facility, an MPEG-2 transport stream can be serialized onto a dedicated asynchronous serial interface (ASI). A serialized ASI stream for broadcast has a payload bit rate of around 20 Mb/s; however, the ASI interface bit rate is 270 Mb/s, chosen so that SDI distribution infrastructure can be used. The ASI interface uses BNC connectors and coaxial cable. ASI is polarity sensitive (unlike SDI), though modern ASI receivers typically detect and correct polarity inversion.

Within a broadcast facility, an MPEG-2 transport stream can be serialized onto a dedicated asynchronous serial interface (ASI). A serialized ASI stream for broadcast has a payload bit rate of around 20 Mb/s; however, the ASI interface bit rate is 270 Mb/s, chosen so that SDI distribution infrastructure can be used. The ASI interface uses BNC connectors and coaxial cable. ASI is polarity sensitive (unlike SDI), though modern ASI receivers typically detect and correct polarity inversion.

ETSI EN 50083-9, *Cable networks for television signals, sound signals and interactive services – Part 9: Interfaces for CATV/SMATV headends and similar professional equipment for DVB/MPEG-2 transport streams*. Standards are not clear on whether transformer coupling is required or whether capacitive coupling suffices.

Although the SDI physical layer is used, the serialized ASI stream has no TRS codes and the interface does not use SDI scrambling. Instead, channel data is encoded according to the 8b/10b code of the Fibre Channel standards (ASI interface data rate is therefore 2.16 Mb/s). An 8b/10b bitstream never has more than four consecutive 0s or 1s, so clock recovery is simple. An 8b/10b encoder minimizes low frequency ("DC") content on the media.

Some people write SDI, however, the elements involved are bits, not bytes, so lowercase *b* is apt.

Since the ASI payload rate is typically far lower than channel capacity, stuffing codes are inserted to occupy idle time. Stuffing codes – Fibre Channel *comma* codes, denoted *K28.5* – are inserted either at the end of each packet (bytewise, "packet mode"), or at the completion of packets (bytewise, "burst mode"). MPEG packets are separated by at least two comma codes.

The *synchronous serial interface* (SSI) was standardized by SMPTE for the purpose of conveying MPEG transport streams between equipment, but has largely fallen into disuse.

It is increasingly common to convey transport streams using IP protocols across Ethernet.

> Read full chapter

Digital Television (DTV)

Keith Jack, in Digital Video and DSP, 2008

Program and System Information Protocol (PSIP)

Enough bandwidth is available within the MPEG-2 transport stream to support several low-bandwidth non-television services such as program guide, closed captioning, weather reports, stock indices, headline news, software downloads, pay-per-view information, etc. The number of additional non-television services (virtual channels) may easily reach ten or more. In addition, the number and type of service will constantly be changing.

Enough bandwidth is available within the MPEG-2 transport stream to support several low-bandwidth non-television services such as program guide, closed captioning, weather reports, stock indices, headline news, software downloads, pay-per-view information, etc. The number of additional non-television services (virtual channels) may easily reach ten or more. In addition, the number and type of service will constantly be changing.

To support these non-television services in a flexible yet consistent manner, the Program and System Information Protocol (PSIP) was developed. PSIP is a small collection of hierarchically related tables (see Figure 8.1 and Table 8.2) designed to extend the MPEG-2 PSI tables. PSIP describes the information for all virtual channels carried in a particular MPEG-2 transport stream. Additionally, information for analog broadcast channels may be incorporated.



Figure 8.1. ATSC PSIP Table Relationships.

Table 8.2. List of ATSC PSIP Tables, Descriptors, and Descriptor Locations

Descriptor	Descriptor Tag					Terrestrial Broadcast Tables Descriptor Tag							
	PMT	MGT	VCT	RRT	EIT	PMT	STT	MGT	DCCT	DCC-SCT	VCM	RRT	EIT
PID	per PAT	PID 0 x1FFB	0-x1FFB	0-x1FFB	per MGT	per PMT	0-x1FFB	00-x1FFB	0-x1FFB	0x0001 x1FFB	0-x1FFB	per MGT
	0x02	0xC7	0xC8	0xCA	0xCB	0x02	0xCD	0xC3	0xD4	0xC8	0xCA	0xCB

Table_ID

			Table_ID												0x80, 0x81 (ECM) 0x82 – 0x8F (EMM)				
Repetition rate		400 ms	**Repetition rate**	150 ms	400 ms	1 min	0.5 sec	400 ms	10 min	1 sec	150 ms	400 ms	1 hour	400 ms		1 min		0.5 sec
AC-3 audio stream	1000 0001	M	**AC-3 audio stream**			1000 0001	M	M											M
ATSC CA	1000 1000		**ATSC CA**		O	1000 1000	O							O					O
ATSC private information*	1010 1101		**ATSC private information***			1010 1101													
CA	0000 1001	M	**CA**			0000 1001		M						M					
Caption service	1000 0110	M	**Caption service**			1000 0110	M	M											M
Component name	1010 0011	M	**Component name**			1010 0011		M											
Content advisory	1000 0111	M	**Content advisory**			1000 0111	M	M											M
Content identifier	1011 0110	O	**Content identifier**			1011 0110	M	O											M
DCC arriv-	1010 1001		**DCC arriv-**			1010 1001					M								

ing
re-
quest

			ing re-quest									
DCC de-part-ing re-quest	1010 1000		**DCC de-part-ing re-quest**	1010 1000			M					
En-hanced signaling	1011 0010	M PMT-E	**En-hanced signaling**	1011 0010		M PMT-E						
Ex-tend-ed chan-nel name	1010 0000		**Ex-tend-ed chan-nel name**	M	1010 0000					M		
Genre	1010 1011		**Genre**		1010 1011	M						M
Redis-tribu-tion con-trol	1010 1010	M	**Redis-tribu-tion con-trol**		1010 1010	M	M					M
Ser-vice loca-tion	1010 0001		**Ser-vice loca-tion**	M	1010 0001					M		
SRM refer-ence	0000 1001		**SRM refer-ence**		0000 1001					M		
Stuf-fing*	1000 0000		**Stuf-fing***		1000 0000							
Time-shifted service	1010 0010		**Time-shifted service**		1010 0010					M		

Note: 1. M=when present, required in this table. O=may be present in this table also.*=no restrictions.

Note: 1. M=when present, required in this table. O=may be present in this table also.*=no restrictions.

Required Tables

Required Tables

Event Information Table (EIT)

There are up to 128 EITs, EIT-0 through EIT-127, each of which describes events or TV programs associated with a listed in the VCT. Each EIT is valid for three hours. Since there are up to 128 EITs, up to 16 days of programming may be advertised in advance. The first four EITs are required (the first 24 are recommended) to be present.

Information provided by the EIT includes start time, duration, title, pointer to optional descriptive text for the event, advisory data, caption service data, audio service descriptor, service descriptor, and so on.

Master Guide Table (MGT)

This table provides general information about the other tables, defines table sizes, version numbers, and packet identifiers (PIDs).

Rating Region Table (RRT)

This table transmits the rating system, commonly referred to as the "V-chip."

System Time Table (STT)

This table serves as a reference for the current time of day. Receivers use it to maintain the correct local time.

Terrestrial Virtual Channel Table (TVCT)

This table, also referred to as the Cable VCT (CVCT) and Satellite VCT (SVCT), contains a list of the channels in the transport stream that are or will be available, plus their attributes. It may also include the broadcaster's analog channels in digital transport streams.

Attributes for each channel include major/minor channel number, short name, Transport/Transmission System ID (TSID), source ID (SID), etc. The Service Location Descriptor is used to list the PIDs for the video, audio, data, and other related elementary streams.

Optional Tables

Extended Text Table (ETT)

For text messages, there can be several ETTs, each having its PID defined by the MGT. Messages can describe channel, program, event, or service.

Directed Channel Change Table (DCCT)

Directed Channel Change Table (DCCT)

The DCCT contains information needed for a channel change to be done at a broadcaster-specified time. The requested channel change may be unconditional or may be based upon criteria specified by the viewer.

Directed Channel Change Selection Code Table (DCCSCT)

The DCCSCT permits a broadcast program categorical classification table to be downloaded for use by some Directed Channel Change requests.

Descriptors

Much like MPEG-2, ATSC uses descriptors to add new functionality. In addition to various MPEG-2 descriptors, one or more of these ATSC-specific descriptors may be included within the PMT or one or more PSIP tables to extend data within the tables. A descriptor not recognized by a decoder must be ignored by that decoder. This enables new descriptors to be implemented without affecting receivers that cannot recognize and process the descriptors.

AC-3 Audio Stream Descriptor

This ATSC descriptor indicates Dolby® Digital or Dolby® Digital Plus audio is present.

ATSC CA Descriptor

This ATSC descriptor has a syntax almost the same as the MPEG-2 CA descriptor.

ATSC Private Information Descriptor

This ATSC descriptor provides a way to carry private information. More than one descriptor may appear within a single descriptor.

Component Name Descriptor

This ATSC descriptor defines a variable-length text-based name for any component of the service.

Content Advisory Descriptor

This ATSC descriptor defines the ratings for a given program.

Content Identifier Descriptor

This ATSC descriptor is used to uniquely identify content with the ATSC transport.

DCC Arriving Request Descriptor

This ATSC descriptor provides instructions for the actions to be performed by a receiver upon arrival to a newly changed channel:

Display text for at least 10 seconds, or for a less amount of time if the viewer issues a "continue," "OK," or equivalent command.

	Display text for at least 10 seconds, or for a less amount of time if the viewer issues a "continue," "OK," or equivalent command.
Display text indefinitely, or until the viewer issues a "continue," "OK," or equivalent command.	*Display text indefinitely, or until the viewer issues a "continue," "OK," or equivalent command.*
DCC Departing Request Descriptor	DCC Departing Request Descriptor
This ATSC descriptor provides instructions to be carried out by a receiver prior to leaving a channel:	This ATSC descriptor provides instructions to be carried out by a receiver prior to leaving a channel:
Cancel any outstanding tuning or navigation commands.	*Cancel any outstanding tuning or navigation commands.*
Display text for at least 10 seconds, or for a less amount of time if the viewer issues a "continue," "OK," or equivalent command.	*Display text for at least 10 seconds, or for a less amount of time if the viewer issues a "continue," "OK," or equivalent command.*
Display text indefinitely, or until the viewer issues a "continue," "OK," or equivalent command.	*Display text indefinitely, or until the viewer issues a "continue," "OK," or equivalent command.*
Enhanced Signaling Descriptor	Enhanced Signaling Descriptor
This ATSC descriptor identifies the terrestrial broadcast transmission method of a program element.	This ATSC descriptor provides a means to signal the transmission method of a program element.
Extended Channel Name Descriptor	Extended Channel Name Descriptor
This ATSC descriptor provides a long channel name for the virtual channel.	This ATSC descriptor provides a long channel name for the virtual channel.
Genre Descriptor	Genre Descriptor
This ATSC descriptor provides type, or category information for events., and may appear in the descriptor() loop of the given EIT event. It references entries in the Categories or the Genres Code Assignments Table and may include references to expansions to that table provided by the DCC Selection Code.	This ATSC descriptor provides genre, or category information for events. It references entries in the Categories or the Genres Code Assignments Table and may include references to expansions to that table provided by the DCC Selection Code.
Redistribution Control Descriptor	Redistribution Control Descriptor
This ATSC descriptor conveys any redistribution control information held by the program rights holder for the content.	This ATSC descriptor conveys any redistribution control information held by the program rights holder for the content.
Service Location Descriptor	Service Location Descriptor
This ATSC descriptor lists the stream type, PID, and language code for each elementary stream present in the VCT for each active channel.	This ATSC descriptor lists the stream type, PID, and language code for each elementary stream present in the VCT for each active channel.
SRM Reference Descriptor	SRM Reference Descriptor
This ATSC descriptor is a specific implementation of the MPEG-2 CA Descriptor. It is used to signal the System Renewability Message Table (SRMT) in the CAT.	This ATSC descriptor is a specific implementation of the MPEG-2 CA Descriptor. It is used to signal the System Renewability Message Table (SRMT) in the CAT.
	This descriptor is present for the System Renewability Message Table (SRMT) if present in the CAT.

Time-Shifted Service Descriptor

Time-Shifted Service Descriptor

This ATSC descriptor is associated with up to 20 other virtual channels carrying the same programming, but time-shifted. A typical application is for Near Video On Demand (NVOD) services.

> Read full chapter

Application

Vinod Joseph, Srinivas Mulugu, in Deploying Next Generation Multicast-enabled Applications, 2011

6.6.6.4.2 Media Loss Rate

Media loss rate is the count of the lost packets over a pre-specified time interval. It is common to measure this on a per second basis. It is important to note that the packets referred to here, are the IP packets, but the MPEG Transport stream packets. So the loss of single IP packet could result in the loss of seven MPEG transport stream packets.

As a practical example in a given network when measured at different points, there may be different MDI values. Normally the lower the MDI values the better the QoE is for the end user. However, since MDI is a combination of two parameters, it gets difficult to compare. For instance, an MDI of 100:5 is better than an MDI of 150:20. However, consider a scenario, if one has two MDI values of 50:20 and 100:5, then it would be a little more complex to analyze which would yield better QoE.

> Read full chapter

Image and Video Coding—Emerging Standards and Beyond

Barry G. Haskell, Patrick Haffner, in Multimedia Computing and Networking, 2002

C. MPEG-2 Coding

The MPEG-2 standard provides the capability for compressing, coding, and transmitting high-quality, multichannel video signals over terrestrial

broadcast, satellite distribution, and broad-band networks, for example, using ATM (asynchronous transmission mode) protocols. The MPEG-2 standard specifies the requirements for video coding, audio coding, systems coding for combining coded audio and video with user-defined private data streams, conformance testing to verify that bit streams and decoders meet the requirements, and software simulation for encoding and decoding of both the program and the transport streams. Because MPEG-2 was designed as a transmission standard, it supports a variety of packet formats (including long and variable-length packets of from 1 up to 64 kbits), and provides error correction capability that is suitable for transmission over cable TV and satellite links.

broadcast, satellite distribution, and broad-band networks, for example, using ATM (asynchronous transmission mode) protocols. The MPEG-2 standard specifies the requirements for video coding, audio coding, systems coding for combining coded audio and video with user-defined private data streams, conformance testing to verify that bit streams and decoders meet the requirements, and software simulation for encoding and decoding of both the program and the transport streams. Because MPEG-2 was designed as a transmission standard, it supports a variety of packet formats (including long and variable-length packets of from 1 up to 64 kbits), and provides error correction capability that is suitable for transmission over cable TV and satellite links.

1) *MPEG-2 Systems:* The MPEG-2 systems level defines two types of streams: the program stream and the transport stream. The program stream is similar to that used in MPEG-1, but with modified syntax and new functions to support advanced functionalities. Program stream decoders typically use long and variable-length packets, which are well suited for software-based processing and error-free environments. The transport stream offers the robustness necessary for noisy channels, and also provides the ability to include multiple programs in a single stream. The transport stream uses fixed-length packets of size 188 bytes, and is well suited for delivering compressed video and audio over error-prone channels such as CATV networks and satellite transponders. The basic data structure that is used for both the program stream and the transport stream data is called the packetized elementary stream (PES) packet. PES packets are generated by packetizing the compressed video and audio data, and a program stream is generated by interleaving PES packets from the various encoders with other data packets to generate a single bitstream. A transport stream consists of packets of fixed length, consisting of 4 bytes of header followed by 184 bytes of data obtained by chopping up the data in the PES packets. The key difference in the streams is that the program streams are intended for error-free environments, whereas the transport streams are intended for noisier environments where some type of error protection is required.

2) *MPEG-2 Video:* MPEG-2 video was designed for high-quality encoding of interlaced video from standard TV broadcasts at bit rates on the order of 4–9 Mbits/s. As it evolved, however, MPEG-2 video was expanded to include high-resolution video, such as HDTV, as well as hierarchical or scalable video coding for a range of applications. Since MPEG-2 video does not standardize the encoding method, but only the bitstream syntax and decoding semantics, there have evolved two generalized video codecs, one for nonscalable video coding and one for scalable video coding. Fig. 7 shows a block diagram of the MPEG-2 nonscalable video encoder. The video encoder consists of an interframe/intraframe DCT encoder, a frame/field DCT encoder, a frame/field motion estimator

and compensator, and a variable-length encoder (VLE). The frame/field DCT encoder exploits spatial redundancies in the video, and the frame/field motion compensator exploits temporal redundancies in the video signal. The coded video bit stream is sent to a systems multiplexer, Sys Mux, which outputs either a transport or a program stream.Fig. 7. Generalized codec for MPEG-2 nonscalable video coding.

and compensator, and a variable-length encoder (VLE). The frame/field DCT encoder exploits spatial redundancies in the video, and the frame/field motion compensator exploits temporal redundancies in the video signal. The coded video bit stream is sent to a systems multiplexer, Sys Mux, which outputs either a transport or a program stream.Fig. 7. Generalized codec for MPEG-2 nonscalable video coding.

The MPEG-2 decoder consists of a variable-length decoder (VLD), inverse frame/field DCT coder, and frame/field motion compensator. Sys Demux performs the complementary function of Sys Mux and presents the video bit stream to VLD for decoding of motion vectors and DCT coefficients. The frame/field motion compensator uses motion vectors decoded by VLD to generate motion-compensated prediction that is added back to the decoded prediction error signal to generate decoded video output. This type of codec produces nonscalable video bit streams since, normally, the full spatial/temporal resolution coded is the one that is expected to be decoded.

A block diagram of a generalized codec for MPEG-2 scalable video coding is shown in Fig. 8. Scalability is the property that allows decoders of various complexities to be able to decode video of resolution/quality commensurate with their complexity from the same bit stream. The generalized structure of Fig. 8 provides capability for both spatial and temporal resolution scalability in the following manner. The input video goes through a preprocessor to produce two video signals, one of which (called the base layer) is input to a standard MPEG-1 or MPEG-2 nonscalable video encoder, and the other (called the enhancement layer) is input to a MPEG-2 enhancement video encoder. The two bit streams, one from each encoder, are multiplexed in Sys Mux (along with user data) to form a composite scalable bit stream. This allows two types of decoders to be able to decode a video signal of quality commensurate with their complexity from the same coded bit stream.



Fig. 8. Generalized codec for MPEG-2 scalable video coding.

> Read full chapter

Video Interfaces

Video Interfaces

Keith Jack, in Digital Video and DSP, 2008

Pro-Video Transport Interfaces

Serial Data Transport Interface (SDTI)

SMPTE 305M and SMPTE 348M define a Serial Data Transport Interface (SDTI) that enables transfer of MPEG-2 transport streams between equipment. The physical layer uses the 270 or 360 Mbps BT.656, 360 Mbps BT.656, BT.1302, and SMPTE 259M digital component video serial interface. Figure 4.31 illustrates the signal format.



Figure 4.31. SDTI Signal Format.

A 53-word header is inserted after the EAV sequence, specifying the source, destination, and data format. Table 4.30 illustrates the header contents.

Table 4.30. DVI-D Connector Signal Assignments

Pin	Signal	Pin	Pin	Signal	Signal	Pin	Signal	Pin	Signa
1	D2–	1	9	D1–	D2–	17	D0–	9	D1–
2	D2	2	10	D1	D2	18	D0	10	D1
3	shield	3	11	shield	shield	19	shield	11	shiel
4	D4–	4	12	D3–	D4–	20	D5–	12	D3–
5	D4	5	13	D3	D4	21	D5	13	D3
6	DDC SCL	6	14	+5V	DDC SCL	22	shield	14	+5V
7	DDC SDA	7	15	ground	DDC SDA	23	CLK	15	grou
8	reserved	8	16	Hot Plug Detect	reserved	24	CLK–	16	Hot tect

The payload data is defined within BT.1381 and by other application-specific standards such as SMPTE 326M. It may consist of MPEG-2 program or transport streams, DV streams, etc., and uses either 8-bit words plus even parity, or 9-bit words plus .

High Data-Rate Serial Data Transport Interface (HD-SDTI)

High Data-Rate Serial Data Transport Interface (HD-SDTI)

SMPTE 348M and SMPTE 344M define a High Data-Rate Serial Data Transport Interface (HD-SDTI) that enables transfer of data between equipment. The physical layer uses the 1.485/1.001 Gbps (or 1.485 Gbps) SMPTE 292M digital component video serial interface.

Figure 4.32 illustrates the signal formats. Two data channels are multiplexed onto the single HD-SDTI stream. The single HD-SDTI stream (or 74.25/1.001 MHz data stream) occupies the Y data space and the other 74.25/1.001 MHz (or 74.25 MHz) data stream occupies the CbCr data space.



Figure 4.32. HD-SDTI Signal Format (two 10-bit words), CRC=line number CRC (two 10-bit words).

A 49-word header is inserted immediately after the EAV data, specifying the source, destination, and data format.

The payload data is defined by specific standards. It may consist of MPEG-2 program or transport streams, DV streams, etc., and uses either 8- or 10-bit words plus even parity, or 9-bit words plus .

> Read full chapter

Multimedia Systems: Content-Based Indexing and Retrieval

Faisal Bashir, ... Dan Schonfeld, in The Electrical Engineering Handbook, 2005

MPEG-2: Coding of High-Quality Moving Pictures (MPEG-2)

operate. MPEG-2 also has a choice of a different DCT coefficient scanning mode **alternate scan** as well as a zigzag scan.

operate. MPEG-2 also has a choice of a different DCT coefficient scanning mode **alternate scan** as well as a zigzag scan.

> Read full chapter

IPTV Architecture

James Farmer, ... Weyl Wang, in FTTx Networks, 2017

MPEG-4

MPEG-4 is the workhorse compression algorithm of Internet video transmission today, and finds some use in satellite and cable transmission. MPEG-4 is also known as advanced video coding (AVC), or by its ITU designation, H.264. As a rule of thumb, assume a bandwidth of 2 Mb/s for SD and 8 Mb/s for HD using MPEG-4. It is optional to put MPEG-4 packets in MPEG-2 transport stream before putting them in TCP or UDP packets. MPEG-4 is specified as a decoding format for Blu-ray players. Oh, what happened to MPEG-3? Originally it was to be the high-definition companion to MPEG-2. But people found that MPEG-2 was a perfectly competent high-definition decoding system, so MPEG-3 was never developed.

You will see so-called HD streams transmitted over the Internet at speeds approximately one-quarter to one-half those cited above. True, you can do that, but the amount of compression required is such that a good video engineer would argue about the picture really being HD. We recently referred one such stream to an experienced video engineer with a major programmer, and he described it as being "a little better than SD, and wide screen." This seems to be the story with much of what passes for "HD" on the Internet today, but many subscribers don't know the difference.

Some OTT programmers detect the device being used to receive the stream, and send a stream with resolution (and speed) appropriate to the device in use. Thus, they will send a faster stream to an STB, and a much slower stream to a phone. The phone screen is so small that you would not see the higher resolution if you could get it into the phone. People will call them "HD" streams, because that is what the public is expecting, and frankly many don't know the difference.

> Read full chapter

MPEG-1 and MPEG-2 Video Standards

Supavadee Aramvith, Ming-Ting Sun, in Handbook of Image and Video Processing (Second Edition), 2005

Supavadee Aramvith, Ming-Ting Sun, in Handbook of Image and Video Processing (Second Edition), 2005

2.1 Introduction

2.1.1 Background and Standardization Activities

The MPEG-2 standard is the result of the joint efforts of the MPEG committee to develop generic video standards after the development of MPEG-1. The idea of MPEG-2 is based on the fact that MPEG-1 is optimized for applications around 1.5 Mb/s with input source in SIF, which is a relatively low resolution format. MPEG-2 aims for higher quality higher bit rate applications and requires digital video source such as ITU-R BT 601, which is an interlaced format. New techniques are developed to code the interlaced video better.

The MPEG-2 committee started working in late 1990 after the completion of the technical work of MPEG-1. The competitive tests of video algorithms were held in November 1991, followed by the collaborative phase. The Committee Draft (CD) for the video part was achieved in November 1993. The MPEG-2 standard (ISO/IEC 13818) [8] consists of five parts. The first three parts are fashioned in the same fashion as MPEG-1: systems, video, audio, conformance testing, and simulation software technical report. The first three parts of MPEG-2 reached International Standard (IS) status in November 1994. Parts 4 and 5 were approved in March 1996. Part 6 of the MPEG-2 standard specifies a full set of Digital Storage Media Control Commands (DSM-CC). Part 7 is the specification of Advanced Audio Coding (AAC). Part 8 was originally planned to be the coding of 10 bit video but was discontinued. Part 9 is the specification of real-time interface (RTI) to decoders which may be utilized for adaptation to a particular network environment. Part 10 is the conformance testing of DSM-CC. Part 6 and Part 9 have already been approved as International Standards in July 1996. Like the MPEG-1 video standard, MPEG-2 video coding standard specifies only the bit stream syntax and the semantics of the decoding process. Many encoding options were left unspecified to encourage technology improvement and product differentiation.

MPEG-3, which was originally intended for HDTV (high definition television) at higher bit-rates, was merged with MPEG-2. Hence there is no MPEG-3. MPEG-2 video coding standard (ISO/IEC 13818-2) was also adopted by ITU-T as ITU-T Recommendation H.262 [9].

2.1 Introduction

2.1.1 Background and Standardization Activities

The MPEG-2 standard is the result of the joint efforts of the MPEG committee to develop generic video standards after the development of MPEG-1. The idea of MPEG-2 is based on the fact that MPEG-1 is optimized for applications around 1.5 Mb/s with input source in SIF, which is a relatively low resolution format. MPEG-2 aims for higher quality higher bit rate applications and requires digital video source such as ITU-R BT 601, which is an interlaced format. New techniques are developed to code the interlaced video better.

The MPEG-2 committee started working in late 1990 after the completion of the technical work of MPEG-1. The competitive tests of video algorithms were held in November 1991, followed by the collaborative phase. The Committee Draft (CD) for the video part was achieved in November 1993. The MPEG-2 standard (ISO/IEC 13818) [8] consists of five parts. The first three parts are fashioned in the same fashion as MPEG-1: systems, video, audio, conformance testing, and simulation software technical report. The first three parts of MPEG-2 reached International Standard (IS) status in November 1994. Parts 4 and 5 were approved in March 1996. Part 6 of the MPEG-2 standard specifies a full set of Digital Storage Media Control Commands (DSM-CC). Part 7 is the specification of Advanced Audio Coding (AAC). Part 8 was originally planned to be the coding of 10 bit video but was discontinued. Part 9 is the specification of real-time interface (RTI) to decoders which may be utilized for adaptation to a particular network environment. Part 10 is the conformance testing of DSM-CC. Part 6 and Part 9 have already been approved as International Standards in July 1996. Like the MPEG-1 video standard, MPEG-2 video coding standard specifies only the bit stream syntax and the semantics of the decoding process. Many encoding options were left unspecified to encourage technology improvement and product differentiation.

MPEG-3, which was originally intended for HDTV (high definition television) at higher bit-rates, was merged with MPEG-2. Hence there is no MPEG-3. MPEG-2 video coding standard (ISO/IEC 13818-2) was also adopted by ITU-T as ITU-T Recommendation H.262 [9].

2.1.2 Target Applications and Requirements

2.1.2 Target Applications and Requirements

MPEG-2 is primarily targeted at coding high-quality video at 4–15 Mb/s for video on demand (VOD), digital broadcast television, and digital storage media such as DVD (digital versatile disc), digital cable/satellite TV, video services over wireless, 2-way networks, and other high-quality digital video applications.

The requirements from MPEG-2 applications have several important features of the compression algorithm. Regarding picture quality, MPEG-2 needs to be able to provide good NTSC quality video at 4–6 Mb/s and transparent NTSC quality video at 8–10 Mb/s. It needs to provide the capability of random access and quick channel switching by means of I-pictures in GOPs. Low-delay mode is specified for delay-sensitive visual communications applications. MPEG-2 has scalable coding modes to support multiple grades of video quality, spatial resolutions, and frame rates for various applications. Error resilience options include data partitioning, data scalable coding, and scalable coding. Compatibility with the existing MPEG-1 video standard is another prominent feature provided by MPEG-2. For example, MPEG-2 decoders should be able to decode MPEG-1 bit streams. If scalable coding is used, the base layer of MPEG-2 signals can be decoded by an MPEG-1 decoder. Finally, it should allow reasonable complexity encoders and low-cost decoders be built with current technology. Since MPEG-2 video is based heavily on MPEG-1, in the following sections, we will focus only on those features which are different from MPEG-1 video.

> Read full chapter