

Network Security Compliance Audit Report

Hostname	EDGE-RT-07
Device ID	cisco-ios-noncompliant
Vendor	Cisco IOS/IOS-XE
OS Version	15.2
Model	n/a
Audit Timestamp	2026-09-05 09:21 UTC

Executive Summary

Compliance Score: **35.0%** | 7 PASS / 13 FAIL / 20 rules evaluated | 5 unrecognized line(s) routed to Training Queue

Top critical findings:

CF-CISCO-001 — Disable Telnet, require SSHv2
CF-CISCO-007 — Default/empty enable credential changed
CF-CISCO-019 — SNMP community strings changed from defaults

Findings

Rule ID	Title	Severity	Status	Source
CF-CISCO-001	Disable Telnet, require SSHv2	CRITICAL	FAIL	Built-in rule
CF-CISCO-007	Default/empty enable credential changed	CRITICAL	FAIL	Built-in rule
CF-CISCO-019	SNMP community strings changed from defaults	CRITICAL	FAIL	Built-in rule
CF-CISCO-002	Disable insecure HTTP management server	HIGH	FAIL	Built-in rule
CF-CISCO-003	Vty lines protected by an inbound access-class	HIGH	FAIL	Built-in rule
CF-CISCO-010	Remote syslog configured	HIGH	FAIL	Built-in rule
CF-CISCO-005	AAA new-model enabled (authentication + authorization)	HIGH	PASS	Built-in rule
CF-CISCO-013	No weak ciphers / hashes in device config	HIGH	PASS	Built-in rule
CF-CISCO-006	Minimum password length >= 8	MEDIUM	FAIL	Built-in rule
CF-CISCO-008	Service password-encryption enabled	MEDIUM	FAIL	Built-in rule
CF-CISCO-009	Login lockout / rate limiting configured	MEDIUM	FAIL	Built-in rule
CF-CISCO-011	Admin access logging (archive/log config) enabled	MEDIUM	FAIL	Built-in rule
CF-CISCO-014	SSH key modulus >= 2048 bits	MEDIUM	FAIL	Built-in rule
CF-CISCO-016	Unused small services disabled (tcp/udp-small-servers, finger, bootp)	MEDIUM	FAIL	Built-in rule
CF-CISCO-004	SSH idle/exec timeout configured (<= 10 minutes)	MEDIUM	PASS	Built-in rule
CF-CISCO-012	ACL entries with explicit logging	MEDIUM	PASS	Built-in rule
CF-CISCO-018	NTP configured for consistent timestamps	MEDIUM	PASS	Built-in rule
CF-CISCO-015	CDP disabled on the device	LOW	FAIL	Built-in rule
CF-CISCO-017	Login banner / warning message present	LOW	PASS	Built-in rule
CF-CISCO-020	SNMP disabled if unused	LOW	PASS	Built-in rule

Remediation Appendix

Exact CLI per failed rule, in vendor-native syntax. AI-suggested mappings that a human confirmed are marked with their source.

CF-CISCO-001 — Disable Telnet require SSHv2

```
line vty 0 4
transport input ssh
no transport input telnet
ip ssh version 2
```

CF-CISCO-007 — Default/emmtv enable credential changed

```
enable secret <STRONG-HASHED-SECRET>
no enable password
```

CF-CISCO-019 — SNMP community strings changed from defaults

```
no snmp-server community public R0
snmp-server community <RANDOM-32-CHAR-STRING> R0 99
```

CF-CISCO-002 — Disable insecure HTTP management server

```
no ip http server
```

CF-CISCO-003 — Vty lines protected by an inbound access-class

```
ip access-list standard MGMT-HOSTS
permit 10.10.10.0 0.0.0.255
deny any log
line vty 0 4
access-class MGMT-HOSTS in
```

CF-CISCO-010 — Remote syslog configured

```
logging host 10.20.30.40
logging trap informational
```

CF-CISCO-006 — Minimum password length >= 8

```
security passwords min-length 8
```

CF-CISCO-008 — Service password-encryption enabled

```
service password-encryption
```

CF-CISCO-009 — Login lockout / rate limiting configured

```
login block-for 120 attempts 3 within 60
```

CF-CISCO-011 — Admin access logging (archive/log config) enabled

```
archive
log config
logging enable
notify syslog
```

CF-CISCO-014 — SSH key modulus >= 2048 bits

```
crypto key generate rsa modulus 2048
```

CF-CISCO-016 — Unused small services disabled (tcp/udp-small-servers, finger, bootp)

```
no service tcp-small-servers
no service udp-small-servers
no ip finger
no ip bootp server
no service pad
```

CF-CISCO-015 — CDP disabled on the device

```
no cdp run
```

Disclaimer: Remediation commands are advisory. Apply in a maintenance window after review — not for unattended auto-execution.