

Minimal Profile, Registration and Final Integration Pack

2026-09-21 · @Someone

1. Purpose and scope rule

The full profile pack describes 57 functional requirements, which is far more than the internship needs. This pack keeps only the small part that the guide requires or that makes a required feature work well, so the project can be finished, verified, and submitted. It also turns the complete guide, now available in full, into a compliance matrix (section 8) and a finishing plan (section 9).

Scope rule. A feature is built now only if it passes all four tests. Anything that fails one goes to the deferred list in section 2.

Test	Question
Required or enabling	Does a guide requirement need it, or does a required feature work poorly without it?
Cheap	Can it be built and tested in about a day using what already exists?
Safe	Does it avoid a new external service, a new secret, and a new privacy risk?
Visible	Can an evaluator see it working within the 2 to 5 minute demo?

How the guide is served

Guide item	Minimal feature that serves it
Task 1: user and profile section	Own profile page and profile editing (MF-06, MF-08)
Task 4: registration, login, logout, protected routes	Two-step registration that captures professional information (MF-01 to MF-05), and sign out of all devices (MF-14)

Guide item	Minimal feature that serves it
Task 4: assign tasks	People picker that shows each member's discipline and company (MF-11), and a member profile page (MF-07)
Task 4: dashboard statistics and recent activity	Profile statistics from data that already exists (MF-06)
UI / UX (15%)	Updated avatar menu, settings, and designed states (MF-12, MF-18)
Code quality (20%) and technical implementation (15%)	Database-enforced fields, one reversible migration, focused tests (MF-19, MT-01 to MT-23)
Documentation (10%) and GitHub repository quality (5%)	README, screenshots, environment example, compliance matrix (MF-22, MF-23)
Demo and presentation (5%)	Demo script and LinkedIn post draft (MF-24)
Innovation and additional features (5%)	Professional registration data, profile completeness, and the discipline-aware people picker
Guideline: AI tools are allowed but the intern must understand the implementation	Understanding notes written for the author (MF-25)

What the full guide changes. The guide sets the demo video at 2 to 5 minutes and asks it to show the application running end to end, the main features in action, key technical implementation details, and the final result. It confirms that the LinkedIn post must tag the official Innovation Hacks page, and it lists what the reward review may consider: quality of all four tasks, technical implementation, innovation, code quality, GitHub activity, documentation, timely submission, demo quality, problem-solving, and professionalism. The submission standard assumed a 3 to 5 minute video, and that assumption is corrected there to match the guide.

2. Minimal feature set

The minimal set adds one registration flow, one profile page and its editor, one people picker, one settings page, and one menu change. It needs one migration, no new external service, and no new secret.

Built now

Area	What is built	Why it passes the scope rule
Registration	Two steps: account, then professional details (discipline, seniority, employment status, company, job title, country, city, time zone) with consent	Task 4 registration, and the request to capture who the person is as a professional
Profile	Own profile page with about, skills, links, and statistics; a page for other members; an editor	Task 1 user and profile section
People picker	Search members by name when assigning a task, showing discipline and company	Task 4 "assign" requirement
Settings	Four tabs: Profile, Account, Preferences, Privacy	A professional platform needs a place for basics, and it is quick to demo
Menu	Avatar menu with name and headline, and a Settings entry	UI and UX score
Data	One migration: two profile tables and two name columns	Database-enforced validation is scored in Task 3

Deferred, with the reason

Deferred feature	Why it waits	Full-pack reference
Email verification, non-enumerating registration, password reset	Needs an email provider, which is a new external service and secret; kept as a documented limitation and the first item to add later	FR-503, FR-512, FR-564
Username and profile addresses by handle	Member identifiers already work as addresses	FR-509, FR-533
Avatar upload	Needs object storage; initials avatars already exist	FR-530

Deferred feature	Why it waits	Full-pack reference
Company records, deduplication, verified employees, company pages	A free-text company name is enough to display and to assign	FR-505, FR-513, FR-536
Experience, education, certifications, portfolio, languages, achievements	Not required by the guide and a large surface to build and test	FR-523 to FR-528
Per-section visibility, public profiles, search indexing	One privacy switch is enough for now	FR-534
A full directory page with filters	The people picker covers the guide's need	FR-535
Availability and work preferences	Not needed by any guide item	FR-531
Contribution graph, profile activity feed, badges	The dashboard already shows activity; profile statistics are enough	FR-540 to FR-542
Two-factor authentication, security log, access tokens, connected accounts, notification settings, consent history, data export, moderation	Each adds a service, a secret, or a large test surface	FR-554, FR-555, FR-557, FR-559 to FR-561, FR-563
Import and export of profiles	Not required by the guide	FR-537, FR-538
Bot challenge, breached-password check, disposable-email blocking	The rate limiting from Task 2 stays in place	FR-511
Additional interface languages	English only	FR-574

The full profile pack remains the source for these items when the team wants to grow the product, and its phase plan already orders them.

3. Registration and profile

Registration collects the minimum that describes a software professional in two short steps, and the profile shows it. Everything is stored in typed columns with database constraints, so the data is trustworthy enough to filter and display.

```

flowchart LR
    A["Step 1<br/>Account"] --> B["Step 2<br/>Professional details<br/>and consent"]
    B --> C["Submit<br/>POST /users"]
    C --> D["Signed in"]
    D --> E["Dashboard with<br/>profile completeness banner"]
  
```

Each step validates its fields on the server without creating anything, and the second step submits everything in one request. Non-secret answers may be kept in `sessionStorage`, and the password never is.

Registration fields

Field	Step	Required	Rules
<code>givenName</code>	1	Yes	1 to 60 characters; Unicode letters, spaces, hyphens, apostrophes; trimmed
<code>familyName</code>	1	Yes	Same as above
<code>email</code>	1	Yes	Existing rules from Task 2: valid, at most 254 characters, stored lowercase, unique
<code>password</code>	1	Yes	Existing rules from Task 2: 12 to 128 characters, not equal to the email or name; a show toggle instead of a confirmation field
<code>discipline</code>	2	Yes	One value from the discipline list
<code>seniority</code>	2	Yes	One value from the seniority list
<code>employmentStatus</code>	2	Yes	One value from the employment status list

Field	Step	Required	Rules
<code>companyName</code>	2	When employed or freelancing	1 to 120 characters; freelancers may enter "Independent"
<code>jobTitle</code>	2	When employed or freelancing	1 to 100 characters
<code>country</code>	2	Yes	ISO 3166-1 alpha-2 code chosen from a list
<code>city</code>	2	No	1 to 80 characters
<code>timeZone</code>	2	Yes	IANA name, defaulted from the browser and editable
<code>termsAccepted</code>	2	Yes	Stores the terms version and the time
<code>ageConfirmed</code>	2	Yes	A checkbox that the person meets the minimum age (16 by default, a setting); no birth date is collected

The display name `name` is built from the given and family names, so every existing screen keeps working.

Controlled lists

List	Values
Discipline	<code>backend</code> , <code>frontend</code> , <code>full_stack</code> , <code>mobile</code> , <code>devops_cloud</code> , <code>data_ai</code> , <code>security</code> , <code>qa</code> , <code>other</code> (labels: Backend, Frontend, Full-stack, Mobile, DevOps and cloud, Data and AI, Security, QA and testing, Other)
Seniority	<code>student_intern</code> , <code>junior</code> , <code>mid</code> , <code>senior</code> , <code>lead_or_above</code>
Employment status	<code>employed</code> , <code>freelance</code> , <code>student</code> , <code>between_roles</code>

The lists live in one configuration file used by the API, the database migration, and the frontend, so the three never disagree.

Profile page

Zone	Contents
Header	Initials avatar, display name, headline, discipline and seniority, company and job title, city and country, the person's local time, and an Edit profile button on the owner's own page
About	Plain text of up to 500 characters
Skills	Up to 10 free-text tags of up to 30 characters, unique ignoring case
Links	GitHub, LinkedIn, and website, each <code>https</code> only; GitHub and LinkedIn must point to that provider's host
Statistics (own page only)	Projects owned, tasks done, tasks open, and member since, from data that already exists
Completeness (own page only)	Percentage and the next suggested step

The headline is composed when shown, for example "Senior Backend engineer at Acme", unless the person stored their own of up to 120 characters. Every text field is plain text and is always escaped, and external links open with `rel` set to `noopener nofollow`. Another member's page shows the professional details only when that member allows it, never shows the email, and never shows statistics.

Profile completeness (owner only; registration alone earns 50)

Component	Points
Name	10
Discipline and seniority	15
Employment: status, and company and title when working	15
Country and time zone	10
Headline	10
About	15

Component	Points
At least three skills	15
At least one link	10

Interface rules. One column, a progress indicator ("Step 1 of 2"), Back and Next buttons, validation when a field loses focus with plain-language messages, correct autocomplete values (given-name , family-name , email , new-password , organization , organization-title , country-name), full keyboard operation, and focus moved to the step heading on each change. After registration the person lands on the dashboard with a dismissible banner showing their completeness and a link to edit the profile.

4. Settings, people picker and navigation

This section covers the parts around the profile that a reviewer will click next: the menu, the settings page, and the place where members meet the rest of the app, which is task assignment.

Avatar menu (replaces the four-item menu)

Item	Goes to	Notes
Header block	Own profile	Initials avatar, display name, and headline; the email address is no longer shown here, so a shared screen reveals less
Profile	/profile	Unchanged label
Projects	/projects	Unchanged
Tasks	/tasks	Unchanged
Settings	/settings	New
Log out	Ends the session	Unchanged; also revokes the refresh token

Settings page (four tabs; every tab has loading, error, and saved states, and works by keyboard)

Tab	Contents	Rules
Profile	Edit given and family name, discipline, seniority, employment status, company, job title, country, city, headline, about, skills, and links	Same rules as registration and the profile page; the display name is rebuilt from the given and family names
Account	Email shown read-only; change password; sign out of all devices; delete account	Changing the password needs the current one and ends every other session; sign out of all devices ends every session including this one; deleting needs the password
Preferences	Theme (light, dark, or system) and time zone	Saved per account and applied on every device, and the theme toggle in the header keeps working and saves to the same setting
Privacy	A switch, "Show my professional details to other members", on by default	Turning it off hides discipline, seniority, company, job title, and location from other members at once; the email is never shown to other members, and leads see it as before (Task 4 BR-403)

Account deletion. The dialog asks for the password and states what will happen. If the person still owns projects, the API answers with the existing `USER_OWNS_PROJECTS` conflict and the dialog explains that the projects must be deleted or handed to someone else first. Otherwise the account is removed, tasks assigned to the person become unassigned, and the person is signed out. These are the referential actions already defined in Task 3.

People picker. Wherever a task is assigned, a keyboard-operable combobox searches members by name.

Aspect	Rule
Search	At least two characters, matched on name, at most 20 results, using the existing <code>GET /users</code> list contract

Aspect	Rule
Each result	Initials avatar, name, and, when the member allows it, discipline and company
Privacy	Members who turned off the privacy switch show name and avatar only; email is never shown to non-leads
Accessibility	The result count is announced in a live region, arrow keys move through results, and Escape closes the list
Visibility of projects	Unchanged: assigning a task still gives the assignee sight of that project only (Task 4 BR-401)

Member profile page. Opening a name anywhere in the app shows `/people/{id}`, which uses the same layout as the own profile without the edit button, statistics, or completeness meter, and with the professional details subject to the privacy switch.

5. Data model and API

The change is one reversible migration, `0006_minimal_profile`, and a handful of endpoints, all following the conventions of Tasks 2 to 4: camelCase JSON, UUIDs, named constraints (`pk_`, `fk_`, `uq_`, `ck_`, `ix_`), the existing error envelope, and additive changes except where section 6 lists a supersession.

Changes to `users`. Two nullable columns are added: `given_name` and `family_name`, each 1 to 60 characters when present. The existing `name` column stays as the display name, and `theme` stays where Task 3 put it.

Table `profiles` (one row per user)

Column	Type	Null	Constraints
<code>user_id</code>	uuid	no	<code>pk_profiles</code> ; <code>fk_profiles_user_id_users</code> , on delete cascade
<code>discipline</code>	text	no	<code>ck_profiles_discipline</code> : one of the discipline values

Column	Type	Null	Constraints
seniority	text	no	ck_profiles_seniority : one of the seniority values
employment_status	text	no	ck_profiles_employment_status : one of the status values
company_name	text	yes	ck_profiles_company_name_length : 1 to 120 characters, trimmed
job_title	text	yes	ck_profiles_job_title_length : 1 to 100 characters, trimmed
(table check)			ck_profiles_employment_details : when the status is employed or freelance , both company and job title are present
country_code	text	no	ck_profiles_country_code : two uppercase letters
city	text	yes	ck_profiles_city_length : 1 to 80 characters
time_zone	text	no	ck_profiles_time_zone_length : at most 64; the value is checked against the IANA list by the service
headline	text	yes	ck_profiles_headline_length : at most 120
about	text	no	default empty; ck_profiles_about_length : at most 500
github_url, linkedin_url, website_url	text	yes	ck_profiles_*_https : starts with https:// and at most 2,048 characters; GitHub and LinkedIn also check their host
show_professional_details	boolean	no	default true
terms_version, terms_accepted_at	text, timestampz	no	Recorded at registration
age_confirmed_at	timestampz	yes	ck_profiles_age_confirmed : present unless terms_version is legacy
created_at, updated_at	timestampz	no	Application-supplied through the injected clock

Table `profile_skills`

Column	Type	Null	Constraints
id	uuid	no	pk_profile_skills
user_id	uuid	no	fk_profile_skills_user_id_users , on delete cascade; indexed
name	text	no	ck_profile_skills_name_length : 1 to 30 characters, trimmed
sort_order	smallint	no	Position in the list
(unique)			uq_profile_skills_user_id_name_lower : one skill per person ignoring case

At most 10 skills per person are enforced by the service under a lock on the profile row and by a constraint trigger on the table.

Migration and existing users. The migration creates both tables, then gives every existing user a profile with `discipline` set to `other`, `seniority` to `mid`, `employment_status` to `between_roles`, `country_code` to `ZZ` (the reserved "unknown" code), `time_zone` to `UTC`, `terms_version` to `legacy`, and `age_confirmed_at` left empty. Their settings page shows a prompt to complete the profile. The downgrade drops both tables and the two columns. No existing data is changed or lost.

Endpoints (under `/api/v1`)

Method	Path	Success	Errors	Requirement
POST	<code>/users</code>	201	409, 422, 429	MF-01 to MF-04 (payload extended)
POST	<code>/users/validate</code>	200	422, 429	MF-01 (validates one step and creates nothing)
GET	<code>/me</code>	200	401	MF-06, MF-09, MF-12
PATCH	<code>/me/profile</code>	200	401, 422	MF-08
PUT	<code>/me/skills</code>	200	401, 422	MF-08
PUT	<code>/me/preferences</code>	200	401, 422	MF-15
PUT	<code>/me/privacy</code>	200	401, 422	MF-16

Method	Path	Success	Errors	Requirement
POST	/me/password	204	401, 403, 422, 429	MF-13
DELETE	/me/sessions	204	401	MF-14
POST	/me/delete	204	401, 403, 409, 422	MF-17
GET	/users	200	401, 422	MF-11 (items extended)
GET	/users/{userId}	200	401, 404	MF-07 (response extended)

A wrong current password on `/me/password` or `/me/delete` returns 403 with the existing `INVALID_CREDENTIALS` code, and not 401, so the client does not mistake it for an expired session. No new error codes are needed.

User representation. The existing user object gains `givenName`, `familyName`, and a `profile` object with `discipline`, `seniority`, `employmentStatus`, `companyName`, `jobTitle`, `country`, `city`, `timeZone`, `headline`, `about`, `links` (`github`, `linkedin`, `website`), and `skills`. For another member the `profile` is present only when that member has professional details switched on, and `email` follows Task 4 BR-403. `GET /me` adds `stats` (`projectsOwned`, `tasksDone`, `tasksOpen`) and `completeness` (`percent` and `next`). The discipline, seniority, and status values appear as enumerations in `openapi.json`, so the frontend types are generated from the same lists.

Settings. Two non-secret settings are added: `MIN_AGE` (default 16) and `TERMS_VERSION` (the current terms version). The controlled lists live in one configuration file used by the migration, the API, and the type generation. There are no new secrets and no new external services.

6. Requirements and business rules

There are 25 functional requirements (22 Must, 3 Should) and 9 non-functional requirements. Every Must blocks release, and Should items are tracked in the gate. IDs use `MF-` and `MN-` so they never clash with the four task packs, and each row names the full-pack requirement it narrows.

Functional requirements

ID	Requirement	Pri	Acceptance criteria	Full pack
MF-01	Two-step registration	M	Steps of section 3; each step is checked by <code>POST /users/validate</code> , which creates nothing; one final <code>POST /users</code> ; success signs the person in	FR-501, FR-504 to FR-506
MF-02	Field rules and controlled lists	M	Every rule of section 3 is enforced on the client, the server, and the database; list values come from one configuration file and appear as OpenAPI enumerations	FR-502, NFR-516
MF-03	Consent and age confirmation	M	Terms version, time, and age confirmation are required and stored; no birth date is kept	FR-508
MF-04	Duplicate email behaviour unchanged	M	A duplicate email still returns 409 <code>EMAIL_ALREADY_EXISTS</code> ; recorded as a known limitation until email verification is added	none
MF-05	Welcome banner	M	After registration the dashboard shows a dismissible banner with the completeness percentage and a link to edit the profile	FR-510
MF-06	Own profile page	M	Header, about, skills, links, statistics, and completeness per section 3, with loading, empty, and error states	FR-520
MF-07	Member profile page	M	<code>/people/{id}</code> shows professional details only when allowed, and never the email or statistics; an unknown id shows the not-found page	FR-520

ID	Requirement	Pri	Acceptance criteria	Full pack
MF-08	Edit profile	M	Every field validated with per-field messages; skills up to 10 and unique ignoring case; links <code>https</code> and host-checked; clear saved and error feedback	FR-521, FR-525, FR-529
MF-09	Profile completeness	S	Percentage by the section 3 formula and the next step, shown to the owner only	FR-532
MF-10	Plain text and safe links	M	Markup in any field appears as text; external links use <code>noopener</code> <code>nofollow</code>	FR-522
MF-11	People picker	M	Behaviour of section 4; results respect the privacy switch; assigning a task still works end to end	FR-535, FR-571
MF-12	Settings page	M	Four tabs, keyboard operable, all states, reachable from the avatar menu	FR-550
MF-13	Change password	M	Needs the current password and follows the password rules; ends every other session; a wrong current password returns 403	FR-552
MF-14	Sign out of all devices	S	Revokes every refresh-token family of the person and returns to the login page	FR-553
MF-15	Preferences	M	Theme and time zone are saved per account and applied on any device at the next sign-in	FR-558
MF-16	Privacy switch	M	Applies at once to the profile page, the people picker, and <code>GET /users</code> responses	FR-556

ID	Requirement	Pri	Acceptance criteria	Full pack
MF-17	Delete account	S	Password required; blocked with <code>USER_OWNS_PROJECTS</code> while projects are owned; otherwise the account is removed and the person signed out	FR-562
MF-18	Avatar menu	M	Items of section 4, with no email in the header	none
MF-19	Migration	M	<code>0006_minimal_profile</code> runs up, down, and up; existing users are backfilled; constraints follow the naming convention; the drift check is clean	FR-575, NFR-519
MF-20	API and generated types	M	Endpoints of section 5 are in <code>openapi.json</code> , and the TypeScript types regenerate and compile with no manual edits	FR-570
MF-21	Existing behaviour preserved	M	The Task 1 to 4 gates pass except for the supersessions below, each logged with the old and new assertion	NFR-518
MF-22	Guide compliance matrix	M	The matrix of section 8 is saved as <code>docs/guide-compliance.md</code> with evidence for every row	none
MF-23	GitHub deliverables	M	README, screenshots, <code>.env.example</code> , and demo link per guide section 08, with no secrets in files or history	none
MF-24	Demo script and post	M	A demo script that fits 2 to 5 minutes and a LinkedIn post draft tagging Innovation Hacks	none

ID	Requirement	Pri	Acceptance criteria	Full pack
MF-25	Understanding notes	M	docs/how-it-works.md explains the architecture and the key code paths of registration, profile, and assignment, with review questions for the author to answer in their own words	none

Non-functional requirements

ID	Category	Requirement	Target	Verified by
MN-01	Accessibility	New screens meet WCAG 2.2 AA, and registration and settings work by keyboard alone	0 axe violations	axe, Playwright
MN-02	Usability	Median time to finish registration	2 minutes or less	Five timed runs
MN-03	Performance	p95 latency of profile reads, and Largest Contentful Paint of the profile page on a mobile profile	150 ms, and 2.5 s	Locust, Lighthouse
MN-04	Privacy	No field collects a category excluded by MB-07; hidden professional details are absent from every response; email shown only to the person and to leads	0 leaks	Schema review, privacy tests

ID	Category	Requirement	Target	Verified by
MN-05	Security	Text is escaped, links are https , password change and deletion need the current password and are rate limited, and no new secret exists	0 findings	Tests, gitleaks
MN-06	Data quality	Every controlled value and length rule is a named database constraint, proved by writing invalid rows directly	100% of constraints	Bypass tests
MN-07	Compatibility	Existing users and their data are unaffected, and OpenAPI changes are additive apart from POST /users	0 losses, 0 other breaking changes	Migration test, OpenAPI diff
MN-08	Documentation	README, compliance matrix, ADRs, supersession log, and changelog are updated	All present	Documentation check
MN-09	Footprint	New external services, new secrets, and migrations	0, 0, 1	Configuration review

Business rules

ID	Rule
MB-01	Discipline, seniority, and company never affect permissions; only the platform role does.

ID	Rule
MB-02	A member sees another member's professional details only when that member's switch is on. The email follows Task 4 BR-403, and statistics and completeness are visible to the owner only.
MB-03	Registration requires the fields of section 3, and company and job title are required when the status is <code>employed</code> or <code>freelance</code> .
MB-04	Profile text is plain text and always escaped. Links are <code>https</code> , and GitHub and LinkedIn links must point to those providers' hosts.
MB-05	A person has at most 10 skills, unique ignoring case.
MB-06	Changing the password ends all other sessions, signing out of all devices ends all of them, and deleting an account needs the password and follows the Task 3 referential actions.
MB-07	The platform does not collect gender, birth date, ethnicity, religion, national identifiers, health data, or precise location.
MB-08	Statistics count only the person's own projects and tasks. Times are stored in UTC and shown in the person's time zone.

Supersessions (the only permitted departures from earlier packs; each is logged in `docs/supersession-log.md`)

ID	Change	Reason	Effect on tests
S-A	<code>POST /users</code> requires <code>givenName</code> , <code>familyName</code> , the <code>profile</code> block, consent, and age confirmation	Registration must capture the professional identity	The shared registration helper used by Task 2 to 4 tests is updated once, and each old assertion is logged

ID	Change	Reason	Effect on tests
S-B	The user representation gains fields, and GET /users items gain a professional summary when allowed	The people picker needs it	Additive; the privacy switch governs it
S-C	The avatar menu no longer shows the email	Privacy on shared screens	Interface tests only
S-D	The Task 1 mock adapter gains the new fields	Keeps mock and real adapters aligned	Test data only

7. Tests and Standards Gate

The tests are few and each proves one requirement, with the most attention on what must not leak and what the database must refuse. The existing Task 1 to 4 suites are reused as the regression net.

Tests

ID	Test	Proves
MT-01	Registration wizard: both steps, per-step validation that creates nothing, final submit, automatic sign-in	MF-01, MF-05
MT-02	Field-rule matrix: every field with valid, empty, too long, and wrong-format values, and every list value plus one invalid	MF-02
MT-03	Database bypass: raw SQL rejects a bad discipline, seniority, or status, a company missing for an employed person, a bad country code, non- https links, and over-long text	MF-02, MN-06
MT-04	Consent and age confirmation are required and stored, and no birth date exists in the schema	MF-03, MN-04
MT-05	A duplicate email still returns 409 EMAIL_ALREADY_EXISTS	MF-04

ID	Test	Proves
MT-06	Own profile page, statistics from real data, and the completeness formula	MF-06, MF-09
MT-07	Member profile: professional details follow the switch, and the email and statistics are never shown	MF-07, MB-02
MT-08	Edit profile: validation messages, 10-skill limit under concurrent requests, case-insensitive uniqueness, link host checks	MF-08, MB-05
MT-09	Markup and script payloads in every text field appear as plain text, and external links carry <code>noopener nofollow</code>	MF-10, MB-04
MT-10	People picker: search, results, privacy switch, and assigning a task, with Task 4 visibility rules unchanged	MF-11
MT-11	Settings navigation, states, and preferences persisting across sign-in	MF-12, MF-15
MT-12	Change password: needs the current one, follows the rules, and ends other sessions; a wrong current password returns 403	MF-13
MT-13	Sign out of all devices ends every session	MF-14
MT-14	The privacy switch takes effect immediately in the profile, the picker, and <code>GET /users</code>	MF-16
MT-15	Delete account: password required, blocked while projects are owned, tasks unassigned, and signed out	MF-17
MT-16	Avatar menu items and no email in the header	MF-18
MT-17	Migration: up, down, and up on an empty and a seeded database, existing users backfilled, drift check clean	MF-19, MN-07
MT-18	OpenAPI diff is additive apart from <code>POST /users</code> , and generated types compile	MF-20, MN-07

ID	Test	Proves
MT-19	Accessibility and keyboard: axe on every new screen, registration and settings by keyboard, three viewports	MN-01
MT-20	Regression: Task 1 to 4 gates, and every changed assertion appears in the supersession log	MF-21
MT-21	Every row of the compliance matrix has an evidence path that exists	MF-22
MT-22	README sections, <code>.env.example</code> completeness, screenshots present, and gitleaks clean over files and history	MF-23, MN-05, MN-08
MT-23	Profile read p95 latency and page load targets	MN-03

Rules for tests

- A test's name starts with its `MT-##` and names the requirement it proves.
- Every hidden-data test checks three things: the field is absent, the count is unchanged, and the answer for hidden data equals the answer for missing data.
- Where a supersession changes an earlier assertion, the earlier test is updated and never deleted, and the change is logged with its reason.
- Tests create their users through one shared helper, so a future change to registration touches one place.

Standards Gate

```

make gate          # Task 1 to 4 gates first (with the supersessions
above), then:

make test-profile  # MT-01 to MT-16 on the API and units, MT-23 timing
make db-check      # migration 0006 up, down, up; drift; bypass matrix (MT-
03, MT-17)
make e2e-profile   # Playwright: registration to banner, profile edit,
settings, picker, 3 viewports, axe
make guide-check   # compliance matrix evidence, README sections,
.env.example, gitleaks (MT-21, MT-22)

# after each deploy
make smoke         # register, edit the profile, assign a task with the
picker, change password, sign out

```

Reviewer checklist (someone other than the author, on the deployed site)

- ☐ Registration takes two steps and about two minutes, every rule shows a clear message, consent is required, and a duplicate email gives the existing message (MF-01 to MF-04)
- ☐ After registering, the dashboard banner shows the completeness and leads to the editor (MF-05)
- ☐ The own profile shows header, about, skills, links, statistics, and completeness, and another member's page shows none of the statistics or email (MF-06, MF-07)
- ☐ Typing markup into every text field shows text, and links must be `https` (MF-10)
- ☐ Turning the privacy switch off hides professional details from another account at once, in the profile and in the picker (MF-16)
- ☐ The picker finds a member by name and assigns a task, and the member sees only that project (MF-11)
- ☐ Changing the password ends a second signed-in browser, and "sign out of all devices" ends both (MF-13, MF-14)
- ☐ Theme and time zone persist after signing in on another browser (MF-15)
- ☐ Deleting an account that owns projects explains what to do first (MF-17)
- ☐ The menu shows name and headline and no email (MF-18)
- ☐ The migration ran on a copy of the real data with no loss, and older accounts see the completion prompt (MF-19)
- ☐ The compliance matrix of section 8 is complete, and every guide deliverable is ready (MF-22 to MF-25)

Failure handling. A failed item gets a defect note naming the requirement ID, the fix, and the test that now covers it, and the gate is then rerun in full.

8. Guide compliance matrix

Every requirement of the Innovation Hacks guide appears below with the feature that satisfies it and the file or test that proves it. The build copies this table to `docs/guide-compliance.md`, adds a status of Pass, Partial, Fail, or Manual step with real evidence to each row, and the reviewer checks it against the running application. The `make guide-check` target verifies that every evidence path exists.

Task 1: Modern frontend (guide section 03)

ID	Guide requirement	Satisfied by	Evidence
G-01	Dashboard as the primary landing view	Dashboard route <code>/</code> ; Task 1 FR-01 to FR-04	Screenshot, TC-001
G-02	Navigation bar with accessible wayfinding	Navigation and the new avatar menu; Task 1 FR-05 to FR-08, MF-18	TC-010 to TC-012, MT-16
G-03	User and profile section	Profile page, editor, and settings; MF-06 to MF-08, MF-12	MT-06, MT-08, screenshots
G-04	Project and task cards with a consistent visual system	Card components on design tokens; Task 1 FR-11, FR-12	TC-030, TC-031
G-05	Progress indicators for tasks and projects	Progress bar and ring; Task 1 FR-13	TC-040, TC-041
G-06	Search and filter	Filters kept in the URL; Task 1 FR-15 to FR-19	TC-050 to TC-054
G-07	Fully responsive on mobile, tablet, and desktop	Mobile-first layouts; Task 1 FR-23	TC-060, MT-19
G-08	Loading and empty states for all dynamic views	Skeletons, empty and error states; Task 1 FR-20 to FR-22	TC-070 to TC-073, MT-19
G-09	Clean, reusable component architecture	Layering rules and boundary lint; Task 1 section 7	TC-080 to TC-083

Task 2: Backend and REST API (section 04)

ID	Guide requirement	Satisfied by	Evidence
G-10	User management endpoints	Task 2 FR-201 to FR-208, plus <code>/me</code> endpoints	TC-201 to TC-208, MT-01
G-11	Project creation and retrieval	Task 2 FR-209 to FR-213	TC-210 to TC-213
G-12	Task creation, update, and deletion	Task 2 FR-214 to FR-218	TC-220 to TC-224
G-13	Task status management	Enforced workflow; Task 2 FR-219	TC-230 to TC-233
G-14	Centralized error handling	One envelope and handlers; Task 2 FR-224	TC-240 to TC-242
G-15	Input validation on all write operations	Schemas with <code>extra="forbid"</code> , including the new endpoints	TC-250 to TC-253, MT-02
G-16	Correct, meaningful HTTP status codes	Status-code decision table; Task 2 FR-226	TC-260 to TC-262
G-17	Environment variables for configuration and secrets	Validated settings and <code>.env.example</code> ; Task 2 FR-227	TC-270 to TC-272, MT-22
G-18	Clear API documentation	<code>docs/openapi.json</code> , Postman collection, README; Task 2 FR-228	TC-280 to TC-283, MT-18

Task 3: Database integration (section 05)

ID	Guide requirement	Satisfied by	Evidence
G-19	User, project, and task data storage	PostgreSQL tables, plus <code>profiles</code> and <code>profile_skills</code>	TC-301 to TC-308
G-20	Full CRUD across all entities	Task 3 FR-305	TC-310 to TC-312

ID	Guide requirement	Satisfied by	Evidence
G-21	Data validation at the database level	Named constraints, including the new ones	TC-303, TC-305, TC-307, MT-03
G-22	Relationships between users, projects, and tasks	Foreign keys with delete rules	TC-320 to TC-324
G-23	Secure database configuration with no hard-coded credentials	Environment-only URLs, separate roles, TLS in production	TC-330 to TC-337
G-24	Repository includes the schema and models	Migrations, models, ERD, and data dictionary	backend/migrations/ , database/docs/

Task 4: Final application (section 06)

ID	Guide requirement	Satisfied by	Evidence
G-25	Registration, login, logout, and protected routes	Task 4 FR-401 to FR-405, and MF-01 to MF-05	TC-401 to TC-408, MT-01
G-26	Project overview, task statistics, progress, and recent activity	Task 4 FR-410	TC-420
G-27	Create, edit, delete, and view project details	Task 4 FR-411 to FR-414	TC-421
G-28	Create, assign, update status, priority, due dates, search, and filter	Task 4 FR-415 to FR-420, and the people picker MF-11	TC-422 to TC-424, MT-10
G-29	At least one AI capability in the product experience	Task generation, with prioritisation and summary; Task 4 FR-421 to FR-428	TC-430 to TC-447, docs/ai-evaluation.md
G-30	Deployed on a recommended platform	Vercel and Render from committed configuration; Task 4 FR-437 to FR-440	make smoke output, live address

Submission and repository (sections 07 and 08)

ID	Guide requirement	Satisfied by	Evidence
G-31	GitHub repository link, mandatory, for each task	A release per task tag, linked from the README	Release pages
G-32	Demo video link, mandatory	Uploaded video with a working public link	Link tested signed out
G-33	Live deployment link, optional	The Vercel address, delivered	Live address
G-34	LinkedIn post link, with Innovation Hacks tagged, mandatory	A public post tagging the official page, with its URL submitted	Post URL
G-35	README.md with installation instructions	Root README, tested from a clean clone	README.md , MT-22
G-36	Technology stack and feature list	README sections	README.md
G-37	Screenshots	docs/screenshots/task-N/ , embedded in the README	Files, MT-22
G-38	Environment variable instructions in .env.example with no real values	Placeholder-only example files	.env.example , MT-22
G-39	Demo link in the repository	Top of the README	README.md
G-40	Never upload keys, passwords, or credentials	gitleaks over files and history, ignored .env files	gitleaks report

Demo, evaluation, and guidelines (sections 09 to 12)

ID	Guide requirement	Satisfied by	Evidence
G-41	Video of 2 to 5 minutes	A script timed to 2 to 5 minutes	docs/submission/demo-script.md

ID	Guide requirement	Satisfied by	Evidence
G-42	Video shows the app end to end, main features, key technical details, and the final result	The script's four segments	Script, and the recorded video
G-43	Scored on the eight-criterion rubric	The self-review sheet from the submission standard	<code>docs/submission/self-review.md</code>
G-44	Complete tasks within the assigned deadlines	The finishing plan of section 9	Dates in the release notes
G-45	Do not copy projects from tutorials or repositories	Original code, with the libraries and sources listed	Sources section of <code>docs/how-it-works.md</code>
G-46	AI tools are allowed, but the intern must understand the implementation	Understanding notes and review questions answered by the author	<code>docs/how-it-works.md</code>
G-47	Organised repositories, no exposed credentials, functional projects	Repository checklist, gitleaks, smoke test	Checklist, gitleaks report, smoke output
G-48	Professional communication	README, post, and release notes reviewed for tone and accuracy	Review
G-49	Reward review may consider GitHub activity and timely submission	A readable commit history in logical commits, tags, and on-time submission	<code>git log</code> , tags

9. Finalization plan

The work runs in parallel where the files do not overlap: the backend fixes the contract first, the frontend and the documents follow from it, and the build then verifies everything together. The steps a machine cannot do are listed separately for the author.

Build order

Step	Work	Output	Parallel with
1. Baseline	Run the existing gates, save the results, copy <code>openapi.json</code> , and read this pack	<code>docs/baseline-final.md</code>	none
2. Backend	Migration <code>0006</code> , validators and lists, endpoints of section 5, backend tests	Green API and database tests, new <code>openapi.json</code>	Step 4
3. Frontend	Generated types, registration wizard, profile pages, editor, settings, people picker, avatar menu, screen tests	Working screens on the Compose stack	Step 4
4. Documents	README, compliance matrix, how-it-works notes, ADRs, supersession log, demo script, post draft, screenshot script, environment example	Files under <code>docs/</code> and the repository root	Steps 2 and 3
5. Integration	End-to-end journey at three viewports, accessibility, regression, <code>make guide-check</code> , <code>make gate</code>	Gate results saved to <code>docs/reports/</code>	none
6. Deploy	The author follows the release order of Task 4: migrate, then API, then frontend, then smoke test	Live addresses	none
7. Submit	Video, post, releases, and links, in the order of the submission standard	Four links per task	none

Decisions to record as ADRs

ADR	Decision	Reason
ADR-601	Scope chosen by the four-test rule of section 1	Finishes the required work first
ADR-602	Company is free text, not a shared record	Enough to display and assign, and no deduplication work
ADR-603	One privacy switch instead of per-section visibility	Small, testable, and easy to explain
ADR-604	Skills in a small table, with the limit enforced by a lock and a constraint trigger	Database-level validation without arrays
ADR-605	No email verification in this release	Avoids a new external service and secret; recorded as the first item to add
ADR-606	Discipline is separate from the platform role	Identity and permissions stay apart
ADR-607	Controlled lists live in one configuration file	The migration, API, and types cannot disagree
ADR-608	Existing users are backfilled with neutral values and legacy terms	No data loss, and honest about what is unknown

Known limitations, stated in the README

- Email addresses are not verified, and there is no password reset, because both need an email provider.
- A duplicate email is reported at registration, so the existence of an account can be learned.
- Companies are free text, and profiles are visible to signed-in members only.
- The rate limiter is per process, so one API instance runs.

Manual steps for the author, in order

1. Read the compliance matrix and mark anything that is not true yet.
2. Run the migration on the production database with the migration role, then deploy the API and then the frontend, as in Task 4 section 8.

3. Run `make smoke` , and sign in on the live site with a second browser to check the privacy switch and the password change.
4. Capture the screenshots the script cannot, and run `make ai-eval` with your own provider key.
5. Rehearse the demo once, then record it within 2 to 5 minutes, covering the application end to end, the main features, key technical details, and the final result.
6. Publish the LinkedIn post tagging the Innovation Hacks page, and copy its URL.
7. Create the release for each task, paste the four links (repository, video, live address if any, post), and reopen each from the confirmation.
8. Keep every secret in the platform dashboards and out of the repository, the screenshots, and the video.

Open items closed by the full guide. The video length is 2 to 5 minutes; the post must tag the official Innovation Hacks LinkedIn page and its URL must be submitted; and the reward review considers GitHub activity, timely submission, and professionalism, so the history should be steady and readable.

Still open. The guide gives no calendar dates, so the author must confirm each task's deadline with the organisers, since late submissions may affect evaluation. The licence is the author's choice. The guide says "every repository you submit" without saying whether that means one repository or one per task; this plan uses one repository with a release per task, and a separate repository per task can be cut from each tag if the organisers prefer.

Contact. Questions about the programme go to `contact@innovationhacks.in` , as the guide states.