Microcement cleaning & maintenance

First days care

Micro cement reaches its desired values of hardness and chemical resistance one month after applying the Sealer.

There is increased risk of damage during the first two weeks.

It is gently accessible after two days. After sealing it can normally be accessed after one week.

DAILY MAINTENANCE

For cleaning use neutral soap, never harsh detergents or descalers. Never let the soap too long on the microcement. Alkaline products such as ammonia, chlorine, bleach, detergent etc. damage the protective layer of the Microcement.

Maintenance is similar to that of a wood parquet floor. It is advisable to avoid permanent flooding and prolonged contact with moisture. You must therefore avoid wet carpets and towels on the floor or e.g. flower pots that spill water. Keep the surface free of stone or sand, which can leave scratches. Grit and dust in excess are causes of wear. It is advisable to place a doormat.

Avoid shock and friction with hard objects and dragging heavy objects to avoid damaging the surface. To move furniture "lift and drop" never drag. It is necessary to protect the floor (metal legs, sharp surfaces), furniture and objects with abrasive contact surfaces or significant weight with furniture protectors or felt. Furniture wheels must be of soft rubber which are less aggressive than the hard plastic wheels.

The greater the resistance to slipping, the more complicated cleaning is because of the textured surface, so it is important to assess what the non-slip need is on the floors. Micro deck is suitable for most cases where a class 1 is required at most. We recommend Microstone outdoors because then that can be cleaned with a high-pressure cleaner.

Periodic maintenance

We recommend the maintenance of microcement with an acrylic wax that leaves a protective layer. There is no specific machinery needed. We recommend the use of a mop for the correct application of the wax. The frequency of maintenance depends on the daily use of the floor (traffic, dust, etc. ..).

Grupo Negocios PO, S.L. / ESB97539076 / Plaza Rojas Clemente nº 17 B / 46008 Valencia - Spain / T. 00 (34) 963 925 989 / info@topciment.com

www.topciment.com