



CYBERARK®
The Identity Security Company™

PAM Administration

Privileged Session Management

Part 1



Agenda

By the end of this session, you will be able to describe the main features, architecture, and flow, as well as enable and use, the following session management solutions:

1. Privileged Session Manager (PSM)

- PSM Ad-Hoc Connections
- PSM via HTML5 Gateway
- PSM for Windows

2. PSM for SSH

Overview

Privileged Session Management Provides 3 Main Benefits:



Isolation

Separate endpoints from critical target systems to prevent lateral movement



Monitoring

Detect and track suspicious activities in privileged sessions and events in real time



Recording


Support forensic analysis and audit with detailed records of privileged activity

Privileged Session Manager

The Privileged Session Manager


When we talk about **PSM**, the **Privileged Session Manager**, we are usually referring to the **PSM** installed on a Windows server.

You can think of this as the “Universal PSM” because you can connect through it practically from any device to any device.




The Privileged Session Manager

- The **PSM** enables organizations to secure, control, and monitor privileged access to network devices
- It creates detailed session audits and video recordings of all IT administrator privileged sessions on remote machines
- Sessions on the target systems are fully isolated and the privileged account credentials are never exposed to the end-users or their client applications and devices



PSM Flow



Enable PSM: Master Policy

POLICIES

Master Policy

Policy by Platform

Access Control (Safes)

Policies > Master Policy

Master Policy

Privileged Access Workflows

Policy Rule	Value
Require dual control password access approval	Inactive
Enforce check-in/check-out exclusive access	Inactive
Enforce one-time password access	Inactive
Allow EPV transparent connections ('Click to connect')	Active
Require users to specify reason for access	Active

Password Management

Policy Rule	Value	Exceptions
Require password change every X days	60	5
Require password verification every X days	7	-

Session Management

Policy Rule	Value	Exceptions
Require privileged session monitoring and isolation	Active	-
Record and save session activity	Active	-

Audit

Policy Rule	Value	Exceptions
Activities audit retention period	90	-

Last sign in: 8/26/2021 | mike

Overview

Policy

Policy allows you to easily create a corporate level policy that aligns with business goals and manage privileged sessions across your organization.

Exceptions, you can define different policy behavior for specific platforms that require different workflows or policies to those defined in the Master Policy. The Master Policy also allows you to measure how well the corporate policy is adhered to and easily view the gaps.

To view or define the Master Policy behavior, select a policy rule to view its current related settings.

Activate Windows

Go to Settings to activate Windows.

Enable the PSM in the Master Policy for all platforms or for specific platforms by use of exceptions

CYBERARK

PSM by Platform

Platform Management

Filter

Search for target account platforms

Targets Dependents Groups Rotational Groups

44 results

Platform Name	Verify password		Change password		Reconcile password			
	Perio...	Manual	Perio...					
Windows (10)								
WIN DOM ADM 15	7 days	✓	15 days					
WIN SVR ADM 45	7 days	✓	45 days					
WIN SVR JIT	-	-	-					
WIN SVR PRV 30	7 days	✓	45 days	✓	-	✓	Approval	Provide Reason
Windows Local Accounts WMI	-	✓	-	✓	-	✓	Approval	Provide Reason
Windows Server Local Acco...	-	✓	-	✓	-	✓	Approval	Provide Reason

By default, Platforms are associated with the first installed PSM server

WIN SVR ADM 45

Search... Go

Target Account Platform

UI & Workflows

Properties

Linked Accounts

Usages

Ticketing System

Privileged Session Management

Connection Components

Automatic Password Management

General Properties

Properties

Name	Value
ID	PSMServer
SubnetPolicy	No
SessionRecorderSafe	PSMRecordings
SessionRecorderSafeRetention	180
MaxSessionDuration	-1
ShowRecordedSessionNotification	Yes
RecordedSessionNotificationDisplayTime	5
ShowLiveMonitoringNotification	Yes
LiveMonitoringNotificationDisplayTime	5
DisableDualControlForPSMConnections	No

- PSM Server
- PSM Server on COMPONENTS
- PSM Server on COMPONENTS
- PSM Server on COMPONENTS
- PSM Server on COMPONENTS
- PSM Server on COMPONENTS



PSM Connection Components

Connection Components/ Connectors

Connection Components
(aka Connectors) define the
configuration settings for using
a given third-party client to
connect to a target platform.


A few common ones are:

- SQLPlus
- RDP
- Putty
- WinSCP




Connection Components/ Connectors

- There are many connection components available out of the box
- Additional connection components can be found in the **CyberArk Marketplace**
- Organizations can also build and add custom connection components to the **PAM** solution



Platform Settings

To enable the use of a particular third-party client to connect to a given account, the appropriate **Connection Component** needs to be assigned to the **Platform** that manages that account



Importing and Managing Connectors

The new interface accelerates and simplifies **Vault** administration by allowing admins to import **PSM** connectors and link them to **Platforms**, all from one location

The screenshot displays the 'Platform Management' interface. At the top, there's a search bar labeled 'Search for target account platforms' and a 'Filter' button. On the right, there's a 'Last sign in: 8/26/2021' status and a user profile 'mike'. Below the search bar, there are tabs for 'Targets', 'Dependents', 'Groups', and 'Rotational Groups'. The 'Targets' tab is selected, showing 42 results. A table lists various platforms, including 'Windows (9)', '*NIX (4)', 'LIN KEYS 90', and 'LIN SSH 30'. A modal dialog titled 'Manage PSM connectors' is open, showing a list of connectors: PSM-SSH, PSM-WinSCP, PSMP-Rsync, PSMP-SCP, PSMP-SFTP, PSMP-SSH, and SSH. The dialog also includes a search bar, a toggle for 'Show only selected connectors (7)', and a 'Find more connectors in the CyberArk Marketplace' link. A pink box highlights the 'Manage PSM connectors' option in the 'Edit' menu of the table.

Platform Management

Last sign in: 8/26/2021 | mike

Filter Search for target account platforms Marketplace Import platform

Targets Dependents Groups Rotational Groups

42 results

Platform Name	Verify password	Change password	Reconcile password	Access workflow poli...	Edit
Windows (9)	Perio... Manual	Perio... Manual	Automatic Manual		Manage PSM connectors
*NIX (4)					Duplicate
LIN KEYS 90					Delete
LIN SSH 30					activate

Manage PSM connectors

The platform is configured to use PSM server PSM Server on COMPONENTS

Show only selected connectors (7) Search

Connector package Drag & drop or browse

PSM-SSH

PSM-WinSCP

PSMP-Rsync

PSMP-SCP

PSMP-SFTP

PSMP-SSH


SSH

Find more connectors in the CyberArk Marketplace

Cancel Save

Universal Connector

The Universal Connector framework facilitates the creation of custom connection components using a (relatively) simple, freeware programming language called AutoIT.



PSM Ad-hoc Sessions

PSM Ad-hoc Connection: Overview

With an **Ad-Hoc Connection**, users can connect securely to any machine supported by the **PSM** if they know the password

- Main use cases:
 - Connecting with accounts that are not stored in the **CyberArk Vault**
 - Connecting with personal accounts
- Provides all the benefits of **PSM**: isolation, monitoring, and recording

Accounts View

Last sign in: 8/26/2021 | mike

Filter | Search for accounts

Ad-Hoc connection | Add account |

33 results for: All accounts

Additional details & actions in classic interface

☆	Status	Username	Address	Platform ID	Safe ↑	Acce:	
☆	⚡	cybrreconcile	acme.corp	WINDOMADM15	CyberArk-Service-Acc...	-	Connect ...
☆	⚡	cybrscan	acme.corp	WINDOMADM15	CyberArk-Service-Acc...	-	Connect ...
☆	⚡	root01	10.0.0.20	LINKEYS90	Lin-Fin-US	-	Connect ...
☆	⚡	app-account01	10.0.0.20	LINSSH30	Lin-Fin-US	-	Connect ...
☆	⚡	logon01	10.0.0.20	LINSSH30	Lin-Fin-US	-	Connect ...

Enable Ad-hoc Connections

- The **PSM Secure Connect** Platform must be activated
- Privileged session monitoring and isolation must be enabled for the **PSM Secure Connect** platform. This can be done either globally or via an exception to the Master policy.

Platform Management

Last sign in: 10/24/2022 | mike

Filter Secure Connect Marketplace Import platform

Targets Dependents Groups Rotational Groups

1 results for: Secure Connect Clear all filters

Platform Name	Verify password		Change password		Reconcile password		Access workflow policies
	Perio...	Manual	Perio...	Manual	Automatic	Manual	
PSM Secure Connect (1)							
PSM Secure Connect	-	-	-	✓	-	-	Approval Provide Reason Cl ...

Launch Ad-hoc Connection

Users will need to specify all the account details when they connect:

- The **Client** they want to use on the PSM
- Target system **Address**
- Username
- Password, etc.

The screenshot displays the 'Ad-Hoc connection' interface. At the top, there is a search bar and a user profile section showing 'Last sign in: 8/26/2021' and 'mike'. Below this, there are two buttons: 'Ad-Hoc connection' (highlighted with a red box) and 'Add account'. A blue callout box points to the 'Ad-Hoc connection' button with the text '? Additional details & actions in classic interface'. The modal form titled 'Ad-Hoc connection' contains the following fields:

- PSMSecureConnect (dropdown menu)
- Client (dropdown menu, highlighted with a red box, showing 'WinSCP')
- Address (text input, highlighted with a red box, showing '10.0.0.20')
- Username (text input, highlighted with a red box, showing 'root01')
- Password (password input, highlighted with a red box, showing '*****')

At the bottom of the modal, there are 'Cancel' and 'Connect' buttons.


HTML5 Gateway

HTML5 Gateway: Overview

- Many organizations block RDP client connections from end-users' machines for security reasons or regulatory requirements.
- RDP is a Microsoft protocol, so in order to use it in Linux, Unix, or MAC environments, users must install a 3rd-party client in order to connect to the PSM.
- The HTML5 Gateway tunnels the session between the end user and the PSM proxy machine using a secure WebSocket protocol (port 443). This solution eliminates the need to open an RDP connection from the end user's machine. Instead, the end user only requires a web browser to establish a connection to a remote machine through PSM.
- Secure access through HTML5 requires integrating an HTML5 gateway on a Linux server (can be co-hosted with PSM for SSH). The Gateway is based on Apache Guacamole.




HTML5 Gateway: Flow




Enable HTML5 Gateway

The **HTML5 GW** is enabled at the system level for each **PSM** server



Use HTML5-based or RDP-file Connection Method

- Users can be given the option to connect either an HTML5-based or RDP-file connection method when connecting to the remote server
- This setting is applied at the **Connection Component** level




PSM for Windows

PSM for Windows: Overview


- Users connect directly from their desktops with an RDP-compliant client to the PSM, which then connects to the target host using the protocol appropriate to that host: SSH, RDP, etc.
- There is no need to go through the PVWA.
- Users can launch the RDP client and sign in into CyberArk using single- or multi-factor authentication (for example, LDAP with RADIUS).
 - The RDP client application must include the ability to configure run “Start Program” for the RDP connections.
 - Connections can be made from Unix / Linux / Mac / Windows end user machines.
- PSM continues to provide complete isolation of the target systems, ensuring that privileged credentials never reach users or their devices.

PSM for Windows: Flow




RDP Client Settings

- PSM IP
- Vault user
- Activate Start Program
- Program path:
 - Privileged Account name
 - Target address
 - Connection Component



The screenshot shows the 'General' tab of the RDP Client settings window. The 'Logon Settings' section is active. The 'Computer' field is set to '192.168.202.141' and is highlighted with a pink box. The 'RDP type' is set to 'Normal'. The 'Username' field is set to 'Rotem' and the 'Domain' field is set to 'cyberark', both highlighted with a pink box. The 'Port' is set to 'Default'.



The screenshot shows the 'Programs' tab of the RDP Client settings window. The 'Start a Program' section is active. The checkbox 'Start the following program on connection' is checked. The 'Program path and filename' field is set to 'psm /u admin01 /a 192.168.202.211 /c PSM-SSH' and is highlighted with a pink box. A pink arrow points to the checkbox. The 'Start in the following folder' field is empty.

Preconfigured RDP Files

You can also configure individual RDP files to connect through the **PSM**

- It is possible to configure connections with or without providing the target system details

```
full address:s:components.acme.corp
enablecredsspssupport:i:0
####
audiomode:i:0
redirectpriinters:i:1
redirectcomports:i:0
redirectsmartcards:i:1
redirectclipboard:i:1
redirectposdevices:i:0
autoconnection enabled:i:1
authentication level:i:2
prompt for credentials:i:0
negotiate security layer:i:1
remoteapplicationmode:i:0
alternate shell:s:
Shell working directory:s:
gatewayhostname:s:
gatewayusagemethod:i:4
gatewaycredentialssource:i:4
gatewayprofileusagemethod:i:0
promptcredentialonce:i:0
gatewaybrokerintype:i:0
use redirection server name:i:0
rdgiskdcproxy:i:0
kdcproxvname:s:
```

PSM Address


Target system details

```
alternate shell:s:psm /u localadmin01 /a target-win.acme.corp /c PSM-RDP
# alternate shell:s:psm
```

PSM for SSH

PSM for SSH: Overview

- The average enterprise manages hundreds of Unix servers and network devices
- Systems are usually critical, but access to them is uncontrolled
- Network and Unix teams are reluctant to change their existing workflows and tool sets
- PSM for SSH (previously PSM SSH Proxy or PSMP) is designed to provide a native Unix/Linux user experience when connecting to any SSH target system



PSM for SSH Client Settings

- The connection settings for **PSM for SSH** resemble those of **PSM for Windows**.
- Connections are not launched via the **PVWA**, but through a special connection string.

Vault user Target account Target system address PSM-SSH address

mike@logon01@10.0.0.20@10.0.30.1

logon01@target-lin:~

PS C:\Users\mike> ssh mike@logon01@10.0.0.20@10.0.30.1

Vault Password:

You are required to specify a reason for this operation:
training stuff

This session is being recorded

Last login: Mon Feb 7 09:59:27 2022 from psm-ssh-gw.acme.corp


[logon01@target-lin ~]\$ ls -al

total 48

drwx-----.	4	logon01	logon01	4096	Jan 19 13:44	.
drwxr-xr-x.	441	root	root	16384	Oct 29 2020	..
-rw-----.	1	logon01	logon01	1208	Feb 7 10:29	.bash_history
-rw-r--r--.	1	logon01	logon01	18	Jul 18 2013	.bash_logout
-rw-r--r--.	1	logon01	logon01	176	Jul 18 2013	.bash_profile
-rw-r--r--.	1	logon01	logon01	124	Jul 18 2013	.bashrc
drwxr-xr-x.	3	logon01	logon01	4096	Nov 7 09:48	.gnome2
drwxr-xr-x.	4	logon01	logon01	4096	Jul 23 2014	.mozilla
-rw-----.	1	logon01	logon01	611	Jan 19 13:44	.viminfo

[logon01@target-lin ~]\$

PSM for SSH: Flow



1. User opens SSH session to the PSM server
2. PSM retrieves privileged account password from the vault
3. Open SSH session to the target using the privileged account
4. Logs forwarded to SIEM and PTA
5. Store SSH session audit

Summary

Summary

In this session we covered the main PSM features, as well as how to enable and use:

- Privileged Session Manager (PSM)
 - PSM Connection Components
 - PSM Ad-Hoc Connections
 - PSM via HTML5 Gateway
 - PSM for Windows
- PSM for SSH

Additional Resources



HTML5 Based Remote Access

<https://training.cyberark.com/elearning/html5-based-remote-access>

Note: You must be logged into the CyberArk training portal to access this material

You may now complete the following exercises:

Privileged Session Management – Part 1

- Remove Privileged Access Workflows Exceptions
- Disabling the PSM Globally
- Privileged Session Manager
 - Adding Exceptions
 - Connect with a Linux Account
 - Connect with an Oracle Account
 - Connect via HTML5 Gateway
 - Connect using PSM Ad-Hoc Connection
- Privileged Session Manager for Windows
 - Connect using RDP file without providing the target system details
 - Connect using RDP file with the target system details
- Privileged Session Manager for SSH