



The classy  $Pro-Max^{\circ}$  combines great looks and great strength with a rugged durability.



The Underbody Hoist is a solid design Class 60 Series, that combines solid reliability with superior load lifting power. The 1/4" trapezoidal longitudinals support the 1/4" crossmemberless floor.



The exceptional durability of the *Pro-Max*® is enhanced by the standard 6-panel tailgate, full depth rear corner posts, and fully enclosed front posts.

## **Features**

- The Pro-Max® body features a modern new styled body with a classy look and superior strength and durability.
- The crossmemberless design and trapezoidal longitudinals allow for efficient and low maintenance operation.
- The Pro-Max® body was designed to easily shed misplaced loaded dirt with its dirt shedding top rail, rub rail and rear corner posts.
- The 1/4" floor provides exceptional durability and is available in AR-400 steel and 304 stainless steel.
- The high capacity Underbody Hoist with 8" lift cylinder provides ample load lifting for the heaviest of loads.
- The standard rugged 6 panel tailgate is double acting and includes flush mounted upper tailgate hinges.

## **Body Specifications**

MODEL	BODY LENGTH	SIDE HEIGHT	STRUCK CAPACITY	BODY CONSTRUCTION	HOIST
PMX-10	10'	28"	6 YARDS	CARBON STEEL	21 TON
PMX-10-SS	10'	28"	6 YARDS	304 STAINLESS STEEL	21 TON

Hoist Specifications	
NTEA class	60
Cylinder bore & stroke	8" x 24 7/8"
Chromed cylinder rod	2 3/4"
Max. operating pressure	2000 PSI
Weight with subframe	1000 lbs.

CAUTION: The combined weights of the truck chassis, hoist, body, and cargo must not exceed the gross vehicle rating of the truck.

Air-Flo® Manufacturing reserves the right to change design specifications and furnish products so altered without prior notice.



## **Air-Flo Manufacturing**

365 Upper Oakwood Ave. Elmira Heights, NY 14903 phone: (607) 733-8284

fax: (607) 733-8379 website: www.air-flo.com