



The classy $Pro-Max^{\circ}$ combines great looks and great strength with a rugged durability.



The Underbody Hoist is a solid design Class 50 Series, that combines solid reliability with superior load lifting power. The 1/4" trapezoidal longitudinals support the 1/4" crossmemberless floor.



The exceptional durability of the $Pro-Max^{\circ}$ is enhanced by the standard 6-panel tailgate, full depth rear corner posts, and fully enclosed front posts.

Features

- The Pro-Max® body features a modern new styled body with a classy look and superior strength and durability.
- The crossmemberless design and trapezoidal longitudinals allow for efficient and low maintenance operation.
- The Pro-Max® body was designed to easily shed misplaced loaded dirt with its dirt shedding top rail, rub rail and rear corner posts.
- The 1/4" floor provides exceptional durability and is available in AR-400 steel and 304 stainless steel.
- The high capacity Underbody Hoist with 8" lift cylinder provides ample load lifting for the heaviest of loads.
- The standard rugged 6 panel tailgate is double acting and includes flush mounted upper tailgate hinges.

Body S	ody Specifications					
Body Length	Side Height	Struck Capacity	Model	Hoist Capacity	Weight	
10'	26"	5.5 Yd.	PMX-10-5	17 Ton	2700 lbs.	
10'	30"	6.4 Yd.	PMX-10-6	17 Ton	2800 lbs.	

Hoist Specifications				
50				
8" x 21"				
2 1/4"				
1500 PSI				
1000 lbs.				

<u>CAUTION</u>: The combined weights of the truck chassis, hoist, body, and cargo must not exceed the gross vehicle rating of the truck.

Air-Flo® Manufacturing reserves the right to change design specifications and furnish products so altered without prior notice.



Air-Flo Manufacturing

40 S. Main Street, Prattsburgh, NY 14873

phone: 607.522.3574 fax: 607.522.4412 www.Air-Flo.com