

Lecture 7. Multilayer Perceptron. Backpropagation

COMP90051 Statistical Machine Learning

Semester 2, 2018
Lecturer: Ben Rubinstein





Copyright: University of Melbourne

This lecture

- Multilayer perceptron
 - * Model structure
 - * Universal approximation
 - * Training preliminaries
- Backpropagation
 - * Step-by-step derivation
 - * Notes on regularisation

Animals in the zoo



art: OpenClipartVectors
at pixabay.com (CC0)




- Recurrent neural networks are not covered in this subject
- An autoencoder is an ANN trained in a specific way.
 - * E.g., a multilayer perceptron can be trained as an autoencoder, or a recurrent neural network can be trained as an autoencoder.

Multilayer Perceptron

Modelling non-linearity via
function composition

Limitations of linear models

Some problems are linearly separable, but many are not



Possible solution: **composition**

$$x_1 \text{ XOR } x_2 = (x_1 \text{ OR } x_2) \text{ AND not}(x_1 \text{ AND } x_2)$$

We are going to compose perceptrons ...

Perceptron is *sort of* a building block for ANN

- ANNs are not restricted to binary classification
- Nodes in ANN can have various **activation functions**


Step function $f(s) = \begin{cases} 1, & \text{if } s \geq 0 \\ 0, & \text{if } s < 0 \end{cases}$

Sign function $f(s) = \begin{cases} 1, & \text{if } s \geq 0 \\ -1, & \text{if } s < 0 \end{cases}$


Logistic function $f(s) = \frac{1}{1 + e^{-s}}$

Many others: *tanh*, rectifier, etc.

Feed-forward Artificial Neural Network



ANN as function composition



$$u_j = g(r_j)$$

$$r_j = v_{0j} + \sum_{i=1}^m x_i v_{ij}$$

here g, h are activation functions. These can be either same (e.g., both sigmoid) or different

$$z_k = h(s_k)$$

$$s_k = w_{0k} + \sum_{j=1}^p u_j w_{jk}$$

note that z_k is a **function composition** (a function applied to the result of another function, etc.)

you can add **bias node** $x_0 = 1$ to simplify equations: $r_j = \sum_{i=0}^m x_i v_{ij}$



similarly you can add bias node $u_0 = 1$ to simplify equations: $s_k = \sum_{j=0}^p u_j w_{jk}$

ANN in supervised learning

- ANNs can be naturally adapted to various supervised learning setups, such as univariate and multivariate regression, as well as binary and multilabel classification
- Univariate regression $y = f(x)$
 - * e.g., linear regression earlier in the course
- Multivariate regression $\mathbf{y} = f(\mathbf{x})$
 - * predicting values for multiple continuous outcomes
- Binary classification
 - * e.g., predict whether a patient has type II diabetes
- Multivariate classification
 - * e.g., handwritten digits recognition with labels “1”, “2”, etc.


The power of ANN as a non-linear model

- ANNs are capable of approximating plethora non-linear functions, e.g., $z(x) = x^2$ and $z(x) = \sin x$
- For example, consider the following network. In this example, hidden unit activation functions are tanh



The power of ANN as a non-linear model

- ANNs are capable of approximating various non-linear functions, e.g., $z(x) = x^2$ and $z(x) = \sin x$



- Universal approximation theorem** (Cybenko 1989): An ANN with a hidden layer with a finite number of units, and mild assumptions on the activation function, can approximate continuous functions on compact subsets of \mathbf{R}^n arbitrarily well

How to train your ~~dragon~~ network?

- You know the drill: Define the loss function and find parameters that minimise the loss on training data




Adapted from Movie Poster from
Flickr user jdxw (CC BY-SA 2.0)

- In the following, we are going to use **stochastic gradient descent** with a **batch size** of one. That is, we will process training examples one by one

Training setup: univariate regression

- Consider regression
- Moreover, we'll use identity output activation function
 $z = h(s) = s = \sum_{j=0}^p u_j w_j$
- This will simplify description of backpropagation. In other settings, the training procedure is similar




Training setup: univariate regression

How many parameters does this ANN have? Assume there are bias nodes x_0, u_0 .

$$mp + (p + 1)$$

$$(m + 2)p + 1$$

$$(m + 1)p$$



Loss function for ANN training

- Need **loss** between training example $\{\mathbf{x}, y\}$ & prediction $\hat{f}(\mathbf{x}, \boldsymbol{\theta}) = z$, where $\boldsymbol{\theta}$ is parameter vector of v_{ij} and w_j

- As regression, can use **squared error**

$$L = \frac{1}{2} (\hat{f}(\mathbf{x}, \boldsymbol{\theta}) - y)^2 = \frac{1}{2} (z - y)^2$$

(the constant is used for mathematical convenience, see later)

- **Decision-theoretic** training: minimise L w.r.t $\boldsymbol{\theta}$
 - * Fortunately $L(\boldsymbol{\theta})$ is differentiable
 - * Unfortunately no analytic solution in general

Stochastic gradient descent for ANN

Choose initial guess $\theta^{(0)}$, $k = 0$

Here θ is a set of all weights form all layers

For i from 1 to T (epochs)

For j from 1 to N (training examples)

Consider example $\{x_j, y_j\}$

Update: $\theta^{(i+1)} = \theta^{(i)} - \eta \nabla L(\theta^{(i)})$

$$L = \frac{1}{2} (z_j - y_j)^2$$

Need to compute partial derivatives $\frac{\partial L}{\partial v_{ij}}$ and $\frac{\partial L}{\partial w_j}$

Backpropagation

= “backward propagation of errors”

Calculating the gradient
of loss of a composition

Backpropagation: start with the chain rule

- Recall that the output z of an ANN is a function composition, and hence $L(z)$ is also a composition


$$* \quad L = 0.5(z - y)^2 = 0.5(h(s) - y)^2 = 0.5(s - y)^2$$

$$* \quad = 0.5 \left(\sum_{j=0}^p u_j w_j - y \right)^2 = 0.5 \left(\sum_{j=0}^p g(r_j) w_j - y \right)^2 = \dots$$

- Backpropagation makes use of this fact by applying the **chain rule** for derivatives

$$\bullet \quad \frac{\partial L}{\partial w_j} = \frac{\partial L}{\partial z} \frac{\partial z}{\partial s} \frac{\partial s}{\partial w_j}$$

$$\bullet \quad \frac{\partial L}{\partial v_{ij}} = \frac{\partial L}{\partial z} \frac{\partial z}{\partial s} \frac{\partial s}{\partial u_j} \frac{\partial u_j}{\partial r_j} \frac{\partial r_j}{\partial v_{ij}}$$




Backpropagation: intermediate step

- Apply the chain rule

- $\frac{\partial L}{\partial w_j} = \frac{\partial L}{\partial z} \frac{\partial z}{\partial s} \frac{\partial s}{\partial w_j}$

- $\frac{\partial L}{\partial v_{ij}} = \frac{\partial L}{\partial z} \frac{\partial z}{\partial s} \frac{\partial s}{\partial u_j} \frac{\partial u_j}{\partial r_j} \frac{\partial r_j}{\partial v_{ij}}$



- Now define

$$\delta \equiv \frac{\partial L}{\partial s} = \frac{\partial L}{\partial z} \frac{\partial z}{\partial s}$$

$$\varepsilon_j \equiv \frac{\partial L}{\partial r_j} = \frac{\partial L}{\partial z} \frac{\partial z}{\partial s} \frac{\partial s}{\partial u_j} \frac{\partial u_j}{\partial r_j}$$

- Here $L = 0.5(z - y)^2$ and $z = s$

Thus $\delta = (z - y)$

- Here $s = \sum_{j=0}^p u_j w_j$ and $u_j = h(r_j)$

Thus $\varepsilon_j = \delta w_j h'(r_j)$

Backpropagation equations

- We have

$$* \frac{\partial L}{\partial w_j} = \delta \frac{\partial s}{\partial w_j}$$

$$* \frac{\partial L}{\partial v_{ij}} = \varepsilon_j \frac{\partial r_j}{\partial v_{ij}}$$

... where

$$* \delta = \frac{\partial L}{\partial s} = (z - y)$$

$$* \varepsilon_j = \frac{\partial L}{\partial r_j} = \delta w_j h'(r_j)$$

- Recall that

$$* s = \sum_{j=0}^p u_j w_j$$


$$* r_j = \sum_{i=0}^m x_i v_{ij}$$

- So $\frac{\partial s}{\partial w_j} = u_j$ and $\frac{\partial r_j}{\partial v_{ij}} = x_i$

- We have

$$* \frac{\partial L}{\partial w_j} = \delta u_j = (z - y) u_j$$

$$* \frac{\partial L}{\partial v_{ij}} = \varepsilon_j x_i = \delta w_j h'(r_j) x_i$$




Forward propagation

- Use current estimates of v_{ij} and w_j



- Calculate r_j , u_j , s and z




- Backpropagation equations

- * $\frac{\partial L}{\partial w_j} = \delta u_j = (z - y)u_j$

- * $\frac{\partial L}{\partial v_{ij}} = \varepsilon_j x_i = \delta w_j h'(r_j) x_i$

Backward propagation of errors

$$\frac{\partial L}{\partial v_{ij}} = \varepsilon_j x_i \quad \leftarrow \quad \varepsilon_j = \delta w_j h'(r_j) \quad \leftarrow \quad \frac{\partial L}{\partial w_j} = \delta u_j \quad \leftarrow \quad \delta = (z - y)$$




- Backpropagation equations

- $$\frac{\partial L}{\partial w_j} = \delta u_j = (z - y)u_j$$

- $$\frac{\partial L}{\partial v_{ij}} = \varepsilon_j x_i = \delta w_j h'(r_j) x_i$$

Some further notes on ANN training

- ANN's are flexible (recall universal approximation theorem), but the flipside is over-parameterisation, hence tendency to **overfitting**
- Starting weights usually random distributed about zero
- Implicit regularisation:
early stopping
 - * With some activation functions, this shrinks the ANN towards a linear model (why?)



Explicit regularisation

- Alternatively, an explicit **regularisation** can be used, much like in ridge regression
- Instead of minimising the loss L , minimise regularised function $L + \lambda \left(\sum_{i=0}^m \sum_{j=1}^p v_{ij}^2 + \sum_{j=0}^p w_j^2 \right)$
- This will simply add $2\lambda v_{ij}$ and $2\lambda w_j$ terms to the partial derivatives
- With some activation functions this also shrinks the ANN towards a linear model

This lecture

- Multilayer perceptron
 - * Model structure
 - * Universal approximation
 - * Training preliminaries
- Backpropagation
 - * Step-by-step derivation
 - * Notes on regularisation
- Next lecture: DNNs, CNNs, autoencoders