

A7 Pointer Syntax Analysis

Contents

A7 Pointer Syntax Analysis & Language Comparison	1
Table of Contents	1
Current Language Implementations	1
A7 Current Syntax	6
Proposed A7 Alternatives	7
Comparative Analysis	8
Recommendations	9

A7 Pointer Syntax Analysis & Language Comparison

Table of Contents

1. [Current Language Implementations](#)
2. [A7 Current Syntax](#)
3. [Proposed A7 Alternatives](#)
4. [Comparative Analysis](#)
5. [Recommendations](#)

Current Language Implementations

C

```
int x = 42;
int *ptr = &x;           // Address-of: & prefix
int value = *ptr;        // Dereference: * prefix
*ptr = 100;              // Assignment through pointer
int **pp = &ptr;         // Pointer to pointer
int v = **pp;            // Multiple dereference

// Struct pointers
struct Point *p = &point;
p->x = 10;                // Arrow operator for struct field access
(*p).x = 10;             // Equivalent explicit dereference
```

C++

```
int x = 42;
int *ptr = &x;           // Same as C for raw pointers
int &ref = x;            // References (no explicit deref needed)
ref = 100;               // Direct assignment through reference

// Smart pointers
```

```

std::unique_ptr<int> smart = std::make_unique<int>(42);
*smart = 100;           // Dereference like raw pointer
int val = *smart;       // Same dereference syntax

// Pointer to member
auto memptr = &Class::member;
obj.*memptr = 42;       // .* operator
ptr->*memptr = 42;       // ->* operator

```

Rust

```

let x = 42;
let ptr = &x;           // Immutable reference
let mut_ptr = &mut x;   // Mutable reference
let value = *ptr;       // Explicit dereference
*mut_ptr = 100;         // Assignment needs mutable ref

// Raw pointers (unsafe)
let raw_ptr = &x as *const i32;
let mut_raw = &mut x as *mut i32;
unsafe {
    let val = *raw_ptr; // Must be in unsafe block
    *mut_raw = 100;
}

// Auto-deref for method calls
let vec = vec![1, 2, 3];
let vec_ref = &vec;
vec_ref.len();          // Auto-deref for methods

// Box (heap allocation)
let boxed = Box::new(42);
let val = *boxed;       // Deref trait

```

Zig

```

const x: i32 = 42;
const ptr = &x;         // Address-of: & prefix
const value = ptr.*;     // Dereference: .* postfix
ptr.* = 100;            // Assignment through pointer

// Optional pointers
const maybe_ptr: ?*i32 = &x;
if (maybe_ptr) |p| {
    p.* = 100;          // Unwrap and dereference
}

// Struct pointers
const point_ptr = &point;
point_ptr.x = 10;       // Auto-deref for field access
point_ptr.*.x = 10;     // Explicit dereference also works

// Multi-pointers (slices)
const array = [_]i32{1, 2, 3};

```

```
const slice: []const i32 = &array;
const first = slice[0]; // No explicit deref needed
```

Odin

```
x := 42
ptr := &x           // Address-of: & prefix
value := ptr^        // Dereference: ^ postfix
ptr^ = 100           // Assignment through pointer
```

```
// Raw pointers
raw_ptr := rawptr(&x)
int_ptr := cast(^int)raw_ptr
int_ptr^ = 100
```

```
// Struct pointers
point_ptr := &point
point_ptr.x = 10    // Auto-deref for fields
point_ptr^.x = 10    // Explicit also works
```

```
// Multi-level
pp := &ptr           // Pointer to pointer
pp^^ = 100           // Double dereference
```

```
// Slices (fat pointers)
array := [3]int{1, 2, 3}
slice := array[:]    // Slice of array
first := slice[0]    // No deref needed
```

Jai

```
x := 42;
ptr := *x;           // Address-of: * prefix (unusual!)
value := <<ptr;       // Dereference: << prefix
<<<ptr = 100;         // Assignment through pointer
```

```
// Struct pointers
point_ptr := *point;
point_ptr.x = 10;    // Auto-deref for fields
(<<point_ptr).x = 10; // Explicit dereference
```

```
// Multiple indirection
pp := *ptr;
<<(<<pp) = 100;      // Double dereference
```

```
// Context-sensitive
ptr: *int = *x;      // Type determines operation
```

Go

```
x := 42
ptr := &x           // Address-of: & prefix
value := *ptr        // Dereference: * prefix
*ptr = 100           // Assignment through pointer
```

```

// No pointer arithmetic
// ptr++ // Not allowed!

// Struct pointers
type Point struct { X, Y int }
point := Point{10, 20}
ptr := &point
ptr.X = 30           // Auto-deref for fields
(*ptr).X = 30        // Explicit also works

// Interfaces hide pointers
var iface interface{} = &x // Pointer stored
// But no explicit deref needed in most cases

```

Swift

```

// Swift mostly hides pointers, but has unsafe variants
var x = 42

// Unsafe pointers
let ptr = withUnsafePointer(to: &x) { $0 }
let value = ptr.pointee // Dereference via property
ptr.pointee = 100        // Assignment (if mutable)

// Unsafe mutable pointer
withUnsafeMutablePointer(to: &x) { ptr in
    ptr.pointee = 100
}

// Class references (implicit pointers)
class MyClass { var value = 42 }
let obj = MyClass() // Reference type
obj.value = 100      // No explicit deref

```

D

```

int x = 42;
int* ptr = &x; // Address-of: & prefix
int value = *ptr; // Dereference: * prefix
*ptr = 100; // Assignment

// Ref parameters (like C++ references)
void func(ref int x) {
    x = 100; // No explicit deref
}

// Pointer properties
ptr.sizeof // Size of pointer
ptr.init // Initial value

// Struct pointers
Point* p = &point;
p.x = 10; // Auto-deref for fields
(*p).x = 10; // Explicit also works

```

Nim

```
var x = 42
var ptr = addr x      # Address-of: addr keyword
var value = ptr[]      # Dereference: [] postfix
ptr[] = 100           # Assignment

# Alternative syntax
var p = x.addr        # Method style
var v = p[]           # Still [] for deref

# Ref types (managed pointers)
type Node = ref object
  value: int
  next: Node

var node = Node(value: 42)
node.value = 100      # Auto-deref for ref types
```

V

```
x := 42
ptr := &x             // Address-of: & prefix
value := *ptr         // Dereference: * prefix
*ptr = 100            // Assignment (unsafe)

// Safe references
mut y := 42
mut ref := &y         // Mutable reference
unsafe {
  *ref = 100          // Must be in unsafe block
}

// Struct pointers
point_ptr := &point
point_ptr.x = 10      // Auto-deref for fields
```

Carbon

```
var x: i32 = 42;
let ptr: i32* = &x;    // Address-of: & prefix
let value: i32 = *ptr; // Dereference: * prefix
*ptr = 100;           // Assignment

// Struct pointers
var point: Point = {.x = 10, .y = 20};
let p: Point* = &point;
p->x = 30;             // Arrow operator
(*p).x = 30;          // Explicit deref
```

Pascal/Delphi

```
var
  x: Integer = 42;
  ptr: ^Integer; // Pointer type: ^ prefix
```

```

value: Integer;

begin
  ptr := @x;           // Address-of: @ prefix
  value := ptr^;       // Dereference: ^ postfix
  ptr^ := 100;         // Assignment

  // Record pointers
  recordPtr^.field := 10; // Deref then field
end;

```

Ada

```

X : Integer := 42;
type Int_Ptr is access Integer;
Ptr : Int_Ptr := X'Access;    -- Address-of: 'Access attribute
Value : Integer := Ptr.all;   -- Dereference: .all suffix
Ptr.all := 100;               -- Assignment

-- Record pointers
type Point_Ptr is access Point;
P : Point_Ptr := new Point;
P.X := 10;                  -- Auto-deref for fields
P.all.X := 10;              -- Explicit deref

```

Modula-2

```

VAR
  x: INTEGER = 42;
  ptr: POINTER TO INTEGER;
  value: INTEGER;

ptr := ADR(x);      (* Address-of: ADR function *)
value := ptr^;      (* Dereference: ^ postfix *)
ptr^ := 100;        (* Assignment *)

(* Record pointers *)
recordPtr^.field := 10; (* Deref then field *)

```

A7 Current Syntax

```

// Property-based approach (current implementation)
x := 42
ptr: ref i32 = x.adr    // Address-of: .adr property
value := ptr.val        // Dereference: .val property
ptr.val = 100           // Assignment through pointer

// Multiple indirection
ptr_ptr: ref ref i32 = ptr.adr
value := ptr_ptr.val.val // Chain dereferences

// Struct pointers
Point :: struct {
  x: f32
  y: f32
}

```

```

}
point := Point{3.14, 2.71}
point_ptr: ref Point = point.adr
point_ptr.val.x = 10.0    // Explicit deref for field access

// In functions
swap :: fn(a: ref $T, b: ref $T) {
    temp := a.val
    a.val = b.val
    b.val = temp
}

// Usage
swap(x.adr, y.adr)      // Pass addresses explicitly

```

Proposed A7 Alternatives

Option 1: Traditional with Twist (C-like)

```

// Similar to C but cleaner
ptr := &x                // Address-of
value := *ptr             // Dereference
*ptr = 100                // Assignment
**ptr_ptr = 100           // Multiple deref

// Auto-deref for struct fields (like Go/Zig)
point_ptr.x = 10          // No arrow operator needed

```

Option 2: Postfix Style (Odin-inspired)

```

// Postfix operators for left-to-right reading
ptr := x&                 // Address-of (or &x)
value := ptr^             // Dereference
ptr^ = 100                // Assignment
ptr^^ = 100               // Multiple deref

// Struct access
point_ptr^.x = 10         // Explicit deref
point_ptr.x = 10          // Auto-deref option

```

Option 3: Zig-inspired (.* operator)

```

// Zig's approach - consistent and clear
ptr := &x                 // Address-of
value := ptr.*            // Dereference
ptr.* = 100               // Assignment
ptr.*.* = 100             // Multiple deref

// Struct access
point_ptr.x = 10          // Auto-deref for fields
point_ptr.*.x = 10        // Explicit also works

```

Option 4: Keyword-based (Ada/Nim-inspired)

```

// Keywords for clarity
ptr := addr x              // or x.addr

```

```
value := ptr.deref    // or deref(ptr)
ptr.deref = 100      // Assignment
```

```
// Alternative keywords
ptr := ref x          // Take reference
value := val ptr      // Get value
```

Option 5: Symbol Minimalism

```
// Single symbol, position matters
ptr := @x             // Address-of (like Pascal)
value := ^ptr         // Dereference (like Pascal postfix but prefix)
^ptr = 100            // Assignment
^^ptr_ptr = 100      // Multiple deref
```

Option 6: Unified Property Access

```
// Everything through dot notation (current)
ptr := x.ref          // or x.adr (current)
value := ptr.val      // or ptr.deref
ptr.val = 100         // Assignment

// Shorter variants
ptr := x.&            // Property-like operator
value := ptr.*        // Consistent with member pointer
```

Option 7: Context-Sensitive (Rust-inspired)

```
// Type system handles most cases
ptr: ref i32 = x      // Auto-address when needed
value: i32 = ptr      // Auto-deref when needed
ptr = 100             // Auto-deref for assignment

// Explicit when necessary
ptr := &x            // Force address-of
value := *ptr        // Force dereference
```

Option 8: Pipeline/Method Style

```
// Method chaining approach
ptr := x.to_ref()     // Take reference
value := ptr.deref()  // Dereference
ptr.set(100)          // Set value

// Or with operators
ptr := x |> ref        // Pipeline to ref
value := ptr |> val    // Pipeline to value
```

Comparative Analysis

Readability Comparison

C/C++:	value = **ptr;	// Prefix stacking
Rust:	value = **ptr;	// Same as C
Zig:	value = ptr.*.*;	// Postfix chaining
Odin:	value = ptr^^;	// Postfix stacking


```

Jai:      value = <<(<<ptr);      // Verbose prefix
Go:       value = **ptr;           // C-style
A7 (current): value = ptr.val.val;  // Property chaining
A7 (option2): value = ptr^^;       // Postfix stacking
A7 (option3): value = ptr.*.*;     // Zig-style

```

Feature Matrix

Language	Address-of	Dereference	Auto-deref fields	Null safety	Arithmetic
C	&x	*ptr	No (-> needed)	No	Yes
C++	&x	*ptr	No (-> needed)	No	Yes
Rust	&x	*ptr	Yes	Yes	No (unsafe)
Zig	&x	ptr.*	Yes	Optional	Yes
Odin	&x	ptr^	Yes	No	Yes
Jai	*x	<<ptr	Yes	No	Yes
Go	&x	*ptr	Yes	No	No
Swift	&x	.pointee	N/A	Yes	Limited
D	&x	*ptr	Yes	No	Yes
Nim	addr x	ptr[]	Yes (ref types)	Yes (ref)	Yes
V	&x	*ptr	Yes	Yes	No (unsafe)
A7 (cur)	x.adr	ptr.val	No	Yes	TBD

Beginner Friendliness Ranking

1. **A7 (current)** - .adr/.val are self-documenting
2. **Ada/Nim** - Keywords are clear
3. **Swift** - .pointee is descriptive
4. **Zig** - .* is learnable, consistent
5. **Odin** - ^ is simple once learned
6. **Go/C/Rust** - &/* are cryptic initially
7. **Jai** - << is unusual

Consistency Analysis

Most Consistent: - Zig: Always & for address, .* for deref - Odin: Always & for address, ^ for deref - A7 (current): Always .adr for address, .val for deref

Least Consistent: - C/C++: -> vs . for struct access - Jai: Unusual * for address-of - Swift: Different APIs for different pointer types

Recommendations

For A7, considering the design goals:

Best Option: Hybrid Approach

```

// Primary syntax (simple, familiar)
ptr := &x           // Like C/Rust/Zig/Go (familiar)
value := ptr^       // Like Odin (clear, postfix)
ptr^ = 100          // Assignment

```

```

// Auto-deref for struct fields (like Zig/Go)
point_ptr.x = 10    // Automatic for field access

```

// Property syntax still available for clarity

```

ptr := x.adr      // When being explicit
value := ptr.val  // When being explicit

// Multiple approaches coexist
fn process(x: i32) {
    p1 := &x      // Quick syntax
    p2 := x.adr   // Explicit syntax

    v1 := p1^     // Quick deref
    v2 := p2.val  // Explicit deref
}

```

Why This Works:

1. **Familiarity:** `&` is recognized by most programmers
2. **Readability:** `ptr^` reads as “pointer’s value”
3. **Consistency:** No special arrow operator needed
4. **Flexibility:** Property syntax remains for teaching/clarity
5. **Modern:** Auto-deref for fields like modern languages

Alternative Recommendation: Pure Zig-style

```

ptr := &x          // Universal address-of
value := ptr.*     // Clear dereference
ptr.* = 100        // Consistent assignment
ptr.*.* = 100      // Chainable
point_ptr.x = 10   // Auto-deref for fields

```

Benefits: - Proven design (Zig is well-regarded) - Clear distinction from multiplication - Consistent and predictable - Works well with method syntax

Final Rankings

For Beginners: 1. Current A7 (`.adr/.val`) 2. Keywords (`addr/deref`) 3. Zig-style (`&/.*`)

For Experienced Developers: 1. Odin-style (`&/^`) 2. Zig-style (`&/.*`) 3. Traditional (`&/*`)

For Language Consistency: 1. Current A7 (all properties) 2. Zig-style (operator pairs) 3. Odin-style (operator pairs)

Overall Best: - **Hybrid:** Support both `&x/ptr^` AND `x.adr/ptr.val` - Let users choose based on context and preference - Auto-deref for struct field access regardless