

Content Items

There two endpoints: "List Content Items" and "Search Content Items". They are designed to be used in different scenarios. If you want to sync content from Shelf into your database - "List CIL Content API" is the right choice.

Search CIL Content API

- **Search event submission:** When using the Search API, a search event is submitted, which is then processed by the Content Insights pipeline. This could be useful for tracking and analyzing user search behavior over time.
- **Appear on Search Queries reports:** The data from the search event will eventually appear on Search Queries reports, providing insights into the types of queries that users are performing.
- **Vector search:** It applies vector search to find the most relevant content items based on the search term.

List CIL Content API

- **Data listing without search events:** This API lists CIL content items without creating a search event or contributing to the Content Insights pipeline.
- **No `searchResultsUrl`:** The response from the List API does not include a `searchResultsUrl`, which would otherwise be used to link directly to the search results.
- **Paginate over content items:** It's designed to paginate over content items rather than perform a relevance-based search.

So, to decide which API to use, consider whether you need insights and tracking of user search behavior (use the "Search CIL Content API") or whether you simply need to list content items without additional analytics (use the "List CIL Content API").

Pagination Mechanics

1. **Initial Request:** The initial API request includes a pagination parameter `size`, which defines the number of items to be returned in a single response. Additionally, clients can specify a `from` parameter to skip a certain number of items from the start, effectively controlling the starting point of the data retrieval.
2. **Iterative Pagination:** To navigate through the content items, the API uses a `nextToken` parameter. After the initial request, the API response includes a `nextToken` value, which is a unique identifier for the next page of results.
3. **Subsequent Requests:** For subsequent requests, clients include this `nextToken` in their request to retrieve the next set of items. This token ensures that each request fetches a new page of results, starting exactly where the last one ended.
4. **Page Info:** Each response also contains a `pageInfo` object, providing metadata about the pagination state. This includes information like `currentPage`, `hasNextPage`, `totalPages`, and `totalResultsCount`, giving a comprehensive overview of the pagination context.
5. **Efficient Data Retrieval:** This pagination system allows for efficient data retrieval, especially in scenarios where the total number of content items is large. Clients can systematically fetch all items in a controlled and manageable manner.

Get Content Item Custom Fields

GET `https://api.shelf.io` `/cil-content/items/{id}/fields`

Used to get the custom fields of a content item.

Authorizations

auth_token ▾

Authorization string required

Shelf API Token. See [Create API Token](#) for more details.

Path parameters

id string · min: 1 · max: 64 required

Content Item ID

Example: `66ad5df9-7884-4061-a8cd-eff6572268c7`

Responses

▾	200 Success	application/json
	Response object	+
>	400 Bad Request	application/json
>	404 Not Found	application/json

GET `/cil-content/items/{id}/fields`

HTTP ▾

```
GET /cil-content/items/{id}/fields HTTP/1.1
Host: api.shelf.io
Authorization: YOUR_API_KEY
Accept: */*
```

Test it ►

200 Success ▾

```
[
  {
    "type": "string",
    "key": "key1",
    "label": "String Field",
    "value": "Custom value"
  },
  {
    "type": "number",
    "key": "key2",
    "label": "Number Field",
    "value": 10
  },
  {
    "type": "boolean",
    "key": "key3",
    "label": "Boolean Field",
    "value": true
  },
  {
    "type": "string-set",
    "key": "key4",
    "label": "Array Field",
    "value": [
      "foo",
      "bar",
      "baz"
    ]
  }
]
```

List Content Items

POST `https://api.shelf.io` `/cil-content/items/list`

Used to list and paginate over CIL content items. Does not apply vector search. Useful to pull content synced from various sources via a single API.

Permissions: users will be able to search only across collections they have access to.

Authorizations

auth_token ▾

Authorization string required

Shelf API Token. See [Create API Token](#) for more details.

Body

application/json ▾

object optional

+

Responses

▾ **200** Page of CIL Items

application/json

Response object

+

> **400** Bad Request

application/json

> **403** Forbidden

application/json

POST `/cil-content/items/list`

HTTP ▾



```
POST /cil-content/items/list HTTP/1.1
Host: api.shelf.io
Authorization: YOUR_API_KEY
Content-Type: application/json
Accept: */*
Content-Length: 1191
```

```
{
  "fieldsFilters": {
    "type": [
      "text"
    ],
    "contentType": [
      "01G7EE3DXZT6V0XN5QMFJZ1AA"
    ],
    "ownerId": [
      "John Doe"
    ],
    "ratingMoreThan": [
      3
    ],
    "shelf_categoryId": [
      "setId#default#categoryId#01GCV9CN566439HHEQBYF34XBR"
    ],
    "shelf_categoryIdToExclude": [
      "setId#default#categoryId#01GCV9CN566439HHEQBYF34XBR"
    ],
    "shelf_categoryOp": "and",
    "shelf_reviewStatus": [
      "un-to-date"
    ]
  }
}
```

200 Page of CIL Items ▾




```
{
  "pageInfo": {
    "currentPage": 1,
    "hasNextPage": true,
    "hasPreviousPage": false,
    "pageSize": 1000,
    "totalPages": 100,
    "totalResultsCount": 10000,
    "nextToken": "text"
  },
  "items": [
    {
      "accountId": "50018985-7134-41fd-96db-9e596488f6a6",
      "collectionIds": [
        "1234567890"
      ],
      "connectorId": "default-zendesk",
      "createdAt": "2022-08-26",
      "externalId": "8149140753169",
      "externalURL": "https://test.zendesk.com/hc/en-us/articles/8149140753169-new-item",
      "fields": [
        {
          "name": "title",
          "value": "New Item Title"
        },
        {
          "name": "description",
          "value": "New Item Description"
        },
        {
          "name": "status",
          "value": "Open"
        },
        {
          "name": "priority",
          "value": "High"
        },
        {
          "name": "category",
          "value": "General Inquiry"
        },
        {
          "name": "tags",
          "value": "tag1,tag2,tag3"
        }
      ]
    }
  ]
}
```

List Content Items with Content Review CSV

POST`https://api.shelf.io` `/cil-content/items/list/csv`

Used to get CSV with CIL content items with their Content Review info. Search parameters are the same as for the List Content Items endpoint. Permissions: users will be able to get CSV with items only across collections they have access to. Users can get CSV only if the Content Review feature is enabled.

Authorizations

`auth_token` **Authorization** `string` **required**

Shelf API Token. See [Create API Token](#) for more details.

Header parameters

time-zone `string` **optional**

Time zone name used to localize date-time values.

Example: `Europe/London`, `America/Lima`, `Asia/Tokyo`; see more here

<https://www.iana.org/time-zones>

Body

`application/json` `object` **optional**

Responses

 **200** CSV URL `application/json`**Response** `object` **400** Bad Request `application/json` **403** Forbidden `application/json`

POST /cil-content/items/list/csv

HTTP ▾

```
POST /cil-content/items/list/csv HTTP/1.1
```

```
Host: api.shelf.io
```

```
Authorization: YOUR_API_KEY
```

```
Content-Type: application/json
```

```
Accept: */*
```

```
Content-Length: 1209
```

```
{
  "fieldsFilters": {
    "type": [
      "text"
    ],
    "contentType": [
      "01G7EE3DXZT6V0XN5QMFJZ1AA"
    ],
    "ownerId": [
      "John Doe"
    ],
    "ratingMoreThan": [
      3
    ],
    "shelf_categoryId": [
      "setId#default#categoryId#01GCV9CN566439HHEQBYF34XBR"
    ],
    "shelf_categoryIdToExclude": [
      "setId#default#categoryId#01GCV9CN566439HHEQBYF34XBR"
    ],
    "shelf_categoryOp": "and",
    "shelf_reviewStatus": [
      "up-to-date"
    ],
    "source": [
      "text"
    ]
  },
  "uiLanguage": "en",
  "collectionIds": [
    "3de6149e-0e4f-41a0-8701-6436eb772e26",
    "7755817680017"
  ]
}
```

200 CSV URL ▾

Search Content Items

POST `https://api.shelf.io` `/cil-search/content`

Returns search results over CIL content items. Applies vector search.

Permissions: users will be able to search only across collections that they have access to.

Authorizations

`auth_token` 

Authorization `string` **required**

Shelf API Token. See [Create API Token](#) for more details.

Body

`application/json` 

`object` **optional**



Responses

 **200** Search results `application/json`

Response `object`



 **400** Bad Request `application/json`

 **403** Forbidden `application/json`

POST `/cil-search/content`

HTTP 



```
POST /cil-search/content HTTP/1.1
Host: api.shelf.io
Authorization: YOUR_API_KEY
Content-Type: application/json
Accept: */*
Content-Length: 1377
```

```
{
  "origin": "acme-api-integration",
  "purpose": "ask-copilot",
  "fieldsFilters": {
    "type": [
      "text"
    ],
    "contentType": [
      "01G7EE3DXZT6V0XN5QMFJZ1AA"
    ],
    "ownerId": [
      "John Doe"
    ],
    "ratingMoreThan": [
      3
    ],
    "shelf_categoryId": [
      "setId#default#categoryId#01GCV9CN566439HHEQBYF34XBR"
    ],
    "shelf_categoryIdToExclude": [
      "setId#default#categoryId#01GCV9CN566439HHEQBYF34XBR"
    ],
    "shelf_categoryOp": "and",
    "shelf_reviewStatus": [
      "up-to-date"
    ],
    "source": [
      "text"
    ]
  },
  "enrichmentsFilters": [
    {
      "type": "NER",
      "ids": [
        "da6c883e-d966-4b36-a523-9f4a8f13520c"
      ],
      "values": [

```

200 Search results ▾



```

{
  "pageInfo": {
    "currentPage": 1,
    "hasNextPage": true,
    "hasPreviousPage": false,
    "pageSize": 1000,
    "totalPages": 100,
    "totalResultsCount": 10000,
    "nextToken": "text"
  },
  "searchEventId": "01GCBNQSC4J64R2SD9FBX3ABH0",
  "searchLanguage": "en",
  "searchResultsUrl": "text",
  "items": [
    {
      "accountId": "50018985-7134-41fd-96db-9e596488f6a6",
      "collectionIds": [
        "1234567890"
      ],
      "connectorId": "default-zendesk",
      "createdAt": "2022-08-26",
      "externalId": "8149140753169",
      "externalURL": "https://test.zendesk.com/hc/en-us/articles/8149140753169-new-item",
      "fields": [
        {
          "type": "string",
          "data": {
            "parents": [
              {
                "id": "01G7EE3D07Q1EBBFN9AN8QPVS",
                "label": "Idea"
              }
            ]
          }
        },
        {
          "key": "shelf_categoryId",
          "label": "gg",
          "value": "setId#default#categoryId#01GCV9CN566439HHEQBYF34XBR"
        }
      ],
      "type": "string",
      "key": "contentType",
      "label": "FAQ",
      "value": "01G7EE3DXZT6V0XN5QMFJZ1AA"
    }
  ],
  "iconURL": "text",

```

```

    "id": "01GBD7BPMW6WGM3PHPWTBC279X",
    "internalCollectionIds": [
      "01FS6XKMMHB85VXEKEPF66DK42"
    ],
    "internalId": "01GBD7BPMW6WGM3PHPWTBC279X",
    "lang": "en",
    "lastViewedAt": "2026-02-09",
    "locations": [
      {
        "collectionId": "aefbb39d-c907-4d5b-9738-4fd982c8e618",
        "grandParentIds": [
          "aefbb39d-c907-4d5b-9738-4fd982c8e618"
        ],
        "parentId": "1b9b60ba-b320-4103-a228-d91036418b0e"
      }
    ],
    "originalCreatedAt": "2022-08-26"
  }

```

Get last 50 updated content items

GET

[https://api.shelf.io](https://api.shelf.io/content-ingestion/preview/{syncFlowId}) /content-ingestion/preview/{syncFlowId}

Get last 50 updated content items in a given sync flow

Authorizations

auth_token ▾

Authorization string **required**

Shelf API Token. See [Create API Token](#) for more details.

Path parameters

syncFlowId all of **required**

string · min: 26 · max: 26 **optional**

Example: 01FS6XKMMHB85VXEKEPF66DK42

AND

any **optional**

Sync Flow ID

Responses

▼ **200** Success

application/json

Response object

+

> **400** Bad Request

application/json

> **403** Forbidden

application/json

GET /content-ingestion/preview/{syncFlowId}

HTTP ▼

GET /content-ingestion/preview/{syncFlowId} HTTP/1.1
Host: api.shelf.io
Authorization: YOUR_API_KEY
Accept: */*

Test it ►

200 Success ▼

```
{
  "items": [
    {
      "collectionIds": [
        "text"
      ],
      "externalURL": "https://shelf.io",
      "title": "Articles",
      "updatedAt": "2020-01-01T00:00:00Z"
    }
  ]
}
```