

# Gergely Daróczy

## Unified plots

### Contents

<b>Options</b>	<b>3</b>
<b>Default options</b>	<b>4</b>
Histogram . . . . .	4
Base R plot . . . . .	4
lattice . . . . .	5
ggplot2 . . . . .	6
Barplot . . . . .	7
Base R plot . . . . .	7
lattice . . . . .	8
ggplot2 . . . . .	9
Points . . . . .	10
Base R plot . . . . .	10
lattice . . . . .	11
ggplot2 . . . . .	12
Grouped plot . . . . .	12
Base R plot . . . . .	12
lattice . . . . .	13
ggplot2 . . . . .	14
Facets . . . . .	14
Base R plot . . . . .	14
lattice . . . . .	15
ggplot2 . . . . .	16

Boxplot . . . . .	17
Base R plot . . . . .	17
lattice . . . . .	18
ggplot2 . . . . .	19
Lines . . . . .	20
Base R plot . . . . .	20
lattice . . . . .	21
ggplot2 . . . . .	22
<b>Custom options</b>	<b>22</b>
Histogram . . . . .	23
Base R plot . . . . .	23
lattice . . . . .	24
ggplot2 . . . . .	25
Barplot . . . . .	26
Base R plot . . . . .	26
lattice . . . . .	29
ggplot2 . . . . .	30
Points . . . . .	31
Base R plot . . . . .	31
lattice . . . . .	32
ggplot2 . . . . .	33
Grouped plot . . . . .	33
Base R plot . . . . .	33
lattice . . . . .	34
ggplot2 . . . . .	35
Facets . . . . .	35
Base R plot . . . . .	35
lattice . . . . .	36
ggplot2 . . . . .	37
Boxplot . . . . .	38

Base R plot . . . . .	38
lattice . . . . .	39
ggplot2 . . . . .	40
Lines . . . . .	41
Base R plot . . . . .	41
lattice . . . . .	42
ggplot2 . . . . .	43

This document demonstrates the features of unifying plots in **pander**. First, if you do not want to deal with styling each of your images, just activate it: `evalsOptions('graph.unify', TRUE)`.

*Note:* please install `lattice` and `ggplot2` on your computer prior to trying to run all examples of this document.

## Options

There are a bunch of options you might want to check out, these are:

- `graph.nomargin`
- `graph.fontfamily`
- `graph.fontcolor`
- `graph.fontsize`
- `graph.grid`
- `graph.grid.minor`
- `graph.grid.color`
- `graph.grid.lty`
- `graph.bboxes`
- `graph.legend.position`
- `graph.background`
- `graph.panel.background`
- `graph.colors`
- `graph.color.rnd`

- `graph.axis.angle`
- `graph.symbol`


Find more details on [pander's homepage](#).

## Default options


Not touching the above ones, let us check out how different plots look like by calling base R graphing function, `lattice` or `ggplot2`!

## Histogram


Base R plot



lattice




ggplot2




## Barplot

Base R plot




lattice






ggplot2




## Points


Base R plot



lattice



ggplot2




Grouped plot


Base R plot

I have no idea how to do that besides manually adding points.

lattice



ggplot2




Facets


Base R plot

I have no idea how to do that besides `par(mfrow=c(foo, bar))`.

lattice




ggplot2






## Boxplot


Base R plot



lattice




ggplot2




## Lines


Base R plot



lattice



## ggplot2



## Custom options


Below you can find some images generated by the exact same commands but with some modified `panderOptions`:

```
panderOptions('graph.fontfamily', "Comic Sans MS")
panderOptions('graph.fontsize', 18)
panderOptions('graph.fontcolor', 'blue')
panderOptions('graph.grid.color', 'blue')
panderOptions('graph.axis.angle', 3)
panderOptions('graph.bboxes', T)
panderOptions('graph.legend.position', 'top')
```


```
panderOptions('graph.colors', rainbow(5))  
panderOptions('graph.grid', FALSE)  
panderOptions('graph.symbol', 22)
```

## Histogram

Base R plot




lattice






ggplot2




## Barplot

Base R plot




Yeah, the “Foo bar” label is cropped. We need a custom `mar` option here:




But wait, we lost the color! Right: unfortunately coloring base R plots is really hackish, **pander** is adding the `col` attribute to the calls. If you start to tweak **par** in a chunk, you should prepare to some unwanted side-effects. Solution:


## Barplot in base R



lattice




ggplot2




Points

Base R plot




lattice





ggplot2




Grouped plot


Base R plot

I have no idea how to do that besides manually adding points.

lattice



ggplot2




Facets

Base R plot


I have no idea how to do that besides `par(mfrow=c(foo, bar))`.

lattice

## Faceted barplot with lattice




ggplot2




Boxplot


Base R plot



lattice




ggplot2






## Lines


Base R plot



lattice



ggplot2



---

This report was generated with [R](#) (2.15.1) and [pander](#) (0.1) in 14.144 sec on x86\_64-unknown-linux-gnu platform.