

The God Core

A video game engine and video game developed in C++

Author: Jeremy Greenburg
Mentor: Dr. Joshua Guerin
Second Reader: Bob Bradley

March 29, 2017

Contents

1	Abstract	3
2	Development Tools	4
2.1	APIs	4
2.2	Development Environment	5
3	The Project	5
3.1	The Game Engine	5
3.2	The Game	11
4	Challenges and Future Considerations	12
4.1	Challenges that I Faced	12
4.2	Future Considerations	13
5	Acknowledgments	13
6	Appendices	13
6.1	Source Code	13
6.2	Database	113
6.3	Images	119
6.4	Music	120

1 Abstract

This project consists of a video game engine developed in C++ and a short video game developed on it. My goal throughout this project was to strengthen my software development skills and prepare me for a career. I developed skills not necessarily part of an ordinary Computer Science curriculum, such as the research, evaluation, and implementation of various APIs, creating a deployment module, and simply developing and maintaining a project for an extended amount of time. Developing this project also served to strengthen the programming principles that have been instilled in me throughout my undergraduate Computer Science experience.

2 Development Tools

2.1 APIs

API's, or *Application Programmer Interfaces*, are a set of methods and tools to allow a programmer to access a piece of software through code. They are useful when developing more complex applications, as you can incorporate useful, quality tools rather than spending time developing tools that have already been created.

2.1.1 OpenGL

OpenGL (Open Graphics Library) is one of the most widely used graphics libraries available. It provides access to matrix manipulation, keyboard and mouse input, windowing, and vector graphics. It provides the ability to draw in both 2D and 3D and gives access to primitives such as rectangles, triangles, and lines. With GLUT (OpenGL Utility Toolkit), OpenGL can also draw simple spheres and cylinders. It is the graphical backbone of both the Unity and Unreal Engines for Mac OS and Linux.

I chose to use OpenGL over its stronger competitor, Microsoft's DirectX, because it is cross platform which would reduce the amount of work needed to port the engine to a different operating system, and because there is a great deal of documentation easily available for OpenGL.

2.1.2 SOIL

SOIL (Simple OpenGL Interface Library), is a small extension to OpenGL that provides an easy to use interface for using textures in OpenGL, including saving images, loading and binding textures, and resizes textures. A *texture* is an image on the hard disk, such as a JPG or PNG file, that is loaded into memory and rendered over an OpenGL primitive, such as a rectangle. I use textures for the main menu and as part of the background for Terminals to make them look nicer, everything else rendered in game is an OpenGL or glut primitive.

2.1.3 FMOD

FMOD is a sound effects engine developed by Firelight Technologies that can play many different files types on numerous Operating Systems including but not limited to: Windows, OSX, IOS, Playstations and Xboxes, and Android; and it is the primary audio system for many game engines including Unity, Unreal, CryEngine, and Havok. I decided to use FMOD because I was impressed with its flexibility and diversity, no other API that I looked at could read as many different sound files, particularly MP3 files which was the format of the sound files that I had acquired.

2.1.4 SQLite

Rather than store game data in a text file, I chose to store the data in a SQL database to use make full use of the SQL queries, which make it easy to request all data for specific levels and to parse the data that is received.

I decided to use SQLite over other implementations of SQL because it is a lightweight and simplified, stripping out features of SQL that I do not need in order to make queries faster and the database size smaller.

2.1.5 Windows API

The Windows API is distributed with the Microsoft Software Development Kit and provides access to many features of the Windows operating system.

The game engine only utilizes one of its eight modules, the Shell Object module, which gives access to the operating system shell. Since programs do not have write permissions to their install folder in Windows, the Shell Object module can be used to locate the user's personal documents folder, where both the save file and the log file are written.

2.2 Development Environment

2.2.1 Microsoft Visual Studio

Microsoft Visual Studio is an IDE (Integrated Development Environment) developed for Windows that supports a variety of programming languages, and it is where I wrote all of the code for the game engine. I chose Visual Studio as my IDE because it give access to an Installer package, which allows me to create a windows installer for my game so that it can be installed on any Windows computer. The Installer packages together the executable source code, any resources that I have developed, as well as system resources such as the Microsoft C++ redistributes necessary to run programs developed in Visual Studio. Visual Studio also provides powerful analytic tools to monitor memory usage to avoid creating memory leaks.

I chose to develop my project in C++ because it is an extremely fast language, and speed is one of the most important qualities in real time software like video games. C++ also allows low level memory access with pointers and the ability to use typeless pointers, which are of great use in section ??.

2.2.2 SQLite Studio

SQLite Studio is a third party GUI for SQLite that allows information to be analyzed and edited quickly and easily. It also provides utilities to export a database to a number of different file formats, allowing me to easily include the database for reference in section 6.2.

SQLStudio (3.1.0) - [doors (Data)]

Database

Structure

View

Tools Help

Database

Structure

Data

Comments

Indexes

Triggers

DDL

Open View

Print View

View Name

View Data (SQL)

Tables

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

doors

columns

indexes

triggers

views

<

Figure 1: A picture of the *doors* table in the SQLite Studio editor.

2.2.3 GitHub

GitHub is an online Git repository that houses many open source projects. It also provides a great source control and branching system, where multiple branches can be created from a single point in the project to experiment with new features without any fear of damaging your code if they do not work out.

3 The Project

The project consists of two entities: the game engine and the game itself, which was developed on the engine. The engine and game are not two fully separated entities as discussed in section 4.2.2.

3.1 The Game Engine

I developed the engine of my game in C++ during two, years starting in spring of 2015 and ending in fall of 2016. It consists of 49 C++ files, in which there are 3,308 lines of code and 1,122 lines of comments. The code can be found in the section 6.1, and it is also located on GitHub at <https://github.com/Jerrrgree/The-God-Core-Source>.

The engine reads a SQLite database (Data.db) that is housed in the same directory as the game executable, and it recognizes six tables in the database that correspond to six different types of in game objects—Walls, Doors, Cylinders, Terminals, Switches, and Triggers. Due to limitations discussed in 4.2.2, it will only properly work with a game that has five levels.

3.1.1 Walls and Doors

Walls are, at their heart, an OpenGL rectangle with a wrapper for additional functionality. In the same vein, Doors are simply Walls with the ability to open and close.

Internally they consist of two arrays: a four dimensional array containing the *rgba* values and a twelve dimensional array containing the 4 *xyz* coordinates of the rectangle's corners.

The rectangles contain the most complex mathematics needed for collision, as the necessary calculus to correctly determine whether or not the player has collided with a rectangle involves determining if a sphere has collided with a plane in 3 Dimensional space.

In the constructor of a rectangle, after all values are initialized, the equation of the plane (Figure 2) is immediately calculated for future reference in collision detection.

$$aX + bY + cZ + d = 0$$

Figure 2: The equation of a plane.

This equation is calculated using the any three corners of the rectangle (A, B, and C) and then creating two vectors (B-A and C-a) using their dot product as show in Figure 3.

$$\vec{AB} = \begin{bmatrix} Bx - Ax \\ By - Ay \\ Bz - Az \end{bmatrix} \quad \vec{AC} = \begin{bmatrix} Cx - Ax \\ Cy - Ay \\ Cz - Az \end{bmatrix}$$

$$a = \vec{AB}_2 * \vec{AC}_3 - \vec{AB}_3 * \vec{AC}_2$$

$$b = \vec{AB}_3 * \vec{AC}_1 - \vec{AB}_1 * \vec{AC}_3$$

$$c = \vec{AB}_1 * \vec{AC}_2 - \vec{AB}_2 * \vec{AC}_1$$

$$d = -(aAx + bAy + cAz)$$

Figure 3: Given three points of a rectangle (A, B, and C), the equation of the plane can be derived with the dot product of two vectors. [4]

The norm of the plane can then be derived using the equation $\sqrt{a^2 + b^2 + c^2}$.

3.1.2 Terminals

Terminals are an in-game computer that the player can access to read parts of the stories lore, as well as unlock new doors for them to explore.

Each terminal is bound to a unique *terminal file* that is heavily structured and contains its data. An example is show in Figure 4

```

1 <FILES>
2 [01] Name1 -- TAG
3 [02] Name2 -- TAG2
4 [03] Name3 -- TAG3
5
6 <TAGS>
7 $HELP$
8 Type Read <num> to read the corresponding file
9 Type Clear to clear a file from the screen
10 Type Exit to exit the terminal
11 Type Help to see this message again
12 $END$
13
14 $TAG$
15 Content 1
16 $END$
17
18 $TAG2$
19 Content 2
20 $END$
21
22 $TAG3$
23 Content 3
24 $END$

```

Figure 4: An example Terminal file

The program parses the file by first separating the in game content (the bracketed number and name) that should be displayed to the user from it's tag. The tags are stored in an array, where its index is equal to the bracketed number. The help display is always stored at the 0th index.

The terminal recognizes a number of commands.

- Help—Displays the help prompt.
- Read X—Reads the requested tag. If X is zero or greater than the highest number, an error is returned.
- Quit or Exit—Removes the player from the terminal and back into the world.

The terminal also stores a history of what the player types, and the up and down arrows can be used to cycle through previous commands.

3.1.3 Switches

A switch is a button that is attached to a wall and is visible on either side. Switches are primarily bound to doors and terminals and are used to open/close a door or power on/off a terminal. Switches are also the mechanism to change levels, each level except for the last contains a switch that, when activated, will trigger a level change. Switches serve as the primary means of progress, as the level change switch and many door switches will initially be off, and the player must navigate through the level to power on more switches and progress through the level.

Internally a switch consists of two three dimension vectors, one containing its *xyz* center and the other containing its *xyz* rotation. It also contains a void pointer to its target and an identifier as to what type of object the target is so that the pointer can be properly typecast.

3.1.4 Triggers

Triggers are not a tangible object in the game, rather, they serve as an event. Triggers are a more sophisticated form of interaction between two different objects. The implementation was designed to be abstracted away from object types so that any arbitrary object could activate another.

The trigger holds two void pointers, one for a triggering object and one for the target object, as well as identifiers for which object type they are. Whenever an object is interacted with, every trigger in the game is tested and if the object is the same as the trigger pointer (no referencing needed as the pointers will always be equal), the target is dereferenced according to the appropriate type and activated.

3.1.5 Cylinders

Cylinders solely exist as decoration. Internally it contains the radius of each base, the height, an *xyz* center, the *rgba* values, and the number of "slices" or how smooth it should appear.

3.1.6 Camera Controller

The camera control describes how the player looks around and moves. Internally it contains the *xyz* rotation, which describes the direction that the player is looking, and the *xyz* coordinates where the player is physically located. The *x* rotation corresponds to left/right movement, the *y* coordinate refers to up/down movement, and *z* rotation would be similar to a barrel roll.

The player can move forwards and backwards, as well as strafe left and right, in respect to the direction that they are facing. The equation to determine movement is the formula to determine a point on the circumference of a circle as seen in Figure 5. Only the angle of *x* rotation is necessary for the formula, as looking left and right are the only things that impact where one would move. Given the formula, it is equally easy to implement other directions of movement by adding and subtracting 90° from the *x* angle.

$$\begin{aligned} z &:= z \pm \text{moveSpeed} * \cos(\text{radian}(\theta)) \\ x &:= x \mp \text{moveSpeed} * \sin(\text{radian}(\theta)) \end{aligned}$$

Figure 5: This equation finds an arbitrary point on a circle's circumference in relation to a specified angle. [6]

Following that formula, it's simple to implement movement to the left, right by adding or subtracting 90° , and backwards movement by adding 180° .




Figure 6: A graphical representation of movement. With the player at the center of the circle and $\theta = x$ rotation, point A would represent forward movement, B and C would represent strafing left and right, and point D would represent backwards movement.

3.1.7 Keyboard Controller

The Keyboard class primarily serves to encapsulate the OpenGL callbacks that receive keystrokes: the normal function that accepts all alphanumeric and punctuation keys, and the special function that handles function keys and arrows. The keyboard function acts differently depending on what mode the player is currently in.

Under normal circumstances, the only normal keystrokes accepted are the WASD keys for movement, the E key for interaction, the ' ' key for toggling the development console, and the escape key which will return the player to the main menu.

When in either a terminal or the development console, all keys are immediately concatenated to an input string with the exception of the ' ' which will close the development console, or the enter key which will send the input string to its appropriate destination to be parsed and interpreted, after which the input string is cleared so that a new command can be entered.

Also accepted are the up and down arrow keys, which will cycle through the console/terminals command history.

When the user is in the main menu, no keyboard keys are accepted other than F2, which will close the game under any circumstances.

3.1.8 Music Controller

To play background music, I created a class that uses the FMOD Low Level API that knows the directory that all sound files are stored and will play a designated one on infinite repeat until the prompted to change songs.

Each song in game is mapped to an integer. On each level change, the song number is incremented and a boolean flag is tripped, which signals the music controller to play the next song. Each song is dynamically allocated, so it is important to properly deallocate the songs before the next one is played. Considerations on how to change the Music Controller are noted in section 4.2.2.

3.1.9 Text Controller

The Text Engine handles displaying all text to the screen, from prompts on the HUD to each Terminal screen. It uses OpenGL's glutBitmapCharacter function to display clear, concise text.

Every function to display text takes the xy coordinates for where on the screen to start printing, and the *RGB* color values for the text. There are two functions for displaying text, the simpler one merely takes in a string and prints it on the corresponding location on the screen. The more complex function takes in a file and a content tag which needs to be parsed. The text files are similar to terminal files as seen in Figure 7.

```
1 $TAG 1$
2 Content 1
3 $END$
4
5 $Tag 2$
6 Content 2
7 $END$
```

Figure 7: An example text file, very similar to a terminal file

The Text Engine searches through the designated file line by line until it discovers the line containing the proper tag. Then, until it reaches the closing 'END' tag, it stores every line inside of a vector. Once it has retrieved all of the necessary content, it will print the vector line by line.

3.1.10 Collision Engine

A *collision* occurs when two or more objects in game attempt to occupy the space. The collision engine handles detecting and preventing any collision between the player and all objects in the level. In this engine there are two types of collisions: player-object collisions and player-wall collisions.

Player object collisions are simple to detect, as both the player and the object can be placed within imaginary "bounding spheres" that extend around the player and object, the collision can be detected easily using the distance formula and the radii of the spheres as seen in Figure 8.

$$\sqrt{(x_2 - x_1)^2 + (y_2 - y_1)^2 + (z_2 - z_1)^2} < r_2 + r_1$$

Figure 8: If the distance between the sphere is shorter than the combined radii of the spheres, a collision has occurred.

Player-wall collisions were much harder to reconcile. Because walls tend to be long and thin, you can't simply place one within a bounding sphere, the resulting sphere would simply be too massive and usually encompass the player entirely.

To rectify that, the collision is split into two phases. In the first phase, we use the plane equation that is derived in the section 3.1.1. Using the equation from Figure 9. If the resulting value is less than the radius of the player's bounding sphere, the player is close enough to collide with that plane. However, a plane is an infinite length, and relying solely on this method would induce false collisions if the player was close to the wall but beyond it.

$$\frac{ax+by+cz+d}{\sqrt{a^2+b^2+c^2}} < r$$

Figure 9: By substituting the player's *xyz* coordinates and dividing by the norm of the plane, we can determine the distance to the plane.

For the second phase, each wall is aligned on an axis: x, y, or z. For the axis that it is aligned on, largest and smallest values of the coordinates are compared to the player's coordinates. player's corresponding coordinate is in between the two values, the player has hit the wall. Otherwise, they hit the plane but not the wall, and they do not collide.

3.1.11 2D

As the player's HUD, the main menu, the developer console, and terminals all need to display in a 2D environment, I extracted the ability to draw in 2D into its own class that is inherited by them in order to reduce reused code.

To convert OpenGL into 2D frame, lighting and depth masking must be disabled. Next an *orthogonal* matrix is pushed onto OpenGL's matrix stack using the length and width of the screen so that all matrix transformations corresponded to a pixel on the screen. Re-enabling 3D is as simple as popping the orthogonal matrix from the stack and re-enabling depth testing and masking.

3.1.12 Level Management

Loading each level involves a series of operations through the SQLite API. First a connection with the database is opened, and then a series of queries are made to the database for each table in the database in turn. All important data from the database is stored in a class of the appropriate type, unnecessary data is discarded, and in the end each class is pushed into a vector of the appropriate type.

The data is loaded in a strict order, due to some objects having dependencies on others (that is, some objects require other objects to already exist). Thus the first things that are loaded are purely independent objects, all doors, walls, cylinders, terminals. Next switches are loaded, because they require both doors and terminals to already exist. Finally, the triggers are loaded, because they require both switches and terminals.

When loading switches and triggers, the objects also need to be *bound* to their appropriate required object(s). This is why doors, switches, and terminals all carry their ID's into the program with them, while triggers and walls discard their ID. Once all of the objects that need to be bound are loaded into the game, the game proceeds to bind them to their target. For each switch that needs to be bound, the game loops through the list of possible target objects and creates a pointer to the correct object inside of the switch, thus ensuring that the switch can toggle its target instantly without needing to search every time it is triggered. The triggers are bound similar, with the difference that each object must perform two searches, one for the triggering object and one for the target object.

If there is any data error in regards to binding — that is, an object attempts to bind to an object that does not exist, the error is considered fatal and the game immediately shuts down after logging the error.

The OpenGL display function calls upon the Level class to display all in game objects. This is a simple matter, because each object knows how to display itself. Thus it is a simple matter to loop through each vector and tell each object to display itself.

3.1.13 Game Saving and Loading

Game saving and loading is a simple file transaction. To save, the current level (as a string) and the song that is playing are appended to each other. The string is then encrypted and written to the save file.

Loading is a two step process. First the contents of the save file are read, decrypted, and parsed into the saved level and the saved song. Next the contents are verified so that they are valid levels to load and songs to play. If either one is invalid, the save file is considered corrupted and the game will refuse to complete the load.

3.1.14 Console and Logging

To aid in debugging a created a Developer Console and a game log. The developer console accepts user commands to perform actions such as writing to the save file, reading the save file, disabling collision, and changing what song is playing.

The logger writes to a log file as the game runs to report on the status of operations, primarily the loading of each level. If an error occurs and the game aborts (without crashing), the appropriate error and error code is written at the end of the log file. There is only ever one log file, which is erased when the game is launched and new data is appended to it as the game runs.

3.2 The Game

The game itself was also developed over a period of two years, starting fall of 2015 and ending in spring of 2017. The game itself consists of the SQLite database containing the game objects, as well as all text, terminal, image, and sound files that the game engine uses. The game is relatively short, an average play through would take 15-20 minutes, although it can easily be speed-ran in approximately five minutes.

3.2.1 Setting

The game takes place in the year 300x. Humanity has united under British rule, and the New British Empire has turned its eyes to colonizing the stars. The player is Special Constable Rikker, an elite agent of the Empire who has been called to scout out one of the Crown's top secret research facilities, The Daedalus, that has stopped communicating in preparation for a full investigative team that will follow behind them.

3.2.2 Level Zero

Level zero is an introductory tutorial level where the player can get a grasp with the controls. It takes place on the Constable's personal shuttle, and there is a terminal that gives access to the prior information.

3.2.3 Level One

In level one, the player explores one hanger of the ship. There they can read logs detailing power outages and mechanical fluctuations, as well as security and intake reports detailing a few objects that the ship has taken on. The last report details them taking on the titular God Core.

3.2.4 Level Two

The next level takes place in offices, where the Constable learns more about the Daedalus. It exists to house strange, unexplainable, and possibly deadly objects that are too dangerous or unknown to be left alone. Ever since taking on the God Core, crew have been slowly disappearing and communications equipment have started to fail. It comes to light that the God Core warps reality itself, and no one can determine if the missing crew has been transported elsewhere, or if they have simply disappeared from reality.

3.2.5 Level Three

Level three takes place in a gallery housing access to eight different objects. Although the Constable can only access the exhibit containing the God Core, the Constable can read information about the abilities and containment procedures for various objects.

3.2.6 Level Four

The final level takes place in the God Core's exhibit. The player can only stare at the God Core as reality starts to deform around them, before they vanish into the unknown, ending the game.

4 Challenges and Future Considerations

4.1 Challenges that I Faced

Development was not always smooth, and I encountered a few interesting problems along the way.

4.1.1 The Death of a Computer

Over the course of my project, I changed computers twice. My laptop died, and I switched to a more powerful desktop in fall 2015, and in spring 2016 my operating system was corrupted and I had to perform a fresh reinstall. Both times I was able to get back up to speed in only a few hours thanks to GitHub, losing only a few hours of progress at most. Frequent commits and syncing is a solid defense against any disaster on the developers end.

4.1.2 Clipping Issues

There is a problem when getting to close to a wall or a door where the player can see through parts of the wall, no doubt to do OpenGL's depth buffering in relation to distance to the wall. Part of the development processes involved balancing collision distance to the walls, at distances where the user could not see through walls the user was a noticeable distance from the wall, so I chose to allow the user to get close enough to slightly peer through the wall, as the distance felt more natural.

4.1.3 APIs and Naming

C++ uses unique identifiers. This means that no class, variable, or function can share the same name. Initially the Plane class was named Rectangle, as it more clearly showed that it was a wrapper for the OpenGL rectangle primitive, but when I included the Windows API I discovered that it had its own function named Rectangle, rendering my program uncompileable until I renamed every instance of my class.

4.2 Future Considerations

Of course, time itself was a constraining factor; I only had two years to develop the project. As such every design choice that I made bore this limit in mind, and there portions of the engine that I was unable to optimize or implement due to lack of development time. Rarely is a project ever done, and there are always changes and improvements that could be made.

4.2.1 Triggers and Switches

Given time, I would have liked to implement the back end of a switch's interaction into triggers. The primary difference between triggers and switches is that a trigger is a one time activation, whereas a switch is a potentially many time toggle, but it would be a simple matter to add in different trigger types.

4.2.2 Engine and Data Separation

A true game engine is fully separate from the game it runs on, however I had a few roadblocks preventing me from completely separating the two of them.

The music files and maximum song number is hard coded into the engine, as are the maximum number of levels in the game. Music and levels could easily be given their own table in the database after reworking the code that directly deals with them, but the major hurdle that led me to hard coding levels is the lack of animation. I was unable to encapsulate animation in a database, which leads to parts of the fourth level's rendering to be hard coded into the game.

5 Acknowledgments

I would like to offer thanks to the following people:

- Kevin MacLeod, Devin Powers, and Arseniy Shkljaev for the music
- Robert Deyoso III for the movement equation
- Cody Robertson for bouncing ideas off of
- Brian Affolter and Lauren Ball for helping test
- Dr. Joshua Guerin for mentoring the project

6 Appendices

6.1 Source Code

6.1.1 main.cpp

```
1  /*****\
2  * main.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file creates an OpenGL window to display the game *
8  * and promptly passes control over to the GameManager object*
9  \*****/
10
11 // Because doth openGL demandeth
```

```

12 #include <cstdlib>
13 // OpenGL API
14 #include <GL\glut.h>
15 // time
16 #include <ctime>
17
18 // The Game manger
19 #include "GameManager.h"
20 GameManager Overlord;
21 // Save manager
22 #include "SaveManager.h"
23 // Return codes
24 #include "Return.h"
25 // System log
26 #include "Logger.h"
27 // Global variables
28 #include "Globals.h"
29
30 // Normal key presses
31 void normal(unsigned char key, int x, int y);
32
33 // For key releases
34 void key_up(unsigned char key, int x, int y);
35
36 // For Special keys
37 void special(int key, int x, int y);
38
39 // Mouse clicks
40 void mouse(int button, int state, int x, int y);
41
42 // Mouse movement
43 void motionPassive(int x, int y);
44
45 // Changing Window size (Not exactly working as hoped...
46 void changeSize(int w, int h);
47
48 // Initializes GLUT callbacks and returns true if core.sav exists (false otherwise
49 )
50 bool initGame(int argc, char **argv);
51
52 // Manages the game's scenes
53 void manageScenes();
54
55 GLfloat light_diffuse[] = { 0.3f, 0.3f, 0.3f, 0.3f };
56 GLfloat light_position[] = { 0.0f, 0.0f, 0.0f, 0.0f }; // Currently nonexistent
57   until I can figure out how lighting works
58 GLfloat mat_specular[] = { 1.0f, 1.0f, 1.0f, 1.0f };
59 GLfloat mat_shininess[] = { 75 };
60 GLfloat lmodel_ambient[] = { 0.6f, 0.6f, 0.6f, 1.0f };
61
62 using namespace std;
63
64 //***** FUNCTION DEFINITIONS *****\
65
66 int main(int argc, char **argv)
67 {

```

```

66     Overlord.canContinue = initGame(argc, argv);
67
68     // Begin the game
69     glutMainLoop();
70
71     // If we ever get here, something bad happened
72
73     Logger log;
74     log.logLine("ERROR: GlutMainLoop exited early");
75
76     return EXIT_EARLY;
77 }
78
79 bool initGame(int argc, char **argv)
80 {
81     // Obliterate log file
82     Logger log;
83     log.nuke();
84
85     // Initialize GLUT
86     glutInit(&argc, argv);
87
88     // Create window
89     glutInitDisplayMode(GLUT_DOUBLE | GLUT_RGBA);
90     glutInitWindowPosition(50, 50);
91     glutInitWindowSize(500, 500);
92     glutCreateWindow("The God Core");
93
94     // register callbacks
95     glutDisplayFunc(manageScenes);
96     glutReshapeFunc(changeSize);
97     glutIdleFunc(manageScenes);
98     glutPassiveMotionFunc(motionPassive);
99     glutMouseFunc(mouse);
100    glutKeyboardFunc(normal);
101    glutKeyboardUpFunc(key_up);
102    glutSpecialFunc(special);
103
104    // Prebuilt function that works transparency
105    glBlendFunc(GL_SRC_ALPHA, GL_ONE_MINUS_SRC_ALPHA);
106
107    // Enable transparency
108    glEnable(GL_BLEND);
109    // Enable depth buffer
110    glEnable(GL_DEPTH_TEST);
111    // Let there be light!
112    glEnable(GL_LIGHTING);
113    // First light source
114    glEnable(GL_LIGHT0);
115
116    // Light properties
117    glMaterialfv(GL_FRONT, GL_SPECULAR, mat_specular);
118    glMaterialfv(GL_FRONT, GL_SHININESS, mat_shininess);
119    glColorMaterial(GL_FRONT_AND_BACK, GL_AMBIENT_AND_DIFFUSE);
120
121    // Light doesnt turn everything grey

```

```

122         glEnable(GL_COLOR_MATERIAL);
123
124         glLightfv(GL_LIGHT0, GL_DIFFUSE, light_diffuse);
125         glLightfv(GL_LIGHT0, GL_POSITION, light_position);
126         glLightModelfv(GL_LIGHT_MODEL_AMBIENT, lmodel_ambient);
127
128         glutWarpPointer(300, 300);
129
130         // Start in Fullscreen
131         glutFullScreen();
132
133         srand(time(NULL));
134
135         HUD.setStatus("INFO-WELL");
136
137         SaveManager SaveSystem;
138         return SaveSystem.checkSave();
139     }
140
141     // Everything below here is just passed along to the overlord
142
143     void mouse(int button, int state, int x, int y)
144     {
145         Overlord.mouse(button, state, x, y);
146     }
147
148     void motionPassive(int x, int y)
149     {
150         Overlord.motionPassive(x, y);
151     }
152
153     void changeSize(int w, int h)
154     {
155         Overlord.changeSize(w, h);
156     }
157
158     void manageScenes()
159     {
160         Overlord.manageScenes();
161     }
162
163     void normal(unsigned char key, int x, int y)
164     {
165         Overlord.normal(key, x, y);
166     }
167
168     void key_up(unsigned char key, int x, int y)
169     {
170         Overlord.key_up(key, x, y);
171     }
172
173     void special(int key, int x, int y)
174     {
175         Overlord.special(key, x, y);
176     }

```


6.1.2 CameraControl.h

```
1  /*****\
2  * CameraControl.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the CameraControl *
8  * Class, which stores: *
9  *     The x, y, z ordered triple of the player's location *
10 *     The degree to which the player is turned, along *
11 *     the x, y, and z axes *
12 * And contains methods to translate the player along *
13 * 3D space *
14 \*****/
15
16 #ifndef CAMERA_CONTROL_H
17 #define CAMERA_CONTROL_H
18
19 class CameraControl
20 {
21 private:
22     // Speeds for moving and rotating
23     double moveSpeed = 0.1f, turnSpeed = 0.5f;
24
25 public:
26     // Negatively adjusts angle and modifies lx
27     void lookLeft();
28     // Positively adjusts angle and modifies lx
29     void lookRight();
30     // Positively adjusts angle and modifies ly
31     void lookUp();
32     // Negatively adjusts angle and modifies ly
33     void lookDown();
34     // Translate the camera to the left
35     void strafeLeft();
36     // Translates the to the right
37     void strafeRight();
38     // Translates the camera forwards
39     void moveForward(int mod);
40     // Translate the camera backards
41     void moveBackward(int mod);
42     // Moves the camera positively along the Y axis
43     void moveUp();
44     // Moves the camera negatively along the Z axis
45     void moveDown();
46     // Flips the camera
47     void invertCam();
48     // If the player begins to run
49     void increaseSpeed();
50     // If the player begins to walk
51     void decreaseSpeed();
52     // Resets the camera to it's initial state
53     void resetCam();
54     // calls gluLookAt
```

```

55         void Display();
56
57         // Location of the camera
58         double x = 0.0, y = 0.0, z = -1.0;
59         double prevx, prevz;
60         // Angles of rotation
61         double x_angle = 0.0, y_angle = 0.0, z_angle = -1.0;
62     };
63
64 #endif

```

6.1.3 CameraControl.cpp

```

1  /*****\
2  * CameraControl.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * * *
7  * This file contains the definition of the CameraControl *
8  * Class. For more information, see CameraControl.h *
9  \*****/
10
11 // Class definition
12 #include "CameraControl.h"
13
14 // For sin()
15 #include <cmath>
16
17 // glut is unhappy when cstdlib isn't here :/
18 #include <cstdlib>
19
20 // OpenGL API
21 #include <GL\glut.h>
22
23 // To display Suit Warnings
24 #include "TextEngine.h"
25
26 // To include Globals Variables
27 #include "Globals.h"
28
29 // For converting degrees to radians
30 const double PI = 3.14159;
31
32 // Takes in an angle, in degrees, and returns the angle in radians
33 double toRadian(double angle)
34 {
35     return angle * PI / 180;
36 }
37
38 void CameraControl::lookLeft()
39 {
40     x_angle -= 3 * turnSpeed;
41
42     // To avoid potential underflow errors
43     if (x_angle < 0)
44     {

```

```

45         x_angle += 360;
46     }
47 }
48 void CameraControl::lookRight()
49 {
50     x_angle += 3 * turnSpeed;
51
52     // To avoid potential overflow errors
53     if (x_angle > 360)
54     {
55         x_angle -= 360;
56     }
57 }
58
59 void CameraControl::lookUp()
60 {
61     y_angle -= 2 * turnSpeed;
62
63     // To avoid potential underflow errors
64     if (y_angle < 0)
65     {
66         y_angle += 360;
67     }
68 }
69
70 void CameraControl::lookDown()
71 {
72     y_angle += 2 * turnSpeed;
73
74     // To avoid potential overflow errors
75     if (y_angle > 360)
76     {
77         y_angle -= 360;
78     }
79 }
80
81 void CameraControl::strafeLeft()
82 {
83     prevz = z;
84     prevx = x;
85     // Angles + 90 degrees for an angle that is perpendicular to x_angle
86     z = z + moveSpeed * cos(toRadian(x_angle + 90));
87     x = x - moveSpeed * sin(toRadian(x_angle + 90));
88 }
89
90 void CameraControl::strafeRight()
91 {
92     prevz = z;
93     prevx = x;
94     // Angles - 90 degrees for an angle that is perpendicular to x_angle
95     z = z + moveSpeed * cos(toRadian(x_angle - 90));
96     x = x - moveSpeed * sin(toRadian(x_angle - 90));
97 }
98
99 void CameraControl::moveForward(int mod)
100 {

```

```

101         prevz = z;
102         prevx = x;
103         z = z + moveSpeed * mod * cos(toRadian(x_angle));
104         x = x - moveSpeed * mod * sin(toRadian(x_angle));
105     }
106
107 void CameraControl::moveBackward(int mod)
108 {
109     prevz = z;
110     prevx = x;
111     z = z - moveSpeed * mod * cos(toRadian(x_angle));
112     x = x + moveSpeed * mod * sin(toRadian(x_angle));
113 }
114
115 void CameraControl::moveUp()
116 {
117     y -= moveSpeed;
118 }
119
120 void CameraControl::moveDown()
121 {
122     y += moveSpeed;
123 }
124
125 void CameraControl::invertCam()
126 {
127     z_angle += 180;
128 }
129
130 void CameraControl::resetCam()
131 {
132     x = 0.0;
133     y = 0.0;
134     z = -1.0;
135     x_angle = 0.0;
136     y_angle = 0.0;
137     z_angle = 0.0;
138 }
139 }
140
141 void CameraControl::increaseSpeed()
142 {
143     moveSpeed *= 2;
144 }
145
146 void CameraControl::decreaseSpeed()
147 {
148     moveSpeed /= 2;
149 }
150
151 void CameraControl::Display()
152 {
153     // To stop eternal movement
154     glLoadIdentity();
155
156     // Rotate along proper axes

```

```

157         glRotatef(y_angle, 1, 0, 0);
158         glRotatef(x_angle, 0, 1, 0);
159         glRotatef(z_angle, 0, 0, 1);
160
161         // Translate along the Plane
162         glTranslatef(x, y, z);
163     }

```

6.1.4 CollisionEngine.h

```

1  /*****\
2  * CollisionEngine.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file creates the declaration of the CollisionEngine *
8  * class, which uses sweet math to determine how the *
9  * player interacts with his environment *
10 \*****/
11
12 #ifndef COLLISION_ENGINE_H
13 #define COLLISION_ENGINE_H
14
15 class CollisionEngine
16 {
17 private:
18     // Determines if wall/door collision occurred
19     bool collideWalls();
20     // Determines if other collision occurred
21     bool collideObjects();
22     // Determines if an object can be interacted with
23     void checkInteract();
24 public:
25     // Master function that calls others
26     bool collide();
27 };
28
29
30 #endif

```

6.1.5 CollisionEngine.cpp

```

1  /*****\
2  * CollisionEngine.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the CollisionEngine *
8  * class. For more information, see SaveManager.h *
9  \*****/
10
11 #include "CollisionEngine.h"
12
13 // For the Cam
14 #include "Globals.h"

```

```

15 // absolute value
16 #include <cmath>
17
18 // System Log
19 #include "Logger.h"
20
21 using namespace std;
22
23 const double PLAYER_RADIUS = 0.5;
24 const double INTERACT_RADIUS = 1; // Object interactivity radius
25 const double COLLIDE_RADIUS = 0.5;
26
27 void CollisionEngine::checkInteract()
28 {
29     activeSwitch = NULL;
30     activeTerminal = NULL;
31     // Auto don't work in these parts
32     for (unsigned int i = 0; i < switches.size(); i++)
33     {
34         double distance = pow((switches[i].getX() + Cam.x), 2) + pow((
            switches[i].getY() + Cam.y), 2) + pow((switches[i].getZ() + Cam
            .z), 2);
35         distance = sqrt(distance);
36         double radii = (PLAYER_RADIUS + INTERACT_RADIUS);
37
38         if (distance < radii && switches[i].checkIfOn())
39         {
40             interactivity = true;
41             activeSwitch = &switches[i];
42             return;
43         }
44     }
45
46     for (unsigned int i = 0; i < terminals.size(); i++)
47     {
48         double distance = pow((terminals[i].getX() + Cam.x), 2) + pow((
            terminals[i].getY() + Cam.y), 2) + pow((terminals[i].getZ() +
            Cam.z), 2);
49         distance = sqrt(distance);
50         double radii = (PLAYER_RADIUS + INTERACT_RADIUS);
51
52         if (distance < radii && terminals[i].checkIfOn())
53         {
54             interactivity = true;
55             activeTerminal = &terminals[i];
56             return;
57         }
58     }
59
60     interactivity = false;
61 }
62
63 bool CollisionEngine::collideObjects()
64 {
65     for (unsigned int i = 0; i < terminals.size(); i++)
66     {

```

```

67         double distance = pow((terminals[i].getX() + Cam.x), 2) + pow((
            terminals[i].getY() + Cam.y), 2) + pow((terminals[i].getZ() +
            Cam.z), 2);
68         distance = sqrt(distance);
69         double radii = (PLAYER_RADIUS + COLLIDE_RADIUS);
70
71         if (distance < radii && terminals[i].checkIfOn())
72         {
73             return true;
74         }
75     }
76
77     return false;
78 }
79
80 bool CollisionEngine::collideWalls()
81 {
82     // Gotta check doors first
83     // And if you hit an open door
84     // You just ignore collision
85     // Because otherwise you can't fit
86     for (auto i : doors)
87     {
88         double distance = fabs(Cam.x * i.a + Cam.y * i.b + Cam.z * i.c + i
            .d); // Distance from door
89
90         if ((distance / i.getNorm() < PLAYER_RADIUS) && i.isInBounds())
91         {
92             if (i.isOpen) return false;
93             else return true;
94         }
95     }
96
97     for (auto i : walls)
98     {
99         double distance = fabs(Cam.x * i.a + Cam.y * i.b + Cam.z * i.c + i
            .d); // Distance from wall
100
101         if ((distance / i.getNorm() < PLAYER_RADIUS) && i.isInBounds())
            return true;
102     }
103
104     return false;
105 }
106
107 bool CollisionEngine::collide()
108 {
109     if (!collision)
110     {
111         return false;
112     }
113
114     checkInteract();
115     return (collideWalls() || collideObjects());
116 }

```

6.1.6 Console.h

```
1  /*****\
2  * Connsole.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the Console Class, *
8  * As well as the Trip struct for holding three integers *
9  * The Developer Console takes input from the user and *
10 * Activates various effects based upon what the user has *
11 * Typed in. *
12 \*****/
13
14 #ifndef CONSOLE_H
15 #define CONSOLE_H
16
17 // To act as a circular buffer for console history
18 #include <deque>
19 // Stores actual console input
20 #include <vector>
21 // std::string
22 #include <string>
23 // For processing text
24 #include "TextEngine.h"
25
26 // Windows API
27 #include <shlobj.h>
28
29
30 // To make rgb values easier to store
31 #include "Triple.h"
32
33 class Console
34 {
35 private:
36     /**** Variables for the console itself ****/
37
38     // Triples for good color, bad color, and neutral colors
39     Triple VALID_COLOR, INVALID_COLOR, NEUTRAL_COLOR;
40     // What the console "says" (aka what appears on screen)
41     std::deque<std::string> console_log;
42     // The colors of said strings
43     std::deque<Triple> console_color;
44     // Contains the actual player input
45     std::vector<std::string> console_input;
46     // The current (finished) input being processed
47     std::string currentInput;
48     // The current (unfinished) input being type
49     std::string currentText;
50     // Console History
51     TextEngine log;
52
53     // Path to core.sav
54     char CHAR_PATH[MAX_PATH];
```



```

55     std::string SAVE_PATH;
56
57     // Is the console active or not
58     bool isActive;
59
60     // The bottom of the console
61     const int SCREENBOTTOM = 500;
62
63     // Prints the current input and console_history
64     void printInput();
65     // Processes completed input
66     void processInput();
67
68     // Command functions
69
70     // Toggles collision on and off
71     void toggleCollision();
72
73     // Toggles godMode on and off
74     void toggleGod();
75
76     // Decrpyts the entry in core.sav
77     void decrpytSave();
78
79     // Shutdowns program
80     void halt();
81
82     // Clears the console log
83     void clear();
84
85     // Writes input to core.sav
86     void writeToSave(std::string input);
87
88     // Reads a bit from the file
89     void readFromFile(std::string input);
90
91     // Changes the currently played track
92     void playSong(std::string input);
93
94 public:
95     // Initializes VALID_COLOR, INVALID_COLOR, NEUTRAL_COLOR, and SAVE_PATH
96     Console();
97     // Manages console functions if input has been provided
98     void activate(std::string input, std::string text);
99     // Manages console function if input is still being provided
100    void activate(std::string text);
101    // Returns the console_input[count]
102    std::string getHist(int count);
103    // Returns console_input.size()
104    int getHistNum();
105
106 };
107
108 #endif

```

6.1.7 Console.cpp

```

1  /*****\
2  * Console.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the Console class *
8  * For more information, see Console.cpp *
9  \*****/
10
11 // File I/O
12 #include <fstream>
13
14 // Class declaration
15 #include "Console.h"
16
17 // For saving and loading
18 #include "SaveManager.h"
19
20 // System log
21 #include "Logger.h"
22
23 // Contains global environment variables
24 #include "Globals.h"
25
26 // Return codes
27 #include "Return.h"
28
29 using namespace std;
30
31 Console::Console()
32 {
33     // Green!
34     VALID_COLOR = makeTrip(0, 1, 0);
35     // Red!
36     INVALID_COLOR = makeTrip(1, 0, 0);
37     // Gray!
38     NEUTRAL_COLOR = makeTrip(1, 1, 1);
39
40     // Get path to documents
41     HRESULT ret = SHGetFolderPath(NULL, CSIDL_PERSONAL, NULL,
42     SHGFP_TYPE_CURRENT, CHAR_PATH);
43     // Assign to SAVE_PATH
44     SAVE_PATH = CHAR_PATH;
45     // Concatenate save file
46     SAVE_PATH += "\\The God Core\\core.sav";
47 }
48
49 void Console::activate(string input, string text)
50 {
51     currentInput = input;
52     // This should be empty. But just incase.
53     currentText = text;
54
55     processInput();
56     printInput();

```

```

56 }
57
58 void Console::activate(string text)
59 {
60     currentText = text;
61
62     printInput();
63 }
64
65 void Console::printInput()
66 {
67     deque<string>::iterator it = console_log.begin();
68     deque<Triple>::iterator jt = console_color.begin();
69     // Iterates through the console's current log and prints it to the screen
70     for (it; it != console_log.end(); it++, jt++)
71     {
72         //                                     Index of it
73         log.printString(0, 10 + 20 * (it - console_log.begin()),
74                         jt->a, jt->b, jt->c, *it);
75     }
76
77     // Prints whatever the user is typing
78     log.printString(0, SCREENBOTTOM / 2.4, 1, 1, 1, currentText);
79 }
80
81 void Console::processInput()
82 {
83     // TODO: Break this behemoth up into little, managable functions
84
85     if (currentInput == "TogClip")
86         toggleCollision();
87
88     else if (currentInput == "TogGod")
89         toggleGod();
90
91     else if (currentInput.substr(0, 5) == "Save ")
92         writeToSave(currentInput.substr(5)); // Save everything after "
93         Save "
94
95     else if (currentInput == "Decrypt")
96         decryptSave();
97
98     else if (currentInput.substr(0, 5) == "Read ")
99         readFromFile(currentInput.substr(5)); // Read everything after "
100         Read "
101
102     else if (currentInput == "Halt")
103         halt();
104
105     else if (currentInput == "Clear")
106         clear();
107
108     else if (currentInput.substr(0, 5) == "Play ")
109         playSong(currentInput.substr(5)); // Process everything after "
110         Play "

```

```

109     else if (currentInput == "Goto Main")
110     {
111         isInMain = true;
112         isInConsole = false;
113         HUD.toggleConsole();
114     }
115
116     // Invalid command
117     else
118     {
119         console_log.push_back("ERROR: Do not recognize \"" + currentInput
120                               + "\",");
121         console_color.push_back(INVALID_COLOR);
122     }
123
124     // Clears the top of the console if too much history is added
125     if (console_log.size() > 9)
126     {
127         console_log.pop_front();
128         console_color.pop_front();
129     }
130
131     // Store the current input
132     console_input.push_back(currentInput);
133 }
134 void Console::writeToSave(string input)
135 {
136     // Writes whatever is in input to the save file.
137     // Probably not going to be good for loading purposes
138
139     SaveManager Jesus;
140
141     Jesus.saveLevel();
142
143     console_log.push_back("Saved: " + input);
144     console_color.push_back(VALID_COLOR);
145 }
146
147 void Console::readFromFile(string input)
148 {
149     // Syntax = Read core.sav
150     if (input == "core.sav")
151     {
152         ifstream infile(SAVE_PATH);
153
154         string text;
155
156         // For now, core.sav only has one line. Hopefully I'll update this
157         // when I change that
158         infile >> text;
159
160         console_log.push_back(text);
161         console_color.push_back(VALID_COLOR);
162     }

```

```

163 // Syntax = Read TAG FILE
164 else
165 {
166     // There should be a space separating the file and the tag. We
167     // find that space
168     size_t pos = input.find(' ');
169
170     // If there ain't no space
171     if (pos == string::npos)
172     {
173         console_log.push_back("ERROR: No tag detected");
174         console_color.push_back(INVALID_COLOR);
175     }
176
177     // Hooray! There's a space
178     else
179     {
180         string tag = input.substr(0, pos);
181         string file = input.substr(pos + 1); // +1 to avoid the
182         // space
183
184         const char* TEXT_PATH = "Resources\\Text\\";
185         string fullPath = TEXT_PATH + file;
186
187         // Simply to test for the file's existence
188         ifstream infile(fullPath);
189
190         string text;
191         getline(infile, text);
192
193         // If there ain't no file
194         if (!infile)
195         {
196             console_log.push_back("ERROR: File \"" + file +
197             "\" not found");
198             console_color.push_back(INVALID_COLOR);
199         }
200
201         // Hooray! There's a file
202         else
203         {
204             console_log.push_back("Reading \"" + file + "\"
205             with tag \"" + tag + '\"');
206             console_color.push_back(VALID_COLOR);
207
208             vector<string> readText = log.getText(file, tag);
209
210             vector<string>::iterator it;
211
212             for (it = readText.begin(); it != readText.end();
213             it++)
214             {
215                 // Push everything we found into the log
216                 console_log.push_back(*it);
217                 console_color.push_back(NEUTRAL_COLOR);
218             }
219         }
220     }
221 }

```

```

214                                     // So we don't grow too much, keep bounds
                                     checking
215                                     if (console_log.size() > 9)
216                                     {
217                                         console_log.pop_front();
218                                         console_color.pop_front();
219                                     }
220                                 }
221                            }
222
223                            infile.close();
224                        }
225                    }
226 }
227
228 void Console::toggleCollision()
229 {
230     console_log.push_back("Noclip toggled.");
231     console_color.push_back(VALID_COLOR);
232
233     collision = !collision;
234 }
235
236 void Console::toggleGod()
237 {
238     console_log.push_back("God Mode toggled.");
239     console_color.push_back(VALID_COLOR);
240
241     godMode = !godMode;
242 }
243
244 void Console::decryptSave()
245 {
246     SaveManager Jesus;
247
248     console_log.push_back(Jesus.readSave());
249     console_color.push_back(VALID_COLOR);
250 }
251
252 void Console::halt()
253 {
254     Logger log;
255     log.logLine("Exiting via console");
256     exit(EXIT_OK);
257 }
258
259 void Console::clear()
260 {
261     console_log.clear();
262     console_color.clear();
263     console_input.clear();
264 }
265
266 void Console::playSong(string input)
267 {
268     int sNum = getSNum(input);

```

```

269
270     if (sNum == -1) // Invalid input
271     {
272         console_log.push_back("ERROR: " + input + " not a valid song file
273                                ");
274         console_color.push_back(INVALID_COLOR);
275     }
276     else // Valid input
277     {
278         songNum = sNum;
279         changeSong = true;
280         string song = getSongName(sNum);
281         console_log.push_back("Now playing " + song);
282         console_color.push_back(VALID_COLOR);
283     }
284 }
285
286 string Console::getHist(int count)
287 {
288     int size = console_input.size();
289     if (console_input.empty())
290     {
291         return "";
292     }
293
294     // If, somehow, a fool manages to get a variable that is out of bounds
295
296     else if (count >= size)
297     {
298         return console_input.back();
299     }
300
301     else if (count < 0)
302     {
303         return console_input.front();
304     }
305
306     else
307     {
308         return console_input[size - count - 1];
309     }
310 }
311
312 int Console::getHistNum()
313 {
314     return console_input.size();
315 }

```

6.1.8 Cylinder.h

```

1  /*****\
2  * Cylinder.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *

```

```

7  * This file contains the declaration of the Cylinder Class, *
8  * Which contains the functionality to load and display a    *
9  * Cylindrical object in game                               *
10 \*****/
11
12 #ifndef CYLINDER_H
13 #define CYLINDER_H
14
15 #include <cstdlib>
16
17 #include <GL\glut.h>
18
19 class Cylinder
20 {
21 private:
22     // A few variables to control the shape of the cylinder
23     double baseRadius, topRadius, height;
24     int stacks, slices;
25
26     // Arrays for the location, orientation, and color of the cylinder
27     double translate[3], rotate[3], color[4];
28     // A thingamajig for glut
29     GLUQuadric *quad;
30 public:
31     Cylinder(double _baseRadius, double _topRadius, double _height, int
        _stacks, int _slices,
32             const double(&_translate)[3], const double(&_rotate)[3], const
        double (&_color)[4]);
33
34     void Display();
35     ~Cylinder();
36 };
37
38 #endif

```

6.1.9 Cylinder.cpp

```

1  /*****\
2  * Cylinder.cpp                                *
3  * This file was created by Jeremy Greenburg    *
4  * As part of The God Core game for the University of    *
5  * Tennessee at Martin's University Scholars Organization *
6  *                                                    *
7  * This file contains the definition of the Cylinder class. *
8  * for more information, see Cylinder.h          *
9  \*****/
10
11 #include "Cylinder.h"
12
13 // For copying
14 #include <iterator>
15 #include <utility>
16
17 using namespace std;
18
19 Cylinder::Cylinder(double _baseRadius, double _topRadius, double _height, int
    _stacks, int _slices,

```



```

20         const double(&_translate)[3], const double(&_rotate)[3], const double(&
           _color)[4])
21     {
22         baseRadius = _baseRadius;
23         topRadius = _topRadius;
24         height = _height;
25         stacks = _stacks;
26         slices = _slices;
27
28         copy(begin(_color), end(_color), color);
29         copy(begin(_translate), end(_translate), translate);
30         copy(begin(_rotate), end(_rotate), rotate);
31
32         quad = gluNewQuadric();
33     }
34
35     Cylinder::~Cylinder()
36     {
37         //gluDeleteQuadric(quad);
38     }
39
40     void Cylinder::Display()
41     {
42         glColor4d(color[0], color[1], color[2], color[3]);
43
44         glPushMatrix();
45
46         glTranslated(translate[0], translate[1], translate[2]);
47         glRotated(rotate[0], 1, 0, 0);
48         glRotated(rotate[1], 0, 1, 0);
49         glRotated(rotate[2], 0, 0, 1);
50
51         gluCylinder(quad, baseRadius, topRadius, height, slices, stacks);
52
53         glPopMatrix();
54     }

```

6.1.10 Door.h

```

1  /*****\
2  * Door.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the Door class *
8  * It's mostly a fancy wrapper for a Plane with a bit *
9  * Of added functionality *
10 \*****/
11
12 #ifndef DOOR_H
13 #define DOOR_H
14
15 // Class decleration
16 #include "Plane.h"
17 // std::string
18 #include <string>

```

```

19
20 // Figure out a way to bind a controller to the door to activate it.
21 class Door
22 {
23 private:
24     // Name, so a switch can find it
25     std::string id;
26     // The physical door
27     Plane rect;
28 public:
29     // Is the door open?
30     bool isOpen;
31     // Plane's a, b, c, and d.
32     // For easier access
33     double a, b, c, d;
34
35     // Takes in the initial Plane and name
36     Door(Plane _rect, std::string _id);
37     // Calls rect.Display()
38     void Display();
39     // Returns rect.getNorm()
40     double getNorm();
41     // Returns id
42     std::string getID();
43     // Returns rect.isInBounds()
44     bool isInBounds();
45 };
46
47 #endif

```

6.1.11 Door.cpp

```

1  /*****\
2  * Door.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the Door class. *
8  * for more information, see Door.h *
9  \*****/
10
11 // Class declaration
12 #include "Door.h"
13
14 using namespace std;
15
16 Door::Door(Plane _rect, std::string _id) : rect(_rect), id(_id)
17 {
18     isOpen = false;
19     a = rect.a;
20     b = rect.b;
21     c = rect.c;
22     d = rect.d;
23 };
24
25 void Door::Display()

```

```

26 {
27     if (!isOpen) rect.Display();
28 }
29
30 double Door::getNorm()
31 {
32     return rect.getNorm();
33 }
34
35 string Door::getID()
36 {
37     return id;
38 }
39
40 bool Door::isInBounds()
41 {
42     return rect.isInBounds();
43 }

```

6.1.12 GameManager.h

```

1  /*****\
2  * GameManager.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the GameManger class*
8  * Which oversees and manages the flow of the game *
9  \*****/
10
11 #ifndef GAMEMANAGER_H
12 #define GAMEMANAGER_H
13
14 //***** LIBRARIES AND CLASSES *****\
15
16 // For the keyboard functionality
17 #include "Keyboard.h"
18
19 // glut really wants cstdlib here
20 #include <cstdlib>
21
22 // For arrays of strings
23 #include <string>
24 #include <vector>
25
26 // OpenGL API
27 #include <GL\glut.h>
28
29 // Standard I/O for debugging
30 #include <iostream>
31
32 // To manage background music
33 #include "MusicManager.h"
34
35 // To manage saving and loading
36 #include "SaveManager.h"

```

```

37
38 class GameManager
39 {
40 private:
41     // Variables
42
43     // Objects
44     MusicManager SoundSystem;
45     Keyboard board;
46
47     // Because the main menu is dumb, we have to know when to get a click
48     bool processClick = false;
49
50     // When in the main menu, mouse coords of a click
51     int mouse_x, mouse_y;
52
53     // Functions
54
55 public:
56
57     // Captures mouse clicks
58     void mouse(int button, int state, int x, int y);
59     // Captures mouse motion
60     void motionPassive(int x, int y);
61     // CHanges window size
62     void changeSize(int w, int h);
63     // Manages scene display
64     void manageScenes();
65     // Displaying function
66     void draw();
67     // Function to bring about game end on Level 4
68     void endGame();
69     // Normal key presses
70     void normal(unsigned char key, int x, int y);
71     // Key releases
72     void key_up(unsigned char key, int x, int y);
73     // Special keys
74     void special(int key, int x, int y);
75     // To manage playing and releasing music
76     void manageMusic();
77
78     // Wether or not core.sav exists
79     bool canContinue;
80
81 };
82
83 #endif

```

6.1.13 GameManager.cpp

```

1  /*****\
2  * GameManager.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the defintion of the GameManager class.*

```

```

8  * for more information, see GameManager.h *
9  \*****/
10
11 // Class declaration
12 #include "GameManager.h"
13 // Globals
14 #include "Globals.h"
15 // Level
16 #include "Level.h"
17 // Main Menu
18 #include "MainMenu.h"
19
20 #include "Logger.h"
21
22 #include "Return.h"
23
24 using namespace std;
25
26 void GameManager::mouse(int button, int state, int x, int y)
27 {
28     if (button == GLUT_RIGHT_BUTTON)
29     {
30         // Jokes on my I never ended up using the right button
31         if (state == GLUT_DOWN)
32         {
33
34         }
35
36         else
37         {
38
39         }
40     }
41
42     else if (button == GLUT_LEFT_BUTTON)
43     {
44         if (state == GLUT_DOWN)
45         {
46             if (isInMain)
47             {
48                 mouse_x = x;
49                 mouse_y = y;
50                 processClick = true;
51             }
52
53             Logger log;
54             vector<string> output = { "X: ", to_string(x), " ", "Y:",
55                                     to_string(y) };
56             log.logLine(output);
57
58         }
59
60         else
61         {
62
63         }
64     }
65 }

```

```

63 }
64
65 void GameManager::motionPassive(int x, int y)
66 {
67     static int _x = 0, _y = 0;
68
69     // If nothing else is happening basically
70     if (!isInConsole && !isInTerminal && !isInMain)
71     {
72         if (x > _x)
73         {
74             Cam.lookRight();
75             _x = x;
76         }
77
78         else if (x < _x)
79         {
80             Cam.lookLeft();
81             _x = x;
82         }
83
84         if (y < _y)
85         {
86             Cam.lookUp();
87             _y = y;
88         }
89
90         else if (y > _y)
91         {
92             Cam.lookDown();
93             _y = y;
94         }
95
96         // Loop around to the other side of the screen
97
98         bool updateMouse = false;
99         int newY = y, newX = x;
100         if (y == 0 || y > 700)
101         {
102             updateMouse = true;
103             newY = 300;
104             _y = 300;
105         }
106
107         if (x == 0 || x > 700)
108         {
109             updateMouse = true;
110             newX = 300;
111             _x = 300;
112         }
113
114         if (updateMouse)
115         {
116             glutWarpPointer(newX, newY);
117         }
118     }

```

```

119 }
120
121 void GameManager::changeSize(int w, int h)
122 {
123     // Don't want to divide by zero
124     if (h == 0)
125         h = 1;
126
127     double ratio = w * 1.0 / h;
128
129     // Use the Projection Matrix
130     glMatrixMode(GL_PROJECTION);
131
132     // Reset Matrix
133     glLoadIdentity();
134
135     // Set the viewport to be the entire window
136     glViewport(0, 0, w, h);
137
138     // Set the correct perspective.
139     gluPerspective(45, ratio, 1, 100);
140
141     // Get Back to the Modelview
142     glMatrixMode(GL_MODELVIEW);
143 }
144
145 void GameManager::draw()
146 {
147     if (loading)
148     {
149         lvl.loadLevel(curr_level);
150
151         loading = false;
152
153         // Save current progress after loading level
154         SaveManager Jesus; // saves
155         Jesus.saveLevel();
156     }
157
158     else
159     {
160         lvl.displayLevel();
161     }
162 }
163
164 void GameManager::endGame()
165 {
166     if (loading)
167     {
168         lvl.loadLevel(curr_level);
169
170         loading = false;
171
172         // Save current progress after loading level
173         SaveManager Jesus; // saves
174         Jesus.saveLevel();

```

```

175     }
176
177     else
178     {
179         // The time left for each segment
180         static int timeLeft = 1000;
181         // The last level is divided into 3 segments
182         static int segment = 1;
183         // Wether the current segment has been initialized yet
184         static bool initSegment = true;
185
186         // The last portion of the game is divided into 3 segments
187         if (segment == 1)
188         {
189             HUD.displayWarning("");
190             glClearColor(1, 1, 1, 1);
191         }
192
193         else if (segment == 2)
194         {
195             if (initSegment)
196             {
197                 HUD.displayWarning("QUANT");
198                 initSegment = false;
199             }
200
201             for (unsigned i = 0; i < walls.size(); i++)
202             {
203                 walls[i].mutate();
204             }
205         }
206
207         else if (segment == 3)
208         {
209             if (initSegment)
210             {
211                 HUD.goFade(15);
212                 HUD.setStatus("INFO-UN");
213                 initSegment = false;
214             }
215
216             for (unsigned i = 0; i < walls.size(); i++)
217             {
218                 walls[i].mutate();
219             }
220         }
221
222         else
223         {
224             // Return to main menu at game end
225             isInMain = true;
226
227             // Return everything to as it was before level 4
228             HUD.setStatus("INFO-WELL");
229             HUD.displayWarning("");
230             segment = 1;

```



```

231             HUD.goDark(0);
232         }
233
234         // Switch segments
235         if (timeLeft == 0)
236         {
237             timeLeft = 1000;
238             segment++;
239             initSegment = true;
240         }
241         timeLeft--;
242
243
244         // Draw the titular object
245         glPushMatrix();
246         glTranslated(0, 0, -7);
247         glColor4d(.9, .9, .9, 1);
248         glutSolidSphere(3, 50, 50);
249         glPopMatrix();
250
251         lvl.displayLevel();
252     }
253 }
254
255 void GameManager::manageScenes()
256 {
257     // If we need to change the song, we can do it here
258     if (changeSong)
259     {
260         manageMusic();
261     }
262
263     // Clears the previous drawing
264     glClear(GL_COLOR_BUFFER_BIT | GL_DEPTH_BUFFER_BIT);
265
266     if (isInTerminal)
267     {
268         activeTerminal->DisplayScreen();
269     }
270
271     else if (isInMain)
272     {
273         // Enable using textures (pictures)
274         glutSetCursor(GLUT_CURSOR_LEFT_ARROW);
275         static MainMenu MM;
276
277         // For some reason, MM breaks horribly when it's a global or class
278         // member
279         // So we'll just handle mouse clicks in the display function
280         // Rather than the mouse click function
281         // Because I'm a competent programmer
282         if (processClick)
283         {
284             MM.getClick(mouse_x, mouse_y);
285             processClick = false;
286         }
287     }
288 }

```

```

286
287         MM.display();
288     }
289
290     // glutSetCursor(GLUT_CURSOR_LEFT_ARROW); Keypads maybe?
291
292     else
293     {
294         // Enable using textures (pictures)
295         glutSetCursor(GLUT_CURSOR_NONE);
296
297         if (curr_level != "LEVELFOUR") draw();
298
299         else endGame();
300
301         // Moves the camera to the correct position
302         Cam.Display();
303
304         // Prompt the user to interact if we should
305         if (interactivity) HUD.displayWarning("INTERACT");
306         else if (curr_level != "LEVELFOUR") HUD.displayWarning("");
307
308         // Prints the HUD
309         HUD.DisplayHUD();
310     }
311
312     // Displays the current drawing
313     glutSwapBuffers();
314 }
315
316 void GameManager::manageMusic()
317 {
318     // All variables need to persist between frames
319     static SoundClass background;
320
321     SoundSystem.releaseSound(background);
322     changeSong = false;
323
324     // Because you can never have too much bounds checking
325     if (songNum >= 0 && songNum <= 9)
326     {
327         std::string song = getSongName(songNum);
328         SoundSystem.makeSound(&background, song.c_str());
329         SoundSystem.playSound(background);
330     }
331 }
332
333 // Normal key presses
334 void GameManager::normal(unsigned char key, int x, int y)
335 {
336     board.normal(key, x, y);
337 }
338
339 // Key releases
340 void GameManager::key_up(unsigned char key, int x, int y)
341 {

```

```

342         board.key_up(key, x, y);
343     }
344
345     // Special keys
346     void GameManager::special(int key, int x, int y)
347     {
348         board.special(key, x, y);
349     }

```

6.1.14 GCTypes.h

```

1  /*****\
2  * GCTypes.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains integer types corresponding to various *
8  * In game object types *
9  \*****/
10
11 #ifndef GC_TYPES_H
12 #define GC_TYPES_H
13
14 // Object Types
15
16 #define T_NULL 0 // Nothing
17 #define T_DOOR 1 // Door
18 #define T_TERMINAL 2 // Terminal
19 #define T_SWITCH 3 // Switch
20 #define T_LEVEL_END 4 // Switch that ends level
21
22 typedef int Gctype;
23
24 #endif

```

6.1.15 Globals.h

```

1  /*****\
2  * Globals.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the Globals *
8  * All of them. *
9  * Thers a lot of them *
10 \*****/
11
12 #ifndef GLOBALS_H
13 #define GLOBALS_H
14
15 // ALLLLLLL the classes
16 #include "HeadsUpDisplay.h"
17 #include "CameraControl.h"
18 #include "Level.h"
19 #include "Terminal.h"

```

```

20 #include "Door.h"
21 #include "Switch.h"
22 #include "Plane.h"
23 #include "Trigger.h"
24 #include "Cylinder.h"
25
26 // Remember that if you're doing anything else, globals are bad.
27 // But we're in the hellscape that is graphics
28 // There are no rules here
29 // Only madness dwells here
30
31 // Typedefs make life easy
32 typedef std::vector<Plane> vr;
33 typedef std::vector<Door> vd;
34 typedef std::vector<Switch> vs;
35 typedef std::vector<Terminal> vt;
36 typedef std::vector<Trigger> vtr;
37 typedef std::vector<Cylinder> vc;
38
39 // Pointers to various interactive objects
40 extern Switch *activeSwitch;
41 extern Terminal *activeTerminal;
42
43 // Vectors containing all of the level's assets
44 extern vr walls;
45 extern vd doors;
46 extern vs switches;
47 extern vt terminals;
48 extern vtr triggers;
49 extern vc cylinders;
50
51 extern bool
52     // Are we colliding / Can we die?
53     collision, godMode,
54     // Go dim or go dark?
55     goDim, goDark,
56     // Dunno if I actually need this one
57     loading,
58     // Is in various different stages of non-normal play
59     isInConsole, isInTerminal, isInMain,
60     // Should we change the song?
61     changeSong,
62     // Is something in interaction range?
63     interactivity;
64
65 // Number of song to change to
66 extern int songNum;
67
68 // Current level (int and string)
69 extern int levelNum;
70 extern std::string curr_level;
71
72 // Constant strings of the song names
73 extern const char *SONG0, *SONG1, *SONG2, *SONG3, *SONG4, *SONG5,
74     *SONG6, *SONG7, *SONG8, *SONG9;
75

```

```

76 // A few global objects
77 extern HeadsUpDisplay HUD;
78 extern CameraControl Cam;
79 extern Level lvl;
80
81 // Converts a songname to an integer
82 int getSongNum(std::string input);
83 // Converts an integer to a songname
84 std::string getSongName(int input);
85 // Converts a level name to an integer
86 int getLevelNum(std::string input);
87 // Converts level_num to a string in curr_level
88 std::string getLevelString(int input);
89 // Safely advance the song
90 void advanceMusic();
91
92 #endif

```

6.1.16 Globals.cpp

```

1  /*****\
2  * Globals.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file instantiates the global variables *
8  \*****/
9
10 #include "Globals.h"
11
12 vr walls;
13 vd doors;
14 vs switches;
15 vt terminals;
16 vtr triggers;
17 vc cylinders;
18
19 Switch *activeSwitch = NULL;
20 Terminal *activeTerminal = NULL;
21
22 bool collision = true;
23 bool godMode = false;
24 bool goDim = false;
25 bool goDark = false;
26 bool loading = true;
27 bool isInConsole = false;
28 bool isInTerminal = false;
29 bool isInMain = true;
30 bool changeSong = true;
31 bool interactivity = false;
32
33 int songNum = 0;
34
35 int levelNum = 0;
36 std::string curr_level = "LEVELZERO";
37

```

```

38 const char* SONG0 = "Dark Fog.mp3";
39 const char* SONG1 = "Mismer.mp3";
40 const char* SONG2 = "One Sly Move.mp3";
41 const char* SONG3 = "Hypnothis.mp3";
42 const char* SONG4 = "Cold Hope.mp3";
43 const char* SONG5 = "Spacial Harvest.mp3";
44
45 HeadsUpDisplay HUD;
46 CameraControl Cam;
47 Level lvl;
48
49 int getSongNum(std::string input)
50 {
51     if (input == SONG0 || input == "0")
52         return 0;
53     if (input == SONG1 || input == "1")
54         return 1;
55     if (input == SONG2 || input == "2")
56         return 2;
57     if (input == SONG3 || input == "3")
58         return 3;
59     if (input == SONG4 || input == "4")
60         return 4;
61     if (input == SONG5 || input == "5")
62         return 5;
63     return -1; // Invalid song
64 }
65
66 std::string getSongName(int input)
67 {
68     std::string ret;
69     switch (input)
70     {
71     case 0: ret = SONG0;
72         break;
73     case 1: ret = SONG1;
74         break;
75     case 2: ret = SONG2;
76         break;
77     case 3: ret = SONG3;
78         break;
79     case 4: ret = SONG4;
80         break;
81     case 5: ret = SONG5;
82         break;
83     default: ret = "\\0";
84         break;
85     }
86
87     return ret;
88 }
89
90 int getLevelNum(std::string input)
91 {
92     if (input == "LEVELZERO" || input == "LEVELZERO\n")
93         return 0;

```

```

94         if (input == "LEVELONE" || input == "LEVELONE\n")
95             return 1;
96         if (input == "LEVELTWO")
97             return 2;
98         if (input == "LEVELTHREE")
99             return 3;
100        if (input == "LEVELFOUR")
101            return 4;
102        return -1; // Invalid song
103    }
104
105    std::string getLevelString(int input)
106    {
107        std::string ret;
108        switch (input)
109        {
110            case 0: ret = "LEVELZERO";
111                    break;
112            case 1: ret = "LEVELONE";
113                    break;
114            case 2: ret = "LEVELTWO";
115                    break;
116            case 3: ret = "LEVELTHREE";
117                    break;
118            case 4: ret = "LEVELFOUR";
119                    break;
120            default: ret = "ERROR";
121                    break;
122        }
123
124        return ret;
125    }
126
127    void advanceMusic()
128    {
129        songNum++;
130        if (songNum > 5) songNum = 0;
131    }

```

6.1.17 HeadsUpDisplay.h

```

1  /*****\
2  * HeadsUpDisplay.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the HeadsUpDisplay *
8  * Class, which created an Orthoganl Matrix infront of the *
9  * Screen which allows for a 2D Heads Up Display to be *
10 * Printed before the user at any time *
11 * It also passes input to the developer console *
12 \*****/
13
14 #ifndef HEADSUPDISPLAY
15 #define HEADSUPDISPLAY
16

```

```

17 // Base class for 2D operations
18 #include "TwoD.h"
19
20 // For displaying text in the HUD
21 #include "TextEngine.h"
22 // The Developer Console
23 #include "Console.h"
24
25 class HeadsUpDisplay : public TwoD
26 {
27 private:
28     // Duration of time to dim screen (Goes from black to clear as time
        progresses)
29     int dimTime = 0;
30     // Duration of time to go dark (completely black)
31     int darkTime = 0;
32     // Duration of the time to fade the screen (goes from clear to black as
        time progresses)
33     int fadeTime = 0;
34     // Wether or not to dim
35     bool dimNow = false;
36     // Wether or not to darken
37     bool darkNow = false;
38     // Wether or not to fade
39     bool fadeNow = false;
40     // Wether or not we are in developer console
41     bool devConsole = false;
42
43     // Tag to current alert
44     std::string currentAlert;
45     // Tag to current status
46     std::string currentStatus;
47     // Text to print to the screen
48     std::string currentText;
49     // What the user is typing
50     std::string currentInput;
51
52     // To Display text
53     TextEngine helmet;
54     // Dev Console
55     Console dev;
56
57     // Draws an info bar at the top of the screen
58     void drawHelmetBounds();
59     // Displays suit alerts
60     void DisplayAlerts();
61     // Draws the Heads Up Display
62     void drawHUD();
63     // Manages the dimming of the screen
64     void dim();
65     // Manages the darkening of the screen
66     void dark();
67     // Manages the fading of the screen
68     void fade();
69     // Draws the box which stores the info text
70     void drawInfoBox();

```



```

71         // Draws the developer console window
72         void drawConsole();
73         // Displays standard info in the top left corner
74         void displayInfo(std::string tag);
75
76
77     public:
78         // Manages the HUD
79         void DisplayHUD();
80
81         /****          ALTERATION FUNCTIONS          *****/
82         \**** Should always be called before DisplayHud *****/
83
84         // Tells the HUD how long to dim
85         void goDim(int time);
86
87         //Tells the HUD how long to go dark
88         void goDark(int time);
89         // Tels the HUD how long to fade for
90         void goFade(int time);
91         // Flips dev_console
92         void toggleConsole();
93
94         // Takes in a tag to print to screen
95         void displayWarning(std::string warning);
96
97         // Takes in a string to display in the status box
98         void setStatus(std::string status);
99
100        // Takes in a string to print to screen
101        void printToConsole(std::string text);
102
103        // Signifies a completed input to the console
104        void inputString(std::string text);
105
106        // Returns an item of the console's log
107        std::string getHist(int count);
108
109        // Returns the number of items in the console's log
110        int getHistNum();
111    };
112
113 #endif

```

6.1.18 HeadsUpDiplay.cpp

```

1  /*****\
2  * HeadsUpDisplay.cpp                                *
3  * This file was created by Jeremy Greenburg        *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  *                                                    *
7  * This file contains the definition of the HeadsUpDisplay *
8  * Class. For more information, see HeadsUpDisplay.h    *
9  \*****/
10
11 // Class Declaration

```

```

12 #include "HeadsUpDisplay.h"
13
14 // OpenGL API
15 #include <gl\glut.h>
16
17 // For counting seconds
18 #include <ctime>
19
20 // For displaying Planes
21 #include "Plane.h"
22
23 // For displaying triangles
24 #include "Triangle.h"
25
26 using namespace std;
27
28 void HeadsUpDisplay::drawHelmetBounds()
29 {
30     // Helmet bounds are black
31     double colors[4] = { 0, 0, 0, 1 };
32
33     // The top of the helmet
34     double top_vertices[9] =
35     {
36         SCREENRIGHT, SCREENTOP, -1,
37         SCREENLEFT, SCREENTOP, -1,
38         SCREENRIGHT / 2.0, SCREENBOTTOM / 20.0, -1
39     };
40
41     // The left of the hemlet
42     double left_vertices[9] =
43     {
44         SCREENLEFT, SCREENBOTTOM, -1,
45         SCREENLEFT, SCREENTOP, -1,
46         SCREENRIGHT / 20.0, 3 * SCREENBOTTOM / 5.0, -1
47     };
48
49     // The back of the helmet
50     double right_vertices[9] =
51     {
52         SCREENRIGHT, SCREENBOTTOM, -1,
53         SCREENRIGHT, SCREENTOP, -1,
54         19 * SCREENRIGHT / 20.0, 3 * SCREENBOTTOM / 5.0, -1
55     };
56
57     Triangle top_helm{ top_vertices, colors };
58     Triangle left_helm{ left_vertices, colors };
59     Triangle right_helm{ right_vertices, colors };
60
61     top_helm.Display2D();
62     left_helm.Display2D();
63     right_helm.Display2D();
64 }
65
66 void HeadsUpDisplay::DisplayAlerts()
67 {

```

```

68         helmet.openFile(.5 * SCREENRIGHT, .5 * SCREENBOTTOM,
69             1, 1, 1,
70             "suitAlerts.log", currentAlert);
71     }
72
73     void HeadsUpDisplay::dim()
74     {
75         static int startTime;
76         static bool timeSet = false;
77         if (dimNow)
78         {
79             if (!timeSet)
80             {
81                 startTime = time(NULL);
82                 timeSet = true;
83             }
84
85             int currentTime = time(NULL);
86             int timeElapsed = currentTime - startTime;
87             if (timeElapsed < dimTime)
88             {
89                 // A black square that grows more transparent as time
90                 // passes
91                 double colors[4] = { 0, 0, 0, (double)(dimTime -
92                     timeElapsed) / dimTime };
93                 double dimVert[12] =
94                 {
95                     SCREENLEFT, SCREENTOP, -1,
96                     SCREENLEFT, SCREENBOTTOM, -1,
97                     SCREENRIGHT, SCREENBOTTOM, -1,
98                     SCREENRIGHT, SCREENTOP, -1
99                 };
100                 Plane black{ dimVert, colors };
101                 black.Display2D();
102             }
103             else
104             {
105                 dimNow = false;
106                 timeSet = false;
107             }
108         }
109     }
110
111     void HeadsUpDisplay::fade()
112     {
113         static int startTime;
114         static bool timeSet = false;
115         if (fadeNow)
116         {
117             if (!timeSet)
118             {
119                 startTime = time(NULL);
120                 timeSet = true;
121             }

```

```

122
123     int currentTime = time(NULL);
124     int timeElapsed = currentTime - startTime;
125     if (timeElapsed < fadeTime)
126     {
127         // A black square that grows more transparent as time
128         // passes
129         double colors[4] = { 0, 0, 0, 1 - ((double)(fadeTime -
130         timeElapsed) / fadeTime) };
131         double dimVert[12] =
132         {
133             SCREENLEFT, SCREENTOP, -1,
134             SCREENLEFT, SCREENBOTTOM, -1,
135             SCREENRIGHT, SCREENBOTTOM, -1,
136             SCREENRIGHT, SCREENTOP, -1
137         };
138         Plane black{ dimVert, colors };
139         black.Display2D();
140     }
141     else
142     {
143         fadeNow = false;
144         timeSet = false;
145
146         // Go dark till game ends
147         darkNow = true;
148         darkTime = 1000;
149     }
150 }
151
152 }
153
154 void HeadsUpDisplay::dark()
155 {
156     static int startTime;
157     static bool timeSet = false;
158     if (darkNow)
159     {
160         if (!timeSet)
161         {
162             startTime = time(NULL);
163             timeSet = true;
164         }
165
166         int currentTime = time(NULL);
167         int timeElapsed = currentTime - startTime;
168         if (timeElapsed < darkTime)
169         {
170             // A black square that obscures vision
171             double colors[4] = { 0, 0, 0, 1 };
172             double dimVert[12] =
173             {
174                 SCREENLEFT, SCREENTOP, -1,
175                 SCREENLEFT, SCREENBOTTOM, -1,

```

```

176             SCREENRIGHT, SCREENBOTTOM, -1,
177             SCREENRIGHT, SCREENTOP, -1
178         };
179
180         Plane black{ dimVert, colors };
181         black.Display2D();
182     }
183
184     else
185     {
186         darkNow = false;
187         timeSet = false;
188     }
189 }
190 }
191
192 void HeadsUpDisplay::drawConsole()
193 {
194     double colors[4] = { .1, .1, .1, .9 };
195     double vertices[12] =
196     {
197         SCREENLEFT, SCREENTOP, -1,
198         SCREENLEFT, SCREENBOTTOM / 5, -1,
199         SCREENRIGHT, SCREENBOTTOM / 5, -1,
200         SCREENRIGHT, SCREENTOP, -1
201     };
202
203     Plane console_tab{ vertices, colors };
204     console_tab.Display2D();
205
206     if (currentInput != "")
207     {
208         dev.activate(currentInput, currentText);
209         currentInput.clear();
210     }
211
212     else
213     {
214         dev.activate(currentText);
215     }
216 }
217
218 void HeadsUpDisplay::drawInfoBox()
219 {
220     double colors[4] = { 0, 1, 1, .5 };
221     double vertices[12] =
222     {
223         SCREENLEFT, SCREENTOP, -1,
224         SCREENLEFT, SCREENBOTTOM / 10, -1,
225         SCREENRIGHT / 10, SCREENBOTTOM / 10, -1,
226         SCREENRIGHT / 10, SCREENTOP, -1
227     };
228
229     Plane info{ vertices, colors };
230     info.Display2D();
231 }

```

```

232
233 void HeadsUpDisplay::displayInfo(string tag)
234 {
235     helmet.openFile(SCREENLEFT, SCREENTOP + 20, 1, 1, 1,
236         "suitAlerts.log", currentStatus);
237 }
238
239 void HeadsUpDisplay::goDim(int time)
240 {
241     dimTime = time;
242     dimNow = true;
243 }
244
245 void HeadsUpDisplay::goDark(int time)
246 {
247     darkTime = time;
248     darkNow = true;
249 }
250
251 void HeadsUpDisplay::goFade(int time)
252 {
253     fadeTime = time;
254     fadeNow = true;
255 }
256
257 void HeadsUpDisplay::displayWarning(std::string warning)
258 {
259     currentAlert = warning;
260 }
261
262 void HeadsUpDisplay::setStatus(std::string status)
263 {
264     currentStatus = status;
265 }
266
267 void HeadsUpDisplay::printToConsole(std::string text)
268 {
269     currentText = text;
270 }
271
272 void HeadsUpDisplay::inputString(std::string text)
273 {
274     currentInput = text;
275 }
276
277 void HeadsUpDisplay::toggleConsole()
278 {
279     devConsole = !devConsole;
280 }
281
282 void HeadsUpDisplay::drawHUD()
283 {
284     drawHelmetBounds();
285
286     if (dimNow)
287     {

```

```

288         dim();
289     }
290
291     else if (fadeNow)
292     {
293         fade();
294     }
295
296     // Not else if due to fade -> dark transition
297     if (darkNow)
298     {
299         dark();
300     }
301
302     drawInfoBox();
303     displayInfo(currentStatus);
304
305     if (devConsole)
306     {
307         drawConsole();
308     }
309
310     if (currentAlert != "")
311     {
312         DisplayAlerts();
313     }
314 }
315
316 string HeadsUpDisplay::getHist(int count)
317 {
318     return dev.getHist(count);
319 }
320
321 int HeadsUpDisplay::getHistNum()
322 {
323     return dev.getHistNum();
324 }
325
326 void HeadsUpDisplay::DisplayHUD()
327 {
328     prepare2D();
329
330     drawHUD();
331
332     prepare3D();
333 }

```

6.1.19 Keyboard.h

```

1  /*****\
2  * Keyboard.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * * *
7  * This file contains the declaration of the Keyboard class, *
8  * which logs keypresses from the user and determines, *

```

```

9  * depending on the context, what action to take such.      *
10 \*****/
11
12 #ifndef KEYBOARD_H
13 #define KEYBOARD_H
14
15 // std::string
16 #include <string>
17
18 class Keyboard
19 {
20 private:
21     // Signals to recieve a part of the console's history
22     bool getPrev, getNext;
23
24 public:
25     // Normal keys
26     void normal(unsigned char key, int x, int y);
27     // To read console input
28     void inputConsole(unsigned char key, int x, int y);
29     // To read terminal input
30     void inputTerminal(unsigned char key, int x, int y);
31     // To interact with the world
32     void interact(unsigned char key, int x, int y);
33     // If a key is released
34     void key_up(unsigned char key, int x, int y);
35     // Special keys (functions, arrows, ect.)
36     void special(int key, int x, int y);
37     // Manages interactivity
38     void interact();
39 };
40
41 #endif

```

6.1.20 Keyboard.cpp

```

1  /*****\
2  * Keyboard.cpp                                *
3  * This file was created by Jeremy Greenburg    *
4  * As part of The God Core game for the University of      *
5  * Tennessee at Martin's University Scholars Organization  *
6  *                                                    *
7  * This file contains the defintion of the Keyboard class.  *
8  * for more information, see Keyboard.h          *
9  \*****/
10
11 // Class decleration
12 #include "Keyboard.h"
13
14 // std::string
15 #include <string>
16
17 // glut really wants cstdlib here
18 #include <cstdlib>
19
20 // OpenGL API
21 #include <GL\glut.h>

```



```

22
23 // To recieve and manage global variables
24 #include "Globals.h"
25 // Collision detection
26 #include "CollisionEngine.h"
27
28 // Return codes
29 #include "Return.h"
30 // System log
31 #include "Logger.h"
32
33 using namespace std;
34
35 void Keyboard::normal(unsigned char key, int x, int y)
36 {
37     // If we are currently capturing input
38     if (isInConsole)
39     {
40         inputConsole(key, x, y);
41     }
42
43     // If we're in a computer
44     else if (isInTerminal)
45     {
46         inputTerminal(key, x, y);
47     }
48
49     // Otherwise (as long we aren't in a menu)
50     else if (!isInMain)
51     {
52         interact(key, x, y);
53     }
54 }
55
56 void Keyboard::inputConsole(unsigned char key, int x, int y)
57 {
58     // User string input
59     static string input;
60     // Number in console history
61     static int count = 0;
62
63     // Up arrow, recieves the next older entry in the console's history
64     if (getPrev)
65     {
66         input = HUD.getHist(count);
67
68         if (count < HUD.getHistNum() - 1)
69         {
70             count++;
71         }
72
73         getPrev = false;
74     }
75
76     // Down arrow, recieves the next newer entry in the console's history
77     else if (getNext)

```

```

78     {
79         input = HUD.getHist(count);
80
81         if (count > 0)
82         {
83             count--;
84         }
85
86         getNext = false;
87     }
88
89     // Enter key, process and clear input
90     else if (key == 13)
91     {
92         HUD.inputString(input);
93         input.clear();
94         count = 0;
95     }
96
97     // Tilda, close the console
98     else if (key == '~' || isInConsole == false)
99     {
100         input.clear();
101         isInConsole = false;
102         HUD.toggleConsole();
103         count = 0;
104     }
105
106     // Backspace. Self explanatory
107     else if (key == 8 && !input.empty())
108     {
109         input.pop_back();
110     }
111
112     // Otherwise, type normally
113     else
114     {
115         input += key;
116     }
117
118     // Print what's been typed so far
119     HUD.printToConsole(input);
120 }
121
122 // Pretty much a copy pasta of inputConsole because I'm a terrible programmer
123 // I'll try to combine em in the future, I swear
124 // Just adjust all of these to do terminally stuff I guess
125 void Keyboard::inputTerminal(unsigned char key, int x, int y)
126 {
127     // TODO: Fix terminal input with active Terminal hijibis
128
129     // User string input
130     static string input;
131     // Number in console history
132     static int count = 0;
133

```

```

134 // Up arrow, recieves the next older entry in the console's history
135 if (getPrev)
136 {
137     input = activeTerminal->getHist(count);
138
139     if (count < activeTerminal->getHistNum() - 1)
140     {
141         count++;
142     }
143
144     getPrev = false;
145 }
146
147 // Down arrow, recieves the next newer entry in the console's history
148 else if (getNext)
149 {
150     input = activeTerminal->getHist(count);
151
152     if (count > 0)
153     {
154         count--;
155     }
156
157     getNext = false;
158 }
159
160 // Enter key, process and clear input
161 else if (key == 13)
162 {
163     activeTerminal->getInput(input);
164     input.clear();
165     count = 0;
166 }
167
168 // Backspace. Self explanatory
169 else if (key == 8 && !input.empty())
170 {
171     input.pop_back();
172 }
173
174 // Otherwise, type normally
175 else
176 {
177     input += key;
178 }
179
180 // Print what's been typed so far
181 activeTerminal->getText(input); // Drawing handled elsewhere?
182 }
183
184 void Keyboard::interact(unsigned char key, int x, int y)
185 {
186     CollisionEngine col;
187     // Speed at which the player moves
188     int speedMod = 1;
189

```

```

190     int modKey = glutGetModifiers();
191
192     if (modKey == GLUT_ACTIVE_SHIFT)
193     {
194         speedMod = 2;
195     }
196
197     else
198     {
199         speedMod = 1;
200     }
201
202     switch (key)
203     {
204     case 'w':
205     case 'W':
206         Cam.moveForward(speedMod);
207         if (col.collide())
208         {
209             Cam.moveBackward(speedMod);
210         }
211         break;
212     case 'a':
213     case 'A':
214         Cam.strafeRight();
215         if (col.collide())
216         {
217             Cam.strafeLeft();
218         }
219         break;
220     case 's':
221     case 'S':
222         Cam.moveBackward(speedMod);
223         if (col.collide())
224         {
225             Cam.moveForward(speedMod);
226         }
227         break;
228     case 'd':
229     case 'D':
230         Cam.strafeLeft();
231         if (col.collide())
232         {
233             Cam.strafeRight();
234         }
235         break;
236     case 'e':
237     case 'E':
238         interact();
239         break;
240     case '~':
241         isInConsole = true;
242         HUD.toggleConsole();
243         break;
244
245         // Enter

```

```

246         case 13:
247             //goDim = true;
248             break;
249
250             // Escape
251         case 27:
252             isInMain = true;
253             songNum = 0;
254             changeSong = true;
255             break;
256     }
257 }
258
259 void Keyboard::key_up(unsigned char key, int x, int y)
260 {
261     // I'm sure I'll do something smart here
262 }
263
264 void Keyboard::special(int key, int x, int y)
265 {
266     Logger log;
267     // We start in fullscreen
268     static bool fullScreen = true;
269     switch (key)
270     {
271     case GLUT_KEY_F1:
272         fullScreen = !fullScreen;
273         break;
274
275     case GLUT_KEY_F2:
276         // Only way to exit main loop.
277         log.logLine("Exiting via F2");
278         exit(EXIT_OK);
279         break;
280
281     case GLUT_KEY_F3:
282         Cam.resetCam();
283         break;
284
285     case GLUT_KEY_F4:
286         isInMain = !isInMain;
287         break;
288
289     case GLUT_KEY_F5:
290         log.logCamCoords();
291         break;
292
293     case GLUT_KEY_UP:
294         if (isInConsole || isInTerminal)
295         {
296             getPrev = true;
297             getNext = false;
298
299             // To ensure that the input is updated BEFORE next key
300             // press
301             normal(0, 0, 0);

```

```

301         }
302         break;
303
304     case GLUT_KEY_DOWN:
305         if (isInConsole || isInTerminal)
306         {
307             getNext = true;
308             getPrev = false;
309
310             // To ensure that the input is updated BEFORE next key
311             // press
312             normal(0, 0, 0);
313         }
314         break;
315     }
316
317     if (fullScreen)
318     {
319         glutFullScreen();
320     }
321     else
322     {
323         glutReshapeWindow(1367, 767);
324         glutPositionWindow(50, 50);
325     }
326 }
327
328 void Keyboard::interact()
329 {
330     // Only do things if we actually can
331     if (interactivity)
332     {
333         if (activeSwitch != NULL)
334         {
335             activeSwitch->toggleTarget();
336
337             for (unsigned int i = 0; i < triggers.size(); i++)
338             {
339                 triggers[i].tryToTrigger(activeSwitch, T_SWITCH);
340             }
341         }
342
343         else if (activeTerminal != NULL)
344         {
345             isInTerminal = true;
346
347             for (unsigned int i = 0; i < triggers.size(); i++)
348             {
349                 triggers[i].tryToTrigger(activeTerminal,
350                                         T_TERMINAL);
351             }
352         }
353     }

```

6.1.21 Level.h

```
1  /*****\
2  * Level.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the Level class *
8  * Which loads all level assets from a sqlite database *
9  * (data.db) *
10 \*****/
11
12 #ifndef LEVEL_H
13 #define LEVEL_H
14
15 // std::string
16 #include <string>
17 // std::vector
18 #include <vector>
19 // Planes for walls/doors/such else
20 #include "Plane.h"
21
22 // SQLite API
23 #include "sqlite3.h"
24
25 // Glut API
26 #include <GL\glut.h>
27
28 class Level
29 {
30 private:
31     // Used to load cylinders
32     GLUquadricObj *quadratic;
33     // The current level being loaded
34     std::string currLevel;
35
36     // Look, the names are self-explanatory
37     void loadWalls(sqlite3 *db);
38     void loadDoors(sqlite3 *db);
39     void loadCylinders(sqlite3 *db);
40     void loadSwitches(sqlite3 *db);
41     void loadTerminals(sqlite3 *db);
42     void loadTriggers(sqlite3 *db);
43
44     // Binds the triggering object and target object to a single trigger
45     bool bindTrigger(std::string id, std::string trigger, std::string
         triggerType);
46     bool bindTarget(std::string id, std::string target, std::string targetType
         );
47
48 public:
49     // Manages the loading of the level
50     void loadLevel(std::string levelName);
51     // Draws the level
52     void displayLevel();
```

```

53 };
54
55 #endif

```

6.1.22 Level.cpp

```

1  /*****\
2  * Level.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the Level class. *
8  * for more information, see Level.h *
9  \*****/
10
11 // Class declaration
12 #include "Level.h"
13 // To use Planes
14 #include "Plane.h"
15 // Vectors to plop stuff in
16 #include "Globals.h"
17 // Return codes
18 #include "Return.h"
19 // System log
20 #include "Logger.h"
21 // Object Types
22 #include "GCTypes.h"
23
24 #include <iostream>
25
26 using namespace std;
27
28 void Level::loadWalls(sqlite3 *db)
29 {
30     walls.clear();
31     // Prepared Statement
32     sqlite3_stmt *stm;
33     // SQL command
34     string cmd;
35     // Connection Error Test
36     int err;
37     cmd = "SELECT * FROM walls WHERE LEVEL = \"" + currLevel + "\"";
38
39     err = sqlite3_prepare(db, cmd.c_str(), -1, &stm, 0);
40
41     if (err != SQLITE_OK)
42     {
43         Logger log;
44         vector<string> output = { "FATAL ERROR: failed to load walls from", currLevel };
45         log.logLine(output);
46         exit(STATEMENT_ERROR);
47     }
48
49     // While we still get rows of output
50     while (sqlite3_step(stm) == SQLITE_ROW)

```



```

51     {
52         double x1, x2, x3, x4,
53                y1, y2, y3, y4,
54                z1, z2, z3, z4,
55                r, g, b, a;
56         string axis;
57
58         x1 = sqlite3_column_double(stm, 2);
59         x2 = sqlite3_column_double(stm, 3);
60         x3 = sqlite3_column_double(stm, 4);
61         x4 = sqlite3_column_double(stm, 5);
62
63         y1 = sqlite3_column_double(stm, 6);
64         y2 = sqlite3_column_double(stm, 7);
65         y3 = sqlite3_column_double(stm, 8);
66         y4 = sqlite3_column_double(stm, 9);
67
68         z1 = sqlite3_column_double(stm, 10);
69         z2 = sqlite3_column_double(stm, 11);
70         z3 = sqlite3_column_double(stm, 12);
71         z4 = sqlite3_column_double(stm, 13);
72
73         r = sqlite3_column_double(stm, 14);
74         g = sqlite3_column_double(stm, 15);
75         b = sqlite3_column_double(stm, 16);
76         a = sqlite3_column_double(stm, 17);
77
78         axis = reinterpret_cast<const char*>(sqlite3_column_text(stm, 18))
79             ;
80
81         char ax;
82         if (axis == "x") ax = 'x';
83         else if (axis == "y") ax = 'y';
84         else if (axis == "z") ax = 'z';
85         else ax = 0;
86
87         double verts[12] =
88         {
89             x1, y1, z1,
90             x2, y2, z2,
91             x3, y3, z3,
92             x4, y4, z4
93         };
94         double colors[4] = { r, g, b, a };
95
96         Plane rect(verts, colors, ax);
97
98         walls.push_back(rect);
99     }
100
101     /*
102     Logger log;
103     vector<string> output = { "Loaded walls on", currLevel };
104     log.logLine(output);
105     */

```

```

106         // Deconstructs the statement
107         sqlite3_finalize(stm);
108     }
109
110     void Level::loadDoors(sqlite3 *db)
111     {
112         doors.clear();
113         // Prepared Statement
114         sqlite3_stmt *stm;
115         // SQL command
116         string cmd;
117         // Connection Error Test
118         int err;
119         cmd = "SELECT * FROM doors WHERE LEVEL = \"" + currLevel + "\"";
120
121         err = sqlite3_prepare(db, cmd.c_str(), -1, &stm, 0);
122
123         if (err != SQLITE_OK)
124         {
125             Logger log;
126             vector<string> output = { "FATAL ERROR: Can't load doors while
                                     loading", currLevel };
127             log.logLine(output);
128
129             exit(STATEMENT_ERROR);
130         }
131
132         // While we still get rows of output
133         while (sqlite3_step(stm) == SQLITE_ROW)
134         {
135             double x1, x2, x3, x4,
136                   y1, y2, y3, y4,
137                   z1, z2, z3, z4,
138                   r, g, b, a;
139             string id;
140             string axis;
141
142             id = reinterpret_cast<const char*>(sqlite3_column_text(stm, 0));
143             x1 = sqlite3_column_double(stm, 2);
144             x2 = sqlite3_column_double(stm, 3);
145             x3 = sqlite3_column_double(stm, 4);
146             x4 = sqlite3_column_double(stm, 5);
147
148             y1 = sqlite3_column_double(stm, 6);
149             y2 = sqlite3_column_double(stm, 7);
150             y3 = sqlite3_column_double(stm, 8);
151             y4 = sqlite3_column_double(stm, 9);
152
153             z1 = sqlite3_column_double(stm, 10);
154             z2 = sqlite3_column_double(stm, 11);
155             z3 = sqlite3_column_double(stm, 12);
156             z4 = sqlite3_column_double(stm, 13);
157
158             r = sqlite3_column_double(stm, 14);
159             g = sqlite3_column_double(stm, 15);
160             b = sqlite3_column_double(stm, 16);

```

```

161         a = sqlite3_column_double(stm, 17);
162
163         a = sqlite3_column_double(stm, 17);
164
165         axis = reinterpret_cast<const char*>(sqlite3_column_text(stm, 18))
            ;
166
167         char ax;
168         if (axis == "x") ax = 'x';
169         else if (axis == "y") ax = 'y';
170         else if (axis == "z") ax = 'z';
171         else ax = 0;
172
173         double verts[12] =
174         {
175             x1, y1, z1,
176             x2, y2, z2,
177             x3, y3, z3,
178             x4, y4, z4
179         };
180         double colors[4] = { r, g, b, a };
181
182         Plane rect(verts, colors, ax);
183
184         doors.push_back(Door(rect, id));
185     }
186
187     Logger log;
188     vector<string> output = { "Loaded doors on", currLevel };
189     log.logLine(output);
190
191     // Deconstructs the statement
192     sqlite3_finalize(stm);
193 }
194
195 void Level::loadCylinders(sqlite3 *db)
196 {
197     cylinders.clear();
198     // Prepared Statement
199     sqlite3_stmt *stm;
200     // SQL command
201     string cmd;
202     // Connection Error Test
203     int err;
204     cmd = "SELECT * FROM cylinders WHERE LEVEL = \"" + currLevel + "\"";
205
206     err = sqlite3_prepare(db, cmd.c_str(), -1, &stm, 0);
207
208     if (err != SQLITE_OK)
209     {
210         Logger log;
211         vector<string> output = { "FATAL ERROR: Can't load cylinders while
            loading", currLevel };
212         log.logLine(output);
213
214         exit(STATEMENT_ERROR);

```

```

215     }
216
217     // While we still get rows of output
218     while (sqlite3_step(stm) == SQLITE_ROW)
219     {
220         double xt, yt, zt,
221                xr, yr, zr,
222                r, g, b, a,
223                baseRadius, topRadius, height;
224         int stacks, slices;
225
226
227         xt = sqlite3_column_double(stm, 1);
228         yt = sqlite3_column_double(stm, 2);
229         zt = sqlite3_column_double(stm, 3);
230
231         xr = sqlite3_column_double(stm, 4);
232         yr = sqlite3_column_double(stm, 5);
233         zr = sqlite3_column_double(stm, 6);
234
235         baseRadius = sqlite3_column_double(stm, 7);
236         topRadius = sqlite3_column_double(stm, 8);
237         height = sqlite3_column_double(stm, 9);
238
239         stacks = sqlite3_column_int(stm, 10);
240         slices = sqlite3_column_int(stm, 11);
241
242         r = sqlite3_column_double(stm, 12);
243         g = sqlite3_column_double(stm, 13);
244         b = sqlite3_column_double(stm, 14);
245         a = sqlite3_column_double(stm, 15);
246
247
248         double translate[3] = { xt, yt, zt };
249         double rotate[3] = { xr, yr, zr };
250         double colors[4] = { r, g, b, a };
251
252         cylinders.push_back(Cylinder(baseRadius, topRadius, height, stacks
253                                   , slices, translate, rotate, colors));
254     }
255
256     Logger log;
257     vector<string> output = { "Loaded cylinders on", currLevel };
258     log.logLine(output);
259
260     // Deconstructs the statement
261     sqlite3_finalize(stm);
262 }
263
264 void Level::loadSwitches(sqlite3 *db)
265 {
266     switches.clear();
267     // Prepared Statement
268     sqlite3_stmt *stm;
269     // SQL command

```

```

270     string cmd;
271     // Connection Error Test
272     int err;
273     cmd = "SELECT * FROM switches WHERE LEVEL = \"" + currLevel + "\"";
274
275     err = sqlite3_prepare(db, cmd.c_str(), -1, &stm, 0);
276
277     if (err != SQLITE_OK)
278     {
279         Logger log;
280         vector<string> output = { "FATAL ERROR: Can't load switches while
                loading", currLevel };
281         log.logLine(output);
282
283         exit(STATEMENT_ERROR);
284     }
285
286     // While we still get rows of output
287     while (sqlite3_step(stm) == SQLITE_ROW)
288     {
289         double xt, yt, zt,
290             xr, yr, zr;
291         string target, s_type, id;
292         int i_type;
293         bool isOn;
294
295         id = reinterpret_cast<const char*>(sqlite3_column_text(stm, 0));
296         target = reinterpret_cast<const char*>(sqlite3_column_text(stm, 2)
                );
297         xt = sqlite3_column_double(stm, 3);
298         yt = sqlite3_column_double(stm, 4);
299         zt = sqlite3_column_double(stm, 5);
300
301         xr = sqlite3_column_double(stm, 6);
302         yr = sqlite3_column_double(stm, 7);
303         zr = sqlite3_column_double(stm, 8);
304
305         s_type = reinterpret_cast<const char*>(sqlite3_column_text(stm, 9)
                );
306
307         isOn = (bool)sqlite3_column_int(stm, 10);
308
309         double translate[3] = { xt, yt, zt };
310         double rotate[3] = { xr, yr, zr };
311
312         if (s_type == "DOOR")
313             i_type = T_DOOR;
314         else if (s_type == "TERMINAL")
315             i_type = T_TERMINAL;
316         else if (s_type == "LEVEL_END")
317             i_type = T_LEVEL_END;
318         else
319         {
320             Logger log;
321             vector<string> output = { "Failed to evaluate string type
                    entry: ", s_type, "for switch ", id };

```

```

322         log.logLine(output);
323
324         exit(DATA_ENTRY_ERROR);
325     }
326
327     switches.push_back(Switch(translate, rotate, i_type, id, isOn));
328
329     bool assigned = false;
330
331     if (s_type == "LEVEL_END")
332     {
333         assigned = true;
334
335         Logger log;
336         vector<string> output = { "Switch ", id, " bound to end
                                level" };
337         log.logLine(output);
338     }
339
340     else if (s_type == "DOOR")
341     {
342         for (unsigned int i = 0; i < doors.size(); i++)
343         {
344             if (doors[i].getID() == target)
345             {
346                 Logger log;
347                 vector<string> output = { "Binding switch
                                ", id, " to door", target };
348                 log.logLine(output);
349
350                 switches[switches.size() - 1].assign(&(
                                doors[i]));
351
352                 assigned = true;
353             }
354         }
355     }
356
357     else if (s_type == "TERMINAL")
358     {
359         for (unsigned int i = 0; i < terminals.size(); i++)
360         {
361             if (terminals[i].getID() == target)
362             {
363                 Logger log;
364                 vector<string> output = { "Binding switch
                                ", id, " to terminal", target };
365                 log.logLine(output);
366
367                 switches[switches.size() - 1].assign(&(
                                terminals[i]));
368
369                 assigned = true;
370             }
371         }
372     }

```

```

373
374         if (!assigned)
375         {
376             Logger log;
377             vector<string> output = { "Failed to bind switch ", id, "
                                     to a ", s_type };
378             log.logLine(output);
379
380             exit(BINDING_ERROR);
381         }
382     }
383
384     Logger log;
385     vector<string> output = { "Loaded switches on", currLevel };
386     log.logLine(output);
387
388     // Deconstructs the statement
389     sqlite3_finalize(stm);
390 }
391
392 void Level::loadTerminals(sqlite3 *db)
393 {
394     terminals.clear();
395     // Prepared Statement
396     sqlite3_stmt *stm;
397     // SQL command
398     string cmd;
399     // Connection Error Test
400     int err;
401     cmd = "SELECT * FROM terminals WHERE LEVEL = \"" + currLevel + "\"";
402
403     err = sqlite3_prepare(db, cmd.c_str(), -1, &stm, 0);
404
405     if (err != SQLITE_OK)
406     {
407         Logger log;
408         vector<string> output = { "FATAL ERROR: Can't load terminals while
                                   loading", currLevel };
409         log.logLine(output);
410
411         exit(STATEMENT_ERROR);
412     }
413
414     // While we still get rows of output
415     while (sqlite3_step(stm) == SQLITE_ROW)
416     {
417         double xt, yt, zt,
418             xr, yr, zr;
419         string file, id;
420         id = reinterpret_cast<const char*>(sqlite3_column_text(stm, 0));
421         file = reinterpret_cast<const char*>(sqlite3_column_text(stm, 2));
422         xt = sqlite3_column_double(stm, 3);
423         yt = sqlite3_column_double(stm, 4);
424         zt = sqlite3_column_double(stm, 5);
425
426         xr = sqlite3_column_double(stm, 6);

```

```

427         yr = sqlite3_column_double(stm, 7);
428         zr = sqlite3_column_double(stm, 8);
429
430         double translate[3] = { xt, yt, zt };
431         double rotate[3] = { xr, yr, zr };
432
433         Logger log;
434         log.logLine(id);
435
436         terminals.push_back(Terminal(translate, rotate, file, id));
437     }
438
439
440     Logger log;
441     vector<string> output = { "Loaded terminals on", currLevel };
442     log.logLine(output);
443
444     // Deconstructs the statement
445     sqlite3_finalize(stm);
446 }
447
448 void Level::loadTriggers(sqlite3 *db)
449 {
450     triggers.clear();
451     // Prepared Statement
452     sqlite3_stmt *stm;
453     // SQL command
454     string cmd;
455     // Connection Error Test
456     int err;
457     cmd = "SELECT * FROM triggers WHERE LEVEL = \"" + currLevel + "\"";
458
459     err = sqlite3_prepare(db, cmd.c_str(), -1, &stm, 0);
460
461     if (err != SQLITE_OK)
462     {
463         Logger log;
464         vector<string> output = { "FATAL ERROR: Can't load triggers while
                                loading", currLevel };
465         log.logLine(output);
466
467         exit(STATEMENT_ERROR);
468     }
469
470     // While we still get rows of output
471     while (sqlite3_step(stm) == SQLITE_ROW)
472     {
473         string target, trigger, targetType, triggerType, id;
474         int i_targetType, i_triggerType;
475
476         id = reinterpret_cast<const char*>(sqlite3_column_text(stm, 0));
477         trigger = reinterpret_cast<const char*>(sqlite3_column_text(stm,
                                2));
478         target = reinterpret_cast<const char*>(sqlite3_column_text(stm, 3)
                                );
479         triggerType = reinterpret_cast<const char*>(sqlite3_column_text(

```



```

        stm, 4));
480     targetType = reinterpret_cast<const char*>(sqlite3_column_text(stm
        , 5));
481
482     if (triggerType == "SWITCH")
483         i_triggerType = T_SWITCH;
484     else if (triggerType == "TERMINAL")
485         i_triggerType = T_TERMINAL;
486     else
487     {
488         Logger log;
489         vector<string> output = { "Failed to evaluate string
            trigger type entry: ", triggerType, "for trigger ", id
            };
490         log.logLine(output);
491
492         exit(DATA_ENTRY_ERROR);
493     }
494
495     if (targetType == "SWITCH")
496         i_targetType = T_SWITCH;
497     else if (targetType == "TERMINAL")
498         i_targetType = T_TERMINAL;
499     else
500     {
501         Logger log;
502         vector<string> output = { "Failed to evaluate string
            trigger type entry: ", targetType, "for trigger ", id
            };
503         log.logLine(output);
504
505         exit(DATA_ENTRY_ERROR);
506     }
507
508     triggers.push_back(Trigger(i_triggerType, i_targetType));
509
510     bool assigned = bindTrigger(id, trigger, triggerType) &&
        bindTarget(id, target, targetType);
511
512     if (!assigned)
513     {
514         Logger log;
515         vector<string> output = { "Failed to bind trigger ", id };
516         log.logLine(output);
517
518         exit(BINDING_ERROR);
519     }
520 }
521
522 Logger log;
523 vector<string> output = { "Loaded trigger on", currLevel };
524 log.logLine(output);
525
526 // Deconstructs the statement
527 sqlite3_finalize(stm);
528 }

```

```

529
530 bool Level::bindTrigger(string id, string trigger, string triggerType)
531 {
532     if (triggerType == "SWITCH")
533     {
534         for (unsigned int i = 0; i < switches.size(); i++)
535         {
536             if (switches[i].getID() == trigger)
537             {
538                 Logger log;
539                 vector<string> output = { "Binding trigger ", id,
540                                         " to trigger-switch", trigger };
541                 log.logLine(output);
542                 triggers[triggers.size() - 1].bindTrigger(&(
543                     switches[i]));
544                 return true;
545             }
546         }
547     }
548     else if (triggerType == "TERMINAL")
549     {
550         for (unsigned int i = 0; i < terminals.size(); i++)
551         {
552             if (terminals[i].getID() == trigger)
553             {
554                 Logger log;
555                 vector<string> output = { "Binding trigger ", id,
556                                         " to trigger-terminal", trigger };
557                 log.logLine(output);
558                 triggers[triggers.size() - 1].bindTrigger(&(
559                     terminals[i]));
560                 return true;
561             }
562         }
563     }
564 }
565
566 return false;
567 }
568
569 bool Level::bindTarget(string id, string target, string targetType)
570 {
571     if (targetType == "SWITCH")
572     {
573         for (unsigned int i = 0; i < switches.size(); i++)
574         {
575             if (switches[i].getID() == target)
576             {
577                 Logger log;
578                 vector<string> output = { "Binding trigger ", id,
579                                         " to target-switch", target };

```

```

580             log.logLine(output);
581
582             triggers[triggers.size() - 1].bindTarget(&(
                    switches[i]));
583
584             return true;
585         }
586     }
587 }
588
589 else if (targetType == "TERMINAL")
590 {
591     for (unsigned int i = 0; i < terminals.size(); i++)
592     {
593         if (terminals[i].getID() == target)
594         {
595             Logger log;
596             vector<string> output = { "Binding trigger ", id,
                    " to target-terminal", target };
597             log.logLine(output);
598
599             triggers[triggers.size() - 1].bindTarget(&(
                    terminals[i]));
600
601             return true;
602         }
603     }
604 }
605
606 return false;
607 }
608
609 void Level::loadLevel(std::string levelName)
610 {
611     Logger log;
612     vector<string> output = { "Starting to load", levelName };
613     log.logLine(output);
614
615     if (quadratic == NULL)
616     {
617         quadratic = gluNewQuadric();
618     }
619
620     currLevel = levelName;
621
622     // Connection to SQL database
623     sqlite3 *db;
624     // 1 if error with DB
625     int connectErr = sqlite3_open("Data.db", &db);
626
627     if (connectErr != SQLITE_OK)
628     {
629         Logger log;
630         log.logLine("FATAL ERROR: Can't access database");
631
632         exit(DATABASE_ERROR);

```

```

633     }
634
635     loadWalls(db);
636     loadDoors(db);
637     loadCylinders(db);
638     loadTerminals(db);
639
640     // Loading switches must be after doors/terminals to properly bind
641     loadSwitches(db);
642
643     // Loading triggers must be done last to properly bind
644     loadTriggers(db);
645
646     // Closes the database
647     sqlite3_close(db);
648
649     output[0] = "Finished loading";
650     log.logLine(output);
651
652     Cam.resetCam();
653
654     interactivity = false;
655
656     // Get out of wall
657     for (unsigned int i = 0; i < 10; i++)
658     {
659         Cam.moveForward(1);
660     }
661
662     // Go dim for 5 seconds
663     HUD.goDim(5);
664 }
665
666 void Level::displayLevel()
667 {
668     for (auto i : doors)
669     {
670         i.Display();
671     }
672
673     for (auto i : cylinders)
674     {
675         i.Display();
676     }
677
678     for (auto i : switches)
679     {
680         i.Display();
681     }
682
683     for (auto i : terminals)
684     {
685         i.Display();
686     }
687
688     for (auto i : walls)

```

```

689         {
690             i.Display();
691         }
692     }

```

6.1.23 Logger.h

```

1  /*****\
2  * Logger.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the Logger class *
8  * Which writes messages to output.log because it's more *
9  * Reliable than stdout *
10 \*****/
11
12 #ifndef LOGGER_H
13 #define LOGGER_H
14
15 // To help find the user's document folder
16 #include <shlobj.h>
17
18 // std::vector
19 #include <vector>
20 // std::string
21 #include <string>
22
23 class Logger
24 {
25 private:
26     // Path to the log file
27     char CHAR_PATH[MAX_PATH];
28     std::string LOG_PATH;
29
30 public:
31     Logger();
32     // Erases the log file, called at the beggining of the program
33     void nuke();
34     // Writes to the log, either multiple lines or one line
35     void logLine(std::vector<std::string> input);
36     void logLine(std::string input);
37     // Writes the Camera Coordinates to the log file
38     void logCamCoords();
39
40 };
41
42 #endif

```

6.1.24 Logger.cpp

```

1  /*****\
2  * Logger.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *

```

```

6  *
7  * This file contains the defintion of the Logger class.
8  * for more information, see Logger.h
9  \*****/
10
11 // Class declaration
12 #include "Logger.h"
13 // For Cam coords
14 #include "Globals.h"
15 // File I/O
16 #include <fstream>
17
18 #include <iostream>
19
20 using namespace std;
21
22 Logger::Logger()
23 {
24     HRESULT ret = SHGetFolderPath(NULL, CSIDL_PERSONAL, NULL,
25     SHGFP_TYPE_CURRENT, CHAR_PATH);
26     LOG_PATH = CHAR_PATH;
27     LOG_PATH += "\\The God Core\\output.log";
28 }
29 void Logger::nuke()
30 {
31     ofstream outfile(LOG_PATH); // Nukes everything within
32 }
33
34 void Logger::logLine(vector<string> input)
35 {
36     ofstream outfile(LOG_PATH, ios::app);
37
38     string output;
39
40     for (auto i : input)
41     {
42         output += i;
43         output += " ";
44     }
45     outfile << output << std::endl;
46 }
47
48 void Logger::logLine(string input)
49 {
50     ofstream outfile(LOG_PATH, ios::app);
51
52     outfile << input << std::endl;
53 }
54
55 void Logger::logCamCoords()
56 {
57     ofstream outfile(LOG_PATH, ios::app);
58
59     outfile << "Player Coordinates:\n";
60     outfile << "X: " << -Cam.x << endl;

```

```

61         outfile << "Y: " << -Cam.y << endl;
62         outfile << "Z: " << -Cam.z << endl;
63     }

```

6.1.25 MainMenu.h

```

1  /*****\
2  * MainMenu.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the MainMenu class *
8  * Which uses the Simple OpenGL Interface Library to load a *
9  * png picture of the main menu, as well as provide button *
10 * Interactivity *
11 \*****/
12
13 #ifndef MAIN_MENU_H
14 #define MAIN_MENU_H
15
16 // For loading pictures
17 #include <SOIL.h>
18 // Inherit 2D functionality
19 #include "TwoD.h"
20
21 // Make OpenGL happy
22 #include <cstdlib>
23 // OpenGL API
24 #include <GL\glut.h>
25
26 class MainMenu : public TwoD
27 {
28 public:
29     // Loads the picture up in memory
30     MainMenu();
31     // Handles drawing to the screen
32     void display();
33     // Handles and processes mouse clicks
34     void getClick(double x, double y);
35
36 private:
37     // Draws the main picture
38     void drawMainPic();
39     // DEBUG: draws boxes around all buttons
40     void drawClickBoxes();
41     // What the picture is bound to
42     GLint texture;
43 };
44
45 #endif

```

6.1.26 MainMenu.cpp

```

1  /*****\
2  * MainMenu.cpp *
3  * This file was created by Jeremy Greenburg *

```

```

4  * As part of The God Core game for the University of      *
5  * Tennessee at Martin's University Scholars Organization  *
6  *                                                         *
7  * This file contains the definition of the MainMenu class. *
8  * for more information, see MainMenu.h                    *
9  \*****/
10
11 // Class declaration
12 #include "MainMenu.h"
13 // isInMain
14 #include "Globals.h"
15 // Return codes
16 #include "Return.h"
17 // System log
18 #include "Logger.h"
19
20 #include "SaveManager.h"
21
22 using namespace std;
23
24 MainMenu::MainMenu()
25 {
26     texture = SOIL_load_OGL_texture
27         (
28             "Resources\\Images\\Main.png",    // Image to load
29             SOIL_LOAD_AUTO,                    //
30             SOIL_CREATE_NEW_ID,
31             SOIL_FLAG_MIPMAPS | SOIL_FLAG_NTSC_SAFE_RGB |
32             SOIL_FLAG_COMPRESS_TO_DXT // !?!?!?!
33         );
34
35     if (texture == 0)
36     {
37         Logger log;
38         vector<string> output = {"FATAL ERROR: SOIL cannot load image",
39             SOIL_last_result()};
40         log.logLine(output);
41         exit(SOIL_ERROR);
42     }
43
44 void MainMenu::drawMainPic()
45 {
46     glEnable(GL_TEXTURE_2D);
47
48     glBindTexture(GL_TEXTURE_2D, texture); // Prepares the texture for usage
49
50     glColor3d(1, 1, 1);
51     glBegin(GL_QUADS);
52     glTexCoord2d(0, 0);    glVertex2d(SCREENLEFT, SCREENTOP);
53     glTexCoord2d(0, 1);    glVertex2d(SCREENLEFT, SCREENBOTTOM);
54     glTexCoord2d(1, 1);    glVertex2d(SCREENRIGHT, SCREENBOTTOM);
55     glTexCoord2d(1, 0);    glVertex2d(SCREENRIGHT, SCREENTOP);
56
57     glEnd();

```



```

57
58         glDisable(GL_TEXTURE_2D);
59
60     }
61
62     void MainMenu::drawClickBoxes()
63     {
64         glColor3d(1, 0, 0);
65
66         // Start a new game
67         glBegin(GL_LINE_LOOP);
68         glVertex2d(SCREENRIGHT / 20.0, SCREENBOTTOM / 2.2);
69         glVertex2d(SCREENRIGHT / 20.0, SCREENBOTTOM / 1.9);
70         glVertex2d(SCREENRIGHT / 3.0, SCREENBOTTOM / 1.9);
71         glVertex2d(SCREENRIGHT / 3.0, SCREENBOTTOM / 2.2);
72         glEnd();
73
74         // Load game
75         glBegin(GL_LINE_LOOP);
76         glVertex2d(SCREENRIGHT / 10.0, SCREENBOTTOM / 1.57);
77         glVertex2d(SCREENRIGHT / 10.0, SCREENBOTTOM / 1.75);
78         glVertex2d(SCREENRIGHT / 3.5, SCREENBOTTOM / 1.75);
79         glVertex2d(SCREENRIGHT / 3.5, SCREENBOTTOM / 1.57);
80         glEnd();
81
82         // Options
83         glBegin(GL_LINE_LOOP);
84         glVertex2d(SCREENRIGHT / 8.5, SCREENBOTTOM / 1.35);
85         glVertex2d(SCREENRIGHT / 8.5, SCREENBOTTOM / 1.45);
86         glVertex2d(SCREENRIGHT / 3.9, SCREENBOTTOM / 1.45);
87         glVertex2d(SCREENRIGHT / 3.9, SCREENBOTTOM / 1.35);
88         glEnd();
89
90         // Exit
91
92         glBegin(GL_LINE_LOOP);
93         glVertex2d(SCREENRIGHT / 6.5, SCREENBOTTOM / 1.16);
94         glVertex2d(SCREENRIGHT / 6.5, SCREENBOTTOM / 1.25);
95         glVertex2d(SCREENRIGHT / 4.5, SCREENBOTTOM / 1.25);
96         glVertex2d(SCREENRIGHT / 4.5, SCREENBOTTOM / 1.16);
97         glEnd();
98     }
99
100     void MainMenu::getClick(double x, double y)
101     {
102         // Start new game
103         if (x >= SCREENRIGHT / 20.0 && x <= SCREENRIGHT / 3.0)
104         {
105             if (y >= SCREENBOTTOM / 2.2 && y <= SCREENBOTTOM / 1.9)
106             {
107                 isInMain = false;
108                 songNum = 1;
109                 changeSong = true;
110                 curr_level = "LEVELZERO";
111                 loading = true;
112             }
113         }
114     }

```

```

113     }
114
115     // Load Game
116     if (x >= SCREENRIGHT / 10.0 && x <= SCREENRIGHT / 3.5)
117     {
118         if (y >= SCREENBOTTOM / 1.75 && y <= SCREENBOTTOM / 1.57)
119         {
120             SaveManager Jesus; // Jesus Saves
121             if (!Jesus.loadGame()); // null
122             else isInMain = false;
123
124         }
125     }
126
127     // Options
128     if (x >= SCREENRIGHT / 8.5 && x <= SCREENRIGHT / 3.9)
129     {
130         if (y >= SCREENBOTTOM / 1.45 && y <= SCREENBOTTOM / 1.35)
131         {
132             // Jokes on me I never did get any options up
133         }
134     }
135
136     // Exit
137     if (x >= SCREENRIGHT / 6.5 && x <= SCREENRIGHT / 4.5)
138     {
139         if (y >= SCREENBOTTOM / 1.25 && y <= SCREENBOTTOM / 1.16)
140         {
141             exit(EXIT_OK);
142         }
143     }
144 }
145
146 void MainMenu::display()
147 {
148     prepare2D();
149
150     drawMainPic();
151
152     // Disable once finished
153     //drawClickBoxes();
154
155     glEnd();
156
157     prepare3D();
158 }

```

6.1.27 MusicManager.h

```

1  /*****\
2  * MusicManager.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * * *
7  * This file contains the declaration of the MusicManager *
8  * Class, which uses the FMOD API to load .mp3 files into *

```

```

9  * Memory, play them when called, and release the memory      *
10 * When the song is no longer needed.                          *
11 \*****/
12
13 #ifndef MUSICMANAGER_H
14 #define MUSICMANAGER_H
15
16 // FMOD API
17 #include <fmod.hpp>
18
19 // Creates new type for ease of use
20 typedef FMOD::Sound* SoundClass;
21
22 class MusicManager
23 {
24 private:
25     // Pointer to dynamic system memory to load music
26     FMOD::System *m_pSystem;
27
28     // The path to the music folder
29     static const char* MUSIC_PATH;
30
31 public:
32     // Loads the song in memory
33     void makeSound(SoundClass *psound, const char *song);
34     // Plays the song (Always loops)
35     void playSound(SoundClass pSound, bool bLoop = true);
36     // Releases the song
37     void releaseSound(SoundClass psound);
38     // Initializes FMOD
39     MusicManager();
40 };
41
42 #endif

```

6.1.28 MusicManager.cpp

```

1  \*****/
2  * MusicManager.cpp                                           *
3  * This file was created by Jeremy Greenburg                 *
4  * As part of The God Core game for the University of       *
5  * Tennessee at Martin's University Scholars Organization    *
6  *                                                           *
7  * This file contains the definition of the MusicManager     *
8  * Class. For more information, see MusicManager.h           *
9  \*****/
10
11 // Class definition
12 #include "MusicManager.h"
13
14 // Because concatenating char*'s are really hard
15 #include <string>
16
17 // Return codes
18 #include "Return.h"
19
20 // System log

```

```

21 #include "Logger.h"
22
23 using namespace std;
24
25 // Initialize the constant member of the class
26 const char* MusicManager::MUSIC_PATH = "Resources\\Music\\";
27
28 MusicManager::MusicManager()
29 {
30     Logger log;
31     if (FMOD::System_Create(&m_pSystem) != FMOD_OK)
32     {
33         log.logLine("FATAL ERROR: FMOD unable to create system");
34         exit(FMOD_ERROR);
35     }
36
37     int driverCount = 0;
38     m_pSystem->getNumDrivers(&driverCount);
39
40     // If you have no driver, you have bigger problems to worry about
41     if (driverCount == 0)
42     {
43         // Report Error
44         log.logLine("ERROR: FMOD unable to detect drivers");
45         exit(FMOD_ERROR);
46     }
47
48     log.logLine("FMOD succesfully initialized");
49     // Initialize our Instance with 36 Channels
50     m_pSystem->init(36, FMOD_INIT_NORMAL, NULL);
51 }
52
53 void MusicManager::makeSound(SoundClass *psound, const char *song)
54 {
55     // MUSIC_PATH is placed in a nice string. Good string. Strings are friends
56     string fullPath = MUSIC_PATH;
57     // Now there is a full path to the song
58     fullPath += song;
59
60     m_pSystem->createSound(fullPath.c_str(), FMOD_DEFAULT, 0, psound);
61 }
62
63 void MusicManager::playSound(SoundClass pSound, bool bLoop)
64 {
65     if (!bLoop)
66         pSound->setMode(FMOD_LOOP_OFF);
67     else
68     {
69         pSound->setMode(FMOD_LOOP_NORMAL);
70         pSound->setLoopCount(-1);
71     }
72
73     m_pSystem->playSound(pSound, NULL, false, 0);
74 }
75
76 void MusicManager::releaseSound(SoundClass pSound)

```

```

77 {
78     pSound->release();
79 }

```

6.1.29 Plane.h

```

1  /*****\
2  * Plane.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the Plane class *
8  * Which is used to hold the details of a 2D Plane and *
9  * draw it to the screen *
10 \*****/
11
12 #ifndef Plane_H
13 #define Plane_H
14
15 class Plane
16 {
17 private:
18     // Arrays containing the color and vertices of the Plane
19     double color[4];
20     // What axis is it aligned on (x y z)
21     char axis;
22     // The vertices of the corners
23     double vertices[12];
24 public:
25
26     // Paramaterized constructor, as there cannot be a Plane without vertices
27     // Can take an axis or can ignore axis
28     Plane(const double(&new_vertices)[12], const double(&new_color)[4], char
        _axis);
29     Plane(const double(&new_vertices)[12], const double(&new_color)[4]);
30
31     // Part of the plane equation, calculated in constructor
32     double a, b, c, d;
33
34     // Determines if the player is in the bounds of the Plane (based on axis)
35     bool isInBounds();
36
37     // Returns the plane norm (Perpendicular line)
38     double getNorm();
39
40     // Mutate's the rectangles coordinates for the end of the game
41     void mutate();
42
43     // Print a Plane in 3D
44     void Display();
45     // Print a Plane in 2D
46     void Display2D();
47 };
48
49 #endif

```

6.1.30 Plane.cpp

```
1  /*****\
2  * Plane.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the Plane class *
8  * For more information, see Plane.h *
9  \*****/
10
11 #include "Plane.h"
12
13 // For std::copy
14 #include <iterator>
15 #include <utility>
16
17 // max and min
18 #include <algorithm>
19
20 // OpenGL API
21 #include <GL\glut.h>
22
23 // For Cam coords
24 #include "Globals.h"
25
26 using namespace std;
27
28 Plane::Plane(const double (&new_vertices)[12], const double (&new_color)[4], char
    _axis)
29 {
30     // Copies the color
31     copy(begin(new_color), end(new_color), color);
32
33     // Copies the vertices
34     copy(begin(new_vertices), end(new_vertices), vertices);
35
36
37     // Somedays I wonder what I'm even doing \\
38     // When I forget what all this means: http://keisan.casio.com/exec/system/1223596129 \\
39
40     // Calculate vector equation  $ax + by + cz + d = 0$ 
41     // Get two vectors from three of the corners
42     double AB[] = { vertices[3] - vertices[0], vertices[4] - vertices[1],
43                     vertices[5] - vertices[2] };
44     double AC[] = { vertices[6] - vertices[0], vertices[7] - vertices[1],
45                     vertices[8] - vertices[2] };
46     // Cross Product of AB and AC
47     a = (AB[1] * AC[2]) - (AB[2] * AC[1]);
48     b = (AB[2] * AC[0]) - (AB[0] * AC[2]);
49     c = (AB[0] * AC[1]) - (AB[1] * AC[0]);
50     d = (a * vertices[0] + b * vertices[1] + c * vertices[2]);
51
52     axis = _axis;
```

```

51 }
52
53 Plane::Plane(const double(&new_vertices)[12], const double(&new_color)[4])
54 {
55     // Copies the color
56     copy(begin(new_color), end(new_color), color);
57
58     // Copies the vertices
59     copy(begin(new_vertices), end(new_vertices), vertices);
60
61
62     // Somedays I wonder what I'm even doing \\
63     // When I forget what all this means: http://keisan.casio.com/exec
64     // /system/1223596129 \\
65
66 // Calculate vector equation  $ax + by + cz + d = 0$ 
67 // Get two vectors from three of the corners
68     double AB[] = { vertices[3] - vertices[0], vertices[4] - vertices[1],
69                     vertices[5] - vertices[2] };
70     double AC[] = { vertices[6] - vertices[0], vertices[7] - vertices[1],
71                     vertices[8] - vertices[2] };
72     // Cross Product of AB and AC
73     a = (AB[1] * AC[2]) - (AB[2] * AC[1]);
74     b = (AB[2] * AC[0]) - (AB[0] * AC[2]);
75     c = (AB[0] * AC[1]) - (AB[1] * AC[0]);
76     d = (a * vertices[0] + b * vertices[1] + c * vertices[2]);
77
78     axis = 0;
79 }
80
81 void Plane::Display()
82 {
83     // Set's OpenGL's color to the color of the Plane
84     glColor4f(color[0], color[1], color[2], color[3]);
85
86     glBegin(GL_QUADS);
87     glVertex3d(vertices[0], vertices[1], vertices[2]);
88     glVertex3d(vertices[3], vertices[4], vertices[5]);
89     glVertex3d(vertices[6], vertices[7], vertices[8]);
90     glVertex3d(vertices[9], vertices[10], vertices[11]);
91     glEnd();
92 }
93
94 void Plane::Display2D()
95 {
96     glColor4f(color[0], color[1], color[2], color[3]);
97
98     glBegin(GL_QUADS);
99     glVertex2d(vertices[0], vertices[1]);
100    glVertex2d(vertices[3], vertices[4]);
101    glVertex2d(vertices[6], vertices[7]);
102    glVertex2d(vertices[9], vertices[10]);
103    glEnd();
104 }
105
106 bool Plane::isInBounds()

```

```

104 {
105     if (axis == 'x')
106     {
107         vector<double> X = { vertices[0], vertices[3], vertices[6],
108                             vertices[9] };
109         double maxX = *max_element(X.begin(), X.end());
110         double minX = *min_element(X.begin(), X.end());
111
112         return (-Cam.x <= maxX && -Cam.x >= minX);
113     }
114
115     else if (axis == 'y')
116     {
117         vector<double> Y = { vertices[1], vertices[4], vertices[7],
118                             vertices[10] };
119         double maxY = *max_element(Y.begin(), Y.end());
120         double minY = *min_element(Y.begin(), Y.end());
121
122         return (-Cam.y <= maxY && -Cam.y >= minY);
123     }
124
125     else if (axis == 'z')
126     {
127         vector<double> Z = { vertices[2], vertices[5], vertices[8],
128                             vertices[11] };
129         double maxZ = *max_element(Z.begin(), Z.end());
130         double minZ = *min_element(Z.begin(), Z.end());
131
132         return (-Cam.z <= maxZ && -Cam.z >= minZ);
133     }
134     else return false;
135 }
136
137 double Plane::getNorm()
138 {
139     return sqrt(a * a + b * b + c * c);
140 }
141
142 void Plane::mutate()
143 {
144     // We're gonna mess stuff up, disable the axis so nothing funky happens
145     // with collision
146     axis = ' ';
147
148     for (unsigned int i = 0; i < 12; i++)
149     {
150         // 0 <= mutator <= 200
151         double mutator = rand() % 201;
152         // -100 <= mutator <= 100
153         mutator -= 100;
154         // -.01 <= mutator <= .01
155         mutator /= 10000;
156
157         vertices[i] += mutator;
158     }
159 }

```


156 }

6.1.31 Return.h

```
1  /*****\
2  * Return.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains various return codes for when things *
8  * Go horribly wrong (and they do) *
9  * (just hopefully not during my senior defense) *
10 \*****/
11
12 #ifndef RETURN_H
13 #define RETURN_H
14
15 #define EXIT_OK 0 // Indicates an intended exit
16 #define EXIT_EARLY 1 // If we exit OpenGL main loop early
17 #define FMOD_ERROR 2 // Fmod can't load sound
18 #define DATABASE_ERROR 3 // sqlite can't load database
19 #define STATEMENT_ERROR 4 // sqlite statement fails to execute
20 #define SOIL_ERROR 5 // SOIL fails to load image
21 #define DATA_ENTRY_ERROR 6 // Indicates an internal error in a database entry
22 #define BINDING_ERROR 7 // Error binding a trigger
23 #define FILE_NOT_FOUND 8 // A file is not found
24
25 #endif
```

6.1.32 Resource.h

```
1  /*****\
2  * Return.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains various return codes for when things *
8  * Go horribly wrong (and they do) *
9  * (just hopefully not during my senior defense) *
10 \*****/
11
12 #ifndef RETURN_H
13 #define RETURN_H
14
15 #define EXIT_OK 0 // Indicates an intended exit
16 #define EXIT_EARLY 1 // If we exit OpenGL main loop early
17 #define FMOD_ERROR 2 // Fmod can't load sound
18 #define DATABASE_ERROR 3 // sqlite can't load database
19 #define STATEMENT_ERROR 4 // sqlite statement fails to execute
20 #define SOIL_ERROR 5 // SOIL fails to load image
21 #define DATA_ENTRY_ERROR 6 // Indicates an internal error in a database entry
22 #define BINDING_ERROR 7 // Error binding a trigger
23 #define FILE_NOT_FOUND 8 // A file is not found
24
25 #endif
```

6.1.33 SaveManager.h

```
1  /*****\
2  * SaveManager.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the SaveManager *
8  * Class, which saves data by encrypting an array of strings *
9  * And writing them to core.sav, or by reading in an array of *
10 * Strings from core.sav and decrypting them *
11 *****/
12
13 #ifndef SAVEMANAGER_H
14 #define SAVEMANAGER_H
15
16 // Windows API
17 #include <shlobj.h>
18
19 // Because concatenating char*'s is really hard
20 #include <string>
21
22 class SaveManager
23 {
24 private:
25     // The path to core.sav
26     char CHAR_PATH[MAX_PATH];
27     std::string SAVE_PATH;
28
29     // Takes an unencrypted string and returns an encrypted string
30     std::string encryptData(std::string data);
31     // Takes an encrypted string and returns a decrypted string
32     std::string decryptData(std::string data);
33 public:
34     SaveManager();
35     // Writes the array of encrypted strings to core.sav
36     void saveLevel();
37     // Sets global variables to load game
38     bool loadGame();
39     // Returns the decrypted string in core.sav
40     std::string readSave();
41     // Returns true if core.sav exists
42     bool checkSave();
43 };
44
45 #endif
```

6.1.34 SaveManager.cpp

```
1  /*****\
2  * SaveManager.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
```

```

7  * This file contains the definition of the SaveManager class*
8  * For more information, see SaveManager.h *
9  \*****/
10
11 // Class definition
12 #include "SaveManager.h"
13
14 // File I/O
15 #include <fstream>
16
17 #include "Globals.h"
18
19 #include "Logger.h"
20
21 using namespace std;
22
23 SaveManager::SaveManager()
24 {
25     HRESULT ret = SHGetFolderPath(NULL, CSIDL_PERSONAL, NULL,
26     SHGFP_TYPE_CURRENT, CHAR_PATH);
27     SAVE_PATH = CHAR_PATH;
28     SAVE_PATH += "\\The God Core\\core.sav";
29 }
30
31 string SaveManager::encryptData(string data)
32 {
33     string ret_str;
34     for (unsigned int i = 0; i < data.length()*3; i+=3)
35     {
36         ret_str += data[i/3] + 48;
37         ret_str += data[i/3] - 48;
38         ret_str += data[i/3] + 53;
39     }
40     return ret_str;
41 }
42
43 string SaveManager::decryptData(string data)
44 {
45     string ret_str;
46     for (unsigned int i = 0; i < data.length(); i+=3)
47     {
48         ret_str += data[i] - 48;
49     }
50     return ret_str;
51 }
52
53 string SaveManager::readSave()
54 {
55     Logger log;
56
57     ifstream save(SAVE_PATH);
58     log.logLine("Checking Save integrity.");
59
60     string enc_data; // Encrypted Data
61     string dcr_data; // Decrypted Data

```

```

62         save >> enc_data; // Read encrypted data from file
63         dcr_data = decryptData(enc_data); // Decrypt data
64
65         vector<string> output{ "Decrypted Data: ", dcr_data };
66         log.logLine(output);
67
68         save.close();
69
70         return dcr_data;
71     }
72
73     void SaveManager::saveLevel()
74     {
75         ofstream save(SAVE_PATH);
76
77         string input = curr_level + " " + to_string(songNum);
78
79         string encr_str = encryptData(input);
80
81         save << encr_str;
82
83         save.close();
84     }
85
86     bool SaveManager::loadGame()
87     {
88         // might change to vector<string> later
89         string data = readSave();
90         size_t pos = data.find(' ');
91
92         if (pos == string::npos) return false;
93         string savedLevel = data.substr(0, pos);
94         int savedSong = stoi(data.substr(pos + 1));
95
96         int temp_levelNum = getLevelNum(savedLevel);
97
98         if (temp_levelNum == -1) return false;
99
100        levelNum = temp_levelNum;
101        curr_level = getLevelString(levelNum);
102        songNum = savedSong;
103
104        loading = true;
105        changeSong = true;
106
107        return true;
108    }
109
110    bool SaveManager::checkSave()
111    {
112        ifstream save(SAVE_PATH);
113
114        if (save)
115        {
116            return true;
117        }

```

```

118
119         else
120         {
121             return false;
122         }
123     }

```

6.1.35 Switch.h

```

1  /*****\
2  * Switch.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the Switch class *
8  * Which is bound to a Door via pointer and can open and *
9  * Close the door at will *
10 \*****/
11
12 #ifndef SWITCH_H
13 #define SWITCH_H
14
15 // Door class
16 #include "Door.h"
17 #include "PoweredObject.h"
18 // Terminal Class
19 #include "Terminal.h"
20
21 // Types
22 #include "GCTypes.h"
23
24 class Switch : public PoweredObject
25 {
26 private:
27     void* target; // The door that this switch activates
28     // Translation and rotation coordinates
29     double translate[3], rotate[3];
30
31     // One of the predefined types
32     GCType targetType;
33
34     // Unique ID
35     std::string id;
36
37 public:
38     // Initializes the translation and rotation matrices
39     Switch(const double(&_translate)[3], const double(&_rotate)[3], GCType
        _type, std::string _id, bool _isOn);
40     // Binds the target pointer to an object
41     void assign(void* _target);
42     // Opens/Closes the door
43     void toggleTarget();
44     // Actually draws the switch
45     void Display();
46
47     // Get's the switch's ID

```

```

48         std::string getID();
49
50         // Gets the translation coordinates
51         double getX();
52         double getY();
53         double getZ();
54     };
55
56 #endif

```

6.1.36 Switch.cpp

```

1  /*****\
2  * Switch.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the Switch class *
8  * For more information, see Switch.h *
9  \*****/
10
11 // Class declaration
12 #include "Switch.h"
13
14 // Allows copying arrays
15 #include <iterator>
16 #include <utility>
17 #include <algorithm>
18
19 #include "Globals.h"
20
21 // OpenGL API
22 #include <GL\glut.h>
23
24 using namespace std;
25
26 Switch::Switch(const double(&_translate)[3], const double(&_rotate)[3], GCTYPE
    _type, string _id, bool _isOn)
27 {
28     // Copies the color
29     copy(begin(_translate), end(_translate), translate);
30
31     // Copies the vertices
32     copy(begin(_rotate), end(_rotate), rotate);
33
34     targetType = _type;
35
36     target = NULL;
37
38     id = _id;
39
40     if (_isOn) activate();
41     else deactivate();
42
43 }
44

```

```

45 void Switch::assign(void* _target)
46 {
47     target = _target;
48 }
49
50 void Switch::toggleTarget()
51 {
52     switch (targetType)
53     {
54         case T_DOOR:
55         {
56             Door* t = (Door*)target;
57             t->isOpen = !t->isOpen;
58             break;
59         }
60         case T_TERMINAL:
61         {
62             Terminal* t = (Terminal*)target;
63             t->toggle();
64             break;
65         }
66         case T_LEVEL_END:
67         {
68             levelNum++;
69             curr_level = getLevelString(levelNum);
70             loading = true;
71
72             // TEMP
73             advanceMusic();
74             changeSong = true;
75         }
76     }
77 }
78
79 void Switch::Display()
80 {
81     glPushMatrix();
82     glTranslated(translate[0], translate[1], translate[2]);
83     glRotated(rotate[0], 1, 0, 0);
84     glRotated(rotate[1], 0, 1, 0);
85     glRotated(rotate[2], 0, 0, 1);
86
87     glColor3d(0.9, 0.9, 0.9);
88     glutSolidCube(.1);
89
90     switch (targetType)
91     {
92     case T_DOOR:
93         glColor3d(0, 1, 0);
94         break;
95     case T_TERMINAL:
96         glColor3d(1, 0, 0);
97         break;
98     default:
99         glColor3d(0, 0, 1);
100    }

```

```

101
102     // If powered off, recolor to black
103     if (!checkIfOn()) glColor3d(0, 0, 0);
104
105     glScaled(.5, .5, 1.5);
106     glutSolidCube(.1);
107
108     glPopMatrix();
109 }
110
111 string Switch::getID()
112 {
113     return id;
114 }
115
116 double Switch::getX()
117 {
118     return translate[0];
119 }
120
121 double Switch::getY()
122 {
123     return translate[1];
124 }
125
126 double Switch::getZ()
127 {
128     return translate[2];
129 }

```

6.1.37 Terminal.h

```

1  /*****\
2  * Terminal.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the Terminal class *
8  * Which draws and manages ingame computer terminals *
9  * And has nothing to do with terminal illness I swear *
10 \*****/
11
12 #ifndef TERMINAL_H
13 #define TERMINAL_H
14
15 #include "TwoD.h" // To inherit 2D class
16 #include "PoweredObject.h"
17
18 #include <cstdlib>
19
20 // For loading pictures
21 #include <SOIL.h>
22
23 #include "TextEngine.h" // To display text to screen
24
25 #include <string>

```



```

26
27 #include <GL\glut.h>
28
29 class Terminal : public TwoD, public PoweredObject // Inherit 2D functionality and
    power functionality
30 {
31 private:
32     // text = what the user is typing, input = completed input
33     std::string currentInput, currentText, error, file;
34     std::vector<std::string> history, prompts, content;
35     std::string id;
36
37     // Where to print each item
38     const double INPUT_LINE = SCREENBOTTOM / 7.0;
39     const double ERROR_LINE = INPUT_LINE - 30;
40     const double PROMPT_START = INPUT_LINE + 30;
41     const double CONTENT_START = PROMPT_START + 150;
42
43     // The banner texture
44     GLint bTexture;
45
46     // The user inputed number
47     int num;
48
49     // Print our text
50     TextEngine text;
51
52     // Translation and rotation matrices
53     double translate[3], rotate[3];
54
55     // Draws the actual terminal
56     void draw();
57
58     // Draws a standing terminal
59     void drawStanding();
60
61     // Draws a wall mounter terminal
62     void drawWallMounted();
63
64     // Processes the user input
65     void processInput();
66
67     // Parse the terminal file
68     void parseFile();
69
70     // The path to the Terminal Files
71     static const char* TERM_PATH;
72
73 public:
74     // Draws the 3D object in the world
75     void Display();
76     // Draws the 2D Terminal screen
77     void DisplayScreen();
78     // Shows the currently typed string
79     void getText(std::string text);
80     // Signifies a completed string to process

```

```

81     void getInput(std::string text);
82     // Returns an item in the terminal's log
83     std::string getHist(int count);
84     // Returns the number of items in the terminal's log
85     int getHistNum();
86
87     // Gets the translation coordinates
88     double getX();
89     double getY();
90     double getZ();
91
92     // Get the terminal's ID
93     std::string getID();
94
95     // To construct and initialize the terminal
96     Terminal(const double(&_translate)[3], const double(&_rotate)[3], std::
        string _file, std::string _id);
97
98 };
99
100 #endif

```

6.1.38 Terminal.cpp

```

1  /*****\
2  * Terminal.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the Terminal class *
8  * For more information, see Terminal.h *
9  \*****/
10
11 //
12 // Class declaration
13 #include "Terminal.h"
14
15 // Planes
16 #include "Plane.h"
17
18 // For system logging
19 #include "Logger.h"
20
21 // Return codes
22 #include "Return.h"
23
24 // Global variables
25 #include "Globals.h"
26
27 // Logger
28 #include "Logger.h"
29
30 // File I/O
31 #include <fstream>
32
33 using namespace std;

```

```

34
35 const char* Terminal::TERM_PATH = "Resources\\Text\\";
36
37 void Terminal::getText(std::string text)
38 {
39     currentText = text;
40 }
41
42 void Terminal::getInput(std::string text)
43 {
44     currentInput = text;
45 }
46
47 string Terminal::getHist(int count)
48 {
49     int size = history.size();
50     if (history.empty())
51     {
52         return "";
53     }
54
55     // If, somehow, a fool manages to get a variable that is out of bounds
56
57     else if (count >= size)
58     {
59         return history.back();
60     }
61
62     else if (count < 0)
63     {
64         return history.front();
65     }
66
67     else
68     {
69         return history[size - count - 1];
70     }
71 }
72
73 int Terminal::getHistNum()
74 {
75     return history.size();
76 }
77
78 void Terminal::draw()
79 {
80     // Completely black background
81     double colors[4] = { 0, 0, 0, 1 };
82     double vertices[12] =
83     {
84         SCREENLEFT, SCREENTOP, -1,
85         SCREENLEFT, SCREENBOTTOM, -1,
86         SCREENRIGHT, SCREENBOTTOM, -1,
87         SCREENRIGHT, SCREENTOP, -1
88     };
89

```

```

90     Plane background{ vertices, colors};
91     background.Display2D();
92
93
94     // Gotta do the banner manually
95     glEnable(GL_TEXTURE_2D);
96
97     glBindTexture(GL_TEXTURE_2D, bTexture); // Prepares the texture for usage
98
99     glColor3d(1, 1, 1);
100    glBegin(GL_QUADS);
101    glTexCoord2d(0, 0);      glVertex2d(SCREENLEFT, SCREENTOP);
102    glTexCoord2d(0, 1); glVertex2d(SCREENLEFT, SCREENBOTTOM / 9.0);
103    glTexCoord2d(1, 1); glVertex2d(SCREENRIGHT, SCREENBOTTOM / 9.0);
104    glTexCoord2d(1, 0);      glVertex2d(SCREENRIGHT, SCREENTOP);
105
106    glEnd();
107
108    glDisable(GL_TEXTURE_2D);
109 }
110
111 void Terminal::DisplayScreen()
112 {
113     prepare2D();
114
115     draw();
116
117     // If we need to proces a command
118     if (currentInput != "")
119     {
120         processInput();
121
122         history.push_back(currentInput);
123
124         currentInput.clear();
125     }
126
127     else
128     {
129         // Print all prompts
130         for (unsigned int i = 0; i < prompts.size(); i++)
131         {
132             text.printString(SCREENLEFT, PROMPT_START + 20 * i, 0, 1,
133                             0, prompts[i]);
134
135             // Print an error
136             text.printString(SCREENLEFT, ERROR_LINE, 1, 0, 0, error);
137             // Echo user text
138             text.printString(SCREENLEFT, INPUT_LINE, 0, 1, 0, "> " +
139                             currentText);
140
141             // If needed, print content
142             if (num != -1 && num < (signed int)content.size())
143             {
144                 text.openFile(SCREENLEFT, CONTENT_START, 0, 1, 0, file,

```

```

144         content[num]);
145     }
146
147     prepare3D();
148 }
149
150 void Terminal::processInput()
151 {
152     error = "";
153     if (currentInput == "exit" || currentInput == "Exit")
154     {
155         isInTerminal = false;
156         history.clear();
157     }
158
159     else if (currentInput == "clear" || currentInput == "Clear")
160     {
161         num = -1;
162     }
163
164     else if (currentInput == "help" || currentInput == "Help")
165     {
166         num = 0;
167     }
168
169     else
170     {
171         string first, last;
172         size_t pos = currentInput.find(" ");
173
174         first = currentInput.substr(0, pos); // First half of string
175         last = currentInput.substr(pos + 1); // Second half of string
176
177         if (first == "read" || first == "Read")
178         {
179             num = atoi(last.c_str());
180             if (num <= 0 || num >= (signed int)prompts.size())
181             {
182                 error = "ERROR: Invalid file number";
183                 num = -1;
184             }
185         }
186
187         else
188         {
189             error = "ERROR: Invalid Command: " + currentInput;
190             num = -1;
191         }
192     }
193 }
194
195 void Terminal::Display()
196 {
197     // Add two styles - Standing and wall mounted
198     glPushMatrix();

```

```

199
200     // Initial Positioning and rotation
201     glTranslated(translate[0], translate[1], translate[2]);
202     glRotated(rotate[0], 1, 0, 0);
203     glRotated(rotate[1], 0, 1, 0);
204     glRotated(rotate[2], 0, 0, 1);
205
206     //drawWallMounted();
207     drawStanding();
208
209     glPopMatrix();
210 }
211
212 void Terminal::drawStanding()
213 {
214     // Steel grey
215     glColor3d(.1, .1, .1);
216
217     // Draw Floor mount
218     glPushMatrix();
219     glTranslated(0, -1, 0);
220     glScaled(.5, .1, 1);
221     glutSolidCube(.5);
222     glPopMatrix();
223
224     // Draw leg
225     glPushMatrix();
226     glTranslated(0, -.6, 0);
227     glScaled(.1, .75, .1);
228     glutSolidCube(1);
229     glPopMatrix();
230
231     // Draw Monitor
232     glPushMatrix();
233     glScaled(.1, .5, .7);
234     glutSolidCube(1);
235
236     // Draw Screen
237     glPushMatrix();
238     // Change Screen based on power
239     if (checkIfOn())
240         glColor3d(0, 1, 1);
241     else
242         glColor3d(0, 0, 0);
243
244     glTranslated(-.3, 0, 0);
245     glutSolidCube(.7);
246
247     glPopMatrix();
248
249     glPopMatrix();
250 }
251
252 void Terminal::drawWallMounted()
253 {
254     glColor3d(0, 1, 1);

```

```

255         glutSolidSphere(1, 50, 50);
256     }
257
258     double Terminal::getX()
259     {
260         return translate[0];
261     }
262
263     double Terminal::getY()
264     {
265         return translate[1];
266     }
267
268     double Terminal::getZ()
269     {
270         return translate[2];
271     }
272
273     void Terminal::parseFile()
274     {
275         ifstream infile{ TERM_PATH + file};
276         string buff;
277
278         if (!infile)
279         {
280             Logger log;
281             vector<string> output = { "FATAL ERROR: File ", file, " NOT FOUND"
                                     };
282             log.logLine(output);
283             exit(FILE_NOT_FOUND);
284         }
285
286         content.push_back("HELP"); // Help text is always the 0th tag in the
            terminals
287
288         getline(infile, buff);
289         prompts.push_back(buff); // Push back the file tag
290         getline(infile, buff);
291
292         while (buff != "<TAGS>")
293         {
294             size_t pos = buff.find("--");
295             if (pos != string::npos)
296             {
297                 prompts.push_back(buff.substr(0, pos));
298                 content.push_back(buff.substr(pos + 3));
299             }
300             getline(infile, buff);
301         }
302     }
303
304     string Terminal::getID()
305     {
306         return id;
307     }
308 }

```

```

309
310 Terminal::Terminal(const double(&_translate)[3], const double(&_rotate)[3], string
    _file, string _id)
311 {
312     // Copies the color
313     copy(begin(_translate), end(_translate), translate);
314
315     // Copies the vertices
316     copy(begin(_rotate), end(_rotate), rotate);
317
318     bTexture = SOIL_load_OGL_texture
319         (
320             "Resources\\Images\\banner.png",    // Image to load
321             SOIL_LOAD_AUTO,                      // ???
322             SOIL_CREATE_NEW_ID,
323             SOIL_FLAG_MIPMAPS | SOIL_FLAG_COMPRESS_TO_DXT // !?!?!?!
324         );
325
326     if (bTexture == 0)
327     {
328         Logger log;
329         vector<string> output = { "FATAL ERROR: SOIL cannot load terminal
            banner", SOIL_last_result() };
330         log.logLine(output);
331         exit(SOIL_ERROR);
332     }
333
334     file = _file;
335
336     id = _id;
337
338     num = 0;
339
340     parseFile();
341 }

```

6.1.39 TextEngine.h

```

1  /*****\
2  * TextEngine.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the TextEngine class*
8  * Which uses glutBitmapCharacter to print strings into the *
9  * OpenGL window. *
10 \*****/
11
12 #ifndef TEXTENGINE_H
13 #define TEXTENGINE_H
14
15 // For string lengths in displaying text
16 #include <string>
17
18 // For multiple lines of text
19 #include <vector>

```



```

20
21 class TextEngine
22 {
23 private:
24     // The path to the game's text files (.log's)
25     static const char* TEXT_PATH;
26     // The offset between lines of characters
27     static const double LINE_OFFSET;
28
29     void displayText(
30         // 2d start location of the text
31         double x, double y,
32         // rgb color of text
33         double r, double g, double b,
34         // glut font and text to be displayed
35         void* font,
36         std::vector<std::string> text);
37
38     // Searches a text file for text related to the tag, and returns all text
39     // within the tag
40     std::vector<std::string> findText(std::string fileName, std::string tag);
41 public:
42     // Takes the location to display the text, color of the text,
43     // The file to read from, and a tag to search for
44     void openFile(double x, double y, double r, double g, double b,
45         std::string fileName, std::string tag);
46
47     // Takes in a string to display
48     void printString(double x, double y, double r, double g, double b,
49         std::string text);
50
51     // Returns text from fileName specified by tag
52     std::vector<std::string> getText(std::string fileName, std::string tag);
53 };
54
55 #endif

```

6.1.40 TextEngine.cpp

```

1  /*****\
2  * TextEngine.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the TextEngine class *
8  * For more information, see TextEngine.h *
9  \*****/
10
11 // TextEngine declaration and std::string
12 #include "TextEngine.h"
13
14 // std::ifstream
15 #include <fstream>
16
17 // Standard I/O for debugging

```

```

18 #include <iostream>
19
20 // OpenGL API
21 #include <gl\glut.h>
22
23 using namespace std;
24
25 // Initializing the constants
26 const char* TextEngine::TEXT_PATH = "Resources\\Text\\";
27 const double TextEngine::LINE_OFFSET = 20;
28
29 void TextEngine::displayText(double x, double y,
30     double r, double g, double b,
31     void* font, vector<string> text)
32 {
33     vector<string>::iterator it;
34
35     // Iterates throuh the text vector and prints it to the screen
36     for (it = text.begin(); it != text.end(); it++)
37     {
38         glColor3d(r, g, b);
39         glRasterPos2d(x, y);
40
41         for (unsigned int i = 0; i < it->length(); i++)
42         {
43             glutBitmapCharacter(font, (*it)[i]);
44         }
45
46         // Because glut does not print newlines
47         y += LINE_OFFSET;
48     }
49 }
50
51 vector<string> TextEngine::findText(string fileName, string tag)
52 {
53     // The tags are listed between dollar signs
54     string fullTag = '$' + tag + '$';
55
56     string fullPath = TEXT_PATH + fileName;
57
58     ifstream infile(fullPath);
59
60     // Buffer to read in data
61     string buff;
62     // Array to store strings
63     vector<string> data;
64
65     // Find the string(s) to read in
66     getline(infile, buff);
67     while (infile && buff != fullTag)
68     {
69         getline(infile, buff);
70     }
71
72     // Store the string(s)
73     getline(infile, buff);

```

```

74         while (infile && buff != "$END$")
75         {
76             data.push_back(buff);
77             getline(infile, buff);
78         }
79
80         infile.close();
81
82         return data;
83     }
84
85     void TextEngine::openFile(double x, double y,
86                             double r, double g, double b,
87                             string fileName, string tag)
88     {
89         vector<string> input = findText(fileName, tag);
90
91         displayText(x, y, r, g, b,
92                     GLUT_BITMAP_HELVETICA_18,
93                     input);
94     }
95
96     vector<string> TextEngine::getText(string fileName, string tag)
97     {
98         vector<string> input = findText(fileName, tag);
99
100        return input;
101    }
102
103     void TextEngine::printString(double x, double y, double r, double g, double b,
104                                 string text)
105     {
106         glColor3d(r, g, b);
107         glRasterPos2d(x, y);
108
109         for (unsigned int i = 0; i < text.length(); i++)
110         {
111             glutBitmapCharacter(GLUT_BITMAP_HELVETICA_18, text[i]);
112         }
113
114         // Vertical spacing
115         y += LINE_OFFSET;
116     }

```

6.1.41 Triangle.h

```

1  /*****\
2  * Triangle.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * * *
7  * This file contains the declaration of the Triangle class *
8  * Which is used to hold the details of a 2D Triangle and *
9  * draw it to the screen *
10 \*****/
11

```

```

12 #ifndef TRIANGLE_H
13 #define TRIANGLE_H
14
15 class Triangle
16 {
17 private:
18     // Arrays containing the colors and the xyz vertices of the triangles
19     double color[4], vertices[9];
20 public:
21     // Takes in the vertices and color of the triangle
22     Triangle(const double(&new_vertices)[9], const double(&new_color)[4]);
23     // Print the triangle in 3D
24     void Display();
25     // Print the triangle in 2D
26     void Display2D();
27 };
28
29 #endif

```

6.1.42 Triangle.cpp

```

1  /*****\
2  * Triangle.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the triangle class *
8  * For more information, see Triangle.h *
9  \*****/
10
11 // Class declaration
12 #include "Triangle.h"
13
14 // For std::copy
15 #include <iterator>
16 #include <utility>
17
18 // OpenGL API
19 #include <GL\glut.h>
20
21 using namespace std;
22
23
24 Triangle::Triangle(const double(&new_vertices)[9], const double(&new_color)[4])
25 {
26     // Copies the color entry
27     copy(begin(new_color), end(new_color), color);
28
29     // Copies the vertices
30     copy(begin(new_vertices), end(new_vertices), vertices);
31 }
32
33 void Triangle::Display()
34 {
35     // Sets OpenGL's color to the triangle's color
36     glColor4f(color[0], color[1], color[2], color[3]);

```

```

37
38     // Draws the triangle
39     glBegin(GL_TRIANGLES);
40     glVertex3d(vertices[0], vertices[1], vertices[2]);
41     glVertex3d(vertices[3], vertices[4], vertices[5]);
42     glVertex3d(vertices[6], vertices[7], vertices[8]);
43     glEnd();
44 }
45
46 void Triangle::Display2D()
47 {
48     // Set's OpenGL's color to the triangle's color
49     glColor4f(color[0], color[1], color[2], color[3]);
50
51     // Draw's the triangle without the Z vertices
52     glBegin(GL_TRIANGLES);
53     glVertex2d(vertices[0], vertices[1]);
54     glVertex2d(vertices[3], vertices[4]);
55     glVertex2d(vertices[6], vertices[7]);
56     glEnd();
57 }

```

6.1.43 Trigger.h

```

1  /*****\
2  * Trigger.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the Trigger class *
8  * Which can be bound to a trigger-object that, upon use, *
9  * Will activate a designated target-object. *
10 \*****/
11
12 #ifndef TRIGGER_H
13 #define TRIGGER_H
14
15 #include "Terminal.h"
16 #include "Switch.h"
17
18 #include "GCTypes.h"
19
20 class Trigger
21 {
22 private:
23     void* trigger; // The object that activates the target
24     void* target; // The object that is activated by the target
25
26     GCType triggerType; // The type (defined from GCTypes.h) of the trigger
27     GCType targetType; // The type (defined from GCTypes.h) of the target
28
29     void activateTarget();
30
31 public:
32     // Get the object type of the trigger
33     int getTriggerType();

```

```

34         // Attempts to trigger the target
35         bool tryToTrigger(void* input, GCtype type);
36         // Binds the triggering object
37         void bindTrigger(void* _trigger);
38         // Binds the target object
39         void bindTarget(void* _target);
40         // Constructor takes in trigger type and target type
41         Trigger(GCtype _triggerType, GCtype _targetType);
42
43     };
44
45 #endif

```

6.1.44 Trigger.cpp

```

1  /*****\
2  * Trigger.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the Trigger class *
8  * For more information, see Trigger.h *
9  \*****/
10
11 #include <cstdlib>
12 #include "Trigger.h"
13
14 int Trigger::getTriggerType()
15 {
16     return triggerType;
17 }
18
19 void Trigger::activateTarget()
20 {
21     switch (targetType)
22     {
23         case T_TERMINAL:
24         {
25             Terminal* t = (Terminal*)target;
26             t->activate();
27             break;
28         }
29         case T_SWITCH:
30         {
31             Switch* s = (Switch*)target;
32             s->activate();
33             break;
34         }
35         default:
36         {
37             break;
38         }
39     }
40 }
41
42 bool Trigger::tryToTrigger(void* input, GCtype type)

```

```

43 {
44     // If this trigger is the correct type
45     if (triggerType != type) return false;
46
47     // If this trigger is the correct object
48     if (trigger != input) return false;
49
50     activateTarget();
51
52     return true;
53 }
54
55 void Trigger::bindTrigger(void* _trigger)
56 {
57     trigger = _trigger;
58 }
59
60 void Trigger::bindTarget(void* _target)
61 {
62     target = _target;
63 }
64
65 Trigger::Trigger(GCtype _triggerType, GCtype _targetType)
66 {
67     trigger = NULL;
68     target = NULL;
69     triggerType = _triggerType;
70     targetType = _targetType;
71 }

```

6.1.45 Triple.h

```

1  /*****\
2  * Triple.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the Triple class *
8  * Which is just a simple 3-tuple really *
9  \*****/
10
11 #ifndef TRIPLE_H
12 #define TRIPLE_H
13
14 class Triple
15 {
16 public:
17     double a, b, c;
18 };
19
20 // For converting to a triple
21 Triple makeTrip(double _a, double _b, double _c);
22
23 #endif

```

6.1.46 Triple.cpp

```
1  /*****\
2  * Triple.cpp                                *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * * * * * * * * * * * * * * * * * * * * * * *
7  * This file contains the definition of the TwoD class *
8  * For more information, see Triple.h *
9  \*****/
10
11 #include "Triple.h"
12
13 Triple makeTrip(double _a, double _b, double _c)
14 {
15     Triple ret;
16     ret.a = _a;
17     ret.b = _b;
18     ret.c = _c;
19
20     return ret;
21 }
```

6.1.47 TwoD.h

```
1  /*****\
2  * TwoD.h                                    *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * * * * * * * * * * * * * * * * * * * * * * *
7  * This file contains the declaration of the TwoD class *
8  * Which is used to hold the data and functionality for *
9  * Drawing in 2D with OpenGL *
10 \*****/
11
12 #ifndef TWOD
13 #define TWOD
14
15 class TwoD
16 {
17 protected:
18     // The pixel boundaries of the screen
19     const double SCREENTOP = 0, SCREENBOTTOM = 1080,
20                SCREENLEFT = 0, SCREENRIGHT = 1920;
21
22     // Prepares OpenGL draw in 2D
23     void prepare2D();
24
25     // "Resets" OpenGL to draw in 3D
26     void prepare3D();
27
28 };
29
30 #endif
```


6.1.48 TwoD.cpp

```
1  /*****\
2  * TwoD.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the TwoD class *
8  * For more information, see TwoD.h *
9  \*****/
10
11 #include "TwoD.h"
12
13 // OpenGL API
14 #include <gl\glut.h>
15
16 void TwoD::prepare2D()
17 {
18     // Disable depth testing
19     glDisable(GL_DEPTH_TEST);
20     // Disable writing to the z buffer
21     glDepthMask(GL_FALSE);
22     // Disables lighting
23     glDisable(GL_LIGHTING);
24
25     // Create an orthogonal matrix to write on
26     glMatrixMode(GL_PROJECTION);
27     glPushMatrix();
28     glLoadIdentity();
29     glOrtho(SCREENLEFT, SCREENRIGHT, SCREENBOTTOM, SCREENTOP, -1, 1);
30     glMatrixMode(GL_MODELVIEW);
31     glPushMatrix();
32     glLoadIdentity();
33 }
34
35 void TwoD::prepare3D()
36 {
37     // Discards the orthogonal matrices
38     glMatrixMode(GL_PROJECTION);
39     glPopMatrix();
40     glMatrixMode(GL_MODELVIEW);
41     glPopMatrix();
42
43     // Enable depth testing
44     glEnable(GL_DEPTH_TEST);
45     // Enables writing to the z buffer
46     glDepthMask(GL_TRUE);
47     // Renable lighting
48     glEnable(GL_LIGHTING);
49 }
```

6.2 Database

6.2.1 Walls

ID	LEVEL	X1	X2	X3	X4	Y1	Y2	Y3	Y4	Z1	Z2	Z3	Z4	R	G	B	A	Axis
ID	LEVEL	X1	X2	X3	X4	Y1	Y2	Y3	Y4	Z1	Z2	Z3	Z4	R	G	B	A	Axis
lviceliling	LEVELZERO	-5	-5	8	8	1	1	1	1	-4	1	1	-4	0.70	0.70	0.70	1	0
lvifloor	LEVELZERO	-5	-5	8	8	-1	-1	-1	-1	-4	1	1	-4	0.70	0.70	0.70	1	0
room0frntlftwall	LEVELZERO	5	5	5	5	-1	1	1	-1	-4	-4	-2.5	-2.5	0.29	0.29	0.29	1	z
room0frntrghtwall	LEVELZERO	5	5	5	5	-1	1	1	-1	-0.5	-0.5	1	1	0.29	0.29	0.29	1	z
room0backwall	LEVELZERO	-5	-5	-5	-5	-1	1	1	-1	-4	-4	1	1	0.29	0.29	0.29	1	z
room0rghtwall	LEVELZERO	-5	-5	5	5	-1	1	1	-1	1	1	1	1	0.29	0.29	0.29	1	x
room0frnttopwall	LEVELZERO	5	5	5	5	0.5	1	1	0.5	-2.5	-2.5	-0.5	-0.5	0.29	0.29	0.29	1	z
room1lftwall	LEVELZERO	5	5	8	8	-1	1	1	-1	-4	-4	-4	-4	0.29	0.29	0.29	1	x
room1rghtwall	LEVELZERO	5	5	8	8	-1	1	1	-1	1	1	1	1	0.29	0.29	0.29	1	x
room1frntbotwall	LEVELZERO	8	8	8	8	-1	-0.5	-0.5	-1	-4	-4	1	1	0.29	0.29	0.29	1	z
room1frnttopwall	LEVELZERO	8	8	8	8	0.5	1	1	0.5	-4	-4	1	1	0.29	0.29	0.29	1	z
room0lftlftwall	LEVELZERO	-5	-5	-1.5	-1.5	-1	1	1	-1	-4	-4	-4	-4	0.29	0.29	0.29	1	x
room0lfttrghtwall	LEVELZERO	1.5	1.5	5	5	-1	1	1	-1	-4	-4	-4	-4	0.29	0.29	0.29	1	x
room0lfttopwall	LEVELZERO	-1.5	-1.5	1.5	1.5	0.70	1	1	0.70	-4	-4	-4	-4	0.29	0.29	0.29	1	x
room0frntmidwall	LEVELZERO	8	8	8	8	0.5	-0.5	-0.5	0.5	-4	-4	1	1	0.12	0.56	1	0.60	z
lv1Floor	LEVELONE	30	30	-30	-30	-1	-1	-1	-1	40	-5	-5	40	0.70	0.70	0.70	1	0
lv1HangarCeiling	LEVELONE	15	15	-15	-15	5	5	5	5	-5	-5	-5	-5	0.70	0.70	0.70	1	0
lv1HangerFrntLeftWall	LEVELONE	15	15	1	1	-1	5	5	-1	5	5	5	5	0.80	0	0	1	x
lv1HangerFrntRghtWall	LEVELONE	-1	-1	-15	-15	-1	5	5	-1	5	5	5	5	0.80	0	0	1	x
lv1HangerFrntTopWall	LEVELONE	1	1	-1	-1	1	5	5	1	5	5	5	5	0.80	0	0	1	x
lv1HangerRghtWall	LEVELONE	-15	-15	-15	-15	-1	5	5	-1	5	5	-5	-5	0.80	0	0	1	z
lv1HangerLeftWall	LEVELONE	15	15	15	15	-1	5	5	-1	5	5	-5	-5	0.80	0	0	1	z
lv1HangerBckWall	LEVELONE	15	15	-15	-15	-1	5	5	-1	-5	-5	-5	-5	0.12	0.56	1	0.402	z
lv1HallLftWall1	LEVELONE	3	3	3	3	-1	1	1	-1	5	5	11	11	0.80	0	0	1	z
lv1HallRghtWall1	LEVELONE	-3	-3	-3	-3	-1	1	1	-1	5	5	8	8	0.80	0	0	1	z
lv1HallLftWall2	LEVELONE	3	3	3	3	-1	1	1	-1	13	13	19	19	0.80	0	0	1	z
lv1HallRghtWall2	LEVELONE	-3	-3	-3	-3	-1	1	1	-1	10	10	15	15	0.80	0	0	1	z
lv1HallRghtWall3	LEVELONE	-3	-3	-3	-3	-1	1	1	-1	17	17	19	19	0.80	0	0	1	z
lv1HallCeiling	LEVELONE	15	15	-15	-15	1	1	1	1	5	29	29	5	0.70	0.70	0.70	1	0
lv1HallLftEnd	LEVELONE	7.5	7.5	1	1	-1	1	1	-1	19	19	19	19	0.80	0	0	1	x
lv1HallRghtEnd	LEVELONE	-3	-3	-1	-1	-1	1	1	-1	19	19	19	19	0.80	0	0	1	x
lv1LftRoom1LeftWall	LEVELONE	-3	-3	-15	-15	-1	1	1	-1	19	19	19	19	0.80	0	0	1	x
lv1LftRoom1RghtWall	LEVELONE	-3	-3	-15	-15	-1	1	1	-1	12.5	12.5	12.5	12.5	0.80	0	0	1	x
lv1LftRoomsBckWall	LEVELONE	-15	-15	-15	-15	-1	1	1	-1	19	19	5	5	0.80	0	0	1	z
lv1Room4LftWall	LEVELONE	7.5	7.5	7.5	7.5	-1	1	1	-1	19	19	29	29	0.80	0	0	1	z
lv1Room4RghtWall	LEVELONE	-7.5	-7.5	-7.5	-7.5	-1	1	1	-1	19	19	29	29	0.80	0	0	1	z
lv1Room3LeftWall	LEVELONE	20	20	20	20	-1	1	1	-1	10	10	-3	-3	0.80	0	0	1	z
lv1Room3BckWall	LEVELONE	20	20	15	15	-1	1	1	-1	-3	-3	-3	-3	0.80	0	0	1	x
lv1Room3FrntWall1	LEVELONE	20	20	6	6	-1	1	1	-1	10	10	10	10	0.80	0	0	1	x
lv1Room3FrntWall2	LEVELONE	4	4	3	3	-1	1	1	-1	10	10	10	10	0.80	0	0	1	x
lv1Room2LftWall	LEVELONE	7.5	7.5	7.5	7.5	-1	1	1	-1	19	19	10	10	0.80	0	0	1	z
lv1Room3Ceiling	LEVELONE	20	20	15	15	1	1	1	1	-3	10	10	-3	0.70	0.70	0.70	1	0
lv1Room4BckWallLft	LEVELONE	7.5	7.5	1	1	-1	1	1	-1	29	29	29	29	0.80	0	0	1	x
lv1Room4BckWallRght	LEVELONE	-1	-1	-7.5	-7.5	-1	1	1	-1	29	29	29	29	0.80	0	0	1	x
lv2Room0BckWallLft	LEVELTWO	5	5	1	1	-1	1	1	-1	2	2	2	2	0	0.80	0	1	x
lv2Room0BckWallRght	LEVELTWO	-5	-5	-1	-1	-1	1	1	-1	2	2	2	2	0	0.80	0	1	x
lv2Room0LftWallLft	LEVELTWO	-5	-5	-5	-5	-1	1	1	-1	2	2	1	1	0	0.80	0	1	z
lv2Room0LftWallRght	LEVELTWO	-5	-5	-5	-5	-1	1	1	-1	-2	-2	-2	-2	0	0.80	0	1	z
lv2Room0FrntWall	LEVELTWO	-5	-5	5	5	-1	1	1	-1	-2	-2	-1	-1	0	0.80	0	1	x
lv2Room0RghtWallLft	LEVELTWO	5	5	5	5	-1	1	1	-1	2	2	2	2	0	0.80	0	1	z
lv2Room0RghtWallRght	LEVELTWO	5	5	5	5	-1	1	1	-1	1	1	2	2	0	0.80	0	1	z
lv2Room0FakeDoor	LEVELTWO	-1	-1	1	1	-1	1	1	-1	2	2	2	2	0.29	0.29	0.29	1	x
lv2LftHallBckWall	LEVELTWO	-5	-5	-18	-18	-1	1	1	-1	1	1	1	1	0	0.80	0	1	x
lv2RghtHallBckWall	LEVELTWO	5	5	18	18	-1	-1	-1	1	1	1	1	1	0	0.80	0	1	z
lv2LftHallLftWall	LEVELTWO	-18	-18	-18	-18	1	1	1	1	1	1	-15	-15	0	0.80	0	1	z
lv2RghtHallRghtWall	LEVELTWO	18	18	18	18	1	-1	-1	1	1	1	-15	-15	0	0.80	0	1	z
lv2LftHallFrntWallRght	LEVELTWO	-5	-5	-9	-9	-0.5	0.5	0.5	-0.5	-1	-1	-1	-1	0	0.80	0	1	x
lv2LftHallLftWall	LEVELTWO	-11	-11	-15	-15	-0.5	0.5	0.5	-0.5	-1	-1	-1	-1	0	0.80	0	1	x
lv2LftHallTopStrip1	LEVELTWO	-5	-5	-15	-15	1	0.5	0.5	1	-1	-1	-1	-1	0	0.80	0	1	x
lv2LftHallBotStrip1	LEVELTWO	-5	-5	-15	-15	-0.5	-1	-1	-0.5	-1	-1	-1	-1	0	0.80	0	1	x
lv2RghtHallFrntWallLft	LEVELTWO	5	5	9	9	-0.5	0.5	0.5	-0.5	-1	-1	-1	-1	0	0.80	0	1	x
lv2RghtHallFrntWallRght	LEVELTWO	11	11	15	15	-0.5	0.5	0.5	-0.5	-1	-1	-1	-1	0	0.80	0	1	x
lv2RghtHallTopStrip1	LEVELTWO	5	5	15	15	0.5	1	1	0.5	-1	-1	-1	-1	0	0.80	0	1	x
lv2RghtHallBotStrip1	LEVELTWO	5	5	15	15	-0.5	-1	-1	-0.5	-1	-1	-1	-1	0	0.80	0	1	x
lv2LftRoomsRghtWall	LEVELTWO	-5	-5	-5	-5	-1	-1	-1	1	-2	-2	-12	-12	0	0.80	0	1	z
lv2RghtRoomsLftWall	LEVELTWO	5	5	5	5	1	1	1	-1	-2	-2	-12	-12	0	0.80	0	1	z
lv2LftHallBckWall2	LEVELTWO	-18	-18	-1	-1	-1	-1	-1	1	-15	-15	-15	-15	0	0.80	0	1	x
lv2RghtHallBckWall2	LEVELTWO	18	18	1	1	-1	-1	-1	1	-15	-15	-15	-15	0	0.80	0	1	x
lv2BckWall	LEVELTWO	-9	-9	9	9	-1	-1	-1	1	-12	-12	-12	-12	0	0.80	0	1	x
lv2LftDividerLft	LEVELTWO	-15	-15	-11	-11	1	-1	-1	1	-5.5	-5.5	-5.5	-5.5	0	0.80	0	1	x
lv2LftDividerRght	LEVELTWO	-9	-9	-5	-5	1	-1	-1	1	-5.5	-5.5	-5.5	-5.5	0	0.80	0	1	x
lv2LftDividerTop	LEVELTWO	-11	-11	-9	-9	0.5	1	1	0.5	-5.5	-5.5	-5.5	-5.5	0	0.80	0	1	x
lv2LftDividerTBot	LEVELTWO	-11	-11	-9	-9	-0.5	-1	-1	-0.5	-5.5	-5.5	-5.5	-5.5	0	0.80	0	1	x
lv2RghtDividerLft	LEVELTWO	15	15	11	11	1	-1	-1	1	-5.5	-5.5	-5.5	-5.5	0	0.80	0	1	x
lv2RghtDividerRght	LEVELTWO	9	9	5	5	1	-1	-1	1	-5.5	-5.5	-5.5	-5.5	0	0.80	0	1	x
lv2RghtDividerTop	LEVELTWO	11	11	9	9	0.5	1	1	0.5	-5.5	-5.5	-5.5	-5.5	0	0.80	0	1	x
lv2RghtDividerTBot	LEVELTWO	11	11	9	9	-0.5	-1	-1	-0.5	-5.5	-5.5	-5.5	-5.5	0	0.80	0	1	x
lv2Ceiling	LEVELTWO	-18	-18	18	18	1	1	1	1	2	-20	-20	2	0.70	0.70	0.70	1	0
lv2Floor	LEVELTWO	-18	-18	18	18	-1	-1	-1	-1	2	-20	-20	2	0.70	0.70	0.70	1	0
lv2LftInnerWallLft	LEVELTWO	-15	-15	-15	-15	-1	1	1	-1	-1	-1	-2	-2	0	0.80	0	1	z
lv2LftInnerWallCtr	LEVELTWO	-15	-15	-15	-15	-1	1	1	-1	-4	-4	-8	-8	0	0.80	0	1	z
lv2LftInnerWallRght	LEVELTWO	-15	-15	-15	-15	-1	1	1	-1	-10	-10	-12	-12	0	0.80	0	1	z
lv2RghtInnerWallLft	LEVELTWO	15	15	15	15	-1	1	1	-1	-1	-1	-2	-2	0	0.80	0	1	z
lv2RghtInnerWallCtr	LEVELTWO	15	15	15	15	-1	1	1	-1	-4	-4	-8	-8	0	0.80	0	1	z
lv2RghtInnerWallRght	LEVELTWO	15	15	15	15	-1	1	1	-1	-10	-10	-12	-12	0	0.80	0	1	z
lv2EndHallLft	LEVELTWO	-1	-1	-1	-1	-1	1	1	-1	-15	-15	-20	-20	0	0.80	0	1	z
lv2EndHallRght	LEVELTWO	1	1	1	1	-1	1	1	-1	-15	-15	-20	-20	0	0.80	0	1	z
lv3StrtWallLft	LEVELTHREE	-1	-1	-13	-13	-1	1	1	-1	1	1	1	1	0	0	0.80	1	x
lv3StrtWallRght	LEVELTHREE	1	1	13	13	-1	1	1	-1	1	1	1	1	0	0	0.80	1	x
lv3Room0RghtWall	LEVEL																	

ID	LEVEL	X1	X2	X3	X4	Y1	Y2	Y3	Y4	Z1	Z2	Z3	Z4	R	G	B	A	Axis
lv13Ceiling	LEVELTHREE	-13	-13	13	13	1	1	1	1	1	-23	-23	1	0.70	0.70	0.70	1	0
lv13Floor	LEVELTHREE	-13	-13	13	13	-1	-1	-1	-1	1	-23	-23	1	0.70	0.70	0.70	1	0
lv13Room0/1Divid	LEVELTHREE	-13	-13	-8	-8	-1	1	1	-1	-5	-5	-5	-5	0	0	0.80	1	x
lv13Room1/2Divid	LEVELTHREE	-13	-13	-8	-8	-1	1	1	-1	-11	-11	-11	-11	0	0	0.80	1	x
lv13Room2/3Divid	LEVELTHREE	-13	-13	-8	-8	-1	1	1	-1	-17	-17	-17	-17	0	0	0.80	1	x
lv13Room7/6Divid	LEVELTHREE	13	13	8	8	-1	1	1	-1	-5	-5	-5	-5	0	0	0.80	1	x
lv13Room6/5Divid	LEVELTHREE	13	13	8	8	-1	1	1	-1	-11	-11	-11	-11	0	0	0.80	1	x
lv13Room5/4Divid	LEVELTHREE	13	13	8	8	-1	1	1	-1	-17	-17	-17	-17	0	0	0.80	1	x
lv13FrntWall	LEVELTHREE	-13	-13	13	13	-1	1	1	-1	-23	-23	-23	-23	0	0	0.80	1	x
lv13InnerLftWall	LEVELTHREE	-3	-3	-3	-3	-1	1	1	-1	-2	-2	-20	-20	0	0	0.80	1	z
lv13InnerRghtWall	LEVELTHREE	3	3	3	3	-1	1	1	-1	-2	-2	-20	-20	0	0	0.80	1	z
lv13Room0LftWall	LEVELTHREE	-13	-13	-13	-13	-1	1	1	-1	1	1	-1	-1	0	0	0.80	1	z
lv13Room0/1LftWall	LEVELTHREE	-13	-13	-13	-13	-1	1	1	-1	-3	-3	-7	-7	0	0	0.80	1	z
lv13Room1/2LftWall	LEVELTHREE	-13	-13	-13	-13	-1	1	1	-1	-9	-9	-13	-13	0	0	0.80	1	z
lv13Room2/3LftWall	LEVELTHREE	-13	-13	-13	-13	-1	1	1	-1	-15	-15	-19	-19	0	0	0.80	1	z
lv13Room3LftWall	LEVELTHREE	-13	-13	-13	-13	-1	1	1	-1	-21	-21	-23	-23	0	0	0.80	1	z
lv13Room7RghtWall	LEVELTHREE	13	13	13	13	-1	1	1	-1	1	1	-1	-1	0	0	0.80	1	z
lv13Room7/6RghtWall	LEVELTHREE	13	13	13	13	-1	1	1	-1	-3	-3	-7	-7	0	0	0.80	1	z
lv13Room6/5RghtWall	LEVELTHREE	13	13	13	13	-1	1	1	-1	-9	-9	-13	-13	0	0	0.80	1	z
lv13Room5/4RghtWall	LEVELTHREE	13	13	13	13	-1	1	1	-1	-15	-15	-19	-19	0	0	0.80	1	z
lv13Room4RghtWall	LEVELTHREE	13	13	13	13	-1	1	1	-1	-21	-21	-23	-23	0	0	0.80	1	z
lv13Entrance	LEVELTHREE	-1	-1	1	1	-1	1	1	-1	1	1	1	1	0.29	0.29	0.29	1	x
lv13Room0FakeDoor	LEVELTHREE	-13	-13	-13	-13	-1	-1	-1	-1	-1	-1	-3	-3	0.5	0.5	0.5	1	z
lv13Room1FakeDoor	LEVELTHREE	-13	-13	-13	-13	-1	1	1	-1	-7	-7	-9	-9	0.5	0.5	0.5	1	z
lv13Room2FakeDoor	LEVELTHREE	-13	-13	-13	-13	-1	1	1	-1	-13	-13	-15	-15	0.5	0.5	0.5	1	z
lv13Room3FakeDoor	LEVELTHREE	-13	-13	-13	-13	-1	1	1	-1	-19	-19	-21	-21	0.5	0.5	0.5	1	z
lv13Room7FakeDoor	LEVELTHREE	13	13	13	13	-1	1	1	-1	-1	-1	-3	-3	0.5	0.5	0.5	1	z
lv13Room6FakeDoor	LEVELTHREE	13	13	13	13	-1	1	1	-1	-7	-7	-9	-9	0.5	0.5	0.5	1	z
lv13Room5FakeDoor	LEVELTHREE	13	13	13	13	-1	1	1	-1	-13	-13	-15	-15	0.5	0.5	0.5	1	z
lv13Room4FakeDoor	LEVELTHREE	13	13	13	13	-1	1	1	-1	-19	-19	-21	-21	0.5	0.5	0.5	1	z
lv13Room8BckWall	LEVELTHREE	-3	-3	3	3	-1	1	1	-1	-12	-12	-12	-12	0	0	0.80	1	x
lv13Room9BckWall	LEVELTHREE	-3	-3	3	3	-1	1	1	-1	-15	-15	-15	-15	0	0	0.80	1	x
lv13Room8FrntWallLft	LEVELTHREE	-3	-3	-1	-1	-1	1	1	-1	-2	-2	-2	-2	0	0	0.80	1	x
lv13Room8FrntWallRght	LEVELTHREE	3	3	1	1	-1	1	1	-1	-2	-2	-2	-2	0	0	0.80	1	x
lv13Room9FrntWallLft	LEVELTHREE	-3	-3	-1	-1	-1	1	1	-1	-20	-20	-20	-20	0	0	0.80	1	x
lv13Room9FrntWallRght	LEVELTHREE	3	3	1	1	-1	1	1	-1	-20	-20	-20	-20	0	0	0.80	1	x
lv14Room0LftWall	LEVELFOUR	-5	-5	-5	-5	-1	1	1	-1	-2	-2	2	2	0.29	0.29	0.29	1	z
lv14Room0RghtWall	LEVELFOUR	5	5	5	5	-1	1	1	-1	2	2	-2	-2	0.29	0.29	0.29	1	z
lv14Room0BckLft	LEVELFOUR	-5	-5	-1	-1	-1	1	1	-1	2	2	2	2	0.29	0.29	0.29	1	x
lv14Room0BckRght	LEVELFOUR	1	1	5	5	-1	1	1	-1	2	2	2	2	0.29	0.29	0.29	1	x
lv14Room0Ceiling	LEVELFOUR	5	5	-5	-5	1	1	1	1	2	-2	-2	-2	0.70	0.70	0.70	1	0
lv14Room0Floor	LEVELFOUR	5	5	-5	-5	-1	-1	-1	-1	2	-2	-2	-2	0.70	0.70	0.70	1	0
lv14Entrance	LEVELFOUR	-1	-1	1	1	-1	1	1	-1	2	2	2	2	0.5	0.5	0.5	1	x
lv14Room1LftWall	LEVELFOUR	10	10	10	10	-5	5	5	-5	-2	-2	-12	-12	0.60	0.60	0.60	1	z
lv14Room1RghtWall	LEVELFOUR	-10	-10	-10	-10	-5	5	5	-5	-2	-2	-12	-12	0.60	0.60	0.60	1	z
lv14Room1FrntWall	LEVELFOUR	10	10	-10	-10	-5	5	5	-5	-12	-12	-12	-12	0.60	0.60	0.60	1	x
lv14Room1BckLftWall	LEVELFOUR	-10	-10	-5	-5	-5	5	5	-5	-2	-2	-2	-2	0.60	0.60	0.60	1	x
lv14Room1BckRghtWall	LEVELFOUR	10	10	5	5	-5	5	5	-5	-2	-2	-2	-2	0.60	0.60	0.60	1	x
lv14Room1Ceiling	LEVELFOUR	10	10	-10	-10	5	5	5	-5	-2	-12	-12	-12	0.70	0.70	0.70	1	0
lv14Room1Floor	LEVELFOUR	10	10	-10	-10	-5	-5	-5	-5	-2	-12	-12	-12	0.70	0.70	0.70	1	0
lv14Room0FrntWall	LEVELFOUR	-5	-5	5	5	-1	1	1	-1	-2	-2	-2	-2	0.1	0.1	0.1	0.90	x
lv12LftBckWindowLft	LEVELTWO	-15	-15	-11	-11	1	-1	-1	1	-12	-12	-12	-12	0	0.80	0	1	x
lv12BckWindowTop	LEVELTWO	-11	-11	-9	-9	0.5	1	1	0.5	-12	-12	-12	-12	0	0.80	0	1	x
lv12BckWindowBot	LEVELTWO	-11	-11	-9	-9	-0.5	-1	-1	-0.5	-12	-12	-12	-12	0	0.80	0	1	x
lv12RghtBckWindowLft	LEVELTWO	15	15	11	11	1	-1	-1	1	-12	-12	-12	-12	0	0.80	0	1	x
lv12RghtWindowTop	LEVELTWO	11	11	9	9	0.5	1	1	0.5	-12	-12	-12	-12	0	0.80	0	1	x
lv12RghtWindowBot	LEVELTWO	11	11	9	9	-0.5	-1	-1	-0.5	-12	-12	-12	-12	0	0.80	0	1	x
lv12lftWindow1	LEVELTWO	-11	-11	-9	-9	-0.5	0.5	0.5	-0.5	-1	-1	-1	-1	0	1	1	0.29	x
lv12lftWindow2	LEVELTWO	-11	-11	-9	-9	-0.5	0.5	0.5	-0.5	-5.5	-5.5	-5.5	-5.5	0	1	1	0.29	x
lv12lftWindow3	LEVELTWO	-11	-11	-9	-9	-0.5	0.5	0.5	-0.5	-12	-12	-12	-12	0	1	1	0.29	x
lv12RghtWindow1	LEVELTWO	11	11	9	9	-0.5	0.5	0.5	-0.5	-1	-1	-1	-1	0	1	1	0.29	x
lv12RghtWindow2	LEVELTWO	11	11	9	9	-0.5	0.5	0.5	-0.5	-5.5	-5.5	-5.5	-5.5	0	1	1	0.29	x
lv12RghtWindow3	LEVELTWO	11	11	9	9	-0.5	0.5	0.5	-0.5	-12	-12	-12	-12	0	1	1	0.29	x

6.2.2 Doors

ID	LEVEL	X1	X2	X3	X4	Y1	Y2	Y3	Y4	Z1	Z2	Z3	Z4	R	G	B	A	axis
room0room1Door	LEVELZERO	5	5	5	5	-1	0.5	0.5	-1	-2.5	-2.5	-0.5	-0.5	0.90	0.90	0.90	1	z
lvl0ExitDoor	LEVELZERO	-1.5	-1.5	1.5	1.5	-1	0.70	0.70	-1	-4	-4	-4	-4	0.5	0.5	0.5	1	x
lvl1HangerHallDoor	LEVELONE	1	1	-1	-1	-1	1	1	-1	5	5	5	5	0.90	0.90	0.90	1	x
lvl1Room2Door	LEVELONE	3	3	3	3	-1	1	1	-1	11	11	13	13	0.90	0.90	0.90	1	z
lvl1Room0Door	LEVELONE	-3	-3	-3	-3	-1	1	1	-1	17	17	15	15	0.90	0.90	0.90	1	z
lvl1Room1Door	LEVELONE	-3	-3	-3	-3	-1	1	1	-1	10	10	8	8	0.90	0.90	0.90	1	z
lvl1Room3Door	LEVELONE	6	6	4	4	-1	1	1	-1	10	10	10	10	0.90	0.90	0.90	1	x
lvl1Room4Door	LEVELONE	1	1	-1	-1	-1	1	1	-1	19	19	19	19	0.90	0.90	0.90	1	x
lvl1ExitDoor	LEVELONE	1	1	-1	-1	1	-1	-1	1	29	29	29	29	0.5	0.5	0.5	1	x
lvl2Room0Door	LEVELTWO	-15	-15	-15	-15	-1	1	1	-1	-2	-2	-4	-4	0.90	0.90	0.90	1	z
lvl2Room1Door	LEVELTWO	-15	-15	-15	-15	-1	1	1	-1	-8	-8	-10	-10	0.90	0.90	0.90	1	z
lvl2Room2Door	LEVELTWO	15	15	15	15	-1	1	1	-1	-8	-8	-10	-10	0.90	0.90	0.90	1	z
lvl2Room3Door	LEVELTWO	15	15	15	15	-1	1	1	-1	-2	-2	-4	-4	0.90	0.90	0.90	1	z
lvl2ExitDoor	LEVELTWO	-1	-1	1	1	-1	1	1	-1	-20	-20	-20	-20	0.5	0.5	0.5	1	x
lvl3Room0Door	LEVELTHREE	-8	-8	-8	-8	-1	1	1	-1	-1	-1	-3	-3	0.13	0.5504	0.13	1	z
lvl3Room1Door	LEVELTHREE	-8	-8	-8	-8	-1	1	1	-1	-7	-7	-9	-9	0.13	0.5504	0.13	1	z
lvl3Room2Door	LEVELTHREE	-8	-8	-8	-8	-1	1	1	-1	-13	-13	-15	-15	0.70	0.13	0.13	1	z
lvl3Room3Door	LEVELTHREE	-8	-8	-8	-8	-1	1	1	-1	-19	-19	-21	-21	1	0.5504	0	1	z
lvl3Room7Door	LEVELTHREE	8	8	8	8	-1	1	1	-1	-1	-1	-3	-3	1	0.5504	0	1	z
lvl3Room6Door	LEVELTHREE	8	8	8	8	-1	1	1	-1	-7	-7	-9	-9	1	0.5504	0	1	z
lvl3Room5Door	LEVELTHREE	8	8	8	8	-1	1	1	-1	-13	-13	-15	-15	0.70	0.13	0.13	1	z
lvl3Room4Door	LEVELTHREE	8	8	8	8	-1	1	1	-1	-19	-19	-21	-21	1	0.5504	0	1	z
lvl3Room8Door	LEVELTHREE	-1	-1	1	1	-1	1	1	-1	-2	-2	-2	-2	0.90	0.90	0.90	1	x
lvl3Room9Door	LEVELTHREE	-1	-1	1	1	-1	1	1	-1	-20	-20	-20	-20	0.90	0.90	0.90	1	x

6.2.3 Switches

ID	LEVEL	target	xt	yt	zt	xr	yr	zr	type	startOn
lv10Door1	LEVELZERO	room0room1Door	5	0	-3	0	90	0	DOOR	1
lv10Door2	LEVELZERO	t'lvlzero'room1	7	0	-4	0	0	0	TERMINAL	1
lv10END	LEVELZERO	NULL	-2	0	-4	0	0	0	LEVEL'END	0
lv11END	LEVELONE	NULL	1.5	0	29	0	0	0	LEVEL'END	0
lv1Door1	LEVELONE	lv11HangerHallDoor	1.5	0	5	0	0	0	DOOR	1
lv11Door2	LEVELONE	lv11Room2Door	3	0	10	0	90	0	DOOR	1
lv11Door3	LEVELONE	lv11Room0Door	-3	0	18	0	90	0	DOOR	1
lv11Door4	LEVELONE	lv11Room1Door	-3	0	11	0	90	0	DOOR	1
lv11Door5	LEVELONE	lv11Room4Door	1.5	0	19	0	0	0	DOOR	1
lv11Door6	LEVELONE	lv11Room3Door	6.5	0	10	0	0	0	DOOR	0
lv12Door0	LEVELTWO	lv12Room0Door	-15	0	-5	0	90	0	DOOR	1
lv12Door1	LEVELTWO	lv12Room1Door	-15	0	-7	0	90	0	DOOR	0
lv12Door2	LEVELTWO	lv12Room2Door	15	0	-7	0	90	0	DOOR	1
lv12Door3	LEVELTWO	lv12Room3Door	15	0	-5	0	90	0	DOOR	0
lv12END	LEVELTWO	NULL	-1	0	-18	0	90	0	LEVEL'END	0
lv13Room0	LEVELTHREE	lv13Room0Door	-8	0	-0.5	0	90	0	DOOR	1
lv13Room1	LEVELTHREE	lv13Room1Door	-8	0	-6.5	0	90	0	DOOR	1
lv13Room2	LEVELTHREE	lv13Room2Door	-8	0	-12.5	0	90	0	DOOR	0
lv13Room3	LEVELTHREE	lv13Room3Door	-8	0	-18.5	0	90	0	DOOR	0
lv13Room7	LEVELTHREE	lv13Room7Door	8	0	-0.5	0	90	0	DOOR	0
lv13Room6	LEVELTHREE	lv13Room6Door	8	0	-6.5	0	90	0	DOOR	0
lv13Room5	LEVELTHREE	lv13Room5Door	8	0	-12.5	0	90	0	DOOR	0
lv13Room4	LEVELTHREE	lv13Room4Door	8	0	-18.5	0	90	0	DOOR	0
lv13Room0END	LEVELTHREE	NULL	-13	0	-0.5	0	90	0	LEVEL'END	0
lv13Room1END	LEVELTHREE	NULL	-13	0	-6.5	0	90	0	LEVEL'END	0
lv13Room2END	LEVELTHREE	NULL	-13	0	-12.5	0	90	0	LEVEL'END	0
lv13Room3END	LEVELTHREE	NULL	-13	0	-18.5	0	90	0	LEVEL'END	0
lv13Room7END	LEVELTHREE	NULL	13	0	-0.5	0	90	0	LEVEL'END	0
lv13Room6END	LEVELTHREE	NULL	13	0	-6.5	0	90	0	LEVEL'END	0
lv13Room5END	LEVELTHREE	NULL	13	0	-12.5	0	90	0	LEVEL'END	0
lv13Room4END	LEVELTHREE	NULL	13	0	-18.5	0	90	0	LEVEL'END	0
lv13Room8	LEVELTHREE	lv13Room8Door	-1.5	0	-2	0	0	0	DOOR	0
lv13Room9	LEVELTHREE	lv13Room9Door	1.5	0	-20	0	0	0	DOOR	1

6.2.4 Terminals

ID	LEVEL	tag	xt	yt	zt	xr	yr	zr
t'lvlzero`room1	LEVELZERO	lv0TM1.tm	7	0	-2	0	0	0
t'lvl1Room0	LEVELONE	lv1TM0.tm	-13	0	15	0	180	0
t'lvl1Room1	LEVELONE	lv1TM1.tm	-13	0	8	0	180	0
t'lvl1Room3	LEVELONE	lv1TM2.tm	17	0	-2	0	90	0
t'lvl2Room0	LEVELTWO	lv2TM0.tm	-6	0	-3	0	0	0
t'lvl2Room1	LEVELTWO	lv2TM1.tm	-6	0	-9	0	0	0
t'lvl2Room2	LEVELTWO	lv2TM2.tm	6	0	-9	0	180	0
t'lvl2Room3	LEVELTWO	lv2TM3.tm	6	0	-3	0	180	0
t'lvl3Room0	LEVELTHREE	lv3TM0.tm	-10	0	-4	180	-90	0
t'lvl3Room1	LEVELTHREE	lv3TM1.tm	-10	0	-10	180	-90	0
t'lvl3Room2	LEVELTHREE	lv3TM2.tm	-10	0	-16	180	-90	0
t'lvl3Room3	LEVELTHREE	lv3TM3.tm	-10	0	-22	180	-90	0
t'lvl3Room4	LEVELTHREE	lv3TM4.tm	10	0	-22	180	-90	0
t'lvl3Room5	LEVELTHREE	lv3TM5.tm	10	0	-16	180	-90	0
t'lvl3Room6	LEVELTHREE	lv3TM6.tm	10	0	-10	180	-90	0
t'lvl3Room7	LEVELTHREE	lv3TM7.tm	10	0	-4	180	-90	0
t'lvl3Room8	LEVELTHREE	lv3TM8.tm	0	0	-11	0	90	0
t'lvl3Room9	LEVELTHREE	lv3TM9.tm	0	0	-16	0	-90	0

6.2.5 Triggers

ID	LEVEL	Trigger	Target	TriggerType	TargetType
tr'lvl0End	LEVELZERO	t'lvlzero`room1	lvl0END	TERMINAL	SWITCH
tr'lvl1Switch	LEVELONE	t'lvl1Room0	lvl1Door6	TERMINAL	SWITCH
tr'lvl1End	LEVELONE	t'lvl1Room3	lvl1END	TERMINAL	SWITCH
tr'lvl2Door1	LEVELTWO	t'lvl2Room0	lvl2Door3	TERMINAL	SWITCH
tr'lvl2Door2	LEVELTWO	t'lvl2Room3	lvl2Door1	TERMINAL	SWITCH
tr'lvl2End	LEVELTWO	t'lvl2Room1	lvl2END	TERMINAL	SWITCH
tr'lvl3Sec1	LEVELTHREE	t'lvl3Room9	lvl3Room3	TERMINAL	SWITCH
tr'lvl3Sec2	LEVELTHREE	t'lvl3Room9	lvl3Room4	TERMINAL	SWITCH
tr'lvl3Sec3	LEVELTHREE	t'lvl3Room9	lvl3Room6	TERMINAL	SWITCH
tr'lvl3Sec4	LEVELTHREE	t'lvl3Room9	lvl3Room8	TERMINAL	SWITCH
tr'lvl3Sec5	LEVELTHREE	t'lvl3Room8	lvl3Room5	TERMINAL	SWITCH
tr'lvl3Sec6	LEVELTHREE	t'lvl3Room8	lvl3Room2	TERMINAL	SWITCH
tr'lvl3End	LEVELTHREE	t'lvl3Room2	lvl3Room2END	TERMINAL	SWITCH
tr'lvl3Sec7	LEVELTHREE	t'lvl3Room8	lvl3Room7	TERMINAL	SWITCH

6.2.6 Cylinders


ID	XT	YT	ZT	XR	YR	ZR	base Radius	top Radius	height	stacks	slices	R	G	B	A	LEVEL
lifePodCenter	-4	1	-1.5	90	0	0	0.5	0.5	2	50	50	0	0.80	0.8195	1	LEVELZERO
lifePodBot	-4	0	-1.5	90	0	0	0.0503	1	1	50	50	0.5	0.5	0.5	1	LEVELZERO
lifePodTop	-4	1	-1.5	90	0	0	1	0.5	0.5	50	50	0.5	0.5	0.5	1	LEVELZERO
kiosk1	5	1	25	90	0	0	0.5	0.5	2	50	50	0	0.75	1	0.598	LEVELONE
kiosk2	-5	1	25	90	0	0	0.5	0.5	2	50	50	0	0.75	1	0.598	LEVELONE
power1	-2	1	-5	90	0	0	0.5	0.5	2	50	50	1	0.8397	0	1	LEVELTHREE
power2	2	1	-5	90	0	0	0.5	0.5	2	50	50	1	0.8397	0	1	LEVELTHREE
power3	-2	1	-18	90	0	0	0.5	0.5	2	50	50	1	0.8397	0	1	LEVELTHREE
power4	2	1	-18	90	0	0	0.5	0.5	2	50	50	1	0.8397	0	1	LEVELTHREE
power1BaseBot	-2	0	-5	90	0	0	0.70	0.70	1	50	50	0.201	0.201	0.201	1	LEVELTHREE
power1BaseTop	-2	1	-5	90	0	0	0.70	0.70	0.5	50	50	0.201	0.201	0.201	1	LEVELTHREE
power2BaseBot	2	0	-5	90	0	0	0.70	0.70	1	50	50	0.201	0.201	0.201	1	LEVELTHREE
power2BaseTop	2	1	-5	90	0	0	0.70	0.70	0.5	50	50	0.201	0.201	0.201	1	LEVELTHREE
power3BaseBot	-2	0	-18	90	0	0	0.70	0.70	1	50	50	0.201	0.201	0.201	1	LEVELTHREE
power3BaseTop	-2	1	-18	90	0	0	0.70	0.70	0.5	50	50	0.201	0.201	0.201	1	LEVELTHREE
power4BaseBot	2	0	-18	90	0	0	0.70	0.70	1	50	50	0.201	0.201	0.201	1	LEVELTHREE
power4BaseTop	2	1	-18	90	0	0	0.70	0.70	0.5	50	50	0.201	0.201	0.201	1	LEVELTHREE

6.3 Images


6.3.1 Main Menu



6.3.2 Terminal Banner



6.3.3 Game Icon



6.4 Music

1. Dark Fog—Kevin MacLeod
2. Mismmer—Devin Powers
3. One Sly Move—Kevin MacLeod
4. Hypnothis—Kevin MacLeod
5. Cold Hope—Arseniy Shkljaev
6. Spacial Harvest—Kevin MacLeod

References

- [1] Firelight Technologies *FMOD Studio API*
<http://www.fmod.org/documentation/>
- [2] Jonathan Dummer *Simple OpenGL Image Library* July 7, 2008
<http://www.lonesock.net/soil.html>
- [3] Khronos Group *OpenGL API Documentation Overview*
<https://www.opengl.org/documentation/>
- [4] Maplesoft *Equation of a Plane - 3 Points*
- [5] Microsoft *SHGetFolderPath function*
[https://msdn.microsoft.com/en-us/library/windows/desktop/bb762181\(v=vs.85\).aspx](https://msdn.microsoft.com/en-us/library/windows/desktop/bb762181(v=vs.85).aspx)
- [6] Robert Deyoso *Personal Interview* February, 2015
- [7] SQLite Consortium *An Introduction To The SQLite C/C++ Interface*
<https://www.sqlite.org/cintro.html>