

The God Core
A Science Fiction Video Game Developed in C++

Author: Jeremy Greenburg
Mentor: Dr. Joshua Guerin
Second Reader: Bob Bradley

February 22, 2017

Contents

1	Preamble	3
2	Programming	3
2.1	The Language	3
2.2	APIs	3
2.3	Game Engine	3
3	Appendices	7
3.1	Source Code	7
3.2	Database	107
3.3	Images	112
3.4	Music	112

1 Preamble

2 Programming

2.1 The Language

2.2 APIs

2.2.1 OpenGL

OpenGL, or the Open Graphics Library, is one of the most popular graphics libraries out there. It gives access to linear algebra functions for matrix manipulation (which is important, as 3D graphics relies heavily upon matrix transformations), keyboard and mouse input, and windowing. I chose to use OpenGL over a different graphics library, such as Microsoft's DirectX, because it is open source and cross platform, which would make porting my game to a different Operating System a much easier task if I ever decide to in the future.

2.2.2 SOIL

SOIL, or the Simple OpenGL Interface Library, is a small extension to OpenGL that I picked up along the way. It is a texture library that can load .jpg and .png images and bind them to an OpenGL texture, making it very simple to incorporate such images into my game.

2.2.3 FMOD

I chose FMOD as the base for my game's audio as it is a simple, lightweight, and free to use sound API, and most other audio APIs that I looked at lacked support for MP3 files.

2.2.4 SQLite

I decided to use SQLite for my database because it is a lightweight simplified version of a SQL database, allowing the game data to be stored and embedded in the application without taking much room or take a great deal of time to perform a query.

2.3 Game Engine

I crafted the engine of my game in C++ over two years starting in my second semester sophomore year and ending the first semester of my senior year. It consists of 53 C++ files and was developed in Microsoft Visual Studio. The code can be found in the Appendix of this writeup or it can be located on GitHub at <https://github.com/Jerrygree/The-God-Core-Source>. The game can also be installed at GitHub.

2.3.1 Rectangles and Triangles

Rectangles and triangles are the two fundamental polygons that build up my game. Rectangles in particular make up the walls, floors, ceilings, doors, terminals, and most of the HUD and menu. They started as simply two arrays- one that holds all 9 (for triangles) or 12 (for rectangles) values describing the coordinates in the game that they inhabit, as well as a 4 value vector containing the objects RGBA values.

For collision purposes, when a rectangle class is expanded with the ability to calculate and store its norm and Plane equation (Form $ax + by + cz + d = 0$).

This equation is calculated using the any three corners of the rectangle (Calling them A, B, and C) as follows:

$$\vec{AB} = \begin{vmatrix} Bx - Ax \\ By - Ay \\ Bz - Az \end{vmatrix} \quad \vec{AC} = \begin{vmatrix} Cx - Ax \\ Cy - Ay \\ Cz - Az \end{vmatrix}$$

$$a = \vec{AB}_2 * \vec{AC}_3 - \vec{AB}_3 * \vec{AC}_2$$

$$b = \vec{AB}_3 * \vec{AC}_1 - \vec{AB}_1 * \vec{AC}_3$$

$$c = \vec{AB}_1 * \vec{AC}_2 - \vec{AB}_2 * \vec{AC}_1$$

$$d = aAx + bAy + cAz$$

Formula obtained from <http://keisan.casio.com/exec/system/1223596129>

The norm of the plane can then be derived using the equation $\sqrt{a^2 + b^2 + c^2}$

2.3.2 In Game Terminals

In game terminals are each bound to a *terminal file*, a unique file that contains the contents of its respective terminal.

The terminal file is divided into two sections: the file names and the file contents. This is an example terminal file:

```

1 <FILES>
2 [01] Name1 -- TAG
3 [02] Name2 -- TAG2
4 [03] Name3 -- TAG3
5
6 <TAGS>
7 $HELP$
8 Type Read <num> to read the corresponding file
9 Type Clear to clear a file from the screen
10 Type Exit to exit the terminal
11 Type Help to see this message again
12 $END$
13
14 $TAG$
15 Content 1
16 $END$
17
18 $TAG2$
19 Content 2
20 $END$
21
22 $TAG3$
23 Content 3
24 $END$
```

The program parses the file by first separating the in game content (the bracketed number and name) that should be displayed to the user from it's tag. The tags are stored in an array, where its index is equal to the bracketed number. The help display is always stored at the 0th index.

Then, whenever the player types in a read command (E.G. Read 1), the program will send the terminal file and the correct tag to the text engine for the content to be displayed to the screen.

2.3.3 Triggers and Switches

Triggers are a more sophisticated way to implement interaction between two different objects. The implementation was designed to be abstracted away from object types so that, in theory, any arbitrary object could activate another, but in practice due to the few classes of objects in my game, it served as a way for terminals to power switches on.

The trigger class works by holding two void pointers, one for a triggering object and one for the target object. It also holds the object types (defined in GCTypes.h) of each object. Whenever an object is interacted with, every trigger in the game is attempted to be triggered (**trying to find better phrasing here**) and if the object is the same as the trigger pointer (no referencing needed as the pointers will always be equal), the target is dereferenced according to the appropriate type and activated.

It holds very similar function to a switch, the primary difference being that the switch is a tangible object in the game with the triggering object being itself, and the triggers being an intangible association between two objects. If I had more time in development, I would have liked to refactor much of the switch's internal functionality so that it is simply an object, with the actual interaction between the switch and its target taking place as a trigger, but the conception and implementation of triggers came too late in development and implementing the switch change would require a good deal of code and data rewrites.

2.3.4 Camera Control

The CameraControl class is designed to control and manipulate the player's perspective as they navigate through the game. It contains two ordered triples of floating point numbers: The xyz location of the player, and the rotation along the x axis (looking left/right), the y axis (up/down), and the z axis (barrel roll). It also contains two additional floating point values, the movement speed and the turning speed.

The player can move forwards and backwards, as well as strafe left and right. To correctly formulate the player's movement, I had to envision a circle centered on the player with a radius of the player's movement speed. Based on the angle from the x and z rotation, the next place that the player move is simply a spot on the circumference of the circle based on the rotation angle, and moving forward can be derived from this formula:

$$\begin{aligned} z &:= z \pm \text{moveSpeed} * \cos(\text{radian}(x_angle)) \\ x &:= x \mp \text{moveSpeed} * \sin(\text{radian}(x_angle)) \end{aligned}$$

Formula obtained from Robert De Yoso

Following that formula, it's simple to implement movement to the left, right by adding or subtracting 90°, and backwards movement by adding 180°.

Whenever OpenGL renders a new frame, the 'camera' is always returned to the origin of the map, so after drawing the level and before flushing the buffer, the Camera Control calls glTranslate to move the camera to the correct location, and then calls glRotate 3 times, once for each axis, to orient the camera in the correct direction.

2.3.5 Heads Up Display

The Heads Up Display is drawn after the level is draw, so that it overlays information to the player. It primarily is used to add a bit of flavor to the game by drawing the helmet for the player, but it also serves to display the developer console when activated.

The display also delivers a prompt to the user whenever they are in range of an object that can be interacted with.

2.3.6 2D

As multiple different objects required the ability to **2D IT UP CHANGE THIS SOON**, I extracted the ability to draw in 2D into its own class and it was inherited whenever it was needed.

To convert OpenGL into 2D frame, I needed to first disable lighting, depth testing and depth masking. Next I pushed an *orthogonal* matrix onto OpenGL's matrix stack using the length and width of the screen so that all matrix transformations corresponded to a pixel on the screen. Re-enabling 3D is as simple as popping the orthogonal matrix from the stack and re-enabling depth testing and masking.

2.3.7 Collision Engine

This determines when the player has collided with an object in the world. There are two types of collisions: player-object collisions and player-wall collisions.

Player object collisions are simple to detect, as both the player and the object can be placed within imaginary "bounding spheres" that extend around the player and object. Collision can be detected with this formula:

$\sqrt{(x_2 - x_1)^2 + (y_2 - y_1)^2 + (z_2 - z_1)^2} < r_2 + r_1$ If the distance between the two spheres is less than the sum of the radii of the two spheres, they must be colliding.

Player-wall collisions were much harder to reconcile. Because walls tend to be long and thin, you can't simply place one within a bounding sphere, the resulting sphere would simply be too massive.

To rectify that, the collision is split into two phases: broad and narrow.

In the broad phase, we use the plane equation $ax + by + cz + d$ that is derived in the Rectangle section. We use the formula $\frac{ax + by + cz + d}{\sqrt{a^2 + b^2 + c^2}}$, where x, y, and z are the player's x, y, and z coordinates. If the resulting value is less than the radius of the player's bounding sphere, the player has hit that plane and we move onto the narrow phase.

In the narrow phase, each wall is aligned on an axis: x, y, or z. We simply take the largest and smallest values of the coordinates on that axis (for instance, if the wall is x aligned, we take the largest and smallest x value). If the sphere is in between the two values, the player has hit the wall. Otherwise, they hit the plane but not the wall.

2.3.8 MusicManager

To play background music, I used the FMOD low level API for C++. FMOD can dynamically load and play as multiple sounds, which can either be set to loop (such as background music) or not to loop (for sound effects). Proper memory management is important, as the individual sounds are dynamically created outside of the Music Manager class and must be allocated and deallocated properly to avoid memory leaks.

2.3.9 TextEngine

The Text Engine was constructed to handle displaying all text to the screen. It uses OpenGL's glutBitmapCharacter function to display clear, concise text.

Every function to display text takes two coordinates (the x,y coordinates on the screen to start displaying the text), and the RGB color values for the text. There are two functions for displaying text, the simpler one merely takes in a string and prints it on the corresponding location on the screen. The more complex function takes in a file and a content tag. The files are structured like so:

```
1 $TAG 1$
2 Content 1
3 $END$
4
5 $Tag 2$
6 Content 2
7 $END$
```

The Text Engine searches through the designated file line by line until it discovers the line containing the proper tag. Then, until it reaches the closing 'END' tag, it stores every line inside of a vector. Once it has retrieved all of the necessary content, it starts to display the text to the screen line by line, starting from the designated XY position and increasing the Y value for each line.

2.3.10 Game Saving and Loading

2.3.11 Keyboard

The Keyboard class primarily serves to encapsulate the OpenGL callbacks that receive keystrokes: the normal function that accepts all alphanumeric and punctuation, and the special function that handles function keys and escape. However, there is a minor bit of overhead that goes into deciding where the input goes.

Under normal circumstances, the only normal keystrokes accepted are the WASD keys for movement, the E key for interaction, and the ' ' key for toggling the development console.

When in either a terminal or the development console, all keys are immediately concatenated to an input string with the exception of the ' ' which will close the development console, or the enter key which will send the input string to its appropriate destination to be parsed and interpreted, after which the input string is cleared so that a new command can be entered.

Also accepted are the up and down arrow keys, which will cycle through the console/terminals command history.

2.3.12 Level Loading and displaying

Loading each level involves a series of SQL queries through the SQLite API. Loading each level first involves opening a connection with the database, and retrieving all data from each table in the database in turn. All important data from the database is stored in a class of the appropriate type, unnecessary data is discarded, and in the end each class is pushed into a vector of the appropriate type.

The data is loaded in a strict order, due to some objects having dependencies on others (that is, some objects require other objects to already exist). Thus the first things that are loaded are purely independent objects, all doors, walls, and terminals. Next switches are loaded, because they require both doors and terminals to already exist. Finally, the triggers are loaded, because they require both switches and terminals.

When loading switches and triggers, the objects also need to be *bound* to their appropriate target. This is why doors, switches, and terminals all carry their ID's into the program with them, while triggers and walls discard their ID. Once all of the objects that need to be bound are loaded into the game, the game proceeds to bind them to their target. For each switch that needs to be bound, the game loops through either the list of terminals or the list of doors for the appropriate object and creates a pointer to that object inside of the switch, thus ensuring that the switch can toggle its target instantly without needing to search every time it is triggered. The triggers are bound similar, with the difference that each object must perform two searches, one for the triggering object and one for the target object.

If there is any data error in regards to binding — that is, an object attempts to bind to an object that does not exist, the error is considered fatal and the game immediately shuts down after logging the error.

The OpenGL display function calls upon the Level class to display all in game objects. This is a simple matter, because each object has its own function to display itself. Thus it is a simple matter to loop through each vector and tell each object to display itself.

2.3.13 Console and Logging

3 Appendices

3.1 Source Code

3.1.1 main.cpp

```
1  /*****\
2  * main.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file creates an OpenGL window to display the game *
8  * and promptly passes control over to the GameManager object*
9  \*****/
10
11 // Because doth openGL demandeth
12 #include <cstdlib>
13 // OpenGL API
14 #include <GL\glut.h>
15 // time
16 #include <ctime>
17
18 // The Game manger
19 #include "GameManager.h"
20 GameManager Overlord;
21 // Save manager
22 #include "SaveManager.h"
23 // Return codes
24 #include "Return.h"
25 // System log
```

```

26 #include "Logger.h"
27 // Global variables
28 #include "Globals.h"
29
30 // Normal key presses
31 void normal(unsigned char key, int x, int y);
32
33 // For key releases
34 void key_up(unsigned char key, int x, int y);
35
36 // For Special keys
37 void special(int key, int x, int y);
38
39 // Mouse clicks
40 void mouse(int button, int state, int x, int y);
41
42 // Mouse movement
43 void motionPassive(int x, int y);
44
45 // Changing Window size (Not exactly working as hoped...
46 void changeSize(int w, int h);
47
48 // Initializes GLUT callbacks and returns true if core.sav exists (false otherwise
49 )
50 bool initGame(int argc, char **argv);
51
52 // Manages the game's scenes
53 void manageScenes();
54
55 GLfloat light_diffuse[] = { 0.3f, 0.3f, 0.3f, 0.3f };
56 GLfloat light_position[] = { 0.0f, 0.0f, 0.0f, 0.0f }; // Currently nonexistent
57   until I can figure out how lighting works
58 GLfloat mat_specular[] = { 1.0f, 1.0f, 1.0f, 1.0f };
59 GLfloat mat_shininess[] = { 75 };
60 GLfloat lmodel_ambient[] = { 0.6f, 0.6f, 0.6f, 1.0f };
61
62 using namespace std;
63
64 //***** FUNCTION DEFINITIONS *****\
65
66 int main(int argc, char **argv)
67 {
68     Overlord.canContinue = initGame(argc, argv);
69
70     // Begin the game
71     glutMainLoop();
72
73     // If we ever get here, something bad happened
74
75     Logger log;
76     log.logLine("ERROR: GlutMainLoop exited early");
77
78     return EXIT_EARLY;
79 }
80
81 bool initGame(int argc, char **argv)

```



```

80 {
81     // Obliterate log file
82     Logger log;
83     log.nuke();
84
85     // Initialize GLUT
86     glutInit(&argc, argv);
87
88     // Create window
89     glutInitDisplayMode(GLUT_DOUBLE | GLUT_RGBA);
90     glutInitWindowPosition(50, 50);
91     glutInitWindowSize(500, 500);
92     glutCreateWindow("The God Core");
93
94     // register callbacks
95     glutDisplayFunc(manageScenes);
96     glutReshapeFunc(changeSize);
97     glutIdleFunc(manageScenes);
98     glutPassiveMotionFunc(motionPassive);
99     glutMouseFunc(mouse);
100    glutKeyboardFunc(normal);
101    glutKeyboardUpFunc(key_up);
102    glutSpecialFunc(special);
103
104    // Prebuilt function that works transparency
105    glBlendFunc(GL_SRC_ALPHA, GL_ONE_MINUS_SRC_ALPHA);
106
107    // Enable transparency
108    glEnable(GL_BLEND);
109    // Enable depth buffer
110    glEnable(GL_DEPTH_TEST);
111    // Let there be light!
112    glEnable(GL_LIGHTING);
113    // First light source
114    glEnable(GL_LIGHT0);
115
116    // Light properties
117    glMaterialfv(GL_FRONT, GL_SPECULAR, mat_specular);
118    glMaterialfv(GL_FRONT, GL_SHININESS, mat_shininess);
119    glColorMaterial(GL_FRONT_AND_BACK, GL_AMBIENT_AND_DIFFUSE);
120
121    // Light doesnt turn everything grey
122    glEnable(GL_COLOR_MATERIAL);
123
124    glLightfv(GL_LIGHT0, GL_DIFFUSE, light_diffuse);
125    glLightfv(GL_LIGHT0, GL_POSITION, light_position);
126    glLightModelfv(GL_LIGHT_MODEL_AMBIENT, lmodel_ambient);
127
128    glutWarpPointer(300, 300);
129
130    // Start in Fullscreen
131    glutFullScreen();
132
133    srand(time(NULL));
134
135    HUD.setStatus("INFO-WELL");

```

```

136
137         SaveManager SaveSystem;
138         return SaveSystem.checkSave();
139     }
140
141     // Everything below here is just passed along to the overlord
142
143     void mouse(int button, int state, int x, int y)
144     {
145         Overlord.mouse(button, state, x, y);
146     }
147
148     void motionPassive(int x, int y)
149     {
150         Overlord.motionPassive(x, y);
151     }
152
153     void changeSize(int w, int h)
154     {
155         Overlord.changeSize(w, h);
156     }
157
158     void manageScenes()
159     {
160         Overlord.manageScenes();
161     }
162
163     void normal(unsigned char key, int x, int y)
164     {
165         Overlord.normal(key, x, y);
166     }
167
168     void key_up(unsigned char key, int x, int y)
169     {
170         Overlord.key_up(key, x, y);
171     }
172
173     void special(int key, int x, int y)
174     {
175         Overlord.special(key, x, y);
176     }

```

3.1.2 CameraControl.h

```

1  /*****\
2  * CameraControl.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the CameraControl *
8  * Class, which stores: *
9  *     The x, y, z ordered triple of the player's location *
10 *     The degree to which the player is turned, along *
11 *         the x, y, and z axes *
12 * And contains methods to translate the player along *
13 * 3D space *

```

```

14 \*****/
15
16 #ifndef CAMERA_CONTROL_H
17 #define CAMERA_CONTROL_H
18
19 class CameraControl
20 {
21 private:
22     // Speeds for moving and rotating
23     double moveSpeed = 0.1f, turnSpeed = 0.5f;
24
25 public:
26     // Negatively adjusts angle and modifies lx
27     void lookLeft();
28     // Positively adjusts angle and modifies lx
29     void lookRight();
30     // Positively adjusts angle and modifies ly
31     void lookUp();
32     // Negatively adjusts angle and modifies ly
33     void lookDown();
34     // Translate the camera to the left
35     void strafeLeft();
36     // Translates the to the right
37     void strafeRight();
38     // Translates the camera forwards
39     void moveForward(int mod);
40     // Translate the camera backards
41     void moveBackward(int mod);
42     // Moves the camera positively along the Y axis
43     void moveUp();
44     // Moves the camera negatively along the Z axis
45     void moveDown();
46     // Flips the camera
47     void invertCam();
48     // If the player begins to run
49     void increaseSpeed();
50     // If the player begins to walk
51     void decreaseSpeed();
52     // Resets the camera to it's initial state
53     void resetCam();
54     // calls gluLookAt
55     void Display();
56
57     // Location of the camera
58     double x = 0.0, y = 0.0, z = -1.0;
59     double prevx, prevz;
60     // Angles of rotation
61     double x_angle = 0.0, y_angle = 0.0, z_angle = -1.0;
62 };
63
64 #endif

```

3.1.3 CameraControl.cpp

```

1 \*****\
2 * CameraControl.cpp *
3 * This file was created by Jeremy Greenburg *

```

```

4  * As part of The God Core game for the University of      *
5  * Tennessee at Martin's University Scholars Organization  *
6  *                                                         *
7  * This file contains the definition of the CameraControl   *
8  * Class. For more information, see CameraControl.h         *
9  \*****/
10
11 // Class definition
12 #include "CameraControl.h"
13
14 // For sin()
15 #include <cmath>
16
17 // glut is unhappy when cstdlib isn't here :/
18 #include <cstdlib>
19
20 // OpenGL API
21 #include <GL\glut.h>
22
23 // To display Suit Warnings
24 #include "TextEngine.h"
25
26 // To include Globals Variables
27 #include "Globals.h"
28
29 // For converting degrees to radians
30 const double PI = 3.14159;
31
32 // Takes in an angle, in degrees, and returns the angle in radians
33 double toRadian(double angle)
34 {
35     return angle * PI / 180;
36 }
37
38 void CameraControl::lookLeft()
39 {
40     x_angle -= 3 * turnSpeed;
41
42     // To avoid potential underflow errors
43     if (x_angle < 0)
44     {
45         x_angle += 360;
46     }
47 }
48 void CameraControl::lookRight()
49 {
50     x_angle += 3 * turnSpeed;
51
52     // To avoid potential overflow errors
53     if (x_angle > 360)
54     {
55         x_angle -= 360;
56     }
57 }
58
59 void CameraControl::lookUp()

```

```

60 {
61     y_angle -= 2 * turnSpeed;
62
63     // To avoid potential underflow errors
64     if (y_angle < 0)
65     {
66         y_angle += 360;
67     }
68 }
69
70 void CameraControl::lookDown()
71 {
72     y_angle += 2 * turnSpeed;
73
74     // To avoid potential overflow errors
75     if (y_angle > 360)
76     {
77         y_angle -= 360;
78     }
79 }
80
81 void CameraControl::strafeLeft()
82 {
83     prevz = z;
84     prevx = x;
85     // Angles + 90 degrees for an angle that is perpendicular to x_angle
86     z = z + moveSpeed * cos(toRadian(x_angle + 90));
87     x = x - moveSpeed * sin(toRadian(x_angle + 90));
88 }
89
90 void CameraControl::strafeRight()
91 {
92     prevz = z;
93     prevx = x;
94     // Angles - 90 degrees for an angle that is perpendicular to x_angle
95     z = z + moveSpeed * cos(toRadian(x_angle - 90));
96     x = x - moveSpeed * sin(toRadian(x_angle - 90));
97 }
98
99 void CameraControl::moveForward(int mod)
100 {
101     prevz = z;
102     prevx = x;
103     z = z + moveSpeed * mod * cos(toRadian(x_angle));
104     x = x - moveSpeed * mod * sin(toRadian(x_angle));
105 }
106
107 void CameraControl::moveBackward(int mod)
108 {
109     prevz = z;
110     prevx = x;
111     z = z - moveSpeed * mod * cos(toRadian(x_angle));
112     x = x + moveSpeed * mod * sin(toRadian(x_angle));
113 }
114
115 void CameraControl::moveUp()

```

```

116 {
117     y -= moveSpeed;
118 }
119
120 void CameraControl::moveDown()
121 {
122     y += moveSpeed;
123 }
124
125 void CameraControl::invertCam()
126 {
127     z_angle += 180;
128 }
129
130 void CameraControl::resetCam()
131 {
132     x = 0.0;
133     y = 0.0;
134     z = -1.0;
135     x_angle = 0.0;
136     y_angle = 0.0;
137     z_angle = 0.0;
138 }
139 }
140
141 void CameraControl::increaseSpeed()
142 {
143     moveSpeed *= 2;
144 }
145
146 void CameraControl::decreaseSpeed()
147 {
148     moveSpeed /= 2;
149 }
150
151 void CameraControl::Display()
152 {
153     // To stop eternal movement
154     glLoadIdentity();
155
156     // Rotate along proper axes
157     glRotatef(y_angle, 1, 0, 0);
158     glRotatef(x_angle, 0, 1, 0);
159     glRotatef(z_angle, 0, 0, 1);
160
161     // Translate along the Plane
162     glTranslatef(x, y, z);
163 }

```

3.1.4 CollisionEngine.h

```

1  /*****\
2  * CollisionEngine.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *

```

```

7  * This file creates the decleration of the CollisionEngine *
8  * class, which uses sweet sweet math to determine how the *
9  * player interacts with his environment *
10 \*****/
11
12 #ifndef COLLISION_ENGINE_H
13 #define COLLISION_ENGINE_H
14
15 class CollisionEngine
16 {
17 private:
18     // Determines if wall/door collision occurred
19     bool collideWalls();
20     // Determines if other collision occurred
21     bool collideObjects();
22     // Determines if an object can be interacted with
23     void checkInteract();
24 public:
25     // Master function that calls others
26     bool collide();
27
28 };
29
30 #endif

```

3.1.5 CollisionEngine.cpp

```

1  /*****\
2  * CollisionEngine.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the CollisionEngine *
8  * class. For more information, see SaveManager.h *
9  \*****/
10
11 #include "CollisionEngine.h"
12
13 // For the Cam
14 #include "Globals.h"
15 // absolute value
16 #include <cmath>
17
18 // System Log
19 #include "Logger.h"
20
21 using namespace std;
22
23 const double PLAYER_RADIUS = 0.5;
24 const double INTERACT_RADIUS = 1; // Object interactivity radius
25 const double COLLIDE_RADIUS = 0.5;
26
27 void CollisionEngine::checkInteract()
28 {
29     activeSwitch = NULL;
30     activeTerminal = NULL;

```

```

31 // Auto don't work in these parts
32 for (unsigned int i = 0; i < switches.size(); i++)
33 {
34     double distance = pow((switches[i].getX() + Cam.x), 2) + pow((
        switches[i].getY() + Cam.y), 2) + pow((switches[i].getZ() + Cam
        .z), 2);
35     distance = sqrt(distance);
36     double radii = (PLAYER_RADIUS + INTERACT_RADIUS);
37
38     if (distance < radii && switches[i].checkIfOn())
39     {
40         interactivity = true;
41         activeSwitch = &switches[i];
42         return;
43     }
44 }
45
46 for (unsigned int i = 0; i < terminals.size(); i++)
47 {
48     double distance = pow((terminals[i].getX() + Cam.x), 2) + pow((
        terminals[i].getY() + Cam.y), 2) + pow((terminals[i].getZ() +
        Cam.z), 2);
49     distance = sqrt(distance);
50     double radii = (PLAYER_RADIUS + INTERACT_RADIUS);
51
52     if (distance < radii && terminals[i].checkIfOn())
53     {
54         interactivity = true;
55         activeTerminal = &terminals[i];
56         return;
57     }
58 }
59
60 interactivity = false;
61 }
62
63 bool CollisionEngine::collideObjects()
64 {
65     for (unsigned int i = 0; i < terminals.size(); i++)
66     {
67         double distance = pow((terminals[i].getX() + Cam.x), 2) + pow((
            terminals[i].getY() + Cam.y), 2) + pow((terminals[i].getZ() +
            Cam.z), 2);
68         distance = sqrt(distance);
69         double radii = (PLAYER_RADIUS + COLLIDE_RADIUS);
70
71         if (distance < radii && terminals[i].checkIfOn())
72         {
73             return true;
74         }
75     }
76
77     return false;
78 }
79
80 bool CollisionEngine::collideWalls()

```



```

81 {
82     // Gotta check doors first
83     // And if you hit an open door
84     // You just ignore collision
85     // Because otherwise you can't fit
86     for (auto i : doors)
87     {
88         double distance = fabs(Cam.x * i.a + Cam.y * i.b + Cam.z * i.c + i
89                               .d); // Distance from door
89
90         if ((distance / i.getNorm() < PLAYER_RADIUS) && i.isInBounds())
91         {
92             if (i.isOpen) return false;
93             else return true;
94         }
95     }
96
97     for (auto i : walls)
98     {
99         double distance = fabs(Cam.x * i.a + Cam.y * i.b + Cam.z * i.c + i
100                              .d); // Distance from wall
101
102         if ((distance / i.getNorm() < PLAYER_RADIUS) && i.isInBounds())
103             return true;
104     }
105     return false;
106 }
107 bool CollisionEngine::collide()
108 {
109     if (!collision)
110     {
111         return false;
112     }
113
114     checkInteract();
115     return (collideWalls() || collideObjects());
116 }

```

3.1.6 Console.h

```

1  /*****\
2  * Connsole.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the Console Class, *
8  * As well as the Trip struct for holding three integers *
9  * The Developer Console takes input from the user and *
10 * Activates various effects based upon what the user has *
11 * Typed in. *
12 \*****/
13
14 #ifndef CONSOLE_H
15 #define CONSOLE_H

```

```

16
17 // To act as a circular buffer for console history
18 #include <deque>
19 // Stores actual console input
20 #include <vector>
21 // std::string
22 #include <string>
23 // For processing text
24 #include "TextEngine.h"
25
26 // Windows API
27 #include <shlobj.h>
28
29
30 // To make rgb calues easier to store
31 #include "Triple.h"
32
33 class Console
34 {
35 private:
36     /***** Variables for the console itself *****/
37
38     // Triples for good color, bad color, and nuetral colors
39     Triple VALID_COLOR, INVALID_COLOR, NEUTRAL_COLOR;
40     // What the console "says" (aka what appears on screen)
41     std::deque<std::string> console_log;
42     // The colors of said strings
43     std::deque<Triple> console_color;
44     // Contains the actual player input
45     std::vector<std::string> console_input;
46     // The current (finished) input being processed
47     std::string currentInput;
48     // The current (unfinished) input being type
49     std::string currentText;
50     // Console History
51     TextEngine log;
52
53     // Path to core.sav
54     char CHAR_PATH[MAX_PATH];
55     std::string SAVE_PATH;
56
57     // Is the console active or not
58     bool isActive;
59
60     // The bottom of the console
61     const int SCREENBOTTOM = 500;
62
63     // Prints the current input and console_history
64     void printInput();
65     // Processes completed input
66     void processInput();
67
68     // Command functions
69
70     // Toggles collision on and off
71     void toggleCollision();

```

```

72
73     // Toggles godMode on and off
74     void toggleGod();
75
76     // Decrpyts the entry in core.sav
77     void decrpytSave();
78
79     // Shutdowns program
80     void halt();
81
82     // Clears the console log
83     void clear();
84
85     // Writes input to core.sav
86     void writeToSave(std::string input);
87
88     // Reads a bit from the file
89     void readFromFile(std::string input);
90
91     // Changes the currently played track
92     void playSong(std::string input);
93
94 public:
95     // Initializes VALID_COLOR, INVALID_COLOR, NEUTRAL_COLOR, and SAVE_PATH
96     Console();
97     // Manages console functions if input has been provided
98     void activate(std::string input, std::string text);
99     // Manages console function if input is still being provided
100    void activate(std::string text);
101    // Returns the console_input[count]
102    std::string getHist(int count);
103    // Returns console_input.size()
104    int getHistNum();
105
106 };
107
108 #endif

```

3.1.7 Console.cpp

```

1  /*****\
2  * Console.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * * *
7  * This file contains the definition of the Console class *
8  * For more information, see Console.cpp *
9  \*****/
10
11 // File I/O
12 #include <fstream>
13
14 // Class declaration
15 #include "Console.h"
16
17 // For saving and loading

```

```

18 #include "SaveManager.h"
19
20 // System log
21 #include "Logger.h"
22
23 // Contains global environment variables
24 #include "Globals.h"
25
26 // Return codes
27 #include "Return.h"
28
29 using namespace std;
30
31 Console::Console()
32 {
33     // Green!
34     VALID_COLOR = makeTrip(0, 1, 0);
35     // Red!
36     INVALID_COLOR = makeTrip(1, 0, 0);
37     // Gray!
38     NEUTRAL_COLOR = makeTrip(1, 1, 1);
39
40     // Get path to documents
41     HRESULT ret = SHGetFolderPath(NULL, CSIDL_PERSONAL, NULL,
42     SHGFP_TYPE_CURRENT, CHAR_PATH);
43     // Assign to SAVE_PATH
44     SAVE_PATH = CHAR_PATH;
45     // Concatenate save file
46     SAVE_PATH += "\\The God Core\\core.sav";
47 }
48
49 void Console::activate(string input, string text)
50 {
51     currentInput = input;
52     // This should be empty. But just incase.
53     currentText = text;
54
55     processInput();
56     printInput();
57 }
58
59 void Console::activate(string text)
60 {
61     currentText = text;
62
63     printInput();
64 }
65
66 void Console::printInput()
67 {
68     deque<string>::iterator it = console_log.begin();
69     deque<Triple>::iterator jt = console_color.begin();
70     // Iterates through the console's current log and prints it to the screen
71     for (it; it != console_log.end(); it++, jt++)
72     {
73         //
74         Index of it

```

```

73         log.printString(0, 10 + 10 * (it - console_log.begin()),
74             jt->a, jt->b, jt->c, *it);
75     }
76
77     // Prints whatever the user is typing
78     log.printString(0, SCREENBOTTOM / 2.4, 1, 1, 1, currentText);
79 }
80
81 void Console::processInput()
82 {
83     // TODO: Break this behemoth up into little, managable functions
84
85     if (currentInput == "TogClip")
86         toggleCollision();
87
88     else if (currentInput == "TogGod")
89         toggleGod();
90
91     else if (currentInput.substr(0, 5) == "Save ")
92         writeToSave(currentInput.substr(5)); // Save everything after "
93         Save "
94
95     else if (currentInput == "Decrypt")
96         decrpytSave();
97
98     else if (currentInput.substr(0, 5) == "Read ")
99         readFromFile(currentInput.substr(5)); // Read everything after "
100         Read "
101
102     else if (currentInput == "Halt")
103         halt();
104
105     else if (currentInput == "Clear")
106         clear();
107
108     else if (currentInput.substr(0, 5) == "Play ")
109         playSong(currentInput.substr(5)); // Process everything after "
110         Play "
111
112     else if (currentInput == "Goto Main")
113     {
114         isInMain = true;
115         isInConsole = false;
116         HUD.toggleConsole();
117     }
118
119     // Invalid command
120     else
121     {
122         console_log.push_back("ERROR: Do not recognize \"" + currentInput
123             + "\"");
124         console_color.push_back(INVALID_COLOR);
125     }
126
127     // Clears the top of the console if too much history is added
128     if (console_log.size() > 9)

```

```

125         {
126             console_log.pop_front();
127             console_color.pop_front();
128         }
129
130         // Store the current input
131         console_input.push_back(currentInput);
132     }
133
134     void Console::writeToSave(string input)
135     {
136         // Writes whatever is in input to the save file.
137         // Probably not going to be good for loading purposes
138
139         SaveManager Jesus;
140
141         Jesus.saveLevel();
142
143         console_log.push_back("Saved: " + input);
144         console_color.push_back(VALID_COLOR);
145     }
146
147     void Console::readFromFile(string input)
148     {
149         // Syntax = Read core.sav
150         if (input == "core.sav")
151         {
152             ifstream infile(SAVE_PATH);
153
154             string text;
155
156             // For now, core.sav only has one line. Hopefully I'll update this
157             // when I change that
158             infile >> text;
159
160             console_log.push_back(text);
161             console_color.push_back(VALID_COLOR);
162         }
163
164         // Syntax = Read TAG FILE
165         else
166         {
167             // There should be a space seperating the file and the tag. We
168             // find that space
169             size_t pos = input.find(' ');
170
171             // If there ain't no space
172             if (pos == string::npos)
173             {
174                 console_log.push_back("ERROR: No tag detected");
175                 console_color.push_back(INVALID_COLOR);
176             }
177
178             // Hooray! There's a space
179             else
180             {

```

```

179         string tag = input.substr(0, pos);
180         string file = input.substr(pos + 1); // +1 to avoid the
           space
181
182         const char* TEXT_PATH = "Resources\\Text\\";
183         string fullPath = TEXT_PATH + file;
184
185         // Simply to test for the file's existence
186         ifstream infile(fullPath);
187
188         string text;
189         getline(infile, text);
190
191         // If there ain't no file
192         if (!infile)
193         {
194             console_log.push_back("ERROR: File \"" + file +
               "\" not found");
195             console_color.push_back(INVALID_COLOR);
196         }
197
198         // Hooray! There's a file
199         else
200         {
201             console_log.push_back("Reading \"" + file + "\"
               with tag \"" + tag + '\"');
202             console_color.push_back(VALID_COLOR);
203
204             vector<string> readText = log.getText(file, tag);
205
206             vector<string>::iterator it;
207
208             for (it = readText.begin(); it != readText.end();
               it++)
209             {
210                 // Push everything we found into the log
211                 console_log.push_back(*it);
212                 console_color.push_back(NEUTRAL_COLOR);
213
214                 // So we don't grow too much, keep bounds
                   checking
215                 if (console_log.size() > 9)
216                 {
217                     console_log.pop_front();
218                     console_color.pop_front();
219                 }
220             }
221         }
222
223         infile.close();
224     }
225 }
226
227 void Console::toggleCollision()
228 {

```

```

230         console_log.push_back("Noclip toggled.");
231         console_color.push_back(VALID_COLOR);
232
233         collision = !collision;
234     }
235
236     void Console::toggleGod()
237     {
238         console_log.push_back("God Mode toggled.");
239         console_color.push_back(VALID_COLOR);
240
241         godMode = !godMode;
242     }
243
244     void Console::decryptSave()
245     {
246         SaveManager Jesus;
247
248         console_log.push_back(Jesus.readSave());
249         console_color.push_back(VALID_COLOR);
250     }
251
252     void Console::halt()
253     {
254         Logger log;
255         log.logLine("Exiting via console");
256         exit(EXIT_OK);
257     }
258
259     void Console::clear()
260     {
261         console_log.clear();
262         console_color.clear();
263         console_input.clear();
264     }
265
266     void Console::playSong(string input)
267     {
268         int sNum = getSongNum(input);
269
270         if (sNum == -1) // Invalid input
271         {
272             console_log.push_back("ERROR: " + input + " not a valid song file
273                                 ");
274             console_color.push_back(INVALID_COLOR);
275         }
276
277         else // Valid input
278         {
279             songNum = sNum;
280             changeSong = true;
281             string song = getSongName(sNum);
282             console_log.push_back("Now playing " + song);
283             console_color.push_back(VALID_COLOR);
284         }
285     }

```



```

285
286 string Console::getHist(int count)
287 {
288     int size = console_input.size();
289     if (console_input.empty())
290     {
291         return "";
292     }
293
294     // If, somehow, a fool manages to get a variable that is out of bounds
295
296     else if (count >= size)
297     {
298         return console_input.back();
299     }
300
301     else if (count < 0)
302     {
303         return console_input.front();
304     }
305
306     else
307     {
308         return console_input[size - count - 1];
309     }
310 }
311
312 int Console::getHistNum()
313 {
314     return console_input.size();
315 }

```

3.1.8 Cylinder.h

```

1  /*****\
2  * Cylinder.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the Cylinder Class, *
8  * Which contains the functionality to load and display a *
9  * Cylindrical object in game *
10 \*****/
11
12 #ifndef CYLINDER_H
13 #define CYLINDER_H
14
15 #include <cstdlib>
16
17 #include <GL\glut.h>
18
19 class Cylinder
20 {
21 private:
22     // A few variables to control the shape of the cylinder
23     double baseRadius, topRadius, height;

```

```

24         int stacks, slices;
25
26         // Arrays for the location, orientation, and color of the cylinder
27         double translate[3], rotate[3], color[4];
28         // A thingamajig for glut
29         GLUQuadric *quad;
30     public:
31         Cylinder(double _baseRadius, double _topRadius, double _height, int
                 _stacks, int _slices,
32                 const double(&_translate)[3], const double(&_rotate)[3], const
                 double (&_color)[4]);
33
34         void Display();
35         ~Cylinder();
36     };
37
38 #endif

```

3.1.9 Cylinder.cpp

```

1  /*****\
2  * Cylinder.cpp                                *
3  * This file was created by Jeremy Greenburg    *
4  * As part of The God Core game for the University of    *
5  * Tennessee at Martin's University Scholars Organization *
6  *                                                    *
7  * This file contains the definition of the Cylinder class. *
8  * for more information, see Cylinder.h          *
9  \*****/
10
11 #include "Cylinder.h"
12
13 // For copying
14 #include <iterator>
15 #include <utility>
16
17 using namespace std;
18
19 Cylinder::Cylinder(double _baseRadius, double _topRadius, double _height, int
                 _stacks, int _slices,
20                 const double(&_translate)[3], const double(&_rotate)[3], const double(&
                 _color)[4])
21 {
22     baseRadius = _baseRadius;
23     topRadius = _topRadius;
24     height = _height;
25     stacks = _stacks;
26     slices = _slices;
27
28     copy(begin(_color), end(_color), color);
29     copy(begin(_translate), end(_translate), translate);
30     copy(begin(_rotate), end(_rotate), rotate);
31
32     quad = gluNewQuadric();
33 }
34
35 Cylinder::~Cylinder()

```

```

36 {
37     //gluDeleteQuadric(quad);
38 }
39
40 void Cylinder::Display()
41 {
42     glColor4d(color[0], color[1], color[2], color[3]);
43
44     glPushMatrix();
45
46     glTranslated(translate[0], translate[1], translate[2]);
47     glRotated(rotate[0], 1, 0, 0);
48     glRotated(rotate[1], 0, 1, 0);
49     glRotated(rotate[2], 0, 0, 1);
50
51     gluCylinder(quad, baseRadius, topRadius, height, slices, stacks);
52
53     glPopMatrix();
54 }

```

3.1.10 Door.h

```

1  /*****\
2  * Door.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the Door class *
8  * It's mostly a fancy wrapper for a Plane with a bit *
9  * Of added functionality *
10 \*****/
11
12 #ifndef DOOR_H
13 #define DOOR_H
14
15 // Class declaration
16 #include "Plane.h"
17 // std::string
18 #include <string>
19
20 // Figure out a way to bind a controller to the door to activate it.
21 class Door
22 {
23 private:
24     // Name, so a switch can find it
25     std::string id;
26     // The physical door
27     Plane rect;
28 public:
29     // Is the door open?
30     bool isOpen;
31     // Plane's a, b, c, and d.
32     // For easier access
33     double a, b, c, d;
34
35     // Takes in the initial Plane and name

```

```

36     Door(Plane _rect, std::string _id);
37     // Calls rect.Display()
38     void Display();
39     // Returns rect.getNorm()
40     double getNorm();
41     // Returns id
42     std::string getID();
43     // Returns rect.isInBounds()
44     bool isInBounds();
45 };
46
47 #endif

```

3.1.11 Door.cpp

```

1  /*****\
2  * Door.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the Door class. *
8  * for more information, see Door.h *
9  \*****/
10
11 // Class declaration
12 #include "Door.h"
13
14 using namespace std;
15
16 Door::Door(Plane _rect, std::string _id) : rect(_rect), id(_id)
17 {
18     isOpen = false;
19     a = rect.a;
20     b = rect.b;
21     c = rect.c;
22     d = rect.d;
23 };
24
25 void Door::Display()
26 {
27     if (!isOpen) rect.Display();
28 }
29
30 double Door::getNorm()
31 {
32     return rect.getNorm();
33 }
34
35 string Door::getID()
36 {
37     return id;
38 }
39
40 bool Door::isInBounds()
41 {
42     return rect.isInBounds();

```

43 }

3.1.12 GameManager.h

```
1  /*****\
2  * GameManager.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the GameManger class*
8  * Which oversees and manages the flow of the game *
9  \*****/
10
11 #ifndef GAMEMANAGER_H
12 #define GAMEMANAGER_H
13
14 //***** LIBRARIES AND CLASSES *****/
15
16 // For the keyboard functionality
17 #include "Keyboard.h"
18
19 // glut really wants cstdlib here
20 #include <cstdlib>
21
22 // For arrays of strings
23 #include <string>
24 #include <vector>
25
26 // OpenGL API
27 #include <GL\glut.h>
28
29 // Standard I/O for debugging
30 #include <iostream>
31
32 // To manage background music
33 #include "MusicManager.h"
34
35 // To manage saving and loading
36 #include "SaveManager.h"
37
38 class GameManager
39 {
40 private:
41     // Variables
42
43     // Objects
44     MusicManager SoundSystem;
45     Keyboard board;
46
47     // Because the main menu is dumb, we have to know when to get a click
48     bool processClick = false;
49
50     // When in the main menu, mouse coords of a click
51     int mouse_x, mouse_y;
52
53     // Functions
```

```

54
55 public:
56
57     // Captures mouse clicks
58     void mouse(int button, int state, int x, int y);
59     // Captures mouse motion
60     void motionPassive(int x, int y);
61     // CHanges window size
62     void changeSize(int w, int h);
63     // Manages scene display
64     void manageScenes();
65     // Displaying function
66     void draw();
67     // Function to bring about game end on Level 4
68     void endGame();
69     // Normal key presses
70     void normal(unsigned char key, int x, int y);
71     // Key releases
72     void key_up(unsigned char key, int x, int y);
73     // Special keys
74     void special(int key, int x, int y);
75     // To manage playing and releasing music
76     void manageMusic();
77
78     // Wether or not core.sav exists
79     bool canContinue;
80
81 };
82
83 #endif

```

3.1.13 GameManager.cpp

```

1  /*****\
2  * GameManager.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the defintion of the GameManager class.*
8  * for more information, see GameManager.h *
9  \*****/
10
11 // Class declaration
12 #include "GameManager.h"
13 // Globals
14 #include "Globals.h"
15 // Level
16 #include "Level.h"
17 // Main Menu
18 #include "MainMenu.h"
19
20 #include "Logger.h"
21
22 #include "Return.h"
23
24 using namespace std;

```

```

25
26 void GameManager::mouse(int button, int state, int x, int y)
27 {
28     if (button == GLUT_RIGHT_BUTTON)
29     {
30         // Jokes on my I never ended up using the right button
31         if (state == GLUT_DOWN)
32         {
33
34         }
35
36         else
37         {
38
39         }
40     }
41
42     else if (button == GLUT_LEFT_BUTTON)
43     {
44         if (state == GLUT_DOWN)
45         {
46             if (isInMain)
47             {
48                 mouse_x = x;
49                 mouse_y = y;
50                 processClick = true;
51             }
52
53             Logger log;
54             vector<string> output = { "X: ", to_string(x), " ", "Y:",
55                                     to_string(y) };
56             log.logLine(output);
57
58             else
59             {
60
61             }
62         }
63     }
64
65 void GameManager::motionPassive(int x, int y)
66 {
67     static int _x = 0, _y = 0;
68
69     // If nothing else is happening basically
70     if (!isInConsole && !isInTerminal && !isInMain)
71     {
72         if (x > _x)
73         {
74             Cam.lookRight();
75             _x = x;
76         }
77
78         else if (x < _x)
79         {

```

```

80         Cam.lookLeft();
81         _x = x;
82     }
83
84     if (y < _y)
85     {
86         Cam.lookUp();
87         _y = y;
88     }
89
90     else if (y > _y)
91     {
92         Cam.lookDown();
93         _y = y;
94     }
95
96     // Loop around to the other side of the screen
97
98     bool updateMouse = false;
99     int newY = y, newX = x;
100    if (y == 0 || y > 700)
101    {
102        updateMouse = true;
103        newY = 300;
104        _y = 300;
105    }
106
107    if (x == 0 || x > 700)
108    {
109        updateMouse = true;
110        newX = 300;
111        _x = 300;
112    }
113
114    if (updateMouse)
115    {
116        glutWarpPointer(newX, newY);
117    }
118 }
119 }
120
121 void GameManager::changeSize(int w, int h)
122 {
123     // Don't want to divide by zero
124     if (h == 0)
125         h = 1;
126
127     double ratio = w * 1.0 / h;
128
129     // Use the Projection Matrix
130     glMatrixMode(GL_PROJECTION);
131
132     // Reset Matrix
133     glLoadIdentity();
134
135     // Set the viewport to be the entire window

```



```

136         glViewport(0, 0, w, h);
137
138         // Set the correct perspective.
139         gluPerspective(45, ratio, 1, 100);
140
141         // Get Back to the Modelview
142         glMatrixMode(GL_MODELVIEW);
143     }
144
145     void GameManager::draw()
146     {
147         if (loading)
148         {
149             lvl.loadLevel(curr_level);
150
151             loading = false;
152
153             // Save current progress after loading level
154             SaveManager Jesus; // saves
155             Jesus.saveLevel();
156         }
157
158         else
159         {
160             lvl.displayLevel();
161         }
162     }
163
164     void GameManager::endGame()
165     {
166         if (loading)
167         {
168             lvl.loadLevel(curr_level);
169
170             loading = false;
171
172             // Save current progress after loading level
173             SaveManager Jesus; // saves
174             Jesus.saveLevel();
175         }
176
177         else
178         {
179             // The time left for each segment
180             static int timeLeft = 1000;
181             // The last level is divided into 3 segments
182             static int segment = 1;
183             // Wether the current segment has been initialized yet
184             static bool initSegment = true;
185
186             // The last portion of the game is divided into 3 segments
187             if (segment == 1)
188             {
189                 glClearColor(1, 1, 1, 1);
190             }
191

```

```

192     else if (segment == 2)
193     {
194         if (initSegment)
195         {
196             HUD.displayWarning("");
197             HUD.displayWarning("QUANT");
198             initSegment = false;
199         }
200
201         for (unsigned i = 0; i < walls.size(); i++)
202         {
203             walls[i].mutate();
204         }
205     }
206
207     else if (segment == 3)
208     {
209         if (initSegment)
210         {
211             HUD.goFade(15);
212             HUD.setStatus("INFO-UN");
213             initSegment = false;
214         }
215
216         for (unsigned i = 0; i < walls.size(); i++)
217         {
218             walls[i].mutate();
219         }
220     }
221
222     else
223     {
224         HUD.setStatus("INFO-WELL");
225         isInMain = true;
226         songNum = 0;
227         changeSong = true;
228     }
229
230     // Switch segments
231     if (timeLeft == 0)
232     {
233         timeLeft = 1000;
234         segment++;
235         initSegment = true;
236     }
237     timeLeft--;
238
239
240     // Draw the titular object
241     glPushMatrix();
242     glTranslated(0, 0, -7);
243     glColor4d(.9, .9, .9, 1);
244     glutSolidSphere(3, 50, 50);
245     glPopMatrix();
246
247     lvl.displayLevel();

```

```

248     }
249 }
250
251 void GameManager::manageScenes()
252 {
253     // If we need to change the song, we can do it here
254     if (changeSong)
255     {
256         manageMusic();
257     }
258
259     // Clears the previous drawing
260     glClear(GL_COLOR_BUFFER_BIT | GL_DEPTH_BUFFER_BIT);
261
262     if (isInTerminal)
263     {
264         activeTerminal->DisplayScreen();
265     }
266
267     else if (isInMain)
268     {
269         // Enable using textures (pictures)
270         glutSetCursor(GLUT_CURSOR_LEFT_ARROW);
271         static MainMenu MM;
272
273         // For some reason, MM breaks horribly when it's a global or class
274         // member
275         // So we'll just handle mouse clicks in the display function
276         // Rather than the mouse click function
277         // Because I'm a competent programmer
278         if (processClick)
279         {
280             MM.getClick(mouse_x, mouse_y);
281             processClick = false;
282         }
283
284         MM.display();
285     }
286
287     // glutSetCursor(GLUT_CURSOR_LEFT_ARROW); Keypads maybe?
288
289     else
290     {
291         // Enable using textures (pictures)
292         glutSetCursor(GLUT_CURSOR_NONE);
293
294         if (curr_level != "LEVELFOUR") draw();
295
296         else endGame();
297
298         // Moves the camera to the correct position
299         Cam.Display();
300
301         // Prompt the user to interact if we should
302         if (interactivity) HUD.displayWarning("INTERACT");
303         else if (curr_level != "LEVELFOUR") HUD.displayWarning("");

```

```

303
304             // Prints the HUD
305             HUD.DisplayHUD();
306         }
307
308         // Displays the current drawing
309         glutSwapBuffers();
310     }
311
312 void GameManager::manageMusic()
313 {
314     // All variables need to persist between frames
315     static SoundClass background;
316
317     SoundSystem.releaseSound(background);
318     changeSong = false;
319
320     // Because you can never have too much bounds checking
321     if (songNum >= 0 && songNum <= 9)
322     {
323         std::string song = getSongName(songNum);
324         SoundSystem.makeSound(&background, song.c_str());
325         SoundSystem.playSound(background);
326     }
327 }
328
329 // Normal key presses
330 void GameManager::normal(unsigned char key, int x, int y)
331 {
332     board.normal(key, x, y);
333 }
334
335 // Key releases
336 void GameManager::key_up(unsigned char key, int x, int y)
337 {
338     board.key_up(key, x, y);
339 }
340
341 // Special keys
342 void GameManager::special(int key, int x, int y)
343 {
344     board.special(key, x, y);
345 }

```

3.1.14 GCTypes.h

```

1  /*****\
2  * GCTypes.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains integer types corresponding to various *
8  * In game object types *
9  \*****/
10
11 #ifndef GC_TYPES_H

```

```

12 #define GC_TYPES_H
13
14 // Object Types
15
16 #define T_NULL 0 // Nothing
17 #define T_DOOR 1 // Door
18 #define T_TERMINAL 2 // Terminal
19 #define T_SWITCH 3 // Switch
20 #define T_LEVEL_END 4 // Switch that ends level
21
22 typedef int Gctype;
23
24 #endif

```

3.1.15 Globals.h

```

1  /*****\
2  * Globals.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the Globals *
8  * All of them. *
9  * Thers a lot of them *
10 \*****/
11
12 #ifndef GLOBALS_H
13 #define GLOBALS_H
14
15 // ALLLLLLL the classes
16 #include "HeadsUpDisplay.h"
17 #include "CameraControl.h"
18 #include "Level.h"
19 #include "Terminal.h"
20 #include "Door.h"
21 #include "Switch.h"
22 #include "Plane.h"
23 #include "Trigger.h"
24 #include "Cylinder.h"
25
26 // Remember that if you're doing anything else, globals are bad.
27 // But we're in the hellscape that is graphics
28 // There are no rules here
29 // Only madness dwells here
30
31 // Typedefs make life easy
32 typedef std::vector<Plane> vr;
33 typedef std::vector<Door> vd;
34 typedef std::vector<Switch> vs;
35 typedef std::vector<Terminal> vt;
36 typedef std::vector<Trigger> vtr;
37 typedef std::vector<Cylinder> vc;
38
39 // Pointers to various interactive objects
40 extern Switch *activeSwitch;
41 extern Terminal *activeTerminal;

```

```

42
43 // Vectors containing all of the level's assets
44 extern vr walls;
45 extern vd doors;
46 extern vs switches;
47 extern vt terminals;
48 extern vtr triggers;
49 extern vc cylinders;
50
51 extern bool
52     // Are we colliding / Can we die?
53     collision, godMode,
54     // Go dim or go dark?
55     goDim, goDark,
56     // Dunno if I actually need this one
57     loading,
58     // Is in various different stages of non-normal play
59     isInConsole, isInTerminal, isInMain,
60     // Should we change the song?
61     changeSong,
62     // Is something in interaction range?
63     interactivity;
64
65 // Number of song to change to
66 extern int songNum;
67
68 // Current level (int and string)
69 extern int levelNum;
70 extern std::string curr_level;
71
72 // Constant strings of the song names
73 extern const char *SONG0, *SONG1, *SONG2, *SONG3, *SONG4, *SONG5,
74                 *SONG6, *SONG7, *SONG8, *SONG9;
75
76 // A few global objects
77 extern HeadsUpDisplay HUD;
78 extern CameraControl Cam;
79 extern Level lvl;
80
81 // Converts a songname to an integer
82 int getSongNum(std::string input);
83 // Converts an integer to a songname
84 std::string getSongName(int input);
85 // Converts a level name to an integer
86 int getLevelNum(std::string input);
87 // Converts level_num to a string in curr_level
88 std::string getLevelString(int input);
89
90 #endif

```

3.1.16 Globals.cpp

```

1  /*****\
2  * Globals.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *

```

```

6  *                                                                 *
7  * This file instantiates the global variables                    *
8  \*****/
9
10 #include "Globals.h"
11
12 vr walls;
13 vd doors;
14 vs switches;
15 vt terminals;
16 vtr triggers;
17 vc cylinders;
18
19 Switch *activeSwitch = NULL;
20 Terminal *activeTerminal = NULL;
21
22 bool collision = true;
23 bool godMode = false;
24 bool goDim = false;
25 bool goDark = false;
26 bool loading = true;
27 bool isInConsole = false;
28 bool isInTerminal = false;
29 bool isInMain = true;
30 bool changeSong = true;
31 bool interactivity = false;
32
33 int songNum = 0;
34
35 int levelNum = 0;
36 std::string curr_level = "LEVELZERO";
37
38 const char* SONG0 = "Dark Fog.mp3";
39 const char* SONG1 = "Mismer.mp3";
40 const char* SONG2 = "One Sly Move.mp3";
41 const char* SONG3 = "Hypnothis.mp3";
42 const char* SONG4 = "Cold Hope.mp3";
43 const char* SONG5 = "Spacial Harvest.mp3";
44
45 HeadsUpDisplay HUD;
46 CameraControl Cam;
47 Level lvl;
48
49 int getSongNum(std::string input)
50 {
51     if (input == SONG0 || input == "0")
52         return 0;
53     if (input == SONG1 || input == "1")
54         return 1;
55     if (input == SONG2 || input == "2")
56         return 2;
57     if (input == SONG3 || input == "3")
58         return 3;
59     if (input == SONG4 || input == "4")
60         return 4;
61     if (input == SONG5 || input == "5")

```

```

62         return 5;
63     return -1; // Invalid song
64 }
65
66 std::string getSongName(int input)
67 {
68     std::string ret;
69     switch (input)
70     {
71     case 0: ret = SONG0;
72             break;
73     case 1: ret = SONG1;
74             break;
75     case 2: ret = SONG2;
76             break;
77     case 3: ret = SONG3;
78             break;
79     case 4: ret = SONG4;
80             break;
81     case 5: ret = SONG5;
82             break;
83     default: ret = "\0";
84             break;
85     }
86
87     return ret;
88 }
89
90 int getLevelNum(std::string input)
91 {
92     if (input == "LEVELZERO" || input == "LEVELZERO\n")
93         return 0;
94     if (input == "LEVELONE" || input == "LEVELONE\n")
95         return 1;
96     if (input == "LEVELTWO")
97         return 2;
98     if (input == "LEVELTHREE")
99         return 3;
100    if (input == "LEVELFOUR")
101        return 4;
102    return -1; // Invalid song
103 }
104
105 std::string getLevelString(int input)
106 {
107     std::string ret;
108     switch (input)
109     {
110     case 0: ret = "LEVELZERO";
111             break;
112     case 1: ret = "LEVELONE";
113             break;
114     case 2: ret = "LEVELTWO";
115             break;
116     case 3: ret = "LEVELTHREE";
117             break;

```



```

118         case 4: ret = "LEVELFOUR";
119             break;
120         default: ret = "ERROR";;
121             break;
122     }
123
124     return ret;
125 }

```

3.1.17 HeadsUpDisplay.h

```

1  /*****\
2  * HeadsUpDisplay.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the HeadsUpDisplay *
8  * Class, which created an Orthoganl Matrix infront of the *
9  * Screen which allows for a 2D Heads Up Display to be *
10 * Printed before the user at any time *
11 * It also passes input to the developer console *
12 \*****/
13
14 #ifndef HEADSUPDISPLAY
15 #define HEADSUPDISPLAY
16
17 // Base class for 2D operations
18 #include "TwoD.h"
19
20 // For displaying text in the HUD
21 #include "TextEngine.h"
22 // The Developer Console
23 #include "Console.h"
24
25 class HeadsUpDisplay : public TwoD
26 {
27 private:
28     // Duration of time to dim screen (Goes from black to clear as time
29     // progresses)
30     int dimTime = 0;
31     // Duration of time to go dark (completely black)
32     int darkTime = 0;
33     // Duration of the time to fade the screen (goes from clear to black as
34     // time progresses)
35     int fadeTime = 0;
36     // Wether or not to dim
37     bool dimNow = false;
38     // Wether or not to darken
39     bool darkNow = false;
40     // Wether or not to fade
41     bool fadeNow = false;
42     // Wether or not we are in developer console
43     bool devConsole = false;
44
45     // Tag to current alert
46     std::string currentAlert;

```

```

45     // Tag to current status
46     std::string currentStatus;
47     // Text to print to the screen
48     std::string currentText;
49     // What the user is typing
50     std::string currentInput;
51
52     // To Display text
53     TextEngine helmet;
54     // Dev Console
55     Console dev;
56
57     // Draws an info bar at the top of the screen
58     void drawHelmetBounds();
59     // Displays suit alerts
60     void DisplayAlerts();
61     // Draws the Heads Up Display
62     void drawHUD();
63     // Manages the dimming of the screen
64     void dim();
65     // Manages the darkening of the screen
66     void dark();
67     // Manages the fading of the screen
68     void fade();
69     // Draws the box which stores the info text
70     void drawInfoBox();
71     // Draws the developer console window
72     void drawConsole();
73     // Displays standard info in the top left corner
74     void displayInfo(std::string tag);
75
76
77 public:
78     // Manages the HUD
79     void DisplayHUD();
80
81     /****          ALTERATION FUNCTIONS          *****/
82     \**** Should always be called before DisplayHud *****/
83
84     // Tells the HUD how long to dim
85     void goDim(int time);
86
87     //Tells the HUD how long to go dark
88     void goDark(int time);
89     // Tels the HUD how long to fade for
90     void goFade(int time);
91     // Flips dev_console
92     void toggleConsole();
93
94     // Takes in a tag to print to screen
95     void displayWarning(std::string warning);
96
97     // Takes in a string to display in the status box
98     void setStatus(std::string status);
99
100    // Takes in a string to print to screen

```

```

101         void printToConsole(std::string text);
102
103         // Signifies a completed input to the console
104         void inputString(std::string text);
105
106         // Returns an item of the console's log
107         std::string getHist(int count);
108
109         // Returns the number of items in the console's log
110         int getHistNum();
111     };
112
113 #endif

```

3.1.18 HeadsUpDisplay.cpp

```

1  /*****\
2  * HeadsUpDisplay.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the HeadsUpDisplay *
8  * Class. For more information, see HeadsUpDisplay.h *
9  \*****/
10
11 // Class Declaration
12 #include "HeadsUpDisplay.h"
13
14 // OpenGL API
15 #include <gl\glut.h>
16
17 // For counting seconds
18 #include <ctime>
19
20 // For displaying Planes
21 #include "Plane.h"
22
23 // For displaying triangles
24 #include "Triangle.h"
25
26 using namespace std;
27
28 void HeadsUpDisplay::drawHelmetBounds()
29 {
30     // Helmet bounds are black
31     double colors[4] = { 0, 0, 0, 1 };
32
33     // The top of the helmet
34     double top_vertices[9] =
35     {
36         SCREENRIGHT, SCREENTOP, -1,
37         SCREENLEFT, SCREENTOP, -1,
38         SCREENRIGHT / 2.0, SCREENBOTTOM / 20.0, -1
39     };
40
41     // The left of the hemlet

```

```

42     double left_vertices[9] =
43     {
44         SCREENLEFT, SCREENBOTTOM, -1,
45         SCREENLEFT, SCREENTOP, -1,
46         SCREENRIGHT / 20.0, 3 * SCREENBOTTOM / 5.0, -1
47     };
48
49     // The back of the helmet
50     double right_vertices[9] =
51     {
52         SCREENRIGHT, SCREENBOTTOM, -1,
53         SCREENRIGHT, SCREENTOP, -1,
54         19 * SCREENRIGHT / 20.0, 3 * SCREENBOTTOM / 5.0, -1
55     };
56
57     Triangle top_helm{ top_vertices, colors };
58     Triangle left_helm{ left_vertices, colors };
59     Triangle right_helm{ right_vertices, colors };
60
61     top_helm.Display2D();
62     left_helm.Display2D();
63     right_helm.Display2D();
64 }
65
66 void HeadsUpDisplay::DisplayAlerts()
67 {
68     helmet.openFile(.5 * SCREENRIGHT, .5 * SCREENBOTTOM,
69         1, 1, 1,
70         "suitAlerts.log", currentAlert);
71 }
72
73 void HeadsUpDisplay::dim()
74 {
75     static int startTime;
76     static bool timeSet = false;
77     if (dimNow)
78     {
79         if (!timeSet)
80         {
81             startTime = time(NULL);
82             timeSet = true;
83         }
84
85         int currentTime = time(NULL);
86         int timeElapsed = currentTime - startTime;
87         if (timeElapsed < dimTime)
88         {
89             // A black square that grows more transparent as time
90             // passes
91             double colors[4] = { 0, 0, 0, (double)(dimTime -
92                 timeElapsed) / dimTime };
93             double dimVert[12] =
94             {
95                 SCREENLEFT, SCREENTOP, -1,
96                 SCREENLEFT, SCREENBOTTOM, -1,
97                 SCREENRIGHT, SCREENBOTTOM, -1,

```

```

96             SCREENRIGHT, SCREENTOP, -1
97         };
98
99         Plane black{ dimVert, colors };
100        black.Display2D();
101    }
102
103    else
104    {
105        dimNow = false;
106        timeSet = false;
107    }
108 }
109 }
110
111 void HeadsUpDisplay::fade()
112 {
113     static int startTime;
114     static bool timeSet = false;
115     if (fadeNow)
116     {
117         if (!timeSet)
118         {
119             startTime = time(NULL);
120             timeSet = true;
121         }
122
123         int currentTime = time(NULL);
124         int timeElapsed = currentTime - startTime;
125         if (timeElapsed < fadeTime)
126         {
127             // A black square that grows more transparent as time
128             // passes
129             double colors[4] = { 0, 0, 0, 1 - ((double)(fadeTime -
130             timeElapsed) / fadeTime) };
131             double dimVert[12] =
132             {
133                 SCREENLEFT, SCREENTOP, -1,
134                 SCREENLEFT, SCREENBOTTOM, -1,
135                 SCREENRIGHT, SCREENBOTTOM, -1,
136                 SCREENRIGHT, SCREENTOP, -1
137             };
138
139             Plane black{ dimVert, colors };
140             black.Display2D();
141         }
142     }
143     else
144     {
145         fadeNow = false;
146         timeSet = false;
147
148         // Go dark till game ends
149         darkNow = true;
150         darkTime = 1000;

```

```

150         }
151     }
152 }
153
154 void HeadsUpDisplay::dark()
155 {
156     static int startTime;
157     static bool timeSet = false;
158     if (darkNow)
159     {
160         if (!timeSet)
161         {
162             startTime = time(NULL);
163             timeSet = true;
164         }
165
166         int currentTime = time(NULL);
167         int timeElapsed = currentTime - startTime;
168         if (timeElapsed < darkTime)
169         {
170             // A black square that obscures vision
171             double colors[4] = { 0, 0, 0, 1 };
172             double dimVert[12] =
173             {
174                 SCREENLEFT, SCREENTOP, -1,
175                 SCREENLEFT, SCREENBOTTOM, -1,
176                 SCREENRIGHT, SCREENBOTTOM, -1,
177                 SCREENRIGHT, SCREENTOP, -1
178             };
179
180             Plane black{ dimVert, colors };
181             black.Display2D();
182         }
183
184         else
185         {
186             darkNow = false;
187             timeSet = false;
188         }
189     }
190 }
191
192 void HeadsUpDisplay::drawConsole()
193 {
194     double colors[4] = { .1, .1, .1, .9 };
195     double vertices[12] =
196     {
197         SCREENLEFT, SCREENTOP, -1,
198         SCREENLEFT, SCREENBOTTOM / 5, -1,
199         SCREENRIGHT, SCREENBOTTOM / 5, -1,
200         SCREENRIGHT, SCREENTOP, -1
201     };
202
203     Plane console_tab{ vertices, colors };
204     console_tab.Display2D();
205 }

```

```

206         if (currentInput != "")
207         {
208             dev.activate(currentInput, currentText);
209             currentInput.clear();
210         }
211
212         else
213         {
214             dev.activate(currentText);
215         }
216     }
217
218     void HeadsUpDisplay::drawInfoBox()
219     {
220         double colors[4] = { 0, 1, 1, .5 };
221         double vertices[12] =
222         {
223             SCREENLEFT, SCREENTOP, -1,
224             SCREENLEFT, SCREENBOTTOM / 10, -1,
225             SCREENRIGHT / 10, SCREENBOTTOM / 10, -1,
226             SCREENRIGHT / 10, SCREENTOP, -1
227         };
228
229         Plane info{ vertices, colors };
230         info.Display2D();
231     }
232
233     void HeadsUpDisplay::displayInfo(string tag)
234     {
235         helmet.openFile(SCREENLEFT, SCREENTOP + 20, 1, 1, 1,
236             "suitAlerts.log", currentStatus);
237     }
238
239     void HeadsUpDisplay::goDim(int time)
240     {
241         dimTime = time;
242         dimNow = true;
243     }
244
245     void HeadsUpDisplay::goDark(int time)
246     {
247         darkTime = time;
248         darkNow = true;
249     }
250
251     void HeadsUpDisplay::goFade(int time)
252     {
253         fadeTime = time;
254         fadeNow = true;
255     }
256
257     void HeadsUpDisplay::displayWarning(std::string warning)
258     {
259         currentAlert = warning;
260     }
261

```

```

262 void HeadsUpDisplay::setStatus(std::string status)
263 {
264     currentStatus = status;
265 }
266
267 void HeadsUpDisplay::printToConsole(std::string text)
268 {
269     currentText = text;
270 }
271
272 void HeadsUpDisplay::inputString(std::string text)
273 {
274     currentInput = text;
275 }
276
277 void HeadsUpDisplay::toggleConsole()
278 {
279     devConsole = !devConsole;
280 }
281
282 void HeadsUpDisplay::drawHUD()
283 {
284     drawHelmetBounds();
285
286     if (dimNow)
287     {
288         dim();
289     }
290
291     else if (fadeNow)
292     {
293         fade();
294     }
295
296     // Not else if due to fade -> dark transition
297     if (darkNow)
298     {
299         dark();
300     }
301
302     drawInfoBox();
303     displayInfo(currentStatus);
304
305     if (devConsole)
306     {
307         drawConsole();
308     }
309
310     if (currentAlert != "")
311     {
312         DisplayAlerts();
313     }
314 }
315
316 string HeadsUpDisplay::getHist(int count)
317 {

```



```

318         return dev.getHist(count);
319     }
320
321     int HeadsUpDisplay::getHistNum()
322     {
323         return dev.getHistNum();
324     }
325
326     void HeadsUpDisplay::DisplayHUD()
327     {
328         prepare2D();
329
330         drawHUD();
331
332         prepare3D();
333     }

```

3.1.19 Keyboard.h

```

1  /*****\
2  * Keyboard.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the Keyboard class, *
8  * which logs keypresses from the user and determines, *
9  * depending on the context, what action to take such. *
10 \*****/
11
12 #ifndef KEYBOARD_H
13 #define KEYBOARD_H
14
15 // std::string
16 #include <string>
17
18 class Keyboard
19 {
20 private:
21     // Signals to recieve a part of the console's history
22     bool getPrev, getNext;
23
24 public:
25     // Normal keys
26     void normal(unsigned char key, int x, int y);
27     // To read console input
28     void inputConsole(unsigned char key, int x, int y);
29     // To read terminal input
30     void inputTerminal(unsigned char key, int x, int y);
31     // To interact with the world
32     void interact(unsigned char key, int x, int y);
33     // If a key is released
34     void key_up(unsigned char key, int x, int y);
35     // Special keys (functions, arrows, ect.)
36     void special(int key, int x, int y);
37     // Manages interactivity
38     void interact();

```

```

39 };
40
41 #endif

```

3.1.20 Keyboard.cpp

```

1  /*****\
2  * Keyboard.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the defintion of the Keyboard class. *
8  * for more information, see Keyboard.h *
9  \*****/
10
11 // Class decleration
12 #include "Keyboard.h"
13
14 // std::string
15 #include <string>
16
17 // glut really wants cstdlib here
18 #include <cstdlib>
19
20 // OpenGL API
21 #include <GL\glut.h>
22
23 // To recieve and manage global variables
24 #include "Globals.h"
25 // Collision detection
26 #include "CollisionEngine.h"
27
28 // Return codes
29 #include "Return.h"
30 // System log
31 #include "Logger.h"
32
33 using namespace std;
34
35 void Keyboard::normal(unsigned char key, int x, int y)
36 {
37     // If we are currently capturing input
38     if (isInConsole)
39     {
40         inputConsole(key, x, y);
41     }
42
43     // If we're in a computer
44     else if (isInTerminal)
45     {
46         inputTerminal(key, x, y);
47     }
48
49     // Otherwise (as long we aren't in a menu)
50     else if (!isInMain)
51     {

```

```

52         interact(key, x, y);
53     }
54 }
55
56 void Keyboard::inputConsole(unsigned char key, int x, int y)
57 {
58     // User string input
59     static string input;
60     // Number in console history
61     static int count = 0;
62
63     // Up arrow, recieves the next older entry in the console's history
64     if (getPrev)
65     {
66         input = HUD.getHist(count);
67
68         if (count < HUD.getHistNum() - 1)
69         {
70             count++;
71         }
72
73         getPrev = false;
74     }
75
76     // Down arrow, recieves the next newer entry in the console's history
77     else if (getNext)
78     {
79         input = HUD.getHist(count);
80
81         if (count > 0)
82         {
83             count--;
84         }
85
86         getNext = false;
87     }
88
89     // Enter key, process and clear input
90     else if (key == 13)
91     {
92         HUD.inputString(input);
93         input.clear();
94         count = 0;
95     }
96
97     // Tilda, close the console
98     else if (key == '~' || isInConsole == false)
99     {
100         input.clear();
101         isInConsole = false;
102         HUD.toggleConsole();
103         count = 0;
104     }
105
106     // Backspace. Self explanatory
107     else if (key == 8 && !input.empty())

```

```

108         {
109             input.pop_back();
110         }
111
112         // Otherwise, type normally
113         else
114         {
115             input += key;
116         }
117
118         // Print what's been typed so far
119         HUD.printToConsole(input);
120     }
121
122     // Pretty much a copy pasta of inputConsole because I'm a terrible programmer
123     // I'll try to combine em in the future, I swear
124     // Just adjust all of these to do terminally stuff I guess
125     void Keyboard::inputTerminal(unsigned char key, int x, int y)
126     {
127         // TODO: Fix terminal input with active Terminal hijibis
128
129         // User string input
130         static string input;
131         // Number in console history
132         static int count = 0;
133
134         // Up arrow, recieves the next older entry in the console's history
135         if (getPrev)
136         {
137             input = activeTerminal->getHist(count);
138
139             if (count < activeTerminal->getHistNum() - 1)
140             {
141                 count++;
142             }
143
144             getPrev = false;
145         }
146
147         // Down arrow, recieves the next newer entry in the console's history
148         else if (getNext)
149         {
150             input = activeTerminal->getHist(count);
151
152             if (count > 0)
153             {
154                 count--;
155             }
156
157             getNext = false;
158         }
159
160         // Enter key, process and clear input
161         else if (key == 13)
162         {
163             activeTerminal->getInput(input);

```

```

164         input.clear();
165         count = 0;
166     }
167
168     // Backspace. Self explanatory
169     else if (key == 8 && !input.empty())
170     {
171         input.pop_back();
172     }
173
174     // Otherwise, type normally
175     else
176     {
177         input += key;
178     }
179
180     // Print what's been typed so far
181     activeTerminal->getText(input); // Drawing handled elsewhere?
182 }
183
184 void Keyboard::interact(unsigned char key, int x, int y)
185 {
186     CollisionEngine col;
187     // Speed at which the player moves
188     int speedMod = 1;
189
190     int modKey = glutGetModifiers();
191
192     if (modKey == GLUT_ACTIVE_SHIFT)
193     {
194         speedMod = 2;
195     }
196
197     else
198     {
199         speedMod = 1;
200     }
201
202     switch (key)
203     {
204     case 'w':
205     case 'W':
206         Cam.moveForward(speedMod);
207         if (col.collide())
208         {
209             Cam.moveBackward(speedMod);
210         }
211         break;
212     case 'a':
213     case 'A':
214         Cam.strafeRight();
215         if (col.collide())
216         {
217             Cam.strafeLeft();
218         }
219         break;

```

```

220     case 's':
221     case 'S':
222         Cam.moveBackward(speedMod);
223         if (col.collide())
224         {
225             Cam.moveForward(speedMod);
226         }
227         break;
228     case 'd':
229     case 'D':
230         Cam.strafeLeft();
231         if (col.collide())
232         {
233             Cam.strafeRight();
234         }
235         break;
236     case 'e':
237     case 'E':
238         interact();
239         break;
240     case '~':
241         isInConsole = true;
242         HUD.toggleConsole();
243         break;
244
245         // Enter
246     case 13:
247         //goDim = true;
248         break;
249
250         // Escape
251     case 27:
252         isInMain = true;
253         songNum = 0;
254         changeSong = true;
255         break;
256     }
257 }
258
259 void Keyboard::key_up(unsigned char key, int x, int y)
260 {
261     // I'm sure I'll do something smart here
262 }
263
264 void Keyboard::special(int key, int x, int y)
265 {
266     Logger log;
267     // We start in fullscreen
268     static bool fullScreen = true;
269     switch (key)
270     {
271     case GLUT_KEY_F1:
272         fullScreen = !fullScreen;
273         break;
274
275     case GLUT_KEY_F2:

```

```

276         // Only way to exit main loop.
277         log.logLine("Exiting via F2");
278         exit(EXIT_OK);
279         break;
280
281     case GLUT_KEY_F3:
282         Cam.resetCam();
283         break;
284
285     case GLUT_KEY_F4:
286         isInMain = !isInMain;
287         break;
288
289     case GLUT_KEY_F5:
290         log.logCamCoords();
291         break;
292
293     case GLUT_KEY_UP:
294         if (isInConsole || isInTerminal)
295         {
296             getPrev = true;
297             getNext = false;
298
299             // To ensure that the input is updated BEFORE next key
300             // press
301             normal(0, 0, 0);
302         }
303         break;
304
305     case GLUT_KEY_DOWN:
306         if (isInConsole || isInTerminal)
307         {
308             getNext = true;
309             getPrev = false;
310
311             // To ensure that the input is updated BEFORE next key
312             // press
313             normal(0, 0, 0);
314         }
315         break;
316
317     if (fullScreen)
318     {
319         glutFullScreen();
320     }
321     else
322     {
323         glutReshapeWindow(1367, 767);
324         glutPositionWindow(50, 50);
325     }
326 }
327
328 void Keyboard::interact()
329 {

```

```

330         // Only do things if we actually can
331         if (interactivity)
332         {
333             if (activeSwitch != NULL)
334             {
335                 activeSwitch->toggleTarget();
336
337                 for (unsigned int i = 0; i < triggers.size(); i++)
338                 {
339                     triggers[i].tryToTrigger(activeSwitch, T_SWITCH);
340                 }
341             }
342
343             else if (activeTerminal != NULL)
344             {
345                 isInTerminal = true;
346
347                 for (unsigned int i = 0; i < triggers.size(); i++)
348                 {
349                     triggers[i].tryToTrigger(activeTerminal,
350                                             T_TERMINAL);
351                 }
352             }
353 }

```

3.1.21 Level.h

```

1  /*****\
2  * Level.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the Level class *
8  * Which loads all level assets from a sqlite database *
9  * (data.db) *
10 \*****/
11
12 #ifndef LEVEL_H
13 #define LEVEL_H
14
15 // std::string
16 #include <string>
17 // std::vector
18 #include <vector>
19 // Planes for walls/doors/such else
20 #include "Plane.h"
21
22 // SQLite API
23 #include "sqlite3.h"
24
25 // Glut API
26 #include <GL\glut.h>
27
28 class Level
29 {

```



```

30 private:
31     // Used to load cylinders
32     GLUQuadricObj *quadratic;
33     // The current level being loaded
34     std::string currLevel;
35
36     // Look, the names are self-explanatory
37     void loadWalls(sqlite3 *db);
38     void loadDoors(sqlite3 *db);
39     void loadCylinders(sqlite3 *db);
40     void loadSwitches(sqlite3 *db);
41     void loadTerminals(sqlite3 *db);
42     void loadTriggers(sqlite3 *db);
43
44     // Binds the triggering object and target object to a single trigger
45     bool bindTrigger(std::string id, std::string trigger, std::string
        triggerType);
46     bool bindTarget(std::string id, std::string target, std::string targetType
        );
47
48 public:
49     // Manages the loading of the level
50     void loadLevel(std::string levelName);
51     // Draws the level
52     void displayLevel();
53 };
54
55 #endif

```

3.1.22 Level.cpp

```

1  /*****\
2  * Level.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * * *
7  * This file contains the definition of the Level class. *
8  * for more information, see Level.h *
9  \*****/
10
11 // Class declaration
12 #include "Level.h"
13 // To use Planes
14 #include "Plane.h"
15 // Vectors to plop stuff in
16 #include "Globals.h"
17 // Return codes
18 #include "Return.h"
19 // System log
20 #include "Logger.h"
21 // Object Types
22 #include "GCTypes.h"
23
24 #include <iostream>
25
26 using namespace std;

```

```

27
28 void Level::loadWalls(sqlite3 *db)
29 {
30     walls.clear();
31     // Prepared Statement
32     sqlite3_stmt *stm;
33     // SQL command
34     string cmd;
35     // Connection Error Test
36     int err;
37     cmd = "SELECT * FROM walls WHERE LEVEL = \"" + currLevel + "\"";
38
39     err = sqlite3_prepare(db, cmd.c_str(), -1, &stm, 0);
40
41     if (err != SQLITE_OK)
42     {
43         Logger log;
44         vector<string> output = { "FATAL ERROR: failed to load walls from
45                                 ", currLevel };
46         log.logLine(output);
47         exit(STATEMENT_ERROR);
48     }
49     // While we still get rows of output
50     while (sqlite3_step(stm) == SQLITE_ROW)
51     {
52         double x1, x2, x3, x4,
53                y1, y2, y3, y4,
54                z1, z2, z3, z4,
55                r, g, b, a;
56         string axis;
57
58         x1 = sqlite3_column_double(stm, 2);
59         x2 = sqlite3_column_double(stm, 3);
60         x3 = sqlite3_column_double(stm, 4);
61         x4 = sqlite3_column_double(stm, 5);
62
63         y1 = sqlite3_column_double(stm, 6);
64         y2 = sqlite3_column_double(stm, 7);
65         y3 = sqlite3_column_double(stm, 8);
66         y4 = sqlite3_column_double(stm, 9);
67
68         z1 = sqlite3_column_double(stm, 10);
69         z2 = sqlite3_column_double(stm, 11);
70         z3 = sqlite3_column_double(stm, 12);
71         z4 = sqlite3_column_double(stm, 13);
72
73         r = sqlite3_column_double(stm, 14);
74         g = sqlite3_column_double(stm, 15);
75         b = sqlite3_column_double(stm, 16);
76         a = sqlite3_column_double(stm, 17);
77
78         axis = reinterpret_cast<const char*>(sqlite3_column_text(stm, 18))
79             ;
80         char ax;

```

```

81         if (axis == "x") ax = 'x';
82         else if (axis == "y") ax = 'y';
83         else if (axis == "z") ax = 'z';
84         else ax = 0;
85
86         double verts[12] =
87         {
88             x1, y1, z1,
89             x2, y2, z2,
90             x3, y3, z3,
91             x4, y4, z4
92         };
93         double colors[4] = { r, g, b, a };
94
95         Plane rect(verts, colors, ax);
96
97         walls.push_back(rect);
98     }
99
100    /*
101    Logger log;
102    vector<string> output = { "Loaded walls on", currLevel };
103    log.logLine(output);
104    */
105
106    // Deconstructs the statement
107    sqlite3_finalize(stm);
108 }
109
110 void Level::loadDoors(sqlite3 *db)
111 {
112     doors.clear();
113     // Prepared Statement
114     sqlite3_stmt *stm;
115     // SQL command
116     string cmd;
117     // Connection Error Test
118     int err;
119     cmd = "SELECT * FROM doors WHERE LEVEL = \"" + currLevel + "\"";
120
121     err = sqlite3_prepare(db, cmd.c_str(), -1, &stm, 0);
122
123     if (err != SQLITE_OK)
124     {
125         Logger log;
126         vector<string> output = { "FATAL ERROR: Can't load doors while
127             loading", currLevel };
128         log.logLine(output);
129
130         exit(STATEMENT_ERROR);
131     }
132
133     // While we still get rows of output
134     while (sqlite3_step(stm) == SQLITE_ROW)
135     {
136         double x1, x2, x3, x4,

```

```

136         y1, y2, y3, y4,
137         z1, z2, z3, z4,
138         r, g, b, a;
139     string id;
140     string axis;
141
142     id = reinterpret_cast<const char*>(sqlite3_column_text(stm, 0));
143     x1 = sqlite3_column_double(stm, 2);
144     x2 = sqlite3_column_double(stm, 3);
145     x3 = sqlite3_column_double(stm, 4);
146     x4 = sqlite3_column_double(stm, 5);
147
148     y1 = sqlite3_column_double(stm, 6);
149     y2 = sqlite3_column_double(stm, 7);
150     y3 = sqlite3_column_double(stm, 8);
151     y4 = sqlite3_column_double(stm, 9);
152
153     z1 = sqlite3_column_double(stm, 10);
154     z2 = sqlite3_column_double(stm, 11);
155     z3 = sqlite3_column_double(stm, 12);
156     z4 = sqlite3_column_double(stm, 13);
157
158     r = sqlite3_column_double(stm, 14);
159     g = sqlite3_column_double(stm, 15);
160     b = sqlite3_column_double(stm, 16);
161     a = sqlite3_column_double(stm, 17);
162
163     a = sqlite3_column_double(stm, 17);
164
165     axis = reinterpret_cast<const char*>(sqlite3_column_text(stm, 18))
        ;
166
167     char ax;
168     if (axis == "x") ax = 'x';
169     else if (axis == "y") ax = 'y';
170     else if (axis == "z") ax = 'z';
171     else ax = 0;
172
173     double verts[12] =
174     {
175         x1, y1, z1,
176         x2, y2, z2,
177         x3, y3, z3,
178         x4, y4, z4
179     };
180     double colors[4] = { r, g, b, a };
181
182     Plane rect(verts, colors, ax);
183
184     doors.push_back(Door(rect, id));
185 }
186
187 Logger log;
188 vector<string> output = { "Loaded doors on", currLevel };
189 log.logLine(output);
190

```

```

191         // Deconstructs the statement
192         sqlite3_finalize(stm);
193     }
194
195     void Level::loadCylinders(sqlite3 *db)
196     {
197         cylinders.clear();
198         // Prepared Statement
199         sqlite3_stmt *stm;
200         // SQL command
201         string cmd;
202         // Connection Error Test
203         int err;
204         cmd = "SELECT * FROM cylinders WHERE LEVEL = \"" + currLevel + "\"";
205
206         err = sqlite3_prepare(db, cmd.c_str(), -1, &stm, 0);
207
208         if (err != SQLITE_OK)
209         {
210             Logger log;
211             vector<string> output = { "FATAL ERROR: Can't load cylinders while
                loading", currLevel };
212             log.logLine(output);
213
214             exit(STATEMENT_ERROR);
215         }
216
217         // While we still get rows of output
218         while (sqlite3_step(stm) == SQLITE_ROW)
219         {
220             double xt, yt, zt,
221                 xr, yr, zr,
222                 r, g, b, a,
223                 baseRadius, topRadius, height;
224             int stacks, slices;
225
226
227             xt = sqlite3_column_double(stm, 1);
228             yt = sqlite3_column_double(stm, 2);
229             zt = sqlite3_column_double(stm, 3);
230
231             xr = sqlite3_column_double(stm, 4);
232             yr = sqlite3_column_double(stm, 5);
233             zr = sqlite3_column_double(stm, 6);
234
235             baseRadius = sqlite3_column_double(stm, 7);
236             topRadius = sqlite3_column_double(stm, 8);
237             height = sqlite3_column_double(stm, 9);
238
239             stacks = sqlite3_column_int(stm, 10);
240             slices = sqlite3_column_int(stm, 11);
241
242             r = sqlite3_column_double(stm, 12);
243             g = sqlite3_column_double(stm, 13);
244             b = sqlite3_column_double(stm, 14);
245             a = sqlite3_column_double(stm, 15);

```

```

246
247
248         double translate[3] = { xt, yt, zt };
249         double rotate[3] = { xr, yr, zr };
250         double colors[4] = { r, g, b, a };
251
252         cylinders.push_back(Cylinder(baseRadius, topRadius, height, stacks
253             , slices, translate, rotate, colors));
254
255     }
256
257     Logger log;
258     vector<string> output = { "Loaded cylinders on", currLevel };
259     log.logLine(output);
260
261     // Deconstructs the statement
262     sqlite3_finalize(stm);
263 }
264
265 void Level::loadSwitches(sqlite3 *db)
266 {
267     switches.clear();
268     // Prepared Statement
269     sqlite3_stmt *stm;
270     // SQL command
271     string cmd;
272     // Connection Error Test
273     int err;
274     cmd = "SELECT * FROM switches WHERE LEVEL = \"" + currLevel + "\"";
275
276     err = sqlite3_prepare(db, cmd.c_str(), -1, &stm, 0);
277
278     if (err != SQLITE_OK)
279     {
280         Logger log;
281         vector<string> output = { "FATAL ERROR: Can't load switches while
282             loading", currLevel };
283         log.logLine(output);
284
285         exit(STATEMENT_ERROR);
286     }
287
288     // While we still get rows of output
289     while (sqlite3_step(stm) == SQLITE_ROW)
290     {
291         double xt, yt, zt,
292             xr, yr, zr;
293         string target, s_type, id;
294         int i_type;
295         bool isOn;
296
297         id = reinterpret_cast<const char*>(sqlite3_column_text(stm, 0));
298         target = reinterpret_cast<const char*>(sqlite3_column_text(stm, 2)
299             );
300         xt = sqlite3_column_double(stm, 3);
301         yt = sqlite3_column_double(stm, 4);

```

```

299         zt = sqlite3_column_double(stm, 5);
300
301         xr = sqlite3_column_double(stm, 6);
302         yr = sqlite3_column_double(stm, 7);
303         zr = sqlite3_column_double(stm, 8);
304
305         s_type = reinterpret_cast<const char*>(sqlite3_column_text(stm, 9)
306             );
307
308         isOn = (bool)sqlite3_column_int(stm, 10);
309
310         double translate[3] = { xt, yt, zt };
311         double rotate[3] = { xr, yr, zr };
312
313         if (s_type == "DOOR")
314             i_type = T_DOOR;
315         else if (s_type == "TERMINAL")
316             i_type = T_TERMINAL;
317         else if (s_type == "LEVEL_END")
318             i_type = T_LEVEL_END;
319         else
320         {
321             Logger log;
322             vector<string> output = { "Failed to evaluate string type
323                 entry: ", s_type, "for switch ", id };
324             log.logLine(output);
325             exit(DATA_ENTRY_ERROR);
326         }
327         switches.push_back(Switch(translate, rotate, i_type, id, isOn));
328
329         bool assigned = false;
330
331         if (s_type == "LEVEL_END")
332         {
333             assigned = true;
334
335             Logger log;
336             vector<string> output = { "Switch ", id, " bound to end
337                 level" };
338             log.logLine(output);
339         }
340         else if (s_type == "DOOR")
341         {
342             for (unsigned int i = 0; i < doors.size(); i++)
343             {
344                 if (doors[i].getID() == target)
345                 {
346                     Logger log;
347                     vector<string> output = { "Binding switch
348                         ", id, " to door", target };
349                     log.logLine(output);
350
351                     switches[switches.size() - 1].assign(&

```

```

351         doors[i]));
352         assigned = true;
353     }
354 }
355 }
356
357 else if (s_type == "TERMINAL")
358 {
359     for (unsigned int i = 0; i < terminals.size(); i++)
360     {
361         if (terminals[i].getID() == target)
362         {
363             Logger log;
364             vector<string> output = { "Binding switch
365                                     ", id, " to terminal", target };
366             log.logLine(output);
367             switches[switches.size() - 1].assign(&(
368                                     terminals[i]));
369             assigned = true;
370         }
371     }
372 }
373
374 if (!assigned)
375 {
376     Logger log;
377     vector<string> output = { "Failed to bind switch ", id, "
378                             to a ", s_type };
379     log.logLine(output);
380     exit(BINDING_ERROR);
381 }
382 }
383
384 Logger log;
385 vector<string> output = { "Loaded switches on", currLevel };
386 log.logLine(output);
387
388 // Deconstructs the statement
389 sqlite3_finalize(stm);
390 }
391
392 void Level::loadTerminals(sqlite3 *db)
393 {
394     terminals.clear();
395     // Prepared Statement
396     sqlite3_stmt *stm;
397     // SQL command
398     string cmd;
399     // Connection Error Test
400     int err;
401     cmd = "SELECT * FROM terminals WHERE LEVEL = \"" + currLevel + "\"";
402

```



```

403     err = sqlite3_prepare(db, cmd.c_str(), -1, &stm, 0);
404
405     if (err != SQLITE_OK)
406     {
407         Logger log;
408         vector<string> output = { "FATAL ERROR: Can't load terminals while
                                loading", currLevel };
409         log.logLine(output);
410
411         exit(STATEMENT_ERROR);
412     }
413
414     // While we still get rows of output
415     while (sqlite3_step(stm) == SQLITE_ROW)
416     {
417         double xt, yt, zt,
418             xr, yr, zr;
419         string file, id;
420         id = reinterpret_cast<const char*>(sqlite3_column_text(stm, 0));
421         file = reinterpret_cast<const char*>(sqlite3_column_text(stm, 2));
422         xt = sqlite3_column_double(stm, 3);
423         yt = sqlite3_column_double(stm, 4);
424         zt = sqlite3_column_double(stm, 5);
425
426         xr = sqlite3_column_double(stm, 6);
427         yr = sqlite3_column_double(stm, 7);
428         zr = sqlite3_column_double(stm, 8);
429
430         double translate[3] = { xt, yt, zt };
431         double rotate[3] = { xr, yr, zr };
432
433         Logger log;
434         log.logLine(id);
435
436         terminals.push_back(Terminal(translate, rotate, file, id));
437     }
438
439
440     Logger log;
441     vector<string> output = { "Loaded terminals on", currLevel };
442     log.logLine(output);
443
444     // Deconstructs the statement
445     sqlite3_finalize(stm);
446 }
447
448 void Level::loadTriggers(sqlite3 *db)
449 {
450     triggers.clear();
451     // Prepared Statement
452     sqlite3_stmt *stm;
453     // SQL command
454     string cmd;
455     // Connection Error Test
456     int err;
457     cmd = "SELECT * FROM triggers WHERE LEVEL = \"" + currLevel + "\"";

```

```

458
459     err = sqlite3_prepare(db, cmd.c_str(), -1, &stm, 0);
460
461     if (err != SQLITE_OK)
462     {
463         Logger log;
464         vector<string> output = { "FATAL ERROR: Can't load triggers while
                                loading", currLevel };
465         log.logLine(output);
466
467         exit(STATEMENT_ERROR);
468     }
469
470     // While we still get rows of output
471     while (sqlite3_step(stm) == SQLITE_ROW)
472     {
473         string target, trigger, targetType, triggerType, id;
474         int i_targetType, i_triggerType;
475
476         id = reinterpret_cast<const char*>(sqlite3_column_text(stm, 0));
477         trigger = reinterpret_cast<const char*>(sqlite3_column_text(stm,
                                2));
478         target = reinterpret_cast<const char*>(sqlite3_column_text(stm, 3)
                                );
479         triggerType = reinterpret_cast<const char*>(sqlite3_column_text(
                                stm, 4));
480         targetType = reinterpret_cast<const char*>(sqlite3_column_text(stm
                                , 5));
481
482         if (triggerType == "SWITCH")
483             i_triggerType = T_SWITCH;
484         else if (triggerType == "TERMINAL")
485             i_triggerType = T_TERMINAL;
486         else
487         {
488             Logger log;
489             vector<string> output = { "Failed to evaluate string
                                trigger type entry: ", triggerType, "for trigger ", id
                                };
490             log.logLine(output);
491
492             exit(DATA_ENTRY_ERROR);
493         }
494
495         if (targetType == "SWITCH")
496             i_targetType = T_SWITCH;
497         else if (targetType == "TERMINAL")
498             i_targetType = T_TERMINAL;
499         else
500         {
501             Logger log;
502             vector<string> output = { "Failed to evaluate string
                                trigger type entry: ", targetType, "for trigger ", id
                                };
503             log.logLine(output);
504

```

```

505             exit(DATA_ENTRY_ERROR);
506         }
507
508         triggers.push_back(Trigger(i_triggerType, i_targetType));
509
510         bool assigned = bindTrigger(id, trigger, triggerType) &&
            bindTarget(id, target, targetType);
511
512         if (!assigned)
513         {
514             Logger log;
515             vector<string> output = { "Failed to bind trigger ", id };
516             log.logLine(output);
517
518             exit(BINDING_ERROR);
519         }
520     }
521
522     Logger log;
523     vector<string> output = { "Loaded trigger on", currLevel };
524     log.logLine(output);
525
526     // Deconstructs the statement
527     sqlite3_finalize(stm);
528 }
529
530 bool Level::bindTrigger(string id, string trigger, string triggerType)
531 {
532     if (triggerType == "SWITCH")
533     {
534         for (unsigned int i = 0; i < switches.size(); i++)
535         {
536             if (switches[i].getID() == trigger)
537             {
538                 Logger log;
539                 vector<string> output = { "Binding trigger ", id,
                    " to trigger-switch", trigger };
540                 log.logLine(output);
541
542                 triggers[triggers.size() - 1].bindTrigger(&(
                    switches[i]));
543
544                 return true;
545             }
546         }
547     }
548
549     else if (triggerType == "TERMINAL")
550     {
551         for (unsigned int i = 0; i < terminals.size(); i++)
552         {
553             if (terminals[i].getID() == trigger)
554             {
555                 Logger log;
556                 vector<string> output = { "Binding trigger ", id,
                    " to trigger-terminal", trigger };

```

```

557             log.logLine(output);
558
559             triggers[triggers.size() - 1].bindTrigger(&(
                    terminals[i]));
560
561             return true;
562         }
563     }
564 }
565
566     return false;
567 }
568
569 bool Level::bindTarget(string id, string target, string targetType)
570 {
571     if (targetType == "SWITCH")
572     {
573         for (unsigned int i = 0; i < switches.size(); i++)
574         {
575             if (switches[i].getID() == target)
576             {
577                 Logger log;
578                 vector<string> output = { "Binding trigger ", id,
579                     " to target-switch", target };
580                 log.logLine(output);
581
582                 triggers[triggers.size() - 1].bindTarget(&(
583                     switches[i]));
584                 return true;
585             }
586         }
587     }
588
589     else if (targetType == "TERMINAL")
590     {
591         for (unsigned int i = 0; i < terminals.size(); i++)
592         {
593             if (terminals[i].getID() == target)
594             {
595                 Logger log;
596                 vector<string> output = { "Binding trigger ", id,
597                     " to target-terminal", target };
598                 log.logLine(output);
599
600                 triggers[triggers.size() - 1].bindTarget(&(
601                     terminals[i]));
602                 return true;
603             }
604         }
605     }
606
607     return false;
608 }

```

```

608
609 void Level::loadLevel(std::string levelName)
610 {
611     Logger log;
612     vector<string> output = { "Starting to load", levelName };
613     log.logLine(output);
614
615     if (quadratic == NULL)
616     {
617         quadratic = gluNewQuadric();
618     }
619
620     currLevel = levelName;
621
622     // Connection to SQL database
623     sqlite3 *db;
624     // 1 if error with DB
625     int connectErr = sqlite3_open("Data.db", &db);
626
627     if (connectErr != SQLITE_OK)
628     {
629         Logger log;
630         log.logLine("FATAL ERROR: Can't access database");
631
632         exit(DATABASE_ERROR);
633     }
634
635     loadWalls(db);
636     loadDoors(db);
637     loadCylinders(db);
638     loadTerminals(db);
639
640     // Loading switches must be after doors/terminals to properly bind
641     loadSwitches(db);
642
643     // Loading triggers must be done last to properly bind
644     loadTriggers(db);
645
646     // Closes the database
647     sqlite3_close(db);
648
649     output[0] = "Finished loading";
650     log.logLine(output);
651
652     Cam.resetCam();
653
654     interactivity = false;
655
656     // Get out of wall
657     for (unsigned int i = 0; i < 10; i++)
658     {
659         Cam.moveForward(1);
660     }
661
662     // Go dim for 5 seconds
663     HUD.goDim(5);

```

```

664 }
665
666 void Level::displayLevel()
667 {
668     for (auto i : doors)
669     {
670         i.Display();
671     }
672
673     for (auto i : cylinders)
674     {
675         i.Display();
676     }
677
678     for (auto i : switches)
679     {
680         i.Display();
681     }
682
683     for (auto i : terminals)
684     {
685         i.Display();
686     }
687
688     for (auto i : walls)
689     {
690         i.Display();
691     }
692 }

```

3.1.23 Logger.h

```

1  /*****\
2  * Logger.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the Logger class *
8  * Which writes messages to output.log because it's more *
9  * Reliable than stdout *
10 \*****/
11
12 #ifndef LOGGER_H
13 #define LOGGER_H
14
15 // To help find the user's document folder
16 #include <shlobj.h>
17
18 // std::vector
19 #include <vector>
20 // std::string
21 #include <string>
22
23 class Logger
24 {
25 private:

```

```

26         // Path to the log file
27         char CHAR_PATH[MAX_PATH];
28         std::string LOG_PATH;
29
30     public:
31         Logger();
32         // Erases the log file, called at the beggining of the program
33         void nuke();
34         // Writes to the log, either multiple lines or one line
35         void logLine(std::vector<std::string> input);
36         void logLine(std::string input);
37         // Writes the Camera Coordinates to the log file
38         void logCamCoords();
39
40     };
41
42 #endif

```

3.1.24 Logger.cpp

```

1  /*****\
2  * Logger.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the defintion of the Logger class. *
8  * for more information, see Logger.h *
9  \*****/
10
11 // Class declaration
12 #include "Logger.h"
13 // For Cam coords
14 #include "Globals.h"
15 // File I/O
16 #include <fstream>
17
18 #include <iostream>
19
20 using namespace std;
21
22 Logger::Logger()
23 {
24     HRESULT ret = SHGetFolderPath(NULL, CSIDL_PERSONAL, NULL,
25     SHGFP_TYPE_CURRENT, CHAR_PATH);
26     LOG_PATH = CHAR_PATH;
27     LOG_PATH += "\\The God Core\\output.log";
28 }
29
30 void Logger::nuke()
31 {
32     ofstream outfile(LOG_PATH); // Nukes everything within
33 }
34
35 void Logger::logLine(vector<string> input)
36 {
37     ofstream outfile(LOG_PATH, ios::app);

```

```

37
38     string output;
39
40     for (auto i : input)
41     {
42         output += i;
43         output += " ";
44     }
45     outfile << output << std::endl;
46 }
47
48 void Logger::logLine(string input)
49 {
50     ofstream outfile(LOG_PATH, ios::app);
51
52     outfile << input << std::endl;
53 }
54
55 void Logger::logCamCoords()
56 {
57     ofstream outfile(LOG_PATH, ios::app);
58
59     outfile << "Player Coordinates:\n";
60     outfile << "X: " << -Cam.x << endl;
61     outfile << "Y: " << -Cam.y << endl;
62     outfile << "Z: " << -Cam.z << endl;
63 }

```

3.1.25 MainMenu.h

```

1  /*****\
2  * MainMenu.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the decleration of the MainMenu class *
8  * Which uses the Simple OpenGL Interface Library to load a *
9  * png picture of the main menu, as well as provide button *
10 * Interactivity *
11 \*****/
12
13 #ifndef MAIN_MENU_H
14 #define MAIN_MENU_H
15
16 // For loading pictures
17 #include <SOIL.h>
18 // Inherit 2D functionality
19 #include "TwoD.h"
20
21 // Make OpenGL happy
22 #include <cstdlib>
23 // OpenGL API
24 #include <GL\glut.h>
25
26 class MainMenu : public TwoD
27 {

```



```

28 public:
29     // Loads the picture up in memory
30     MainMenu();
31     // Handles drawing to the screen
32     void display();
33     // Handles and processes mouse clicks
34     void getClick(double x, double y);
35
36 private:
37     // Draws the main picture
38     void drawMainPic();
39     // DEBUG: draws boxes around all buttons
40     void drawClickBoxes();
41     // What the picture is bound to
42     GLint texture;
43 };
44
45 #endif

```

3.1.26 MainMenu.cpp

```

1  /*****\
2  * MainMenu.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the MainMenu class. *
8  * for more information, see MainMenu.h *
9  \*****/
10
11 // Class declaration
12 #include "MainMenu.h"
13 // isInMain
14 #include "Globals.h"
15 // Return codes
16 #include "Return.h"
17 // System log
18 #include "Logger.h"
19
20 #include "SaveManager.h"
21
22 using namespace std;
23
24 MainMenu::MainMenu()
25 {
26     texture = SOIL_load_OGL_texture
27         (
28             "Resources\\Images\\Main.png", // Image to load
29             SOIL_LOAD_AUTO, //
30             ???
31             SOIL_CREATE_NEW_ID,
32             SOIL_FLAG_MIPMAPS | SOIL_FLAG_NTSC_SAFE_RGB |
33             SOIL_FLAG_COMPRESS_TO_DXT // !!!!!!!
34         );
35
36     if (texture == 0)

```

```

35     {
36         Logger log;
37         vector<string> output = {"FATAL ERROR: SOIL cannot load image",
                                SOIL_last_result()};
38         log.logLine(output);
39         exit(SOIL_ERROR);
40     }
41 }
42
43 void MainMenu::drawMainPic()
44 {
45     glEnable(GL_TEXTURE_2D);
46
47     glBindTexture(GL_TEXTURE_2D, texture); // Prepares the texture for usage
48
49     glColor3d(1, 1, 1);
50     glBegin(GL_QUADS);
51     glTexCoord2d(0, 0);      glVertex2d(SCREENLEFT, SCREENTOP);
52     glTexCoord2d(0, 1);      glVertex2d(SCREENLEFT, SCREENBOTTOM);
53     glTexCoord2d(1, 1);      glVertex2d(SCREENRIGHT, SCREENBOTTOM);
54     glTexCoord2d(1, 0);      glVertex2d(SCREENRIGHT, SCREENTOP);
55
56     glEnd();
57
58     glDisable(GL_TEXTURE_2D);
59
60 }
61
62 void MainMenu::drawClickBoxes()
63 {
64     glColor3d(1, 0, 0);
65
66     // Start a new game
67     glBegin(GL_LINE_LOOP);
68     glVertex2d(SCREENRIGHT / 20.0, SCREENBOTTOM / 2.2);
69     glVertex2d(SCREENRIGHT / 20.0, SCREENBOTTOM / 1.9);
70     glVertex2d(SCREENRIGHT / 3.0, SCREENBOTTOM / 1.9);
71     glVertex2d(SCREENRIGHT / 3.0, SCREENBOTTOM / 2.2);
72     glEnd();
73
74     // Load game
75     glBegin(GL_LINE_LOOP);
76     glVertex2d(SCREENRIGHT / 10.0, SCREENBOTTOM / 1.57);
77     glVertex2d(SCREENRIGHT / 10.0, SCREENBOTTOM / 1.75);
78     glVertex2d(SCREENRIGHT / 3.5, SCREENBOTTOM / 1.75);
79     glVertex2d(SCREENRIGHT / 3.5, SCREENBOTTOM / 1.57);
80     glEnd();
81
82     // Options
83     glBegin(GL_LINE_LOOP);
84     glVertex2d(SCREENRIGHT / 8.5, SCREENBOTTOM / 1.35);
85     glVertex2d(SCREENRIGHT / 8.5, SCREENBOTTOM / 1.45);
86     glVertex2d(SCREENRIGHT / 3.9, SCREENBOTTOM / 1.45);
87     glVertex2d(SCREENRIGHT / 3.9, SCREENBOTTOM / 1.35);
88     glEnd();
89

```

```

90         // Exit
91
92         glBegin(GL_LINE_LOOP);
93         glVertex2d(SCREENRIGHT / 6.5, SCREENBOTTOM / 1.16);
94         glVertex2d(SCREENRIGHT / 6.5, SCREENBOTTOM / 1.25);
95         glVertex2d(SCREENRIGHT / 4.5, SCREENBOTTOM / 1.25);
96         glVertex2d(SCREENRIGHT / 4.5, SCREENBOTTOM / 1.16);
97         glEnd();
98     }
99
100 void MainMenu::getClick(double x, double y)
101 {
102     // Start new game
103     if (x >= SCREENRIGHT / 20.0 && x <= SCREENRIGHT / 3.0)
104     {
105         if (y >= SCREENBOTTOM / 2.2 && y <= SCREENBOTTOM / 1.9)
106         {
107             isInMain = false;
108             songNum++;
109             changeSong = true;
110         }
111     }
112
113     // Load Game
114     if (x >= SCREENRIGHT / 10.0 && x <= SCREENRIGHT / 3.5)
115     {
116         if (y >= SCREENBOTTOM / 1.75 && y <= SCREENBOTTOM / 1.57)
117         {
118             SaveManager Jesus; // Jesus Saves
119             if (!Jesus.loadGame()); // null
120             else isInMain = false;
121         }
122     }
123
124
125     // Options
126     if (x >= SCREENRIGHT / 8.5 && x <= SCREENRIGHT / 3.9)
127     {
128         if (y >= SCREENBOTTOM / 1.45 && y <= SCREENBOTTOM / 1.35)
129         {
130             // Jokes on me I never did get any options up
131         }
132     }
133
134     // Exit
135     if (x >= SCREENRIGHT / 6.5 && x <= SCREENRIGHT / 4.5)
136     {
137         if (y >= SCREENBOTTOM / 1.25 && y <= SCREENBOTTOM / 1.16)
138         {
139             exit(EXIT_OK);
140         }
141     }
142 }
143
144 void MainMenu::display()
145 {

```

```

146         prepare2D();
147
148         drawMainPic();
149
150         // Disable once finished
151         //drawClickBoxes();
152
153         glEnd();
154
155         prepare3D();
156     }

```

3.1.27 MusicManager.h

```

1  /*****\
2  * MusicManager.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the MusicManager *
8  * Class, which uses the FMOD API to load .mp3 files into *
9  * Memory, play them when called, and release the memory *
10 * When the song is no longer needed. *
11 \*****/
12
13 #ifndef MUSICMANAGER_H
14 #define MUSICMANAGER_H
15
16 // FMOD API
17 #include <fmod.hpp>
18
19 // Creates new type for ease of use
20 typedef FMOD::Sound* SoundClass;
21
22 class MusicManager
23 {
24 private:
25     // Pointer to dynamic system memory to load music
26     FMOD::System *m_pSystem;
27
28     // The path to the music folder
29     static const char* MUSIC_PATH;
30
31 public:
32     // Loads the song in memory
33     void makeSound(SoundClass *psound, const char *song);
34     // Plays the song (Always loops)
35     void playSound(SoundClass pSound, bool bLoop = true);
36     // Releases the song
37     void releaseSound(SoundClass psound);
38     // Initializes FMOD
39     MusicManager();
40 };
41
42 #endif

```

3.1.28 MusicManager.cpp

```
1  /*****\
2  * MusicManager.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the MusicManager *
8  * Class. For more information, see MusicManager.h *
9  \*****/
10
11 // Class definition
12 #include "MusicManager.h"
13
14 // Because concatenating char*'s are really hard
15 #include <string>
16
17 // Return codes
18 #include "Return.h"
19
20 // System log
21 #include "Logger.h"
22
23 using namespace std;
24
25 // Initialize the constant member of the class
26 const char* MusicManager::MUSIC_PATH = "Resources\\Music\\";
27
28 MusicManager::MusicManager()
29 {
30     Logger log;
31     if (FMOD::System_Create(&m_pSystem) != FMOD_OK)
32     {
33         log.logLine("FATAL ERROR: FMOD unable to create system");
34         exit(FMOD_ERROR);
35     }
36
37     int driverCount = 0;
38     m_pSystem->getNumDrivers(&driverCount);
39
40     // If you have no driver, you have bigger problems to worry about
41     if (driverCount == 0)
42     {
43         // Report Error
44         log.logLine("ERROR: FMOD unable to detect drivers");
45         exit(FMOD_ERROR);
46     }
47
48     log.logLine("FMOD succesfully initialized");
49     // Initialize our Instance with 36 Channels
50     m_pSystem->init(36, FMOD_INIT_NORMAL, NULL);
51 }
52
53 void MusicManager::makeSound(SoundClass *psound, const char *song)
54 {
```

```

55         // MUSIC_PATH is placed in a nice string. Good string. Strings are friends
56         string fullPath = MUSIC_PATH;
57         // Now there is a full path to the song
58         fullPath += song;
59
60         m_pSystem->createSound(fullPath.c_str(), FMOD_DEFAULT, 0, psound);
61     }
62
63     void MusicManager::playSound(SoundClass pSound, bool bLoop)
64     {
65         if (!bLoop)
66             pSound->setMode(FMOD_LOOP_OFF);
67         else
68         {
69             pSound->setMode(FMOD_LOOP_NORMAL);
70             pSound->setLoopCount(-1);
71         }
72
73         m_pSystem->playSound(pSound, NULL, false, 0);
74     }
75
76     void MusicManager::releaseSound(SoundClass pSound)
77     {
78         pSound->release();
79     }

```

3.1.29 Plane.h

```

1  /*****\
2  * Plane.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * * *
7  * This file contains the declaration of the Plane class *
8  * Which is used to hold the details of a 2D Plane and *
9  * draw it to the screen *
10 \*****/
11
12 #ifndef Plane_H
13 #define Plane_H
14
15 class Plane
16 {
17 private:
18     // Arrays containing the color and vertices of the Plane
19     double color[4];
20     // What axis is it aligned on (x y z)
21     char axis;
22     // The vertices of the corners
23     double vertices[12];
24 public:
25
26     // Paramaterized constructor, as there cannot be a Plane without vertices
27     // Can take an axis or can ignore axis
28     Plane(const double(&new_vertices)[12], const double(&new_color)[4], char
        _axis);

```

```

29         Plane(const double(&new_vertices)[12], const double(&new_color)[4]);
30
31         // Part of the plane equation, calculated in constructor
32         double a, b, c, d;
33
34         // Determines if the player is in the bounds of the Plane (based on axis)
35         bool isInBounds();
36
37         // Returns the plane norm (Perpendicular line)
38         double getNorm();
39
40         // Mutate's the rectangles coordinates for the end of the game
41         void mutate();
42
43         // Print a Plane in 3D
44         void Display();
45         // Print a Plane in 2D
46         void Display2D();
47     };
48
49 #endif

```

3.1.30 Plane.cpp

```

1  /*****\
2  * Plane.cpp                                     *
3  * This file was created by Jeremy Greenburg      *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  *                                                 *
7  * This file contains the definition of the Plane class *
8  * For more information, see Plane.h               *
9  \*****/
10
11 #include "Plane.h"
12
13 // For std::copy
14 #include <iterator>
15 #include <utility>
16
17 // max and min
18 #include <algorithm>
19
20 // OpenGL API
21 #include <GL\glut.h>
22
23 // For Cam coords
24 #include "Globals.h"
25
26 using namespace std;
27
28 Plane::Plane(const double (&new_vertices)[12], const double (&new_color)[4], char
    _axis)
29 {
30     // Copies the color
31     copy(begin(new_color), end(new_color), color);
32

```

```

33 // Copies the vertices
34 copy(begin(new_vertices), end(new_vertices), vertices);
35
36
37 // Somedays I wonder what I'm even doing \\
38 // When I forget what all this means: http://keisan.casio.com/exec/system
    /1223596129 \\
39
40 // Calculate vector equation  $ax + by + cz + d = 0$ 
41 // Get two vectors from three of the corners
42 double AB[] = { vertices[3] - vertices[0], vertices[4] - vertices[1],
    vertices[5] - vertices[2] };
43 double AC[] = { vertices[6] - vertices[0], vertices[7] - vertices[1],
    vertices[8] - vertices[2] };
44 // Cross Product of AB and AC
45 a = (AB[1] * AC[2]) - (AB[2] * AC[1]);
46 b = (AB[2] * AC[0]) - (AB[0] * AC[2]);
47 c = (AB[0] * AC[1]) - (AB[1] * AC[0]);
48 d = (a * vertices[0] + b * vertices[1] + c * vertices[2]);
49
50 axis = _axis;
51 }
52
53 Plane::Plane(const double(&new_vertices)[12], const double(&new_color)[4])
54 {
55     // Copies the color
56     copy(begin(new_color), end(new_color), color);
57
58     // Copies the vertices
59     copy(begin(new_vertices), end(new_vertices), vertices);
60
61
62     // Somedays I wonder what I'm even doing \\
63     // When I forget what all this means: http://keisan.casio.com/exec
        /system/1223596129 \\
64
65 // Calculate vector equation  $ax + by + cz + d = 0$ 
66 // Get two vectors from three of the corners
67 double AB[] = { vertices[3] - vertices[0], vertices[4] - vertices[1],
    vertices[5] - vertices[2] };
68 double AC[] = { vertices[6] - vertices[0], vertices[7] - vertices[1],
    vertices[8] - vertices[2] };
69 // Cross Product of AB and AC
70 a = (AB[1] * AC[2]) - (AB[2] * AC[1]);
71 b = (AB[2] * AC[0]) - (AB[0] * AC[2]);
72 c = (AB[0] * AC[1]) - (AB[1] * AC[0]);
73 d = (a * vertices[0] + b * vertices[1] + c * vertices[2]);
74
75 axis = 0;
76 }
77
78 void Plane::Display()
79 {
80     // Set's OpenGL's color to the color of the Plane
81     glColor4f(color[0], color[1], color[2], color[3]);
82

```



```

83         glBegin(GL_QUADS);
84         glVertex3d(vertices[0], vertices[1], vertices[2]);
85         glVertex3d(vertices[3], vertices[4], vertices[5]);
86         glVertex3d(vertices[6], vertices[7], vertices[8]);
87         glVertex3d(vertices[9], vertices[10], vertices[11]);
88         glEnd();
89     }
90
91     void Plane::Display2D()
92     {
93         glColor4f(color[0], color[1], color[2], color[3]);
94
95         glBegin(GL_QUADS);
96         glVertex2d(vertices[0], vertices[1]);
97         glVertex2d(vertices[3], vertices[4]);
98         glVertex2d(vertices[6], vertices[7]);
99         glVertex2d(vertices[9], vertices[10]);
100        glEnd();
101    }
102
103    bool Plane::isInBounds()
104    {
105        if (axis == 'x')
106        {
107            vector<double> X = { vertices[0], vertices[3], vertices[6],
108                                vertices[9] };
109            double maxX = *max_element(X.begin(), X.end());
110            double minX = *min_element(X.begin(), X.end());
111
112            return (-Cam.x <= maxX && -Cam.x >= minX);
113        }
114
115        else if (axis == 'y')
116        {
117            vector<double> Y = { vertices[1], vertices[4], vertices[7],
118                                vertices[10] };
119            double maxY = *max_element(Y.begin(), Y.end());
120            double minY = *min_element(Y.begin(), Y.end());
121
122            return (-Cam.y <= maxY && -Cam.y >= minY);
123        }
124
125        else if (axis == 'z')
126        {
127            vector<double> Z = { vertices[2], vertices[5], vertices[8],
128                                vertices[11] };
129            double maxZ = *max_element(Z.begin(), Z.end());
130            double minZ = *min_element(Z.begin(), Z.end());
131
132            return (-Cam.z <= maxZ && -Cam.z >= minZ);
133        }
134        else return false;
135    }
136
137    double Plane::getNorm()

```

```

136 {
137     return sqrt(a * a + b * b + c * c);
138 }
139
140 void Plane::mutate()
141 {
142     // We're gonna mess stuff up, disable the axis so nothing funky happens
143     // with collision
144     axis = ' ';
145
146     for (unsigned int i = 0; i < 12; i++)
147     {
148         // 0 <= mutator <= 200
149         double mutator = rand() % 201;
150         // -100 <= mutator <= 100
151         mutator -= 100;
152         // -.01 <= mutator <= .01
153         mutator /= 10000;
154
155         vertices[i] += mutator;
156     }
157 }

```

3.1.31 Return.h

```

1  /*****\
2  * Return.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * * *
7  * This file contains various return codes for when things *
8  * Go horribly wrong (and they do) *
9  * (just hopefully not during my senior defense) *
10 \*****/
11
12 #ifndef RETURN_H
13 #define RETURN_H
14
15 #define EXIT_OK 0 // Indicates an intended exit
16 #define EXIT_EARLY 1 // If we exit OpenGL main loop early
17 #define FMOD_ERROR 2 // Fmod can't load sound
18 #define DATABASE_ERROR 3 // sqlite can't load database
19 #define STATEMENT_ERROR 4 // sqlite statement fails to execute
20 #define SOIL_ERROR 5 // SOIL fails to load image
21 #define DATA_ENTRY_ERROR 6 // Indicates an internal error in a database entry
22 #define BINDING_ERROR 7 // Error binding a trigger
23 #define FILE_NOT_FOUND 8 // A file is not found
24
25 #endif

```

3.1.32 Resource.h

```

1  /*****\
2  * Return.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *

```

```

5  * Tennessee at Martin's University Scholars Organization      *
6  *                                                              *
7  * This file contains various return codes for when things     *
8  * Go horribly wrong (and they do)                             *
9  * (just hopefully not during my senior defense)               *
10 \*****/
11
12 #ifndef RETURN_H
13 #define RETURN_H
14
15 #define EXIT_OK 0 // Indicates an intended exit
16 #define EXIT_EARLY 1 // If we exit OpenGL main loop early
17 #define FMOD_ERROR 2 // Fmod can't load sound
18 #define DATABASE_ERROR 3 // sqlite can't load database
19 #define STATEMENT_ERROR 4 // sqlite statement fails to execute
20 #define SOIL_ERROR 5 // SOIL fails to load image
21 #define DATA_ENTRY_ERROR 6 // Indicates an internal error in a database entry
22 #define BINDING_ERROR 7 // Error binding a trigger
23 #define FILE_NOT_FOUND 8 // A file is not found
24
25 #endif

```

3.1.33 SaveManager.h

```

1  /*****\
2  * SaveManager.h                                              *
3  * This file was created by Jeremy Greenburg                  *
4  * As part of The God Core game for the University of        *
5  * Tennessee at Martin's University Scholars Organization    *
6  *                                                              *
7  * This file contains the declaration of the SaveManager     *
8  * Class, which saves data by encrypting an array of strings *
9  * And writing them to core.sav, or by reading in an array of *
10 * Strings from core.sav and decrypting them                  *
11 \*****/
12
13 #ifndef SAVEMANAGER_H
14 #define SAVEMANAGER_H
15
16 // Windows API
17 #include <shlobj.h>
18
19 // Because concatenating char*'s is really hard
20 #include <string>
21
22 class SaveManager
23 {
24 private:
25     // The path to core.sav
26     char CHAR_PATH[MAX_PATH];
27     std::string SAVE_PATH;
28
29     // Takes an unencrypted string and returns an encrypted string
30     std::string encryptData(std::string data);
31     // Takes an encrypted string and returns a decrypted string
32     std::string decryptData(std::string data);
33 public:

```

```

34     SaveManager();
35     // Writes the array of encrypted strings to core.sav
36     void saveLevel();
37     // Sets global variables to load game
38     bool loadGame();
39     // Returns the decrypted string in core.sav
40     std::string readSave();
41     // Returns true if core.save exists
42     bool checkSave();
43 };
44
45 #endif

```

3.1.34 SaveManager.cpp

```

1  /*****\
2  * SaveManager.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the SaveManager class*
8  * For more information, see SaveManager.h *
9  \*****/
10
11 // Class definition
12 #include "SaveManager.h"
13
14 // File I/O
15 #include <fstream>
16
17 #include "Globals.h"
18
19 #include "Logger.h"
20
21 using namespace std;
22
23 SaveManager::SaveManager()
24 {
25     HRESULT ret = SHGetFolderPath(NULL, CSIDL_PERSONAL, NULL,
26     SHGFP_TYPE_CURRENT, CHAR_PATH);
27     SAVE_PATH = CHAR_PATH;
28     SAVE_PATH += "\\The God Core\\core.sav";
29 }
30
31 string SaveManager::encryptData(string data)
32 {
33     string ret_str;
34     for (unsigned int i = 0; i < data.length()*3; i+=3)
35     {
36         ret_str += data[i/3] + 48;
37         ret_str += data[i/3] - 48;
38         ret_str += data[i/3] + 53;
39     }
40     return ret_str;
41 }

```

```

42 string SaveManager::decryptData(string data)
43 {
44     string ret_str;
45     for (unsigned int i = 0; i < data.length(); i+=3)
46     {
47         ret_str += data[i] - 48;
48     }
49
50     return ret_str;
51 }
52
53 string SaveManager::readSave()
54 {
55     Logger log;
56
57     ifstream save(SAVE_PATH);
58     log.logLine("Checking Save integrity.");
59
60     string enc_data; // Encrypted Data
61     string dcr_data; // Decrypted Data
62     save >> enc_data; // Read encrypted data from file
63     dcr_data = decryptData(enc_data); // Decrypt data
64
65     vector<string> output{ "Decrypted Data: ", dcr_data };
66     log.logLine(output);
67
68     save.close();
69
70     return dcr_data;
71 }
72
73 void SaveManager::saveLevel()
74 {
75     ofstream save(SAVE_PATH);
76
77     string input = curr_level + " " + to_string(songNum);
78
79     string encr_str = encryptData(input);
80
81     save << encr_str;
82
83     save.close();
84 }
85
86 bool SaveManager::loadGame()
87 {
88     // might change to vector<string> later
89     string data = readSave();
90     size_t pos = data.find(' ');
91
92     if (pos == string::npos) return false;
93     string savedLevel = data.substr(0, pos);
94     int savedSong = stoi(data.substr(pos + 1));
95
96     int temp_levelNum = getLevelNum(savedLevel);
97

```

```

98         if (temp_levelNum == -1) return false;
99
100        levelNum = temp_levelNum;
101        curr_level = getLevelString(levelNum);
102        songNum = savedSong;
103
104        loading = true;
105        changeSong = true;
106
107        return true;
108    }
109
110    bool SaveManager::checkSave()
111    {
112        ifstream save(SAVE_PATH);
113
114        if (save)
115        {
116            return true;
117        }
118
119        else
120        {
121            return false;
122        }
123    }

```

3.1.35 Switch.h

```

1  /*****\
2  * Switch.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the Switch class *
8  * Which is bound to a Door via pointer and can open and *
9  * Close the door at will *
10 \*****/
11
12 #ifndef SWITCH_H
13 #define SWITCH_H
14
15 // Door class
16 #include "Door.h"
17 #include "PoweredObject.h"
18 // Terminal Class
19 #include "Terminal.h"
20
21 // Types
22 #include "GCTypes.h"
23
24 class Switch : public PoweredObject
25 {
26 private:
27     void* target; // The door that this switch activates
28     // Translation and rotation coordinates

```

```

29         double translate[3], rotate[3];
30
31         // One of the predefined types
32         GType targetType;
33
34         // Unique ID
35         std::string id;
36
37     public:
38         // Initializes the translation and rotation matrices
39         Switch(const double(&_translate)[3], const double(&_rotate)[3], GType
            _type, std::string _id, bool _isOn);
40         // Binds the target pointer to an object
41         void assign(void* _target);
42         // Opens/Closes the door
43         void toggleTarget();
44         // Actually draws the switch
45         void Display();
46
47         // Get's the switch's ID
48         std::string getID();
49
50         // Gets the translation coordinates
51         double getX();
52         double getY();
53         double getZ();
54     };
55
56 #endif

```

3.1.36 Switch.cpp

```

1  /*****\
2  * Switch.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the Switch class *
8  * For more information, see Switch.h *
9  \*****/
10
11 // Class decleration
12 #include "Switch.h"
13
14 // Allows copying arrays
15 #include <iterator>
16 #include <utility>
17 #include <algorithm>
18
19 #include "Globals.h"
20
21 // OpenGL API
22 #include <GL\glut.h>
23
24 using namespace std;
25

```

```

26 Switch::Switch(const double(&_translate)[3], const double(&_rotate)[3], GCtype
    _type, string _id, bool _isOn)
27 {
28     // Copies the color
29     copy(begin(_translate), end(_translate), translate);
30
31     // Copies the vertices
32     copy(begin(_rotate), end(_rotate), rotate);
33
34     targetType = _type;
35
36     target = NULL;
37
38     id = _id;
39
40     if (_isOn) activate();
41     else deactivate();
42
43 }
44
45 void Switch::assign(void* _target)
46 {
47     target = _target;
48 }
49
50 void Switch::toggleTarget()
51 {
52     switch (targetType)
53     {
54         case T_DOOR:
55         {
56             Door* t = (Door*)target;
57             t->isOpen = !t->isOpen;
58             break;
59         }
60         case T_TERMINAL:
61         {
62             Terminal* t = (Terminal*)target;
63             t->toggle();
64             break;
65         }
66         case T_LEVEL_END:
67         {
68             levelNum++;
69             curr_level = getLevelString(levelNum);
70             loading = true;
71
72             // TEMP
73             songNum++;
74             changeSong = true;
75         }
76     }
77 }
78
79 void Switch::Display()
80 {

```



```

81         glPushMatrix();
82         glTranslated(translate[0], translate[1], translate[2]);
83         glRotated(rotate[0], 1, 0, 0);
84         glRotated(rotate[1], 0, 1, 0);
85         glRotated(rotate[2], 0, 0, 1);
86
87         glColor3d(0.9, 0.9, 0.9);
88         glutSolidCube(.1);
89
90         switch (targetType)
91         {
92             case T_DOOR:
93                 glColor3d(0, 1, 0);
94                 break;
95             case T_TERMINAL:
96                 glColor3d(1, 0, 0);
97                 break;
98             default:
99                 glColor3d(0, 0, 1);
100         }
101
102         // If powered off, recolor to black
103         if (!checkIfOn()) glColor3d(0, 0, 0);
104
105         glScaled(.5, .5, 1.5);
106         glutSolidCube(.1);
107
108         glPopMatrix();
109     }
110
111     string Switch::getID()
112     {
113         return id;
114     }
115
116     double Switch::getX()
117     {
118         return translate[0];
119     }
120
121     double Switch::getY()
122     {
123         return translate[1];
124     }
125
126     double Switch::getZ()
127     {
128         return translate[2];
129     }

```

3.1.37 Terminal.h

```

1  /*****\
2  * Terminal.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *

```

```

6  *
7  * This file contains the declaration of the Terminal class *
8  * Which draws and manages ingame computer terminals      *
9  * And has nothing to do with terminal illness I swear    *
10 \*****/
11
12 #ifndef TERMINAL_H
13 #define TERMINAL_H
14
15 #include "TwoD.h" // To inherit 2D class
16 #include "PoweredObject.h"
17
18 #include <cstdlib>
19
20 // For loading pictures
21 #include <SOIL.h>
22
23 #include "TextEngine.h" // To display text to screen
24
25 #include <string>
26
27 #include <GL\glut.h>
28
29 class Terminal : public TwoD, public PoweredObject // Inherit 2D functionality and
    power functionality
30 {
31 private:
32     // text = what the user is typing, input = completed input
33     std::string currentInput, currentText, error, file;
34     std::vector<std::string> history, prompts, content;
35     std::string id;
36
37     // Where to print each item
38     const double INPUT_LINE = SCREENBOTTOM / 7.0;
39     const double ERROR_LINE = INPUT_LINE - 30;
40     const double PROMPT_START = INPUT_LINE + 30;
41     const double CONTENT_START = PROMPT_START + 150;
42
43     // The banner texture
44     GLint bTexture;
45
46     // The user inputed number
47     int num;
48
49     // Print our text
50     TextEngine text;
51
52     // Translation and rotation matrices
53     double translate[3], rotate[3];
54
55     // Draws the actual terminal
56     void draw();
57
58     // Draws a standing terminal
59     void drawStanding();
60

```

```

61         // Draws a wall mounter terminal
62         void drawWallMounted();
63
64         // Processes the user input
65         void processInput();
66
67         // Parse the terminal file
68         void parseFile();
69
70         // The path to the Terminal Files
71         static const char* TERM_PATH;
72
73     public:
74         // Draws the 3D object in the world
75         void Display();
76         // Draws the 2D Terminal screen
77         void DisplayScreen();
78         // Shows the currently typed string
79         void getText(std::string text);
80         // Signifies a completed string to process
81         void getInput(std::string text);
82         // Returns an item in the terminal's log
83         std::string getHist(int count);
84         // Returns the number of items in the terminal's log
85         int getHistNum();
86
87         // Gets the translation coordinates
88         double getX();
89         double getY();
90         double getZ();
91
92         // Get the terminal's ID
93         std::string getID();
94
95         // To construct and initialize the terminal
96         Terminal(const double(&_translate)[3], const double(&_rotate)[3], std::
            string _file, std::string _id);
97
98     };
99
100 #endif

```

3.1.38 Terminal.cpp

```

1  /*****\
2  * Terminal.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the Terminal class *
8  * For more information, see Terminal.h *
9  \*****/
10
11 //
12 // Class declaration
13 #include "Terminal.h"

```

```

14
15 // Planes
16 #include "Plane.h"
17
18 // For system logging
19 #include "Logger.h"
20
21 // Return codes
22 #include "Return.h"
23
24 // Global variables
25 #include "Globals.h"
26
27 // Logger
28 #include "Logger.h"
29
30 // File I/O
31 #include <fstream>
32
33 using namespace std;
34
35 const char* Terminal::TERM_PATH = "Resources\\Text\\";
36
37 void Terminal::getText(std::string text)
38 {
39     currentText = text;
40 }
41
42 void Terminal::getInput(std::string text)
43 {
44     currentInput = text;
45 }
46
47 string Terminal::getHist(int count)
48 {
49     int size = history.size();
50     if (history.empty())
51     {
52         return "";
53     }
54
55     // If, somehow, a fool manages to get a variable that is out of bounds
56
57     else if (count >= size)
58     {
59         return history.back();
60     }
61
62     else if (count < 0)
63     {
64         return history.front();
65     }
66
67     else
68     {
69         return history[size - count - 1];

```

```

70     }
71 }
72
73 int Terminal::getHistNum()
74 {
75     return history.size();
76 }
77
78 void Terminal::draw()
79 {
80     // Completely black background
81     double colors[4] = { 0, 0, 0, 1 };
82     double vertices[12] =
83     {
84         SCREENLEFT, SCREENTOP, -1,
85         SCREENLEFT, SCREENBOTTOM, -1,
86         SCREENRIGHT, SCREENBOTTOM, -1,
87         SCREENRIGHT, SCREENTOP, -1
88     };
89
90     Plane background{ vertices, colors};
91     background.Display2D();
92
93
94     // Gotta do the banner manually
95     glEnable(GL_TEXTURE_2D);
96
97     glBindTexture(GL_TEXTURE_2D, bTexture); // Prepares the texture for usage
98
99     glColor3d(1, 1, 1);
100    glBegin(GL_QUADS);
101    glTexCoord2d(0, 0);    glVertex2d(SCREENLEFT, SCREENTOP);
102    glTexCoord2d(0, 1);    glVertex2d(SCREENLEFT, SCREENBOTTOM / 9.0);
103    glTexCoord2d(1, 1);    glVertex2d(SCREENRIGHT, SCREENBOTTOM / 9.0);
104    glTexCoord2d(1, 0);    glVertex2d(SCREENRIGHT, SCREENTOP);
105
106    glEnd();
107
108    glDisable(GL_TEXTURE_2D);
109 }
110
111 void Terminal::DisplayScreen()
112 {
113     prepare2D();
114
115     draw();
116
117     // If we need to proces a command
118     if (currentInput != "")
119     {
120         processInput();
121
122         history.push_back(currentInput);
123
124         currentInput.clear();
125     }

```

```

126
127     else
128     {
129         // Print all prompts
130         for (unsigned int i = 0; i < prompts.size(); i++)
131         {
132             text.printString(SCREENLEFT, PROMPT_START + 20 * i, 0, 1,
133                             0, prompts[i]);
134
135             // Print an error
136             text.printString(SCREENLEFT, ERROR_LINE, 1, 0, 0, error);
137             // Echo user text
138             text.printString(SCREENLEFT, INPUT_LINE, 0, 1, 0, "> " +
139                             currentText);
140
141             // If needed, print content
142             if (num != -1 && num < (signed int)content.size())
143             {
144                 text.openFile(SCREENLEFT, CONTENT_START, 0, 1, 0, file,
145                             content[num]);
146             }
147         }
148     }
149     prepare3D();
150 void Terminal::processInput()
151 {
152     error = "";
153     if (currentInput == "exit" || currentInput == "Exit")
154     {
155         isInTerminal = false;
156         history.clear();
157     }
158
159     else if (currentInput == "clear" || currentInput == "Clear")
160     {
161         num = -1;
162     }
163
164     else if (currentInput == "help" || currentInput == "Help")
165     {
166         num = 0;
167     }
168
169     else
170     {
171         string first, last;
172         size_t pos = currentInput.find(" ");
173
174         first = currentInput.substr(0, pos); // First half of string
175         last = currentInput.substr(pos + 1); // Second half of string
176
177         if (first == "read" || first == "Read")
178         {

```

```

179         num = atoi(last.c_str());
180         if (num <= 0 || num >= (signed int)prompts.size())
181         {
182             error = "ERROR: Invalid file number";
183             num = -1;
184         }
185     }
186
187     else
188     {
189         error = "ERROR: Invalid Command: " + currentInput;
190         num = -1;
191     }
192 }
193 }
194
195 void Terminal::Display()
196 {
197     // Add two styles - Standing and wall mounted
198     glPushMatrix();
199
200     // Initial Positioning and rotation
201     glTranslated(translate[0], translate[1], translate[2]);
202     glRotated(rotate[0], 1, 0, 0);
203     glRotated(rotate[1], 0, 1, 0);
204     glRotated(rotate[2], 0, 0, 1);
205
206     //drawWallMounted();
207     drawStanding();
208
209     glPopMatrix();
210 }
211
212 void Terminal::drawStanding()
213 {
214     // Steel grey
215     glColor3d(.1, .1, .1);
216
217     // Draw Floor mount
218     glPushMatrix();
219     glTranslated(0, -1, 0);
220     glScaled(.5, .1, 1);
221     glutSolidCube(.5);
222     glPopMatrix();
223
224     // Draw leg
225     glPushMatrix();
226     glTranslated(0, -.6, 0);
227     glScaled(.1, .75, .1);
228     glutSolidCube(1);
229     glPopMatrix();
230
231     // Draw Monitor
232     glPushMatrix();
233     glScaled(.1, .5, .7);
234     glutSolidCube(1);

```

```

235
236     // Draw Screen
237     glPushMatrix();
238     // Change Screen based on power
239     if (checkIfOn())
240         glColor3d(0, 1, 1);
241     else
242         glColor3d(0, 0, 0);
243
244     glTranslated(-.3, 0, 0);
245     glutSolidCube(.7);
246
247     glPopMatrix();
248
249     glPopMatrix();
250 }
251
252 void Terminal::drawWallMounted()
253 {
254     glColor3d(0, 1, 1);
255     glutSolidSphere(1, 50, 50);
256 }
257
258 double Terminal::getX()
259 {
260     return translate[0];
261 }
262
263 double Terminal::getY()
264 {
265     return translate[1];
266 }
267
268 double Terminal::getZ()
269 {
270     return translate[2];
271 }
272
273 void Terminal::parseFile()
274 {
275     ifstream infile{ TERM_PATH + file};
276     string buff;
277
278     if (!infile)
279     {
280         Logger log;
281         vector<string> output = { "FATAL ERROR: File ", file, " NOT FOUND"
282             };
283         log.logLine(output);
284         exit(FILE_NOT_FOUND);
285     }
286
287     content.push_back("HELP"); // Help text is always the 0th tag in the
288                                // terminals
289
290     getline(infile, buff);

```



```

289     prompts.push_back(buff); // Push back the file tag
290     getline(infile, buff);
291
292     while (buff != "<TAGS>")
293     {
294         size_t pos = buff.find("--");
295         if (pos != string::npos)
296         {
297             prompts.push_back(buff.substr(0, pos));
298             content.push_back(buff.substr(pos + 3));
299         }
300         getline(infile, buff);
301     }
302
303 }
304
305 string Terminal::getID()
306 {
307     return id;
308 }
309
310 Terminal::Terminal(const double(&_translate)[3], const double(&_rotate)[3], string
    _file, string _id)
311 {
312     // Copies the color
313     copy(begin(_translate), end(_translate), translate);
314
315     // Copies the vertices
316     copy(begin(_rotate), end(_rotate), rotate);
317
318     bTexture = SOIL_load_OGL_texture
319         (
320             "Resources\\Images\\banner.png",    // Image to load
321             SOIL_LOAD_AUTO,                      // ???
322             SOIL_CREATE_NEW_ID,
323             SOIL_FLAG_MIPMAPS | SOIL_FLAG_COMPRESS_TO_DXT // !!!!!!!
324         );
325
326     if (bTexture == 0)
327     {
328         Logger log;
329         vector<string> output = { "FATAL ERROR: SOIL cannot load terminal
            banner", SOIL_last_result() };
330         log.logLine(output);
331         exit(SOIL_ERROR);
332     }
333
334     file = _file;
335
336     id = _id;
337
338     num = 0;
339
340     parseFile();
341 }

```

3.1.39 TextEngine.h

```
1  /*****\
2  * TextEngine.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the TextEngine class*
8  * Which uses glutBitmapCharacter to print strings into the *
9  * OpenGL window. *
10 \*****/
11
12 #ifndef TEXTENGINE_H
13 #define TEXTENGINE_H
14
15 // For string lengths in displaying text
16 #include <string>
17
18 // For multiple lines of text
19 #include <vector>
20
21 class TextEngine
22 {
23 private:
24     // The path to the game's text files (.log's)
25     static const char* TEXT_PATH;
26     // The offset between lines of characters
27     static const double LINE_OFFSET;
28
29     void displayText(
30         // 2d start location of the text
31         double x, double y,
32         // rgb color of text
33         double r, double g, double b,
34         // glut font and text to be displayed
35         void* font,
36         std::vector<std::string> text);
37
38     // Searches a text file for text related to the tag, and returns all text
39     // within the tag
40     std::vector<std::string> findText(std::string fileName, std::string tag);
41 public:
42     // Takes the location to display the text, color of the text,
43     // The file to read from, and a tag to search for
44     void openFile(double x, double y, double r, double g, double b,
45         std::string fileName, std::string tag);
46
47     // Takes in a string to display
48     void printString(double x, double y, double r, double g, double b,
49         std::string text);
50
51     // Returns text from fileName specified by tag
52     std::vector<std::string> getText(std::string fileName, std::string tag);
53 };
```

54
55 #endif

3.1.40 TextEngine.cpp

```
1  /*****\
2  * TextEngine.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the TextEngine class *
8  * For more information, see TextEngine.h *
9  \*****/
10
11 // TextEngine declaration and std::string
12 #include "TextEngine.h"
13
14 // std::ifstream
15 #include <fstream>
16
17 // Standard I/O for debugging
18 #include <iostream>
19
20 // OpenGL API
21 #include <gl\glut.h>
22
23 using namespace std;
24
25 // Initializing the constants
26 const char* TextEngine::TEXT_PATH = "Resources\\Text\\";
27 const double TextEngine::LINE_OFFSET = 20;
28
29 void TextEngine::displayText(double x, double y,
30     double r, double g, double b,
31     void* font, vector<string> text)
32 {
33     vector<string>::iterator it;
34
35     // Iterates throguh the text vector and prints it to the screen
36     for (it = text.begin(); it != text.end(); it++)
37     {
38         glColor3d(r, g, b);
39         glRasterPos2d(x, y);
40
41         for (unsigned int i = 0; i < it->length(); i++)
42         {
43             glutBitmapCharacter(font, (*it)[i]);
44         }
45
46         // Because glut does not print newlines
47         y += LINE_OFFSET;
48     }
49 }
50
51 vector<string> TextEngine::findText(string fileName, string tag)
52 {
```

```

53         // The tags are listed between dollar signs
54         string fullTag = '$' + tag + '$';
55
56         string fullPath = TEXT_PATH + fileName;
57
58         ifstream infile(fullPath);
59
60         // Buffer to read in data
61         string buff;
62         // Array to store strings
63         vector<string> data;
64
65         // Find the string(s) to read in
66         getline(infile, buff);
67         while (infile && buff != fullTag)
68         {
69             getline(infile, buff);
70         }
71
72         // Store the string(s)
73         getline(infile, buff);
74         while (infile && buff != "$END$")
75         {
76             data.push_back(buff);
77             getline(infile, buff);
78         }
79
80         infile.close();
81
82         return data;
83     }
84
85     void TextEngine::openFile(double x, double y,
86                             double r, double g, double b,
87                             string fileName, string tag)
88     {
89         vector<string> input = findText(fileName, tag);
90
91         displayText(x, y, r, g, b,
92                     GLUT_BITMAP_HELVETICA_18,
93                     input);
94     }
95
96     vector<string> TextEngine::getText(string fileName, string tag)
97     {
98         vector<string> input = findText(fileName, tag);
99
100        return input;
101    }
102
103     void TextEngine::printString(double x, double y, double r, double g, double b,
104                                 string text)
105     {
106         glColor3d(r, g, b);
107         glRasterPos2d(x, y);
108

```

```

109         for (unsigned int i = 0; i < text.length(); i++)
110         {
111             glutBitmapCharacter(GLUT_BITMAP_HELVETICA_18, text[i]);
112         }
113
114         // Vertical spacing
115         y += LINE_OFFSET;
116     }

```

3.1.41 Triangle.h

```

1  /*****\
2  * Triangle.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the declaration of the Triangle class *
8  * Which is used to hold the details of a 2D Triangle and *
9  * draw it to the screen *
10 \*****/
11
12 #ifndef TRIANGLE_H
13 #define TRIANGLE_H
14
15 class Triangle
16 {
17 private:
18     // Arrays containing the colors and the xyz vertices of the triangles
19     double color[4], vertices[9];
20 public:
21     // Takes in the vertices and color of the triangle
22     Triangle(const double(&new_vertices)[9], const double(&new_color)[4]);
23     // Print the triangle in 3D
24     void Display();
25     // Print the triangle in 2D
26     void Display2D();
27 };
28
29 #endif

```

3.1.42 Triangle.cpp

```

1  /*****\
2  * Triangle.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the triangle class *
8  * For more information, see Triangle.h *
9  \*****/
10
11 // Class declaration
12 #include "Triangle.h"
13
14 // For std::copy

```

```

15 #include <iterator>
16 #include <utility>
17
18 // OpenGL API
19 #include <GL\glut.h>
20
21 using namespace std;
22
23
24 Triangle::Triangle(const double(&new_vertices)[9], const double(&new_color)[4])
25 {
26     // Copies the color entry
27     copy(begin(new_color), end(new_color), color);
28
29     // Copies the vertices
30     copy(begin(new_vertices), end(new_vertices), vertices);
31 }
32
33 void Triangle::Display()
34 {
35     // Sets OpenGL's color to the triangle's color
36     glColor4f(color[0], color[1], color[2], color[3]);
37
38     // Draws the triangle
39     glBegin(GL_TRIANGLES);
40     glVertex3d(vertices[0], vertices[1], vertices[2]);
41     glVertex3d(vertices[3], vertices[4], vertices[5]);
42     glVertex3d(vertices[6], vertices[7], vertices[8]);
43     glEnd();
44 }
45
46 void Triangle::Display2D()
47 {
48     // Set's OpenGL's color to the triangle's color
49     glColor4f(color[0], color[1], color[2], color[3]);
50
51     // Draw's the triangle without the Z vertices
52     glBegin(GL_TRIANGLES);
53     glVertex2d(vertices[0], vertices[1]);
54     glVertex2d(vertices[3], vertices[4]);
55     glVertex2d(vertices[6], vertices[7]);
56     glEnd();
57 }

```

3.1.43 Trigger.h

```

1  /*****\
2  * Trigger.h *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * * *
7  * This file contains the declaration of the Trigger class *
8  * Which can be bound to a trigger-object that, upon use, *
9  * Will activate a designated target-object. *
10 \*****/
11

```

```

12 #ifndef TRIGGER_H
13 #define TRIGGER_H
14
15 #include "Terminal.h"
16 #include "Switch.h"
17
18 #include "GCTypes.h"
19
20 class Trigger
21 {
22 private:
23     void* trigger; // The object that activates the target
24     void* target;  // The object that is activated by the target
25
26     GCType triggerType; // The type (defined from GCTypes.h) of the trigger
27     GCType targetType;  // The type (defined from GCTypes.h) of the target
28
29     void activateTarget();
30
31 public:
32     // Get the object type of the trigger
33     int getTriggerType();
34     // Attempts to trigger the target
35     bool tryToTrigger(void* input, GCType type);
36     // Binds the triggering object
37     void bindTrigger(void* _trigger);
38     // Binds the target object
39     void bindTarget(void* _target);
40     // Constructor takes in trigger type and target type
41     Trigger(GCType _triggerType, GCType _targetType);
42
43 };
44
45 #endif

```

3.1.44 Trigger.cpp

```

1  /*****\
2  * Trigger.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the Trigger class *
8  * For more information, see Trigger.h *
9  \*****/
10
11 #include <cstdlib>
12 #include "Trigger.h"
13
14 int Trigger::getTriggerType()
15 {
16     return triggerType;
17 }
18
19 void Trigger::activateTarget()
20 {

```

```

21     switch (targetType)
22     {
23         case T_TERMINAL:
24         {
25             Terminal* t = (Terminal*)target;
26             t->activate();
27             break;
28         }
29         case T_SWITCH:
30         {
31             Switch* s = (Switch*)target;
32             s->activate();
33             break;
34         }
35         default:
36         {
37             break;
38         }
39     }
40 }
41
42 bool Trigger::tryToTrigger(void* input, GCtype type)
43 {
44     // If this trigger is the correct type
45     if (triggerType != type) return false;
46
47     // If this trigger is the correct object
48     if (trigger != input) return false;
49
50     activateTarget();
51
52     return true;
53 }
54
55 void Trigger::bindTrigger(void* _trigger)
56 {
57     trigger = _trigger;
58 }
59
60 void Trigger::bindTarget(void* _target)
61 {
62     target = _target;
63 }
64
65 Trigger::Trigger(GCtype _triggerType, GCtype _targetType)
66 {
67     trigger = NULL;
68     target = NULL;
69     triggerType = _triggerType;
70     targetType = _targetType;
71 }

```

3.1.45 Triple.h

```

1  /*****\
2  * Triple.h *
3  * This file was created by Jeremy Greenburg *

```



```

4  * As part of The God Core game for the University of      *
5  * Tennessee at Martin's University Scholars Organization  *
6  *                                                         *
7  * This file contains the declaration of the Triple class   *
8  * Which is just a simple 3-tuple really                     *
9  \*****/
10
11 #ifndef TRIPLE_H
12 #define TRIPLE_H
13
14 class Triple
15 {
16 public:
17     double a, b, c;
18 };
19
20 // For converting to a triple
21 Triple makeTrip(double _a, double _b, double _c);
22
23 #endif

```

3.1.46 Triple.cpp

```

1  /*****\
2  * Triple.cpp                                           *
3  * This file was created by Jeremy Greenburg           *
4  * As part of The God Core game for the University of   *
5  * Tennessee at Martin's University Scholars Organization *
6  *                                                         *
7  * This file contains the definition of the TwoD class   *
8  * For more information, see Triple.h                   *
9  \*****/
10
11 #include "Triple.h"
12
13 Triple makeTrip(double _a, double _b, double _c)
14 {
15     Triple ret;
16     ret.a = _a;
17     ret.b = _b;
18     ret.c = _c;
19
20     return ret;
21 }

```

3.1.47 TwoD.h

```

1  /*****\
2  * TwoD.h                                              *
3  * This file was created by Jeremy Greenburg           *
4  * As part of The God Core game for the University of   *
5  * Tennessee at Martin's University Scholars Organization *
6  *                                                         *
7  * This file contains the declaration of the TwoD class   *
8  * Which is used to hold the data and functionality for   *
9  * Drawing in 2D with OpenGL                           *
10 \*****/

```

```

11
12 #ifndef TWOD
13 #define TWOD
14
15 class TwoD
16 {
17 protected:
18     // The pixel boundaries of the screen
19     const double SCREENTOP = 0, SCREENBOTTOM = 1080,
20             SCREENLEFT = 0, SCREENRIGHT = 1920;
21
22     // Prepares OpenGL draw in 2D
23     void prepare2D();
24
25     // "Resets" OpenGL to draw in 3D
26     void prepare3D();
27
28 };
29
30 #endif

```

3.1.48 TwoD.cpp

```

1  /*****\
2  * TwoD.cpp *
3  * This file was created by Jeremy Greenburg *
4  * As part of The God Core game for the University of *
5  * Tennessee at Martin's University Scholars Organization *
6  * *
7  * This file contains the definition of the TwoD class *
8  * For more information, see TwoD.h *
9  \*****/
10
11 #include "TwoD.h"
12
13 // OpenGL API
14 #include <gl\glut.h>
15
16 void TwoD::prepare2D()
17 {
18     // Disable depth testing
19     glDisable(GL_DEPTH_TEST);
20     // Disable writing to the z buffer
21     glDepthMask(GL_FALSE);
22     // Disables lighting
23     glDisable(GL_LIGHTING);
24
25     // Create an orthogonal matrix to write on
26     glMatrixMode(GL_PROJECTION);
27     glPushMatrix();
28     glLoadIdentity();
29     glOrtho(SCREENLEFT, SCREENRIGHT, SCREENBOTTOM, SCREENTOP, -1, 1);
30     glMatrixMode(GL_MODELVIEW);
31     glPushMatrix();
32     glLoadIdentity();
33 }
34

```

```

35 void TwoD::prepare3D()
36 {
37     // Discards the orthogonal matrices
38     glMatrixMode(GL_PROJECTION);
39     glPopMatrix();
40     glMatrixMode(GL_MODELVIEW);
41     glPopMatrix();
42
43     // Enable depth testing
44     glEnable(GL_DEPTH_TEST);
45     // Enables writing to the z buffer
46     glDepthMask(GL_TRUE);
47     // Renable lighting
48     glEnable(GL_LIGHTING);
49 }

```

3.2 Database

3.2.1 Walls

ID	LEVEL	X1	X2	X3	X4	Y1	Y2	Y3	Y4	Z1	Z2	Z3	Z4	R	G	B	A	Axis
lvlceiling	LEVELZERO	-5	-5	8	8	1	1	1	1	-4	1	1	-4	0.70	0.70	0.70	1	0
lvlfloor	LEVELZERO	-5	-5	8	8	-1	-1	-1	-1	-4	1	1	-4	0.70	0.70	0.70	1	0
room0frntftwall	LEVELZERO	5	5	5	5	-1	1	1	-1	-4	-4	-2.5	-2.5	0.29	0.29	0.29	1	z
room0frntrghtwall	LEVELZERO	5	5	5	5	-1	1	1	-1	-0.5	-0.5	1	1	0.29	0.29	0.29	1	z
room0backwall	LEVELZERO	-5	-5	-5	-5	-1	1	1	-1	-4	-4	1	1	0.29	0.29	0.29	1	z
room0rghtwall	LEVELZERO	-5	-5	5	5	-1	1	1	-1	1	1	1	1	0.29	0.29	0.29	1	x
room0frnttopwall	LEVELZERO	5	5	5	5	0.5	1	1	0.5	-2.5	-2.5	-0.5	-0.5	0.29	0.29	0.29	1	z
room1lftwall	LEVELZERO	5	5	8	8	-1	1	1	-1	-4	-4	-4	-4	0.29	0.29	0.29	1	x
room1rghtwall	LEVELZERO	5	5	8	8	-1	1	1	-1	1	1	1	1	0.29	0.29	0.29	1	x
room1frntbotwall	LEVELZERO	8	8	8	8	-1	-0.5	-0.5	-1	-4	-4	1	1	0.29	0.29	0.29	1	z
room1frnttopwall	LEVELZERO	8	8	8	8	0.5	1	1	0.5	-4	-4	1	1	0.29	0.29	0.29	1	z
room0lftlftwall	LEVELZERO	-5	-5	-1.5	-1.5	-1	1	1	-1	-4	-4	-4	-4	0.29	0.29	0.29	1	x
room0lfrghtwall	LEVELZERO	1.5	1.5	5	5	-1	1	1	-1	-4	-4	-4	-4	0.29	0.29	0.29	1	x
room0lftptwall	LEVELZERO	-1.5	-1.5	1.5	1.5	0.70	1	1	0.70	-4	-4	-4	-4	0.29	0.29	0.29	1	x
room0frntmidwall	LEVELZERO	8	8	8	8	0.5	-0.5	-0.5	0.5	-4	-4	1	1	0.12	0.56	1	0.598	z
lvl1Floor	LEVELONE	30	30	-30	-30	-1	-1	-1	40	-5	-5	40	0.70	0.70	0.70	1	0	
lvl1HangarCeiling	LEVELONE	15	15	-15	-15	5	5	5	5	5	5	5	5	0.80	0	0	1	0
lvl1HangarFrntLeftWall	LEVELONE	15	15	1	1	-1	5	5	-1	5	5	5	5	0.80	0	0	1	x
lvl1HangarFrntRghtWall	LEVELONE	-1	-1	-15	-15	-1	5	5	-1	5	5	5	5	0.80	0	0	1	x
lvl1HangarFrntTopWall	LEVELONE	1	1	-1	-1	1	5	5	1	5	5	5	5	0.80	0	0	1	x
lvl1HangarRghtWall	LEVELONE	-15	-15	-15	-15	-1	5	5	-1	5	5	-5	-5	0.80	0	0	1	z
lvl1HangarLeftWall	LEVELONE	15	15	15	15	-1	5	5	-1	5	5	-5	-5	0.80	0	0	1	z
lvl1HangarBckWall	LEVELONE	15	15	-15	-15	-1	5	5	-1	-5	-5	-5	-5	0.12	0.56	1	0.402	x
lvl1HallLftWall1	LEVELONE	3	3	3	3	-1	1	1	-1	5	5	11	11	0.80	0	0	1	z
lvl1HallRghtWall1	LEVELONE	-3	-3	-3	-3	-1	1	1	-1	5	5	8	8	0.80	0	0	1	z
lvl1HallLftWall2	LEVELONE	3	3	3	3	-1	1	1	-1	13	13	19	19	0.80	0	0	1	z
lvl1HallRghtWall2	LEVELONE	-3	-3	-3	-3	-1	1	1	-1	10	10	15	15	0.80	0	0	1	z
lvl1HallRghtWall3	LEVELONE	-3	-3	-3	-3	-1	1	1	-1	17	17	19	19	0.80	0	0	1	z
lvl1HallCeiling	LEVELONE	15	15	-15	-15	1	1	1	5	29	29	5	0.70	0.70	0.70	1	0	
lvl1HallLftEnd	LEVELONE	7.5	7.5	1	1	-1	1	1	-1	19	19	19	19	0.80	0	0	1	x
lvl1HallRghtEnd	LEVELONE	-3	-3	-1	-1	-1	1	1	-1	19	19	19	19	0.80	0	0	1	x
lvl1LftRoom1LeftWall	LEVELONE	-3	-3	-15	-15	-1	1	1	-1	19	19	19	19	0.80	0	0	1	x
lvl1LftRoom1RghtWall	LEVELONE	-3	-3	-15	-15	-1	1	1	-1	12.5	12.5	12.5	12.5	0.80	0	0	1	x
lvl1LftRoomsBckWall	LEVELONE	-15	-15	-15	-15	-1	1	1	-1	19	19	5	5	0.80	0	0	1	z
lvl1Room4LeftWall	LEVELONE	7.5	7.5	7.5	7.5	-1	1	1	-1	19	19	29	29	0.80	0	0	1	z
lvl1Room4RghtWall	LEVELONE	-7.5	-7.5	-7.5	-7.5	-1	1	1	-1	19	19	29	29	0.80	0	0	1	z
lvl1Room3LeftWall	LEVELONE	20	20	20	20	-1	1	1	-1	10	10	-3	-3	0.80	0	0	1	z
lvl1Room3BckWall	LEVELONE	20	20	15	15	-1	1	1	-1	-3	-3	-3	-3	0.80	0	0	1	x
lvl1Room3FrntWall1	LEVELONE	20	20	6	6	-1	1	1	-1	10	10	10	10	0.80	0	0	1	x
lvl1Room3FrntWall2	LEVELONE	4	4	3	3	-1	1	1	-1	10	10	10	10	0.80	0	0	1	x
lvl1Room2LftWall	LEVELONE	7.5	7.5	7.5	7.5	-1	1	1	-1	19	19	10	10	0.80	0	0	1	z
lvl1Room3Ceiling	LEVELONE	20	20	15	15	1	1	1	-3	10	10	-3	0.70	0.70	0.70	1	0	
lvl1Room4BckWallLft	LEVELONE	7.5	7.5	1	1	-1	1	1	-1	29	29	29	29	0.80	0	0	1	x
lvl1Room4BckWallRght	LEVELONE	-1	-1	-7.5	-7.5	-1	1	1	-1	29	29	29	29	0.80	0	0	1	x
lvl2Room0BckWallLft	LEVELTWO	5	5	1	1	-1	1	1	-1	2	2	2	2	0	0.80	0	1	x
lvl2Room0BckWallRght	LEVELTWO	-5	-5	-1	-1	-1	1	1	-1	2	2	2	2	0	0.80	0	1	x
lvl2Room0LftWallLft	LEVELTWO	-5	-5	-5	-5	-1	1	1	-1	2	2	1	1	0	0.80	0	1	z
lvl2Room0LftWallRght	LEVELTWO	-5	-5	-5	-5	-1	1	1	-1	-1	-1	-2	-2	0	0.80	0	1	z
Lvl2Room0FrntWall	LEVELTWO	-5	-5	5	5	-1	1	1	-1	-2	-2	-2	-2	0	0.80	0	1	x
Lvl2Room0RghtWallLft	LEVELTWO	5	5	5	5	-1	1	1	-1	-2	-2	-1	-1	0	0.80	0	1	z
Lvl2Room0RghtWallRght	LEVELTWO	5	5	5	5	-1	1	1	-1	1	1	2	2	0	0.80	0	1	z
Lvl2Room0FakeDoor	LEVELTWO	-1	-1	1	1	-1	1	1	-1	2	2	2	2	0.29	0.29	0.29	1	x
Lvl2LftHallBckWall	LEVELTWO	-5	-5	-18	-18	-1	1	1	-1	1	1	1	1	0	0.80	0	1	x
lvl2RghtHallBckWall	LEVELTWO	5	5	18	18	1	-1	-1	1	1	1	1	1	0	0.80	0	1	x
Lvl2LftHallLftWall	LEVELTWO	-18	-18	-18	-18	1	-1	-1	1	1	1	-15	-15	0	0.80	0	1	z
lvl2RghtHallRghtWall	LEVELTWO	18	18	18	18	1	-1	-1	1	1	1	-15	-15	0	0.80	0	1	z
lvl2LftHallFrntWallRght	LEVELTWO	-5	-5	-9	-9	-0.5	0.5	0.5	-0.5	-1	-1	-1	-1	0	0.80	0	1	x
lvl2LftHallLftWall	LEVELTWO	-11	-11	-15	-15	-0.5	0.5	0.5	-0.5	-1	-1	-1	-1	0	0.80	0	1	x
lvl2LftHallTopStrip1	LEVELTWO	-5	-5	-15	-15	1	0.5	0.5	1	-1	-1	-1	-1	0	0.80	0	1	x
lvl2LftHallBotStrip1	LEVELTWO	-5	-5	-15	-15	-0.5	-1	-1	-0.5	-1	-1	-1	-1	0	0.80	0	1	x
lvl2RghtHallFrntWallLft	LEVELTWO	5	5	9	9	-0.5	0.5	0.5	-0.5	-1	-1	-1	-1	0	0.80	0	1	x
lvl2RghtHallFrntWallRght	LEVELTWO	11	11	15	15	-0.5	0.5	0.5	-0.5	-1	-1	-1	-1	0	0.80	0	1	x
lvl2RghtHallTopStrip1	LEVELTWO	5	5	15	15	0.5	1	1	0.5	-1	-1	-1	-1	0	0.80	0	1	x
lvl2RghtHallBotStrip1	LEVELTWO	5	5	15	15	-0.5	-1	-1	-0.5	-1	-1	-1	-1	0	0.80	0	1	x
lvl2LftRoomsRghtWall	LEVELTWO	-5	-5	-5	-5	1	-1	-1	1	-2	-2	-12	-12	0	0.80	0	1	z
lvl2RghtRoomsLftWall	LEVELTWO	5	5	5	5	1	-1	-1	1	-2	-2	-12	-12	0	0.80	0	1	z

ID	LEVEL	X1	X2	X3	X4	Y1	Y2	Y3	Y4	Z1	Z2	Z3	Z4	R	G	B	A	Axis
lv2LftHallBckWall2	LEVELTWO	-18	-18	-1	-1	1	-1	-1	1	-15	-15	-15	-15	0	0.80	0	1	x
lv2RghtHallBckWall2	LEVELTWO	18	18	1	1	1	-1	-1	1	-15	-15	-15	-15	0	0.80	0	1	x
lv2BckWall	LEVELTWO	-9	-9	9	9	1	-1	-1	1	-12	-12	-12	-12	0	0.80	0	1	x
lv2LftDividerLft	LEVELTWO	-15	-15	-11	-11	1	-1	-1	1	-5.5	-5.5	-5.5	-5.5	0	0.80	0	1	x
lv2LftDividerRght	LEVELTWO	-9	-9	-5	-5	1	-1	-1	1	-5.5	-5.5	-5.5	-5.5	0	0.80	0	1	x
lv2LftDividerTop	LEVELTWO	-11	-11	-9	-9	0.5	1	1	0.5	-5.5	-5.5	-5.5	-5.5	0	0.80	0	1	x
lv2LftDividerTBot	LEVELTWO	-11	-11	-9	-9	-0.5	-1	-1	-0.5	-5.5	-5.5	-5.5	-5.5	0	0.80	0	1	x
lv2RghtDividerLft	LEVELTWO	15	15	11	11	1	-1	-1	1	-5.5	-5.5	-5.5	-5.5	0	0.80	0	1	x
lv2RghtDividerRght	LEVELTWO	9	9	5	5	1	-1	-1	1	-5.5	-5.5	-5.5	-5.5	0	0.80	0	1	x
lv2RghtDividerTop	LEVELTWO	11	11	9	9	0.5	1	1	0.5	-5.5	-5.5	-5.5	-5.5	0	0.80	0	1	x
lv2RghtDividerTBot	LEVELTWO	11	11	9	9	-0.5	-1	-1	-0.5	-5.5	-5.5	-5.5	-5.5	0	0.80	0	1	x
lv2Ceiling	LEVELTWO	-18	-18	18	18	1	1	1	1	2	-20	-20	2	0.70	0.70	0.70	1	0
lv2Floor	LEVELTWO	-18	-18	18	18	-1	-1	-1	-1	2	-20	-20	2	0.70	0.70	0.70	1	0
lv2LftInnerWallLft	LEVELTWO	-15	-15	-15	-15	-1	1	1	-1	-1	-1	-1	-2	0	0.80	0	1	z
lv2LftInnerWallCtr	LEVELTWO	-15	-15	-15	-15	-1	1	1	-1	-4	-4	-8	-8	0	0.80	0	1	z
lv2LftInnerWallRght	LEVELTWO	-15	-15	-15	-15	-1	1	1	-1	-10	-10	-12	-12	0	0.80	0	1	z
lv2RghtInnerWallLft	LEVELTWO	15	15	15	15	-1	1	1	-1	-1	-1	-2	-2	0	0.80	0	1	z
lv2RghtInnerWallCtr	LEVELTWO	15	15	15	15	-1	1	1	-1	-4	-4	-8	-8	0	0.80	0	1	z
lv2RghtInnerWallRght	LEVELTWO	15	15	15	15	-1	1	1	-1	-10	-10	-12	-12	0	0.80	0	1	z
lv2EndHallLft	LEVELTWO	-1	-1	-1	-1	-1	1	1	1	-15	-15	-20	-20	0	0.80	0	1	z
lv2EndHallRght	LEVELTWO	1	1	1	1	-1	-1	-1	-1	-15	-15	-20	-20	0	0.80	0	1	z
lv3StrtWallLft	LEVELTHREE	-1	-1	-13	-13	1	1	1	-1	1	1	1	1	0	0	0.80	1	x
lv3StrtWallRght	LEVELTHREE	1	1	13	13	-1	-1	-1	-1	1	1	1	1	0	0	0.80	1	x
lv3Room0RghtWall	LEVELTHREE	-8	-8	-8	-8	-1	1	1	-1	1	1	-1	-1	0	0	0.80	1	z
lv3Room0/1RghtWall	LEVELTHREE	-8	-8	-8	-8	-1	1	1	-1	-3	-7	-7	-7	0	0	0.80	1	z
lv3Room1/2RghtWall	LEVELTHREE	-8	-8	-8	-8	-1	1	1	-1	-9	-9	-13	-13	0	0	0.80	1	z
lv3Room2/3RghtWall	LEVELTHREE	-8	-8	-8	-8	-1	1	1	-1	-15	-15	-19	-19	0	0	0.80	1	z
lv3Room3RghtWall	LEVELTHREE	-8	-8	-8	-8	-1	1	1	-1	-21	-21	-23	-23	0	0	0.80	1	z
lv3Room7LftWall	LEVELTHREE	8	8	8	8	-1	1	1	-1	1	1	-1	-1	0	0	0.80	1	z
lv3Room7/6LftWall	LEVELTHREE	8	8	8	8	-1	1	1	-1	-3	-7	-7	-7	0	0	0.80	1	z
lv3Room6/5LftWall	LEVELTHREE	8	8	8	8	-1	1	1	-1	-9	-9	-13	-13	0	0	0.80	1	z
lv3Room5/4LftWall	LEVELTHREE	8	8	8	8	-1	1	1	-1	-15	-15	-19	-19	0	0	0.80	1	z
lv3Room4LftWall	LEVELTHREE	8	8	8	8	-1	1	1	-1	-21	-21	-23	-23	0	0	0.80	1	z
lv3Ceiling	LEVELTHREE	-13	-13	13	13	1	1	1	1	1	-23	-23	1	0.70	0.70	0.70	1	0
lv3Floor	LEVELTHREE	-13	-13	13	13	-1	-1	-1	-1	1	-23	-23	1	0.70	0.70	0.70	1	0
lv3Room0/1Divid	LEVELTHREE	-13	-13	-8	-8	-1	1	1	-1	-5	-5	-5	-5	0	0	0.80	1	x
lv3Room1/2Divid	LEVELTHREE	-13	-13	-8	-8	-1	1	1	-1	-11	-11	-11	-11	0	0	0.80	1	x
lv3Room2/3Divid	LEVELTHREE	-13	-13	-8	-8	-1	1	1	-1	-17	-17	-17	-17	0	0	0.80	1	x
lv3Room7/6Divid	LEVELTHREE	13	13	8	8	-1	1	1	-1	-5	-5	-5	-5	0	0	0.80	1	x
lv3Room6/5Divid	LEVELTHREE	13	13	8	8	-1	1	1	-1	-11	-11	-11	-11	0	0	0.80	1	x
lv3Room5/4Divid	LEVELTHREE	13	13	8	8	-1	1	1	-1	-17	-17	-17	-17	0	0	0.80	1	x
lv3FrntWall	LEVELTHREE	-13	-13	13	13	-1	1	1	-1	-23	-23	-23	-23	0	0	0.80	1	x
lv3InnerLftWall	LEVELTHREE	-3	-3	-3	-3	-1	1	1	-1	-2	-2	-20	-20	0	0	0.80	1	z
lv3InnerRghtWall	LEVELTHREE	3	3	3	3	-1	1	1	-1	-2	-2	-20	-20	0	0	0.80	1	z
lv3Room0LftWall	LEVELTHREE	-13	-13	-13	-13	-1	1	1	-1	1	1	-1	-1	0	0	0.80	1	z
lv3Room0/1LftWall	LEVELTHREE	-13	-13	-13	-13	-1	1	1	-1	-3	-7	-7	-7	0	0	0.80	1	z
lv3Room1/2LftWall	LEVELTHREE	-13	-13	-13	-13	-1	1	1	-1	-9	-9	-13	-13	0	0	0.80	1	z
lv3Room2/3LftWall	LEVELTHREE	-13	-13	-13	-13	-1	1	1	-1	-15	-15	-19	-19	0	0	0.80	1	z
lv3Room3LftWall	LEVELTHREE	-13	-13	-13	-13	-1	1	1	-1	-21	-21	-23	-23	0	0	0.80	1	z
lv3Room7RghtWall	LEVELTHREE	13	13	13	13	-1	1	1	-1	1	1	-1	-1	0	0	0.80	1	z
lv3Room7/6RghtWall	LEVELTHREE	13	13	13	13	-1	1	1	-1	-3	-7	-7	-7	0	0	0.80	1	z
lv3Room6/5RghtWall	LEVELTHREE	13	13	13	13	-1	1	1	-1	-9	-9	-13	-13	0	0	0.80	1	z
lv3Room5/4RghtWall	LEVELTHREE	13	13	13	13	-1	1	1	-1	-15	-15	-19	-19	0	0	0.80	1	z
lv3Room4RghtWall	LEVELTHREE	13	13	13	13	-1	1	1	-1	-21	-21	-23	-23	0	0	0.80	1	z
lv3Entrance	LEVELTHREE	-1	-1	1	1	-1	1	1	-1	1	1	1	1	0.29	0.29	0.29	1	x
lv3Room0FakeDoor	LEVELTHREE	-13	-13	-13	-13	-1	-1	-1	-1	-1	-3	-3	0.5	0.5	0.5	1	z	
lv3Room1FakeDoor	LEVELTHREE	-13	-13	-13	-13	-1	1	1	-1	-7	-7	-9	-9	0.5	0.5	0.5	1	z
lv3Room2FakeDoor	LEVELTHREE	-13	-13	-13	-13	-1	1	1	-1	-13	-13	-15	-15	0.5	0.5	0.5	1	z
lv3Room3FakeDoor	LEVELTHREE	-13	-13	-13	-13	-1	1	1	-1	-19	-19	-21	-21	0.5	0.5	0.5	1	z
lv3Room7FakeDoor	LEVELTHREE	13	13	13	13	-1	1	1	-1	-1	-3	-3	0.5	0.5	0.5	1	z	
lv3Room6FakeDoor	LEVELTHREE	13	13	13	13	-1	1	1	-1	-7	-7	-9	-9	0.5	0.5	0.5	1	z
lv3Room5FakeDoor	LEVELTHREE	13	13	13	13	-1	1	1	-1	-13	-13	-15	-15	0.5	0.5	0.5	1	z
lv3Room4FakeDoor	LEVELTHREE	13	13	13	13	-1	1	1	-1	-19	-19	-21	-21	0.5	0.5	0.5	1	z
lv3Room8BckWall	LEVELTHREE	-3	-3	3	3	-1	1	1	-1	-12	-12	-12	-12	0	0	0.80	1	x
lv3Room9BckWall	LEVELTHREE	-3	-3	3	3	-1	1	1	-1	-15	-15	-15	-15	0	0	0.80	1	x
lv3Room8FrntWallLft	LEVELTHREE	-3	-3	-1	-1	-1	1	1	-1	-2	-2	-2	-2	0	0	0.80	1	x
lv3Room8FrntWallRght	LEVELTHREE	3	3	1	1	-1	1	1	-1	-2	-2	-2	-2	0	0	0.80	1	x
lv3Room9FrntWallLft	LEVELTHREE	-3	-3	-1	-1	-1	1	1	-1	-20	-20	-20	-20	0	0	0.80	1	x
lv3Room9FrntWallRght	LEVELTHREE	3	3	1	1	-1	1	1	-1	-20	-20	-20	-20	0	0	0.80	1	x
lv4Room0LftWall	LEVELFOUR	-5	-5	-5	-5	-1	1	1	-1	-2	-2	2	2	0.29	0.29	0.29	1	z
lv4Room0RghtWall	LEVELFOUR	5	5	5	5	-1	1	1	-1	2	2	-2	-2	0.29	0.29	0.29	1	z
lv4Room0BckLft	LEVELFOUR	-5	-5	-1	-1	-1	1	1	-1	2	2	2	2	0.29	0.29	0.29	1	x
lv4Room0BckRght	LEVELFOUR	1	1	5	5	-1	1	1	-1	2	2	2	2	0.29	0.29	0.29	1	x
lv4Room0Ceiling	LEVELFOUR	5	5	-5	-5	1	1	1	1	2	-2	-2	2	0.70	0.70	0.70	1	0
lv4Room0Floor	LEVELFOUR	5	5	-5	-5	-1	-1	-1	-1	2	-2	-2	2	0.70	0.70	0.70	1	0
lv4Entrance	LEVELFOUR	-1	-1	1	1	-1	1	1	-1	2	2	2	2	0.5	0.5	0.5	1	x
lv4Room1LftWall	LEVELFOUR	10	10	10	10	-5	5	5	-5	-2	-2	-12	-12	0.598	0.598	0.598	1	z
lv4Room1RghtWall	LEVELFOUR	-10	-10	-10	-10	-5	5	5	-5	-2	-2	-12	-12	0.598	0.598	0.598	1	z
lv4Room1FrntWall	LEVELFOUR	10	10	-10	-10	-5	5	5	-5	-12	-12	-12	-12	0.598	0.598	0.598	1	x
lv4Room1BckLftWall	LEVELFOUR	-10	-10	-5	-5	-5	5	5	-5	-2	-2	-2	-2	0.598	0.598	0.598	1	x
lv4Room1BckRghtWall	LEVELFOUR	10	10	5	5	-5	5	5	-5	-2	-2	-2	-2	0.598	0.598	0.598	1	x
lv4Room1Ceiling	LEVELFOUR	10	10	-10	-10	5	5	5	-5	-2	-12	-12	-2	0.70	0.70	0.70	1	0
lv4Room1Floor	LEVELFOUR	10	10	-10	-10	-5	-5	-5	-5	-2	-12	-12	-2	0.70	0.70	0.70	1	0
lv4Room0FrntWall	LEVELFOUR	-5	-5	5	5	-1	1	1	-1	-2	-2	-2	-2	0.101	0.101	0.101	0.902	x
lv2LftBckWindowLft	LEVELTWO	-15	-15	-11	-11	1	-1	-1	1	-12	-12	-12	-12	0	0.80	0	1	x
lv2BckWindowTop	LEVELTWO	-11	-11	-9	-9	0.5	1	1	0.5	-12	-12	-12	-12	0	0.80	0	1	x
lv2BckWindowBot	LEVELTWO	-11	-11	-9	-9	-0.5	-1	-1	-0.5	-12	-12	-12	-12	0	0.80	0	1	x
lv2RghtBckWindowLft	LEVELTWO	15	15	11	11	1	-1	-1	1	-12	-12	-12	-12	0	0.80	0	1	x
lv2RghtWindowTop	LEVELTWO	11	11	9	9	0.5	1	1	0.5	-12	-12	-12	-12	0	0.80	0	1	x
lv2RghtWindowBot	LEVELTWO	11	11	9	9	-0.5	-1	-1	-0.5	-12	-12	-12	-1					

3.2.2 Doors

ID	LEVEL	X1	X2	X3	X4	Y1	Y2	Y3	Y4	Z1	Z2	Z3	Z4	R	G	B	A	axis
room0room1Door	LEVELZERO	5	5	5	5	-1	0.5	0.5	-1	-2.5	-2.5	-0.5	-0.5	0.90	0.90	0.90	1	z
lvl0ExitDoor	LEVELZERO	-1.5	-1.5	1.5	1.5	-1	0.70	0.70	-1	-4	-4	-4	-4	0.5	0.5	0.5	1	x
lvl1HangerHallDoor	LEVELONE	1	1	-1	-1	-1	1	1	-1	5	5	5	5	0.90	0.90	0.90	1	x
lvl1Room2Door	LEVELONE	3	3	3	3	-1	1	1	-1	11	11	13	13	0.90	0.90	0.90	1	z
lvl1Room0Door	LEVELONE	-3	-3	-3	-3	-1	1	1	-1	17	17	15	15	0.90	0.90	0.90	1	z
lvl1Room1Door	LEVELONE	-3	-3	-3	-3	-1	1	1	-1	10	10	8	8	0.90	0.90	0.90	1	z
lvl1Room3Door	LEVELONE	6	6	4	4	-1	1	1	-1	10	10	10	10	0.90	0.90	0.90	1	x
lvl1Room4Door	LEVELONE	1	1	-1	-1	-1	1	1	-1	19	19	19	19	0.90	0.90	0.90	1	x
lvl1ExitDoor	LEVELONE	1	1	-1	-1	1	-1	-1	1	29	29	29	29	0.5	0.5	0.5	1	x
lvl2Room0Door	LEVELTWO	-15	-15	-15	-15	-1	1	1	-1	-2	-2	-4	-4	0.90	0.90	0.90	1	z
lvl2Room1Door	LEVELTWO	-15	-15	-15	-15	-1	1	1	-1	-8	-8	-10	-10	0.90	0.90	0.90	1	z
lvl2Room2Door	LEVELTWO	15	15	15	15	-1	1	1	-1	-8	-8	-10	-10	0.90	0.90	0.90	1	z
lvl2Room3Door	LEVELTWO	15	15	15	15	-1	1	1	-1	-2	-2	-4	-4	0.90	0.90	0.90	1	z
lvl2ExitDoor	LEVELTWO	-1	-1	1	1	-1	1	1	-1	-20	-20	-20	-20	0.5	0.5	0.5	1	x
lvl3Room0Door	LEVELTHREE	-8	-8	-8	-8	-1	1	1	-1	-1	-1	-3	-3	0.13	0.5504	0.13	1	z
lvl3Room1Door	LEVELTHREE	-8	-8	-8	-8	-1	1	1	-1	-7	-7	-9	-9	0.13	0.5504	0.13	1	z
lvl3Room2Door	LEVELTHREE	-8	-8	-8	-8	-1	1	1	-1	-13	-13	-15	-15	0.70	0.13	0.13	1	z
lvl3Room3Door	LEVELTHREE	-8	-8	-8	-8	-1	1	1	-1	-19	-19	-21	-21	1	0.5504	0	1	z
lvl3Room7Door	LEVELTHREE	8	8	8	8	-1	1	1	-1	-1	-1	-3	-3	0.13	0.5504	0.13	1	z
lvl3Room6Door	LEVELTHREE	8	8	8	8	-1	1	1	-1	-7	-7	-9	-9	1	0.5504	0	1	z
lvl3Room5Door	LEVELTHREE	8	8	8	8	-1	1	1	-1	-13	-13	-15	-15	0.70	0.13	0.13	1	z
lvl3Room4Door	LEVELTHREE	8	8	8	8	-1	1	1	-1	-19	-19	-21	-21	1	0.5504	0	1	z
lvl3Room8Door	LEVELTHREE	-1	-1	1	1	-1	1	1	-1	-2	-2	-2	-2	0.90	0.90	0.90	1	x
lvl3Room9Door	LEVELTHREE	-1	-1	1	1	-1	1	1	-1	-20	-20	-20	-20	0.90	0.90	0.90	1	x

3.2.3 Switches

ID	LEVEL	target	xt	yt	zt	xr	yr	zr	type	startOn
lv10Door1	LEVELZERO	room0room1Door	5	0	-3	0	90	0	DOOR	1
lv10Door2	LEVELZERO	t'lvlzero'room1	7	0	-4	0	0	0	TERMINAL	1
lv10END	LEVELZERO	NULL	-2	0	-4	0	0	0	LEVEL'END	0
lv11END	LEVELONE	NULL	1.5	0	29	0	0	0	LEVEL'END	0
lv1Door1	LEVELONE	lv11HangerHallDoor	1.5	0	5	0	0	0	DOOR	1
lv11Door2	LEVELONE	lv11Room2Door	3	0	10	0	90	0	DOOR	1
lv11Door3	LEVELONE	lv11Room0Door	-3	0	18	0	90	0	DOOR	1
lv11Door4	LEVELONE	lv11Room1Door	-3	0	11	0	90	0	DOOR	1
lv11Door5	LEVELONE	lv11Room4Door	1.5	0	19	0	0	0	DOOR	1
lv11Door6	LEVELONE	lv11Room3Door	6.5	0	10	0	0	0	DOOR	0
lv12Door0	LEVELTWO	lv12Room0Door	-15	0	-5	0	90	0	DOOR	1
lv12Door1	LEVELTWO	lv12Room1Door	-15	0	-7	0	90	0	DOOR	0
lv12Door2	LEVELTWO	lv12Room2Door	15	0	-7	0	90	0	DOOR	1
lv12Door3	LEVELTWO	lv12Room3Door	15	0	-5	0	90	0	DOOR	0
lv12END	LEVELTWO	NULL	-1	0	-18	0	90	0	LEVEL'END	0
lv13Room0	LEVELTHREE	lv13Room0Door	-8	0	-0.5	0	90	0	DOOR	1
lv13Room1	LEVELTHREE	lv13Room1Door	-8	0	-6.5	0	90	0	DOOR	1
lv13Room2	LEVELTHREE	lv13Room2Door	-8	0	-12.5	0	90	0	DOOR	0
lv13Room3	LEVELTHREE	lv13Room3Door	-8	0	-18.5	0	90	0	DOOR	0
lv13Room7	LEVELTHREE	lv13Room7Door	8	0	-0.5	0	90	0	DOOR	1
lv13Room6	LEVELTHREE	lv13Room6Door	8	0	-6.5	0	90	0	DOOR	0
lv13Room5	LEVELTHREE	lv13Room5Door	8	0	-12.5	0	90	0	DOOR	0
lv13Room4	LEVELTHREE	lv13Room4Door	8	0	-18.5	0	90	0	DOOR	0
lv13Room0END	LEVELTHREE	NULL	-13	0	-0.5	0	90	0	LEVEL'END	0
lv13Room1END	LEVELTHREE	NULL	-13	0	-6.5	0	90	0	LEVEL'END	0
lv13Room2END	LEVELTHREE	NULL	-13	0	-12.5	0	90	0	LEVEL'END	0
lv13Room3END	LEVELTHREE	NULL	-13	0	-18.5	0	90	0	LEVEL'END	0
lv13Room7END	LEVELTHREE	NULL	13	0	-0.5	0	90	0	LEVEL'END	0
lv13Room6END	LEVELTHREE	NULL	13	0	-6.5	0	90	0	LEVEL'END	0
lv13Room5END	LEVELTHREE	NULL	13	0	-12.5	0	90	0	LEVEL'END	0
lv13Room4END	LEVELTHREE	NULL	13	0	-18.5	0	90	0	LEVEL'END	0
lv13Room8	LEVELTHREE	lv13Room8Door	-1.5	0	-2	0	0	0	DOOR	0
lv13Room9	LEVELTHREE	lv13Room9Door	1.5	0	-20	0	0	0	DOOR	1

3.2.4 Terminals

ID	LEVEL	tag	xt	yt	zt	xr	yr	zr
t'lvlzero'room1	LEVELZERO	lv0TM1.tm	7	0	-2	0	0	0
t'lvl1Room0	LEVELONE	lv1TM0.tm	-13	0	15	0	180	0
t'lvl1Room1	LEVELONE	lv1TM1.tm	-13	0	8	0	180	0
t'lvl1Room3	LEVELONE	lv1TM2.tm	17	0	-2	0	90	0
t'lvl2Room0	LEVELTWO	lv2TM0.tm	-6	0	-3	0	0	0
t'lvl2Room1	LEVELTWO	lv2TM1.tm	-6	0	-9	0	0	0
t'lvl2Room2	LEVELTWO	lv2TM2.tm	6	0	-9	0	180	0
t'lvl2Room3	LEVELTWO	lv2TM3.tm	6	0	-3	0	180	0
t'lvl3Room0	LEVELTHREE	lv3TM0.tm	-10	0	-4	180	-90	0
t'lvl3Room1	LEVELTHREE	lv3TM1.tm	-10	0	-10	180	-90	0
t'lvl3Room2	LEVELTHREE	lv3TM2.tm	-10	0	-16	180	-90	0
t'lvl3Room3	LEVELTHREE	lv3TM3.tm	-10	0	-22	180	-90	0
t'lvl3Room4	LEVELTHREE	lv3TM4.tm	10	0	-22	180	-90	0
t'lvl3Room5	LEVELTHREE	lv3TM5.tm	10	0	-16	180	-90	0
t'lvl3Room6	LEVELTHREE	lv3TM6.tm	10	0	-10	180	-90	0
t'lvl3Room7	LEVELTHREE	lv3TM7.tm	10	0	-4	180	-90	0
t'lvl3Room8	LEVELTHREE	lv3TM8.tm	0	0	-11	0	90	0
t'lvl3Room9	LEVELTHREE	lv3TM9.tm	0	0	-16	0	-90	0

3.2.5 Triggers

ID	LEVEL	Trigger	Target	TriggerType	TargetType
tr'lvl0End	LEVELZERO	t'lvlzero'room1	lvl0END	TERMINAL	SWITCH
tr'lvl1Switch	LEVELONE	t'lvl1Room0	lvl1Door6	TERMINAL	SWITCH
tr'lvl1End	LEVELONE	t'lvl1Room3	lvl1END	TERMINAL	SWITCH
tr'lvl2Door1	LEVELTWO	t'lvl2Room0	lvl2Door3	TERMINAL	SWITCH
tr'lvl2Door2	LEVELTWO	t'lvl2Room3	lvl2Door1	TERMINAL	SWITCH
tr'lvl2End	LEVELTWO	t'lvl2Room1	lvl2END	TERMINAL	SWITCH
tr'lvl3Sec1	LEVELTHREE	t'lvl3Room9	lvl3Room3	TERMINAL	SWITCH
tr'lvl3Sec2	LEVELTHREE	t'lvl3Room9	lvl3Room4	TERMINAL	SWITCH
tr'lvl3Sec3	LEVELTHREE	t'lvl3Room9	lvl3Room6	TERMINAL	SWITCH
tr'lvl3Sec4	LEVELTHREE	t'lvl3Room9	lvl3Room8	TERMINAL	SWITCH
tr'lvl3Sec5	LEVELTHREE	t'lvl3Room8	lvl3Room5	TERMINAL	SWITCH
tr'lvl3Sec6	LEVELTHREE	t'lvl3Room8	lvl3Room2	TERMINAL	SWITCH
tr'lvl3End	LEVELTHREE	t'lvl3Room2	lvl3Room2END	TERMINAL	SWITCH

3.2.6 Cylinders

ID	XT	YT	ZT	XR	YR	ZR	base Radius	top Radius	height	stacks	slices	R	G	B	A	LEVEL
lifePodCenter	-4	1	-1.5	90	0	0	0.5	0.5	2	50	50	0	0.80	0.8195	1	LEVELZERO
lifePodBot	-4	0	-1.5	90	0	0	0.0503	1	1	50	50	0.5	0.5	0.5	1	LEVELZERO
lifePodTop	-4	1	-1.5	90	0	0	1	0.5	0.5	50	50	0.5	0.5	0.5	1	LEVELZERO
kiosk1	5	1	25	90	0	0	0.5	0.5	2	50	50	0	0.75	1	0.598	LEVELONE
kiosk2	-5	1	25	90	0	0	0.5	0.5	2	50	50	0	0.75	1	0.598	LEVELONE
power1	-2	1	-5	90	0	0	0.5	0.5	2	50	50	1	0.8397	0	1	LEVELTHREE
power2	2	1	-5	90	0	0	0.5	0.5	2	50	50	1	0.8397	0	1	LEVELTHREE
power3	-2	1	-18	90	0	0	0.5	0.5	2	50	50	1	0.8397	0	1	LEVELTHREE
power4	2	1	-18	90	0	0	0.5	0.5	2	50	50	1	0.8397	0	1	LEVELTHREE
power1BaseBot	-2	0	-5	90	0	0	0.70	0.70	1	50	50	0.201	0.201	0.201	1	LEVELTHREE
power1BaseTop	-2	1	-5	90	0	0	0.70	0.70	0.5	50	50	0.201	0.201	0.201	1	LEVELTHREE
power2BaseBot	2	0	-5	90	0	0	0.70	0.70	1	50	50	0.201	0.201	0.201	1	LEVELTHREE
power2BaseTop	2	1	-5	90	0	0	0.70	0.70	0.5	50	50	0.201	0.201	0.201	1	LEVELTHREE
power3BaseBot	-2	0	-18	90	0	0	0.70	0.70	1	50	50	0.201	0.201	0.201	1	LEVELTHREE
power3BaseTop	-2	1	-18	90	0	0	0.70	0.70	0.5	50	50	0.201	0.201	0.201	1	LEVELTHREE
power4BaseBot	2	0	-18	90	0	0	0.70	0.70	1	50	50	0.201	0.201	0.201	1	LEVELTHREE
power4BaseTop	2	1	-18	90	0	0	0.70	0.70	0.5	50	50	0.201	0.201	0.201	1	LEVELTHREE

3.3 Images

3.3.1 Main Menu



3.3.2 Terminal Banner



3.3.3 Game Icon



3.4 Music