
Serializable
ConstantUtils
ZERO Integer
ONE Integer
CONNECT_SUCCESS String
CONNECT_FAIL String
TWENTY_SIX String
NO_USER String
TWENTY_THREE String
TWENTY_EIGHT String
DISCONNECT_MESSAGE String
TWENTY_TWO int
TWO Integer
TWENTY_ONE int
TWENTY String
TWENTY_SIX int
NEW_USER_MESSAGE String
SPACE String
NULLSTRING String
CHATROOM_SIZE Integer
NINETEEN int
TWENTY_FOUR int
FIVE Integer
EQUAL Integer
SEVEN Integer
TWENTY_SEVEN int
DATE_FORMAT String
SERVER_WAITING_MESSAGE String
TWENTY_THREE_INT int
TWENTY_SIX_INT int
TWENTY_EIGHT_INT int
NEW_CLIENT_MESSAGE String
SERVER_CLOSE_MESSAGE String
USER_THREAD_ERROR String
SERVER_NOT_FOUND_MESSAGE String
IO_MESSAGE String
INPUT_STREAM_ERROR_MESSAGE String
SERVER_READING_ERROR String
UNKNOWN_HOSTNAME_MESSAGE String
GET_USERNAME String
NINETEEN_STR String
ARROW String
MESSAGE_SENT String
MESSAGE_SEND_ERROR String
SIX Integer
THREE Integer
COMMA String
CONNECTED_USERS String
AT_USER String
AT_ALL String
TWENTY_FOUR_STRING String
TWENTY_FIVE_STRING String
DECLARATION String
TWENTY_SEVEN_STRING String
usersrunning static String
GAME_OFF String
WHO String
protocolMapping Map<String, Integer>
COMMAND String
RULLE_INPUT String
DIRNAME_DIRECTORY String
DIRNAME_FILE String
ThreadDie
serialVersionUID long
backtrace Object
detailMessage String
SUPPRESSED_SENTINEL List<Throwable>
NULL_CAUSE_MESSAGE String
SELF_SUPPRESSION_MESSAGE String
CAUSE_CAPTION String
SUPPRESSED_CAPTION String
EMPTY_THROWABLE_ARRAY Throwable[]
Throwable()
Throwable(String)
Throwable(String, Throwable)
Throwable(Throwable)
Throwable(String, Throwable, boolean, boolean)
initCause(Throwable) Throwable
toString() String
printStackTrace() void
printStackTrace(PrintStream) void
printStackTrace(PrintWriter) void
printStackTrace(PrintStream[], String, String, IdentityHashMap<Throwable,Integer>) void
printStackTrace(IdentityHashMap<Throwable,Integer>) void
fillInStackTrace() Throwable
fillInStackTrace(int) Throwable
getStackTrace() StackTraceElement[]
readObject(ObjectInputStream) void
writeObject(ObjectOutputStream) void
addSuppressed(Throwable) void
cause Throwable
message String
suppressed Throwable[]
localizedMessage String
stackTrace StackTraceElement[]
Protocol
Exception
serialVersionUID long
Exception()
Exception(String)
Exception(String, Throwable)
Exception(Throwable)
Exception(String, Throwable, boolean, boolean)
FunctionalInterface
PrintStreamWriter
PrintStream(PrintWriter)
lock Object
print(Object) void
SetLineBuilder
STACK_TRACE_ELEMENT_SENTINEL StackTraceElement
STACK_TRACE_METHOD_NAME_FILTER BiPredicate<String>
SetLineBuilder()
DirectMessage
process(String, String)
ConnectResponse
process(String, String)
FailedMessage
QueryUser
DisconnectMessage
DisconnectResponse
ConnectMessage
SendDirect
process(String, String)
BroadcastMessage
process(String, String)
QueryResponse
process(String, String)
InvalidIdentifierException
InvalidIdentifierException(String)
State
NEW
RUNNABLE
BLOCKED
WAITING
TIMED_WAITING
TERMINATED
State()
UncaughtExceptionHandler
uncaught(Throwable, Throwable) void
Runnable
run() void
WrappedPrintStream
print(Object) PrintStream
WrappedPrintStream(PrintStream)
lock() Object
print(Object) void
WrappedPrintWriter
print(Object) PrintWriter
lock() Object
print(Object) void
Thread
name String
priority int
daemon boolean
stillborn boolean
eetop long
target Runnable
group ThreadGroup
contextClassLoader ClassLoader
inheritedAccessControlContext AccessControlContext
threadInitNumber int
threadLocals ThreadLocalMap
inheritableThreadLocals ThreadLocalMap
stackSize long
nativeParkEventPointer long
tid long
threadSeqNumber long
threadStatus int
parkBlocker Object
blocker Interruptible
blockerLock Object
MIN_PRIORITY int
NORM_PRIORITY int
MAX_PRIORITY int
EMPTY_STACK_TRACE StackTraceElement[]
uncaughtExceptionHandler UncaughtExceptionHandler
defaultUncaughtExceptionHandler UncaughtExceptionHandler
threadLocalRandomSeed long
threadLocalRandomProbe int
threadLocalRandomSecondarySeed int
Thread(ThreadGroup, Runnable, String, long, AccessControlContext, boolean)
Thread()
Thread(Runnable)
Thread(Runnable, AccessControlContext)
Thread(ThreadGroup, Runnable)
Thread(String)
Thread(ThreadGroup, String)
Thread(Runnable, String)
Thread(ThreadGroup, Runnable, String)
Thread(ThreadGroup, Runnable, String, long)
Thread(ThreadGroup, Runnable, String, long, boolean)
registerNatives() void
currentThread() Thread
yield() void
sleep(long) void
sleep(long, int) void
onSpinWait() void
clone() Object
start() void
exit() void
run() void
init() void
stop() void
interrupt() void
interrupted() boolean
isInterrupted(boolean) boolean
suspend() void
resume() void
countStackFrames() int
enumerate(Thread[]) int
setPriorityImpl() void
dumpThreads(Thread[]) void
getThreads() Thread[]
setDefaultUncaughtExceptionHandler(UncaughtExceptionHandler) void
getDefaultUncaughtExceptionHandler() UncaughtExceptionHandler
dispatchUncaughtException(Throwable) void
processDeadReferenceQueue(ReferenceQueue<Class<?>>, ConcurrentMap<? extends WeakReference<Class<?>>,?>) void
setPriority0(int) void
stop0(Object) void
suspend0() void
resume0() void
interrupt0() void
setNativeName(String) void
name String
contextClassLoader ClassLoader
priority int
alive boolean
state State
daemon boolean
eat long
uncaughtExceptionHandler UncaughtExceptionHandler
interrupted boolean
threadGroup ThreadGroup
stackTrace StackTraceElement[]
ByteStringParserUtils
stringToByte(String) byte[]
byteToString(byte[]) String
PatternUtils
getInstance(String, String)
UserThread
socket Socket
server Server
writer PrintWriter
UserThread(Socket, Server)
run() void
copyMessageToWriter() void
Server
userThreads Vector<UserThread>
userNames Vector<String>
users Map<String, UserThread>
rand Random
grammar Grammar
port Integer
Server(Integer)
run() void
broadcast(String, UserThread) void
sendToAll(String, String) void
sendToAll(String, UserThread) void
processRequestsAgent() UserThread[]
main(String...) void
WriteThread
writer PrintWriter
socket Socket
client Client
valid Boolean
WriteThread(Socket, Client)
run() void
WeakClassKey
hash int
WeakClassKey(Class<?>, ReferenceQueue<Class<?>>)
hashCode() int
equals(Object) boolean
Caches
subclassAuditsCache ConcurrentMap<WeakClassKey, Boolean>
subclassAuditQueue ReferenceQueue<Class<?>>
Caches()
ReadThread
reader BufferedReader
socket Socket
ReadThread(Socket)
run() void
Client
ipAddress String
port int
Client(String, int)
run() void
main(String...) void
equals(Object) boolean
hashCode() int
toString() String
userName String
extends
extends
extends