

**Customer Name:** UNILEVER Job Name: OW KNORR MASALA 31.5G (RS.30) Job card #: 23070174 Structure: PET (12 $\mu$ )+BOPP.COM (18 $\mu$ ) Dispatched Date: 27-Jul-23 **Production Date:** 25-Jul-23 **Best Before:** 6 Months **Sampling Plan:** SOP-QA-11-19 10109.68Kg Vehicle Number: TMK919 **Dispatch Quantity:** S.NO Unit **Results** Standard **Test method Parameters** 1 Grammage 35-41 ISO 536 g/m<sup>2</sup> 36.8 Width 2 244-246 245 Internal mm Coef of Fr. Dynamic Face/Face 0.229-0.232 ASTM-D1894 Number 0.262 3 Coef of Fr. Dynamic Reverse/Face Number 0.322 4 0.318 - 0.323ASTM-D1894 Coef of Fr. Dynamic Reverse/Metal 5 0.17-0.201 ASTM-D1894 Number 0.185 Coef of Fr. Dynamic Reverse/Reverse 6 0.337-0.358 ASTM-D1894 Number 0.351 Coef of Fr. Static Face/Face 0.243 7 0.238-0.244 ASTM-D1894 Number Coef of Fr. Static Face/Metal 8 0.18-0.201 ASTM-D1894 Number 0.189 9 Coef of Fr. Static Reverse/Face 0.337-0.358 ASTM-D1894 Number 0.347 Coef of Fr. Static Reverse/Metal 10 0.18-0.212 ASTM-D1894 Number 0.209 11 Repeat Length 144-146 Internal 145 mm Seal Strenght **ASTM F88** N/15mm 4.8 12 4.5 Thickness 32.5-37.5 DIN 53370 13 μm Lamination Quality N/A OK 14 ASTM-F904 N/A **Print Quality** 15 N/A Visual Test N/A OK Machineability 16 N/A Undefined N/A OK 17 **Odour in Laminates** N/A ISO-13302 N/A ОК

Remarks: Storage condition, Temperature should be below 30°C & 50% humidity.

Universal Packaging Company(pvt) Ltd. Plot No : GA-65-66-A4-A5, Korangi Creek National Industrial park, Korangi Town Karachi,Pakistan