

Universal Packaging Company (Pvt) Ltd Certificate Of Analysis REC-QA-34-22 Effective Date 12.12.2022 Rev:0 Page 1 of 1

Customer Name: REEL RIN WP 500G X 24 CP UNILEVER Job Name: Job card #: 23090016 Structure: PET (10μ) + M.LDPE (60μ) Dispatched Date: 13-Sep-23 **Production Date:** 10-Sep-23 **Best Before:** 6 Months **Sampling Plan:** SOP-QA-11-19 C-1391 Vehicle Number: **Dispatch Quantity:** 406,353.00

S.NO	Parameters	Target	Min	Max	Test method	Unit	Results
1	Grammage	71.52	65.07	79.97	ISO 536	g/m²	74.8
2	Reel Width	450	449	451	Internal	mm	450
3	Coef of Fr. Dynamic face\face	0.25	0.22	0.28	ASTM D1894	Number	0.28
4	Coef of Fr. Dynamic Reverse\Reverse	0.23	0.2	0.26	ASTM D1894	Number	0.23
5	Coef of Fr. Static face\face	0.23	0.2	0.26	ASTM D1894	Number	0.25
6	Coef of Fr. Static Reverse\Face	0.25	0.22	0.28	ASTM D1894	Number	0.26
7	Lamination Strength	1.25	1.1	-	F 904-98	N/15mm	2.49
8	Repeat Length	220	218	222	Internal	mm	220
9	Seal Strength	10	7.3	-	ASTM F88	N/15mm	32
10	Tensile Strength @ Break (CD)	41	37	-	ASTM D882	N/mm²	39
11	Tensile Strength @ Break F - max (CD)	45	37	-	ASTM D882	N/15mm	42
12	Tensile Strength @ Break (MD)	32	27	-	ASTM D882	N/mm²	31
13	Tensile Strength @ Break F - max (MD)	35	27	-	ASTM D882	N/15mm	30
14	Thickness	72.75	65.98	79.53	DIN 53370	μ	74

Remarks: Storage condition, Temperature should be below 30°C & 50% humidity.

Note: System generated document signature donot required.

Universal Packaging Company(pvt) Ltd. Plot No : GA-65-66-A4-A5, Korangi Creek National Industrial park, Korangi Town Karachi, Pakistan