



اَوْنُوْرْسِيْتِيْ تِيْكْنُوْلُوْجِيْ مَّارَا
UNIVERSITI
TEKNOLOGI
MARA

ITT544: WEB TECHNOLOGY

PREPARED FOR

MOHD ALI BIN MOHD ISA

NAME	ID NO
NUR ALYA BATRISYIA BINTI MOHD HAIZAN	2017696612
SITI NUR HANISAH BINTI IBRAHIM	2017696598
SITI SALIZA BINTI MD SAID	2017696632
NURUL HASANAH BINTI ZAKARIA	2017696634

COMPANY BACKGROUND

Jasin Pizza will be owned and operated by Jasin Pizza, LLC, a limited liability company with the sole member being Salnis Alsahaza. Jasin Pizza will be located at 1525 Wilson Blvd. in Jasin, Melaka. Jasin Pizza, LLC, will maintain a corporate office at the same address. The facility is a pre-existing lease space of approximately 1500 square feet. Jasin Pizza will be a family owned pizza restaurant featuring hand-tossed New York style pizza, chicken wings and toasted subs. The restaurant will offer a dine-in buffet, carryout and delivery to the surrounding neighborhoods and area businesses. The signature crust and mouthwatering sauce featured at Jasin Pizza are from family recipes that have been passed down from generation to generation.

SOURCE CODE

pizza.model (UserBean.java)

```
package pizza.model;

public class UserBean {

    private String email;
    private String firstname;
    private String lastname;
    private String address;
    private String phone;
    private String password;
    public boolean valid;

    public String getEmail() {
        return email;
    }

    public void setEmail(String email) {
        this.email = email;
    }

    public String getFirstname() {
        return firstname;
    }

    public void setFirstname(String firstname) {
        this.firstname = firstname;
    }

    public String getLastname() {
        return lastname;
    }

    public void setLastname(String lastname) {
        this.lastname = lastname;
    }

    public String getAddress() {
        return address;
    }

    public void setAddress(String address) {
        this.address = address;
    }

    public String getPhone() {
        return phone;
    }

    public void setPhone(String phone) {
        this.phone = phone;
    }
}
```

```

    public String getPassword() {
        return password;
    }

    public void setPassword(String password) {
        this.password = password;
    }

    public boolean isValid() {
        return valid;
    }

    public void setValid(boolean valid) {
        this.valid = valid;
    }
}

```

pizza.model (OrderBean.java)

```

package pizza.model;

public class OrderBean {

    private int orderid;
    private String crust;
    private String extracheese;
    private String topping;
    private int quantity;
    private String email;

    public int getOrderid() {
        return orderid;
    }

    public void setOrderid(int orderid) {
        this.orderid = orderid;
    }

    public String getCrust() {
        return crust;
    }

    public void setCrust(String crust) {
        this.crust = crust;
    }

    public String getExtracheese() {
        return extracheese;
    }

    public void setExtracheese(String extracheese) {

```

```

        this.extracheese = extracheese;
    }

    public String getTopping() {
        return topping;
    }

    public void setTopping(String topping) {
        this.topping = topping;
    }

    public int getQuantity() {
        return quantity;
    }

    public void setQuantity(int quantity) {
        this.quantity = quantity;
    }

    public String getEmail() {
        return email;
    }

    public void setEmail(String email) {
        this.email = email;
    }

    @Override
    public String toString() {
        return "OrderBean [orderid=" + orderid + ", crust=" + crust
            + ", extracheese=" + extracheese + ", topping=" +
topping
            + ", quantity=" + quantity + ", email=" + email +
" ]";
    }
}

```

pizza.controller (LoginController.java)

```
package pizza.controller;

import java.io.IOException;
import java.security.NoSuchAlgorithmException;

import javax.servlet.RequestDispatcher;
import javax.servlet.ServletException;
import javax.servlet.http.HttpServlet;
import javax.servlet.http.HttpServletRequest;
import javax.servlet.http.HttpServletResponse;
import javax.servlet.http.HttpSession;
import pizza.dao.OrderDAO;
import pizza.dao.UserDAO;
import pizza.model.UserBean;

/**
 * Servlet implementation class UserController
 */
public class LoginController extends HttpServlet {
    private static final long serialVersionUID = 1L;
    private UserDAO dao;
    HttpServletRequest request;
    HttpServletResponse response;
    String forward="";
    String action="";

    /**
     * @see HttpServlet#HttpServlet()
     */
    public LoginController() {
        super();
        dao = new UserDAO();
        // TODO Auto-generated constructor stub
    }

    /**
     * @see HttpServlet#doGet(HttpServletRequest request,
    HttpServletResponse response)
     */
    protected void doGet(HttpServletRequest request, HttpServletResponse
    response) throws ServletException, IOException {
        // TODO Auto-generated method stub

        action = request.getParameter("action");

        try {

            UserBean user = new UserBean();
            user.setEmail(request.getParameter("email"));
            user.setPassword(request.getParameter("password"));

            user = UserDAO.login(user);

            if(user.isValid())
```

```

        {
            HttpSession session = request.getSession(true);
            session.setAttribute("currentSessionUser",
user.getEmail());

            response.sendRedirect("/PizzaOrdering/customer/index.jsp"); // logged-
in page
        }
        else
        {

            response.sendRedirect("/PizzaOrdering/invalidLogin.jsp");
        }

    }

    catch (Throwable ex) {
        System.out.println(ex);
    }
}
}

```

pizza.controller (AccountController.java)

```

package pizza.controller;

import java.io.IOException;
import java.security.NoSuchAlgorithmException;
import javax.servlet.*;
import javax.servlet.http.*;
import pizza.dao.UserDAO;
import pizza.model.UserBean;

/**
 * Servlet implementation class UserServlet
 */
public class AccountController extends HttpServlet {
    private static final long serialVersionUID = 1L;
    private static String LOGIN = "/login.jsp";
    private static String REGISTER = "/register.jsp";
    private static String UPDATE = "/customer/updateAccount.jsp";
    private static String INDEX = "/customer/index.jsp";
    private static String VIEW = "/customer/viewAccount.jsp";
    private UserDAO dao;
    String forward="";

    /**
     * @see HttpServlet#HttpServlet()
     */
    public AccountController() {
        super();
        dao = new UserDAO();
        // TODO Auto-generated constructor stub
    }
}

```

```

    protected void doGet(HttpServletRequest request, HttpServletResponse
response) throws ServletException, IOException {
    // TODO Auto-generated method stub

    String action = request.getParameter("action");

    if (action.equalsIgnoreCase("updateAccount")){
        forward = UPDATE;
        String email = request.getParameter("email");
        UserBean user = dao.getUserByEmail(email);
        request.setAttribute("user", user);
    }
    else if (action.equalsIgnoreCase("viewAccount")){
        forward = VIEW;
        String email= request.getParameter("email");
        UserBean user = dao.getUserByEmail(email);
        request.setAttribute("user", user);
    }
    else {
        forward = REGISTER;
    }

    RequestDispatcher view = request.getRequestDispatcher(forward);
    view.forward(request, response);
}

/**
 * @see HttpServlet#doPost(HttpServletRequest request,
HttpServletResponse response)
 */
protected void doPost(HttpServletRequest request, HttpServletResponse
response) throws ServletException, IOException {
    // TODO Auto-generated method stub

    UserBean user = new UserBean();
    user.setEmail(request.getParameter("email"));
    user.setFirstname(request.getParameter("firstname"));
    user.setLastname(request.getParameter("lastname"));
    user.setAddress(request.getParameter("address"));
    user.setPhone(request.getParameter("phone"));
    user.setPassword(request.getParameter("password"));

    String email = request.getParameter("email");

    user.setEmail(email);

    user = UserDao.getUser(user);

    if (!user.isValid()){
        try {
            dao.add(user);
        } catch (NoSuchAlgorithmException e) {
            // TODO Auto-generated catch block
            e.printStackTrace();
        }

        response.sendRedirect("login.jsp");
    }
}

```



```

    }

    else{
        try {
            dao.updateAccount(user);
        } catch (NoSuchAlgorithmException e) {
            // TODO Auto-generated catch block
            e.printStackTrace();
        }

        RequestDispatcher view = request.getRequestDispatcher(VIEW);
        request.setAttribute("user", dao.getUserByEmail(email));
        view.forward(request, response);
    }
}
}

```

pizza.controller (OrderController.java)

```

package pizza.controller;

import java.io.IOException;

import javax.servlet.RequestDispatcher;
import javax.servlet.ServletException;
import javax.servlet.http.HttpServlet;
import javax.servlet.http.HttpServletRequest;
import javax.servlet.http.HttpServletResponse;

import pizza.dao.OrderDAO;
import pizza.model.OrderBean;

/**
 * Servlet implementation class OrderController
 */
public class OrderController extends HttpServlet {
    private static final long serialVersionUID = 1L;
    private static String INSERT = "/customer/order.jsp";
    private static String LIST_PIZZA = "/customer/listOrder.jsp";
    private OrderDAO dao;
    String forward="";

    /**
     * @see HttpServlet#HttpServlet()
     */
    public OrderController() {
        super();
        dao = new OrderDAO();
        // TODO Auto-generated constructor stub
    }

    /**
     * @see HttpServlet#doGet(HttpServletRequest request,
     HttpServletResponse response)
     */
}

```

```

        protected void doGet(HttpServletRequest request, HttpServletResponse
response) throws ServletException, IOException {
            // TODO Auto-generated method stub
            String action = request.getParameter("action");

            if (action.equalsIgnoreCase("listOrder")){
                String email= request.getParameter("email");
                forward = LIST_PIZZA;
                request.setAttribute("pizzas", dao.getAllUserOrder(email));
            }else {
                forward = INSERT;
            }

            RequestDispatcher view = request.getRequestDispatcher(forward);
            view.forward(request, response);
        }

        /**
         * @see HttpServlet#doPost(HttpServletRequest request,
HttpServletResponse response)
         */
        protected void doPost(HttpServletRequest request, HttpServletResponse
response) throws ServletException, IOException {
            // TODO Auto-generated method stub

            OrderBean pizza = new OrderBean();
            pizza.setCrust(request.getParameter("crust"));
            pizza.setExtracheese(request.getParameter("extracheese"));
            pizza.setTopping(request.getParameter("topping"));

            pizza.setQuantity(Integer.parseInt(request.getParameter("quantity")));
            pizza.setEmail(request.getParameter("email"));

            String orderid = request.getParameter("orderid");
            String email = request.getParameter("email");

            if(orderid == null || orderid.isEmpty()){
                dao.add(pizza);
            }
            else{
                pizza.setOrderid(Integer.parseInt(orderid));
                dao.updateOrder(pizza);
            }

            forward = LIST_PIZZA;
            request.setAttribute("pizzas", dao.getAllUserOrder(email));
            RequestDispatcher view = request.getRequestDispatcher(forward);
            view.forward(request, response);
        }
    }
}

```

pizza.dao (UserDAO.java)

```
package pizza.dao;

import java.util.*;
import java.sql.*;
import java.security.MessageDigest;
import java.security.NoSuchAlgorithmException;
import pizza.model.UserBean;
import com.pizza.ConnectionManager;

public class UserDAO {
    static Connection currentCon = null;
    static ResultSet rs = null;
    static PreparedStatement ps=null;
    static Statement stmt=null;
    static String email, firstname, lastname, address, phone, password;

    //login
    public static UserBean login(UserBean bean) throws
    NoSuchAlgorithmException {

        email = bean.getEmail();
        password = bean.getPassword();

        //convert the password to MD5
        MessageDigest md = MessageDigest.getInstance("MD5");
        md.update(password.getBytes());

        byte byteData[] = md.digest();

        //convert the byte to hex format
        StringBuffer sb = new StringBuffer();
        for (int i = 0; i < byteData.length; i++) {
            sb.append(Integer.toString((byteData[i] & 0xff) + 0x100,
16).substring(1));
        }

        String searchQuery = "select * from users where email='" + email + "'
AND password='" + sb.toString() + "'";

        System.out.println("Your email is " + email);
        System.out.println("Your password is " + password);
        System.out.println("Query: " + searchQuery);

        try {
            currentCon = ConnectionManager.getConnection();
            stmt = currentCon.createStatement();
            rs = stmt.executeQuery(searchQuery);
            boolean more = rs.next();

            // if user exists set the isValid variable to true
            if (more) {
                String email = rs.getString("email");

                System.out.println("Welcome " + email);
            }
        }
    }
}
```

```

        bean.setEmail(email);
        bean.setValid(true);
    }

    // if user does not exist set the isValid variable to false
    else if (!more) {
        System.out.println("Sorry, you are not a registered user!
Please sign up first");
        bean.setValid(false);
    }
}

catch (Exception ex) {
    System.out.println("Log In failed: An Exception has occurred! " +
ex);
}

finally {
    if (rs != null) {
        try {
            rs.close();
        } catch (Exception e) {
        }
        rs = null;
    }

    if (stmt != null) {
        try {
            stmt.close();
        } catch (Exception e) {
        }
        stmt = null;
    }

    if (currentCon != null) {
        try {
            currentCon.close();
        } catch (Exception e) {
        }

        currentCon = null;
    }
}

return bean;
}

//add new user (register)
public void add(UserBean bean) throws NoSuchAlgorithmException{

    email = bean.getEmail();
    firstname = bean.getFirstname();
    lastname = bean.getLastname();
    address = bean.getAddress();
    phone = bean.getPhone();
    password = bean.getPassword();

```

```

MessageDigest md = MessageDigest.getInstance("MD5");
md.update(password.getBytes());

byte byteData[] = md.digest();

//convert the byte to hex format
StringBuffer sb = new StringBuffer();
for (int i = 0; i < byteData.length; i++) {
    sb.append(Integer.toString((byteData[i] & 0xff) + 0x100,
16).substring(1));
}

String pass = sb.toString();

try {
    currentCon = ConnectionManager.getConnection();
    ps=currentCon.prepareStatement("insert into users
(email,firstname,lastname,address,phone,password)values(?,?,?,?,?,?,?)");
    ps.setString(1,email);
    ps.setString(2,firstname);
    ps.setString(3,lastname);
    ps.setString(4,address);
    ps.setString(5,phone);
    ps.setString(6,pass);
    ps.executeUpdate();

    System.out.println("Your email is " + email);
    System.out.println("Your password is " + pass);

}

catch (Exception ex) {
    System.out.println("failed: An Exception has occurred! " + ex);
}

finally {
    if (ps != null) {
        try {
            ps.close();
        } catch (Exception e) {
        }
        ps = null;
    }

    if (currentCon != null) {
        try {
            currentCon.close();
        } catch (Exception e) {
        }
        currentCon = null;
    }
}

}

public void deleteUser(String email) {
    try {

```

```

        currentCon = ConnectionManager.getConnection();
        ps=currentCon.prepareStatement("delete from users where
email=?");
        ps.setString(1, email);
        ps.executeUpdate();

    } catch (SQLException e) {
        e.printStackTrace();
    }
}

//update account
public void updateAccount(UserBean bean) throws NoSuchAlgorithmException
{

    email = bean.getEmail();
    address = bean.getAddress();
    phone = bean.getPhone();
    password = bean.getPassword();

    //convert the password to MD5
    MessageDigest md = MessageDigest.getInstance("MD5");
    md.update(password.getBytes());

    byte byteData[] = md.digest();

    //convert the byte to hex format
    StringBuffer sb = new StringBuffer();
    for (int i = 0; i < byteData.length; i++) {
        sb.append(Integer.toString((byteData[i] & 0xff) + 0x100,
16).substring(1));
    }

    String searchQuery = "UPDATE users SET address='" + address + "',
phone='" + phone + "', password='" + sb.toString() + "' WHERE email= '" +
email + "'";

    try {

        currentCon = ConnectionManager.getConnection();
        stmt = currentCon.createStatement();
        stmt.executeUpdate(searchQuery);

    } catch (SQLException e) {
        e.printStackTrace();
    }
}

//get all user
public List<UserBean> getAllUser() {
    List<UserBean> users = new ArrayList<UserBean>();
    try {
        currentCon = ConnectionManager.getConnection();
        stmt = currentCon.createStatement();
        ResultSet rs = stmt.executeQuery("select * from users");

        while (rs.next()) {

```

```

        UserBean user = new UserBean();
        user.setEmail(rs.getString("email"));
        user.setPassword(rs.getString("password"));
        users.add(user);
    }
} catch (SQLException e) {
    e.printStackTrace();
}

return users;
}

//get user by email
public UserBean getUserByEmail(String email) {
    UserBean user = new UserBean();
    try {
        currentCon = ConnectionManager.getConnection();
        ps=currentCon.prepareStatement("select * from users where
email=?");

        ps.setString(1, email);

        ResultSet rs = ps.executeQuery();

        if (rs.next()) {

            user.setEmail(rs.getString("email"));
            user.setFirstname(rs.getString("firstname"));
            user.setLastname(rs.getString("lastname"));
            user.setAddress(rs.getString("address"));
            user.setPhone(rs.getString("phone"));
            user.setPassword(rs.getString("password"));
        }
    } catch (SQLException e) {
        e.printStackTrace();
    }

    return user;
}

//get user by email
public static UserBean getUser(UserBean bean) {

    email = bean.getEmail();

    String searchQuery = "select * from users where email='" + email +
    "'";

    try {
        currentCon = ConnectionManager.getConnection();
        stmt = currentCon.createStatement();
        rs = stmt.executeQuery(searchQuery);
        boolean more = rs.next();

        // if user exists set the isValid variable to true
        if (more) {
            String email = rs.getString("email");

```

```

        bean.setEmail(email);
        bean.setValid(true);
    }

    else if (!more) {
        System.out.println("Sorry");
        bean.setValid(false);
    }

}

catch (Exception ex) {
    System.out.println("Log In failed: An Exception has occurred! " +
ex);
}

finally {
    if (rs != null) {
        try {
            rs.close();
        } catch (Exception e) {
        }
        rs = null;
    }

    if (stmt != null) {
        try {
            stmt.close();
        } catch (Exception e) {
        }
        stmt = null;
    }

    if (currentCon != null) {
        try {
            currentCon.close();
        } catch (Exception e) {
        }

        currentCon = null;
    }
}

return bean;
}
}

```


pizza.dao (OrderDAO.java)

```
package pizza.dao;

import java.util.*;
import java.sql.*;
import pizza.model.OrderBean;
import com.pizza.ConnectionManager;

public class OrderDAO {
    static Connection currentCon = null;
    static ResultSet rs = null;
    static PreparedStatement ps=null;
    static Statement stmt=null;

    //add new order
    public void add(OrderBean bean) {

        int orderid = bean.getOrderid();
        String crust = bean.getCrust();
        String extracheese = bean.getExtracheese();
        String topping = bean.getTopping();
        int quantity = bean.getQuantity();
        String email = bean.getEmail();

        try {
            currentCon = ConnectionManager.getConnection();
            ps=currentCon.prepareStatement("insert into orders (crust,
extracheese, topping, quantity, email)values(?,?,?,?,?)");
            ps.setString(1,crust);
            ps.setString(2,extracheese);
            ps.setString(3,topping);
            ps.setInt(4,quantity);
            ps.setString(5,email);
            ps.executeUpdate();
        }

        catch (Exception ex) {
            System.out.println("failed: An Exception has occurred! " + ex);
        }

        finally {
            if (ps != null) {
                try {
                    ps.close();
                } catch (Exception e) {
                }
                ps = null;
            }

            if (currentCon != null) {
                try {
                    currentCon.close();
                } catch (Exception e) {
                }
                currentCon = null;
            }
        }
    }
}
```

```

        }
    }
    //return bean;
}

//update order
public void updateOrder(OrderBean bean) {

    int orderid = bean.getOrderid();
    String crust = bean.getCrust();
    String extracheese = bean.getExtracheese();
    String topping = bean.getTopping();
    int quantity = bean.getQuantity();
    String email = bean.getEmail();

    String searchQuery = "UPDATE orders SET crust= '" + crust + "',
extracheese='" + extracheese + "', topping='" + topping + "', quantity='" +
quantity + "', email='" + email + "' WHERE orderid= '" + orderid + "'";

    try {

        currentCon = ConnectionManager.getConnection();
        stmt = currentCon.createStatement();
        stmt.executeUpdate(searchQuery);

    } catch (SQLException e) {
        e.printStackTrace();
    }
}

//list order by email (customer)
public List<OrderBean> getAllUserOrder(String email) {

    List<OrderBean> pizzas = new ArrayList<OrderBean>();

    try {
        currentCon = ConnectionManager.getConnection();
        stmt = currentCon.createStatement();

        String q = "select * from orders where email = '" + email + "'";
        ResultSet rs = stmt.executeQuery(q);

        while (rs.next()) {
            OrderBean pizza = new OrderBean();
            pizza.setOrderid(rs.getInt("orderid"));
            pizza.setCrust(rs.getString("crust"));
            pizza.setExtracheese(rs.getString("extracheese"));
            pizza.setTopping(rs.getString("topping"));
            pizza.setQuantity(rs.getInt("quantity"));
            pizza.setEmail(rs.getString("email"));
            pizzas.add(pizza);
        }
    } catch (SQLException e) {
        e.printStackTrace();
    }
}

```

```

        return pizzas;
    }

    //get order by orderid
    public OrderBean getOrderById(int orderid) {
        OrderBean pizza = new OrderBean();
        try {
            currentCon = ConnectionManager.getConnection();
            ps=currentCon.prepareStatement("select * from orders where
orderid=?");

            ps.setInt(1, orderid);
            ResultSet rs = ps.executeQuery();

            if (rs.next()) {
                pizza.setOrderid(rs.getInt("orderid"));
                pizza.setCrust(rs.getString("crust"));
                pizza.setExtracheese(rs.getString("extracheese"));
                pizza.setTopping(rs.getString("topping"));
                pizza.setQuantity(rs.getInt("quantity"));
                pizza.setEmail(rs.getString("email"));
            }
        } catch (SQLException e) {
            e.printStackTrace();
        }

        return pizza;
    }

    //get order by email
    public OrderBean getOrderById(String email) {
        OrderBean pizza = new OrderBean();
        try {
            currentCon = ConnectionManager.getConnection();
            ps=currentCon.prepareStatement("select * from orders where email=?");

            ps.setString(1, email);
            ResultSet rs = ps.executeQuery();

            if (rs.next()) {
                pizza.setOrderid(rs.getInt("orderid"));
                pizza.setCrust(rs.getString("crust"));
                pizza.setExtracheese(rs.getString("extracheese"));
                pizza.setTopping(rs.getString("topping"));
                pizza.setQuantity(rs.getInt("quantity"));
                pizza.setEmail(rs.getString("email"));
            }
        } catch (SQLException e) {
            e.printStackTrace();
        }

        return pizza;
    }
}

```

View (login.jsp)

```
<%@ page language="java"
    contentType="text/html; charset=windows-1256"
    pageEncoding="windows-1256"
%>

<!DOCTYPE html>
<!--[if lt IE 7 ]><html class="ie ie6" lang="en"> <![endif]-->
<!--[if IE 7 ]><html class="ie ie7" lang="en"> <![endif]-->
<!--[if IE 8 ]><html class="ie ie8" lang="en"> <![endif]-->
<!--[if (gte IE 9) || (IE) ]><!--><html lang="en"> <!--<![endif]-->
<head>

    <!-- Basic Page Needs
    ===== -->
    <meta charset="utf-8">
    <title></title>

    <!-- Mobile Specific Metas
    ===== -->
    <meta name="viewport" content="width=device-width, initial-scale=1,
maximum-scale=1">

    <!-- CSS
    ===== -->
    <link rel="stylesheet" href="css/zerogrid.css">
    <link rel="stylesheet" href="css/style.css">
    <link rel="stylesheet" href="css/menu.css">
    <link rel="stylesheet" href="css/responsiveslides.css">
    <link href="font-awesome/css/font-awesome.min.css" rel="stylesheet"
type="text/css">

    <script src="js/jquery-latest.min.js"></script>
    <script src="js/script.js"></script>
    <script src="js/jquery183.min.js"></script>
    <script src="js/responsiveslides.min.js"></script>
    <script>
        // You can also use "$(window).load(function() {"
        $(function () {
            // Slideshow
            $("#slider").responsiveSlides({
                auto: true,
                pager: false,
                nav: true,
                speed: 500,
                namespace: "callbacks",
                before: function () {
                    $('.events').append("<li>before event fired.</li>");
                },
                after: function () {
                    $('.events').append("<li>after event fired.</li>");
                }
            });
        });
    </script>
```

[illegible]

[illegible]

[register.jsp](#)

```
%@ page language="java"
contentType="text/html; charset=windows-1256"
pageEncoding="windows-1256"
%>

<!DOCTYPE html>
<!--[if lt IE 7 ]><html class="ie ie6" lang="en"> <![endif]-->
<!--[if IE 7 ]><html class="ie ie7" lang="en"> <![endif]-->
<!--[if IE 8 ]><html class="ie ie8" lang="en"> <![endif]-->
<!--[if (gte IE 9) || (IE) ]><!--><html lang="en"> <!--<![endif]-->
<head>

    <!-- Basic Page Needs
    ===== -->
    <meta charset="utf-8">
    <title></title>

    <!-- Mobile Specific Metas
    ===== -->
    <meta name="viewport" content="width=device-width, initial-scale=1,
maximum-scale=1">

    <!-- CSS
    ===== -->
    <link rel="stylesheet" href="css/zerogrid.css">
    <link rel="stylesheet" href="css/style.css">
    <link rel="stylesheet" href="css/menu.css">
    <link rel="stylesheet" href="css/responsiveslides.css">
    <link href="font-awesome/css/font-awesome.min.css"
rel="stylesheet" type="text/css">

    <script src="js/jquery-latest.min.js"></script>
    <script src="js/script.js"></script>
    <script src="js/jquery183.min.js"></script>
    <script src="js/responsiveslides.min.js"></script>
    <script>
    // You can also use "$(window).load(function() {"
    $(function () {
        // Slideshow
        $("#slider").responsiveSlides({
            auto: true,
            pager: false,
            nav: true,
            speed: 500,
            namespace: "callbacks",
            before: function () {
                $('.events').append("<li>before event fired.</li>");
            },
            after: function () {
                $('.events').append("<li>after event fired.</li>");
            }
        });
    });
    </script>
```



```

        <div class="wrap-col">
            <input type="text"
name="lastname" id="lastname" placeholder="Enter Lastname"
required="required" />
        </div>
    </div>
</label>
<label class="row">
    <div class="col-1-2">
        <div class="wrap-col">
            <input type="text" name="address"
id="address" placeholder="Enter Address"/>
        </div>
    </div>
</label>
<label class="row">
    <div class="col-1-2">
        <div class="wrap-col">
            <input type="text" name="phone"
id="phone" placeholder="Enter Phone"/>
        </div>
    </div>
</label>
<label class="row">
    <div class="col-1-2">
        <div class="wrap-col">
            <input type="password"
name="password" id="password" placeholder="Enter Password"
required="required" />
        </div>
    </div>
</label>
<label class="row">
    <div class="wrap-col">
        <input class="submitButton"
type="submit" name="submitcontact" value="Submit">
    </div>
</label>
<label class="row">
    <div class="wrap-col">
        <input class="submitButton"
type="reset" name="submitcontact" value="Reset">
    </div>
</label>
<br/><a href="login.jsp">Login
Here</a><br/>

</form>

<!-- END OF FORM -->

</div>
</div>
</div>
</div>
</div>
</div>

```

```

        </div>
    </div>
</section>

<!--////////////////////////////////////Footer-->
<div class="copyright">
    <div class="zerogrid wrapper">
        Copyright 2017
    </div>
</div>

</div>
</body></html>

```

invalidLogin.jsp

```

<%@ page language="java"
    contentType="text/html; charset=windows-1256"
    pageEncoding="windows-1256"
%>

<!DOCTYPE html>
<!--[if lt IE 7 ]><html class="ie ie6" lang="en"> <![endif]-->
<!--[if IE 7 ]><html class="ie ie7" lang="en"> <![endif]-->
<!--[if IE 8 ]><html class="ie ie8" lang="en"> <![endif]-->
<!--[if (gte IE 9) || (IE) ]><!--><html lang="en"> <!--<![endif]-->
<head>

    <!-- Basic Page Needs
    ===== -->
    <meta charset="utf-8">
    <title>Jasin Pizza</title>

    <!-- Mobile Specific Metas
    ===== -->
    <meta name="viewport" content="width=device-width, initial-scale=1,
maximum-scale=1">

    <!-- CSS
    ===== -->
    <link rel="stylesheet" href="css/zerogrid.css">
    <link rel="stylesheet" href="css/style.css">
    <link rel="stylesheet" href="css/menu.css">
    <link rel="stylesheet" href="css/responsiveslides.css">
    <link href="font-awesome/css/font-awesome.min.css" rel="stylesheet"
type="text/css">

    <script src="js/jquery-latest.min.js"></script>
    <script src="js/script.js"></script>
    <script src="js/jquery183.min.js"></script>
    <script src="js/responsiveslides.min.js"></script>
    <script>
        // You can also use "$(window).load(function() {"
        $(function () {
            // Slideshow
            $("#slider").responsiveSlides({

```

```

        auto: true,
        pager: false,
        nav: true,
        speed: 500,
        namespace: "callbacks",
        before: function () {
            $(''.events').append("<li>before event fired.</li>");
        },
        after: function () {
            $(''.events').append("<li>after event fired.</li>");
        }
    });
});
</script>
</head>
<body>
<div class="wrap-body">

<!-- //////////////////////////////////////Top -->
<div class="top">
    <div class="zerogrid">
        <div class="row">
            <div class="f-left">
                <span><i class="fa fa-map-marker"></i> Jasin </span>
                <span><i class="fa fa-phone"></i> 06-26401111</span>
                <span><i class="fa fa-envelope"></i>
jasinpizza@gmail.com</span>
            </div>
            <div class="f-right">
            </div>
        </div>
    </div>
</div>

<!--////////////////////////////////////Container-->
<section id="container" class="home-page">
    <div class="wrap-container clearfix">
        <div id="main-content">
            <section><!--Start Box-->
                <div class="wrap-box">
                    <div class="zerogrid">
                        <div class="row">
                            <div class="col-2-3">
                                <div class="wrap-col">
                                    <div>
not a registered user
                                <br/><br/> OR
                                <br/>You entered wrong
                                <br/><a
href="login.jsp">Login Here</a>
                                    </div>
                                </div>
                            </div>
                        </div>
                    </div>
                </div>
            </section>
        </div>
    </div>
</section>

```

```

        <div class="wrap-col">
            <div class="sub-title">
                <h2></h2>
            </div>
        </div>
    </div>
    <div class="col-1-3">
        <div class="wrap-col">
            <div class="sub-title">
                <h2></h2>
            </div>
        </div>
    </div>
</div>
</section>
</div>
</div>
</body></html>

```

invalidAccount.jsp

```

<%@ page language="java"
    contentType="text/html; charset=windows-1256"
    pageEncoding="windows-1256"
%>

<!DOCTYPE html>
<!--[if lt IE 7 ]><html class="ie ie6" lang="en"> <![endif]-->
<!--[if IE 7 ]><html class="ie ie7" lang="en"> <![endif]-->
<!--[if IE 8 ]><html class="ie ie8" lang="en"> <![endif]-->
<!--[if (gte IE 9) || (IE)]><!--><html lang="en"> <!--<![endif]-->
<head>

    <!-- Basic Page Needs
    ===== -->
    <meta charset="utf-8">
    <title>Jasin Pizza</title>

    <!-- Mobile Specific Metas
    ===== -->
    <meta name="viewport" content="width=device-width, initial-scale=1,
maximum-scale=1">

    <!-- CSS
    ===== -->
    <link rel="stylesheet" href="css/zerogrid.css">
    <link rel="stylesheet" href="css/style.css">
    <link rel="stylesheet" href="css/menu.css">

```

```

    <link rel="stylesheet" href="css/responsiveslides.css">
    <link href="font-awesome/css/font-awesome.min.css" rel="stylesheet"
type="text/css">

    <script src="js/jquery-latest.min.js"></script>
    <script src="js/script.js"></script>
    <script src="js/jquery183.min.js"></script>
    <script src="js/responsiveslides.min.js"></script>
    <script>
        // You can also use "$(window).load(function() {"
        $(function () {
            // Slideshow
            $("#slider").responsiveSlides({
                auto: true,
                pager: false,
                nav: true,
                speed: 500,
                namespace: "callbacks",
                before: function () {
                    $('.events').append("<li>before event fired.</li>");
                },
                after: function () {
                    $('.events').append("<li>after event fired.</li>");
                }
            });
        });
    </script>

    <!--[if lt IE 8]>
        <div style=' clear: both; text-align:center; position: relative;'>
            <a href="http://windows.microsoft.com/en-US/internet-
explorer/products/ie/home?ocid=ie6_countdown_bannercode">
                
            </a>
        </div>
    <![endif]-->
    <!--[if lt IE 9]>
        <script src="js/html5.js"></script>
        <script src="js/css3-mediaqueries.js"></script>
    <![endif]-->

</head>
<body>
<div class="wrap-body">

<!-- //////////////////////////////////////Top -->
<div class="top">
    <div class="zerogrid">
        <div class="row">
            <div class="f-left">
                <span><i class="fa fa-map-marker"></i> Jasin </span>
                <span><i class="fa fa-phone"></i> 06-26401111</span>
            </div>
        </div>
    </div>
</div>

```

```

        <span><i class="fa fa-envelope"></i>
jasinpizza@gmail.com</span>
    </div>
    <div class="f-right">
    </div>
</div>
</div>
</div>
</div>
<!--////////////////////Container-->
<section id="container" class="home-page">
    <div class="wrap-container clearfix">
        <div id="main-content">
            <section><!--Start Box-->
                <div class="wrap-box">
                    <div class="zerogrid">
                        <div class="row">
                            <div class="col-2-3">
                                <div class="wrap-col">
                                    <div>
                                        <p>Email address
exists.Please choose different email address
                                        <br/><br/> OR
                                        <br/>Login to use the
                                        <br/><a
                                        </div>
                                        </div>
                                    </div>
                                <div class="col-1-3">
                                    <div class="wrap-col">
                                        <div class="sub-title">
                                            <h2></h2>
                                        </div>
                                    </div>
                                </div>
                                <div class="col-1-3">
                                    <div class="wrap-col">
                                        <div class="sub-title">
                                            <h2></h2>
                                        </div>
                                    </div>
                                </div>
                            </div>
                        </div>
                    </div>
                </div>
            </section>
        </div>
    </div>
</section>
</div>
</body></html>

```

Index.jsp

```
<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
pageEncoding="ISO-8859-1"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/fmt" prefix="fmt"%>

<%
    response.setHeader("Cache-Control","no-cache");
    response.setHeader("Cache-Control","no-store");
    response.setHeader("Pragma","no-cache");
    response.setDateHeader ("Expires", 0);

    if(session.getAttribute("currentSessionUser")==null)
        response.sendRedirect("/PizzaOrdering/login.jsp");

%>

<!DOCTYPE html>
<!--[if lt IE 7 ]><html class="ie ie6" lang="en"> <![endif]-->
<!--[if IE 7 ]><html class="ie ie7" lang="en"> <![endif]-->
<!--[if IE 8 ]><html class="ie ie8" lang="en"> <![endif]-->
<!--[if (gte IE 9) || (IE)]><!--><html lang="en"> <!--<![endif]-->
<head>

    <!-- Basic Page Needs
    ===== -->
    <meta charset="utf-8">
    <title>Jasin Pizza</title>

    <!-- Mobile Specific Metas
    ===== -->
    <meta name="viewport" content="width=device-width, initial-scale=1,
maximum-scale=1">

    <!-- CSS
    ===== -->
    <link rel="stylesheet" href="../../css/zerogrid.css">
    <link rel="stylesheet" href="../../css/style.css">
    <link rel="stylesheet" href="../../css/menu.css">
    <link rel="stylesheet" href="../../css/responsiveslides.css">
    <link href="../../PizzaOrdering/font-awesome/css/font-awesome.min.css"
rel="stylesheet" type="text/css">

    <script src="../../js/jquery-latest.min.js"></script>
    <script src="../../js/script.js"></script>
    <script src="../../js/jquery183.min.js"></script>
    <script src="../../js/responsiveslides.min.js"></script>
    <script>
        // You can also use "$(window).load(function() {"
        $(function () {
            // Slideshow
            $("#slider").responsiveSlides({
                auto: true,
                pager: false,
                nav: true,
```

```

        speed: 500,
        namespace: "callbacks",
        before: function () {
            $(' .events').append("<li>before event fired.</li>");
        },
        after: function () {
            $(' .events').append("<li>after event fired.</li>");
        }
    });
});
</script>
<script>
src="https://ajax.googleapis.com/ajax/libs/jquery/3.3.1/jquery.min.js"></scri
pt>
<script>
$(document).ready(function() {
    $("button").click(function() {
        $("#div1").load("demotest.txt");
        $("#div2").load("demotest1.txt");
        $("#div3").load("demotest2.txt");
    });
});
</script>

<!--[if lt IE 8]>
    <div style=' clear: both; text-align:center; position: relative;'>
        <a href="http://windows.microsoft.com/en-US/internet-
explorer/products/ie/home?ocid=ie6_countdown_bannercode">
            
        </a>
    </div>
<![endif]-->
<!--[if lt IE 9]>
    <script src="js/html5.js"></script>
    <script src="js/css3-mediaqueries.js"></script>
<![endif]-->

</head>
<body>
<div class="wrap-body">
<%    String email = (String)session.getAttribute("currentSessionUser");%>
<!-- ///////////////////////////////////////////////////Top -->
<div class="top">
    <div class="zerogrid">
        <div class="row">
            <div class="f-left">
                <span><i class="fa fa-map-marker"></i> Jasin </span>
                <span><i class="fa fa-phone"></i> 06-26401111</span>
                <span><i class="fa fa-envelope"></i>
jasinpizza@gmail.com</span>
            </div>
            <div class="f-right">
            </div>
        </div>
    </div>
</div>

```



```

        </div>
</div>

<!--////////////////////Header-->
<header>
    <div class="wrap-header zerogrid">
        <div class="row">
            <div id="cssmenu">
                <ul>
                    <li class='active'><a
href="/PizzaOrdering/customer/index.jsp">Home</a></li>
                    <li><a
href="/PizzaOrdering/customer/menu.jsp">Menu</a></li>
                    <li><a
href="/PizzaOrdering/OrderController?action=listOrder&email=<c:out
value="<%=email%>" />">My Order </a></li>
                    <li><a
href="/PizzaOrdering/AccountController?action=viewAccount&email=<c:out
value="<%=email%>" />">My Account </a></li>
                    <li><a
href="/PizzaOrdering/customer/logout.jsp">Logout</a></li>
                </ul>
            </div>
            <a href='index.html' class="logo"><img src="" /></a>
        </div>
    </div>
</header>

<!--////////////////////Container-->
<section id="container" class="home-page">
    <div class="wrap-container clearfix">
        <div id="main-content">
            <section class="content-box box-1 box-style-1"><!--Start
Box-->
                <div class="wrap-box">
                    <div class="zerogrid">
                        <div class="row">
                            <div class="col-1-3">
                                <div class="wrap-col">
                                    <button>NEW
PIZZA</button>
                                    <div id="div3"></div>
                                    <h2 style="font-size:
35px;line-height: 1.3;margin-bottom: 10px;"></h2>
                                    
                                    <p>NO IDEA WHAT TO
COOK? CRAVING FOR PIZZA?</p>
                                    <a href="menu.jsp"
class="button btl">VIEW MENU</a>
                                </div>
                            </div>
                            <div class="col-1-3">
                                <div class="wrap-col">
                                    <button>NEW SIDE
ORDER</button>
                                </div>
                            </div>
                        </div>
                    </div>
                </div>
            </section>
        </div>
    </div>
</section>

```

```

35px;line-height: 1.3;margin-bottom: 10px;"></h2>
src="../../images/side-1.png" />
EAT WITH PIZZA?</p>
class="button bt1">VIEW MENU</a>
DRINK</button>
title">
DRINKS</h2>
35px;line-height: 1.3;margin-bottom: 10px;"></h2>
src="../../images/drinks-1.jpg" />
WHAT YOU NEEDED</p>
class="button bt1">VIEW MENU</a>
</div>
</div>
</div>
</div>
</div>
</section>
</div>
</div>
</section>
<!--////////////////////////////////////Footer-->
<div class="copyright">
    <div class="zerogrid wrapper">
        <a href="map.jsp">OUR LOCATION</a>
    </div>
</div>
</div>
</body></html>
```

menu.jsp

```
<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
pageEncoding="ISO-8859-1"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/fmt" prefix="fmt"%>

<%
    response.setHeader("Cache-Control","no-cache");
    response.setHeader("Cache-Control","no-store");
    response.setHeader("Pragma","no-cache");
    response.setDateHeader ("Expires", 0);

    if(session.getAttribute("currentSessionUser")==null)
        response.sendRedirect("/PizzaOrdering/login.jsp");

%>

<!DOCTYPE html>
<!--[if lt IE 7 ]><html class="ie ie6" lang="en"> <![endif]-->
<!--[if IE 7 ]><html class="ie ie7" lang="en"> <![endif]-->
<!--[if IE 8 ]><html class="ie ie8" lang="en"> <![endif]-->
<!--[if (gte IE 9) || (IE)]><!--><html lang="en"> <!--<![endif]-->
<head>

    <!-- Basic Page Needs
    ===== -->
    <meta charset="utf-8">
    <title></title>

    <!-- Mobile Specific Metas
    ===== -->
    <meta name="viewport" content="width=device-width, initial-scale=1,
maximum-scale=1">

    <!-- CSS
    ===== -->
    <link rel="stylesheet" href="../../css/zerogrid.css">
    <link rel="stylesheet" href="../../css/style.css">
    <link rel="stylesheet" href="../../css/menu.css">
    <link rel="stylesheet" href="../../css/responsiveslides.css">
    <link href="../../font-awesome/css/font-awesome.min.css" rel="stylesheet"
type="text/css">

    <script src="../../js/jquery-latest.min.js"></script>
    <script src="../../js/script.js"></script>
    <script src="../../js/jquery183.min.js"></script>
    <script src="../../js/responsiveslides.min.js"></script>
    <script>
        // You can also use "$(window).load(function() {"
        $(function () {
            // Slideshow
            $("#slider").responsiveSlides({
                auto: true,
                pager: false,
                nav: true,
```

```

        speed: 500,
        namespace: "callbacks",
        before: function () {
            $('<li>before event fired.</li>');
        },
        after: function () {
            $('<li>after event fired.</li>');
        }
    });
});
</script>

<!--[if lt IE 8]>
    <div style=' clear: both; text-align:center; position: relative;'>
        <a href="http://windows.microsoft.com/en-US/internet-
explorer/products/ie/home?ocid=ie6_countdown_bannercode">
            
        </a>
    </div>
<![endif]>
<!--[if lt IE 9]>
    <script src="js/html5.js"></script>
    <script src="js/css3-mediaqueries.js"></script>
<![endif]>

</head>
<body>
<div class="wrap-body">
<%    String email = (String)session.getAttribute("currentSessionUser");%>

<!-- //////////////////////////////////////Top -->
<div class="top">
    <div class="zerogrid">
        <div class="row">
            <div class="f-left">
                <span><i class="fa fa-map-marker"></i> Jasin </span>
                <span><i class="fa fa-phone"></i> 06-26401111</span>
                <span><i class="fa fa-envelope"></i>
jasinpizza@gmail.com</span>
            </div>
            <div class="f-right">
            </div>
        </div>
    </div>
</div>

<!--////////////////////////////////////Header-->
<header>
    <div class="wrap-header zerogrid">
        <div class="row">
            <div id="cssmenu">
                <ul>

```

```

        <li><a
href="/PizzaOrdering/customer/index.jsp">Home</a></li>
        <li class='active'><a
href="/PizzaOrdering/customer/menu.jsp">Menu</a></li>
        <li><a
href="/PizzaOrdering/OrderController?action=listOrder&email=<c:out
value="<%=email%>" />">My Order </a></li>
        <li><a
href="/PizzaOrdering/AccountController?action=viewAccount&email=<c:out
value="<%=email%>" />">My Account </a></li>
        <li><a
href="/PizzaOrdering/customer/logout.jsp">Logout</a></li>
    </ul>
</div>
    <a href='index.html' class="logo"><img src="" /></a>
</div>
</div>
</header>

<div class="bg-white">
    <div class="zerogrid">

        <div class="widget wid-gallery">
            <div class="wid-header">
                <h5>Pizza</h5>
            </div>
            <div class="wid-content">
                
                
                
                
            </div>
        </div>

        <div class="widget wid-gallery">
            <div class="wid-header">
                <h5>Side Order</h5>
            </div>
            <div class="wid-content">
                
                
                
                
            </div>
        </div>

        <div class="widget wid-gallery">
            <div class="wid-header">
                <h5>Drinks</h5>
            </div>
            <div class="wid-content">
                
                
                
                
            </div>
        </div>
    </div>

```

```

        <div class="clear"></div>
    </div>
</div>

<!--////////////////////////////////////Footer-->

<div class="copyright">
    <div class="zerogrid wrapper">
        Copyright 2017
    </div>
</div>

</div>
</body></html>

```

order.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
pageEncoding="ISO-8859-1"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/fmt" prefix="fmt"%>

<%
    response.setHeader("Cache-Control","no-cache");
    response.setHeader("Cache-Control","no-store");
    response.setHeader("Pragma","no-cache");
    response.setDateHeader ("Expires", 0);

    if(session.getAttribute("currentSessionUser")==null)
        response.sendRedirect("/PizzaOrdering/login.jsp");

%>

<!DOCTYPE html>
<!--[if lt IE 7 ]><html class="ie ie6" lang="en"> <![endif]-->
<!--[if IE 7 ]><html class="ie ie7" lang="en"> <![endif]-->
<!--[if IE 8 ]><html class="ie ie8" lang="en"> <![endif]-->
<!--[if (gte IE 9) || (IE)]><!--><html lang="en"> <!--<![endif]-->
<head>

    <!-- Basic Page Needs
    ===== -->
    <meta charset="utf-8">
    <title></title>

    <!-- Mobile Specific Metas
    ===== -->
    <meta name="viewport" content="width=device-width, initial-scale=1,
maximum-scale=1">

    <!-- CSS
    ===== -->
    <link rel="stylesheet" href="css/zerogrid.css">
    <link rel="stylesheet" href="css/style.css">
    <link rel="stylesheet" href="css/menu.css">

```

```

    <link rel="stylesheet" href="css/responsiveslides.css">
    <link href="font-awesome/css/font-awesome.min.css" rel="stylesheet"
type="text/css">

    <script src="js/jquery-latest.min.js"></script>
    <script src="js/script.js"></script>
    <script src="js/jquery183.min.js"></script>
    <script src="js/responsiveslides.min.js"></script>
    <script>
        // You can also use "$(window).load(function() {"
        $(function () {
            // Slideshow
            $("#slider").responsiveSlides({
                auto: true,
                pager: false,
                nav: true,
                speed: 500,
                namespace: "callbacks",
                before: function () {
                    $('.events').append("<li>before event fired.</li>");
                },
                after: function () {
                    $('.events').append("<li>after event fired.</li>");
                }
            });
        });
    </script>

    <!--[if lt IE 8]>
        <div style=' clear: both; text-align:center; position: relative;'>
            <a href="http://windows.microsoft.com/en-US/internet-
explorer/products/ie/home?ocid=ie6_countdown_bannercode">
                
            </a>
        </div>
    <![endif]-->
    <!--[if lt IE 9]>
        <script src="js/html5.js"></script>
        <script src="js/css3-mediaqueries.js"></script>
    <![endif]-->

</head>
<body>
<div class="wrap-body">
<% String email = (String)session.getAttribute("currentSessionUser");%>
<!-- ////////////////////////////////////////Top -->
<div class="top">
    <div class="zerogrid">
        <div class="row">
            <div class="f-left">
                <span><i class="fa fa-map-marker"></i> Jasin </span>
                <span><i class="fa fa-phone"></i> 06-26401111</span>
            </div>
        </div>
    </div>
</div>

```

```

                <span><i class="fa fa-envelope"></i>
jasinpizza@gmail.com</span>
            </div>
            <div class="f-right">
            </div>
        </div>
    </div>
</div>

<!--////////////////////Header-->
<header>
    <div class="wrap-header zerogrid">
        <div class="row">
            <div id="cssmenu">
                <ul>
                    <li><a
href="/PizzaOrdering/customer/index.jsp">Home</a></li>
                    <li><a
href="/PizzaOrdering/customer/menu.jsp">Menu</a></li>
                    <li><a
href="/PizzaOrdering/OrderController?action=listOrder&email=<c:out
value="<%=email%>" />">My Order </a></li>
                    <li><a
href="/PizzaOrdering/AccountController?action=viewAccount&email=<c:out
value="<%=email%>" />">My Account </a></li>
                    <li><a
href="/PizzaOrdering/customer/logout.jsp">Logout</a></li>
                </ul>
            </div>
            <a href='index.html' class="logo"><img src="" /></a>
        </div>
    </div>
</header>
<div class="bg-white">
    <div class="zerogrid">
        <p>Welcome <b><c:out value="<%=email%>" /></b></p>
    <section id="container">
        <div class="zerogrid">
            <div class="wrap-container clearfix">
                <div id="main-content">
                    <div class="wrap-box"><!--Start Box-->
                        <div class="row">
                            <div class="col-2-3">
                                <div class="wrap-col">
                                    <div class="contact">
                                        <div class="contact-
header">
                                            <h5>ADD NEW
ORDER</h5>
                                            </div>
                                            <div id="contact_form">
                                                <!-- START OF FORM -->
                                                <form
method="POST" action='OrderController'>

```



```

class="row">
class="col-1-3">
    <div class="wrap-col">Crust
    </div>
    </div>

class="col-2-3">
    <div class="wrap-col">
        <select name="crust">
            <option value="Classic">Classic</option>
            <option value="Thin Crust">Thin Crust</option>
            <option value="Melaka Crust">Melaka Crust</option>
            <option value="Cheese Burst">Cheese Burst</option>
        </select>
    </div>
    </div>
</label>
<label class="row">
    <div class="col-1-3">
        <div class="wrap-col">Extra Cheese:
        </div>
        </div>

    <div class="col-2-3">
        <div class="wrap-col">
            <input type="radio" name="extracheese" value="Yes">Yes
            <input type="radio" name="extracheese" value="No">No
        </div>
        </div>
</label>

```

```

class="row">
class="col-1-3">
    <div class="wrap-col">Topping:
    </div>
</div>

class="col-2-3">
    <div class="wrap-col">
        <input type="radio" name="topping" value="Beef">Beef
        <input type="radio" name="topping" value="Chicken ">Chicken
        <input type="radio" name="topping" value="Mushroom">Mushroom
        <input type="radio" name="topping" value="Pineapple">Pineapple
    </div>
</div>

</label>

<label
class="row">
class="col-1-3">
    <div class="wrap-col">Quantity:
    </div>
</div>

class="col-2-3">
    <div class="wrap-col">
        <input type="number" name="quantity" value="" min="1"
required="required"/>

    </div>
</div>

</label>

<label class="row">

```

```
<div>  
  
    <div class="wrap-col">  
  
    </div>  
  
    </div>  
  
        <div class="wrap-col">  
  
            <input type="hidden" name="email" value="<c:out  
value="<%=email%"/>" /></div>  
  
            </div>  
  
            </div>  
  
                </label>  
  
                <label  
class="row">  
  
                    <div class="wrap-col">  
  
                        <input class="send" type="submit" name="submitcontact" value="Submit">  
  
                        </div>  
  
                            </label>  
                            <label  
class="row">  
  
                                <div class="wrap-col">  
  
                                    <input class="send" type="reset" name="submitcontact" value="Reset">  
  
                                    </div>  
  
                                        </label>  
                                        </form>  
  
                                            <!-- END OF FORM -->  
                                            </div>  
                                        </div>  
                                    </div>  
                                </div>  
                            </div>  
                        </div>  
                    </div>  
                </div>  
            </div>  
        </section>  
    </div>  
    </div>  
</body></html>
```

viewAccount.jsp

```
%@ page language="java" contentType="text/html; charset=ISO-8859-1"
pageEncoding="ISO-8859-1"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/fmt" prefix="fmt"%>

<%
    response.setHeader("Cache-Control","no-cache");
    response.setHeader("Cache-Control","no-store");
    response.setHeader("Pragma","no-cache");
    response.setDateHeader ("Expires", 0);

    if(session.getAttribute("currentSessionUser")==null)
        response.sendRedirect("/PizzaOrdering/login.jsp");

%>

<!DOCTYPE html>
<!--[if lt IE 7 ]><html class="ie ie6" lang="en"> <![endif]-->
<!--[if IE 7 ]><html class="ie ie7" lang="en"> <![endif]-->
<!--[if IE 8 ]><html class="ie ie8" lang="en"> <![endif]-->
<!--[if (gte IE 9) || (IE)]><!--><html lang="en"> <!--<![endif]-->
<head>

    <!-- Basic Page Needs
    ===== -->
    <meta charset="utf-8">
    <title></title>

    <!-- Mobile Specific Metas
    ===== -->
    <meta name="viewport" content="width=device-width, initial-scale=1,
maximum-scale=1">

    <!-- CSS
    ===== -->
    <link rel="stylesheet" href="css/zerogrid.css">
    <link rel="stylesheet" href="css/style.css">
    <link rel="stylesheet" href="css/menu.css">
    <link rel="stylesheet" href="css/responsiveslides.css">
    <link href="font-awesome/css/font-awesome.min.css" rel="stylesheet"
type="text/css">

    <style>

        table, td, th {
            font-family: "Oswald",Arial,Helvetica,"Nimbus Sans L",sans-serif;
            border: 1px solid #FFCD02;
            text-align: left;
        }

        table {
            width: 100%;
        }
```

```

    th, td {
padding-left: 10px;
    }

    th {
background-color: #FFCD02;
color: white;
font-size: 20px;
    }

    td{
font-size: 18px;
    }

    p {
font-family: "Oswald", Arial, Helvetica, "Nimbus Sans L", sans-serif;
font-size: 18px;
    }
</style>
<script src="js/jquery-latest.min.js"></script>
<script src="js/script.js"></script>
<script src="js/jquery183.min.js"></script>
<script src="js/responsiveslides.min.js"></script>
<script>
    // You can also use "$(window).load(function() {"
    $(function () {
        // Slideshow
        $("#slider").responsiveSlides({
            auto: true,
            pager: false,
            nav: true,
            speed: 500,
            namespace: "callbacks",
            before: function () {
                $('.events').append("<li>before event fired.</li>");
            },
            after: function () {
                $('.events').append("<li>after event fired.</li>");
            }
        });
    });
</script>

<!--[if lt IE 8]>
<div style=' clear: both; text-align:center; position: relative;'>
    <a href="http://windows.microsoft.com/en-US/internet-
explorer/products/ie/home?ocid=ie6_countdown_bannercode">
        
    </a>
</div>
<![endif]-->
<!--[if lt IE 9]>
    <script src="js/html5.js"></script>

```

```

        <script src="js/css3-mediaqueries.js"></script>
    <![endif]-->

</head>
<body>
<div class="wrap-body">
<%    String email = (String)session.getAttribute("currentSessionUser");%>
<!-- //////////////////////////////////////Top -->
<div class="top">
    <div class="zerogrid">
        <div class="row">
            <div class="f-left">
                <span><i class="fa fa-map-marker"></i> Jasin </span>
                <span><i class="fa fa-phone"></i> 06-26401111</span>
                <span><i class="fa fa-envelope"></i>
jasinpizza@gmail.com</span>
            </div>
            <div class="f-right">
            </div>
        </div>
    </div>
</div>

<!--////////////////////////////////////Header-->
<header>
    <div class="wrap-header zerogrid">
        <div class="row">
            <div id="cssmenu">
                <ul>
                    <li><a
href="/PizzaOrdering/customer/index.jsp">Home</a></li>
                    <li><a
href="/PizzaOrdering/customer/menu.jsp">Menu</a></li>
                    <li><a
href="/PizzaOrdering/OrderController?action=listOrder&email=<c:out
value="<%=email%>" />">My Order </a></li>
                    <li class='active'><a
href="/PizzaOrdering/AccountController?action=viewAccount&email=<c:out
value="<%=email%>" />">My Account </a></li>
                    <li><a
href="/PizzaOrdering/customer/logout.jsp">Logout</a></li>
                </ul>
            </div>
            <a href='index.html' class="logo"><img src="" /></a>
        </div>
    </div>
</header>

<div class="bg-white">
    <div class="zerogrid">
        <p>Welcome <b><c:out value="<%=email%>" /></b></p>
        <br/><h1>My Account</h1>
        <br/><br/>

        <!-- START DISPLAY ACCOUNT -->

        <p><b>Email:</b> <c:out value="<%=email%>" /></p>

```

```

    <p><b>Firstname:</b> <c:out value="\${user.firstname}" /></p>
    <p><b>Lastname:</b> <c:out value="\${user.lastname}" /></p>
    <p><b>Address:</b> <c:out value="\${user.address}" /></p>
    <p><b>Phone:</b> <c:out value="\${user.phone}" /></p>

    <br/><br/>
    <p><a href="AccountController?action=updateAccount&email=<c:out
value="\${email}" />"><b>Update Account</b></a></p>

    <!-- END DISPLAY ACCOUNT -->

</div>

<div class="clear"></div>
</div>
</div>

<!--////////////////////////Footer-->

</body></html>

```

updateAccount.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
pageEncoding="ISO-8859-1"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/core" prefix="c"%>
<%@ taglib uri="http://java.sun.com/jsp/jstl/fmt" prefix="fmt"%>

<%
    response.setHeader("Cache-Control","no-cache");
    response.setHeader("Cache-Control","no-store");
    response.setHeader("Pragma","no-cache");
    response.setDateHeader ("Expires", 0);

    if(session.getAttribute("currentSessionUser")==null)
        response.sendRedirect("/PizzaOrdering/login.jsp");

%>

<!DOCTYPE html>
<!--[if lt IE 7 ]><html class="ie ie6" lang="en"> <![endif]-->
<!--[if IE 7 ]><html class="ie ie7" lang="en"> <![endif]-->
<!--[if IE 8 ]><html class="ie ie8" lang="en"> <![endif]-->
<!--[if (gte IE 9) || (IE) ]><!--><html lang="en"> <!--<![endif]-->
<head>

    <!-- Basic Page Needs
    ===== -->
    <meta charset="utf-8">
    <title></title>

    <!-- Mobile Specific Metas
    ===== -->
    <meta name="viewport" content="width=device-width, initial-scale=1,
maximum-scale=1">

```

```

<!-- CSS
===== -->
<link rel="stylesheet" href="css/zerogrid.css">
<link rel="stylesheet" href="css/style.css">
<link rel="stylesheet" href="css/menu.css">
<link rel="stylesheet" href="css/responsiveslides.css">
<link href="font-awesome/css/font-awesome.min.css" rel="stylesheet"
type="text/css">

<script src="js/jquery-latest.min.js"></script>
<script src="js/script.js"></script>
<script src="js/jquery183.min.js"></script>
<script src="js/responsiveslides.min.js"></script>
<script>
    // You can also use "$(window).load(function() {"
    $(function () {
        // Slideshow
        $("#slider").responsiveSlides({
            auto: true,
            pager: false,
            nav: true,
            speed: 500,
            namespace: "callbacks",
            before: function () {
                $('.events').append("<li>before event fired.</li>");
            },
            after: function () {
                $('.events').append("<li>after event fired.</li>");
            }
        });
    });
</script>

<!--[if lt IE 8]>
    <div style=' clear: both; text-align:center; position: relative;'>
        <a href="http://windows.microsoft.com/en-US/internet-
explorer/products/ie/home?ocid=ie6_countdown_bannercode">
            
            </a>
        </div>
    <![endif]-->
<!--[if lt IE 9]>
    <script src="js/html5.js"></script>
    <script src="js/css3-mediaqueries.js"></script>
    <![endif]-->

</head>
<body>
<div class="wrap-body">
<% String email = (String)session.getAttribute("currentSessionUser");%>
<!-- ////////////////////////////////////////Top -->
<div class="top">
    <div class="zerogrid">

```



```

        <div class="row">
            <div class="f-left">
                <span><i class="fa fa-map-marker"></i> Jasin </span>
                <span><i class="fa fa-phone"></i> 06-26401111</span>
                <span><i class="fa fa-envelope"></i>
jasinpizza@gmail.com</span>
            </div>
            <div class="f-right">
            </div>
        </div>
    </div>
</div>

<!--////////////////////////////////////Header-->
<header>
    <div class="wrap-header zerogrid">
        <div class="row">
            <div id="cssmenu">
                <ul>
                    <li><a
href="/PizzaOrdering/customer/index.jsp">Home</a></li>
                    <li><a
href="/PizzaOrdering/customer/menu.jsp">Menu</a></li>
                    <li><a
href="/PizzaOrdering/OrderController?action=listOrder&email=<c:out
value="<%=email%>" />">My Order </a></li>
                    <li><a
href="/PizzaOrdering/AccountController?action=viewAccount&email=<c:out
value="<%=email%>" />">My Account </a></li>
                    <li><a
href="/PizzaOrdering/customer/logout.jsp">Logout</a></li>
                </ul>
            </div>
            <a href='index.html' class="logo"><img src="" /></a>
        </div>
    </div>
</header>

<div class="bg-white">
    <div class="zerogrid">
        <p>Welcome <b><c:out value="<%=email%>" /></b></p>

<!--////////////////////////////////////Container-->
<section id="container">
    <div class="zerogrid">
        <div class="wrap-container clearfix">
            <div id="main-content">
                <div class="wrap-box"><!--Start Box-->
                    <div class="row">
                        <div class="col-2-3">
                            <div class="wrap-col">
                                <div class="contact">
                                    <div class="contact-
header">
                                        <h5>UPDATE
ACCOUNT</h5>
                                </div>

```

```

<div id="contact_form">

<!-- START OF FORM -->

    <form
name="form1" method="post" id="ff" action="AccountController">
        <label
class="row">
            <div
class="col-1-2">
                <div class="wrap-col">
                    <input type="email" name="email" id="email" value="<c:out
value="<%=email%>" />" readonly/>
                </div>
            </div>
        </label>
        <label
class="row">
            <div
class="col-1-2">
                <div class="wrap-col">
                    <input type="text" name="firstname" id="firstname" value="<c:out
value="\${user.firstname}" />" readonly/>
                </div>
            </div>
        </label>
        <label
class="row">
            <div
class="col-1-2">
                <div class="wrap-col">
                    <input type="text" name="lastname" id="lastname" value="<c:out
value="\${user.lastname}" />" readonly/>
                </div>
            </div>
        </label>
        <label
class="row">
            <div
class="col-1-2">
                <div class="wrap-col">
                    <input type="text" name="address" id="address" value="<c:out
value="\${user.address}" />" />

```

```

        </div>

        </div>

        </label>
        <label
class="row">
        <div
class="col-1-2">
        <div class="wrap-col">
        <input type="text" name="phone" id="phone" value="<c:out
value="\${user.phone}" />"/>
        </div>
        </div>
        </label>
        <label
class="row">
        <div
class="col-1-2">
        <div class="wrap-col">
        <input type="password" name="password" id="password"
required="required" />
        </div>
        </div>
        </label>
        <label
class="row">
        <div
class="wrap-col">
        <input class="submitButton" type="submit" name="submitcontact"
value="Submit">
        </div>
        </label>
        <label
class="row">
        <div
class="wrap-col">
        <input class="submitButton" type="reset" name="submitcontact"
value="Reset">
        </div>
        </label>
        </form>

        <!-- END OF FORM
-->

```



```
<link href="font-awesome/css/font-awesome.min.css" rel="stylesheet"
type="text/css">
```

```
<style>
```

```
table, td, th {
    font-family: "Oswald",Arial,Helvetica,"Nimbus Sans L",sans-serif;
border: 1px solid #FFCD02;
text-align: left;
}
```

```
table {
width: 100%;
}
```

```
th, td {
padding-left: 10px;
}
```

```
th {
background-color: #FFCD02;
color: white;
font-size:20px;
}
```

```
td{
font-size:18px;
}
```

```
p {
    font-family: "Oswald",Arial,Helvetica,"Nimbus Sans L",sans-serif;
font-size:18px;
}
```

```
</style>
```

```
<script src="js/jquery-latest.min.js"></script>
```

```
<script src="js/script.js"></script>
```

```
<script src="js/jquery183.min.js"></script>
```

```
<script src="js/responsiveslides.min.js"></script>
```

```
<script>
```

```
    // You can also use "$(window).load(function() {"
```

```
    $(function () {
```

```
        // Slideshow
```

```
        $("#slider").responsiveSlides({
```

```
            auto: true,
```

```
            pager: false,
```

```
            nav: true,
```

```
            speed: 500,
```

```
            namespace: "callbacks",
```

```
            before: function () {
```

```
                $('<li>before event fired.</li>');
```

```
            },
```

```
            after: function () {
```

```
                $('<li>after event fired.</li>');
```

```
            }
```

```
        });
```

```
    });
```

```
</script>
```

```

</head>
<body>
<div class="wrap-body">
<%    String email = (String)session.getAttribute("currentSessionUser");%>
<!-- //////////////////////////////////////Top -->
<div class="top">
    <div class="zerogrid">
        <div class="row">
            <div class="f-left">
                <span><i class="fa fa-map-marker"></i> Jasin </span>
                <span><i class="fa fa-phone"></i> 06-26401111</span>
                <span><i class="fa fa-envelope"></i>
jasinpizza@gmail.com</span>
            </div>
            <div class="f-right">
            </div>
        </div>
    </div>
</div>
<!--////////////////////////////////////Header-->
<header>
    <div class="wrap-header zerogrid">
        <div class="row">
            <div id="cssmenu">
                <ul>
                    <li><a
href="/PizzaOrdering/customer/index.jsp">Home</a></li>
                    <li><a
href="/PizzaOrdering/customer/menu.jsp">Menu</a></li>
                    <li class='active'><a
href="/PizzaOrdering/OrderController?action=listOrder&email=<c:out
value="<%=email%>" />">My Order </a></li>
                    <li><a
href="/PizzaOrdering/AccountController?action=viewAccount&email=<c:out
value="<%=email%>" />">My Account </a></li>
                    <li><a
href="/PizzaOrdering/customer/logout.jsp">Logout</a></li>
                </ul>
            </div>
            <a href='index.html' class="logo"><img src="" /></a>
        </div>
    </div>
</header>
<div class="bg-white">
    <div class="zerogrid">
        <p>Welcome <b><c:out value="<%=email%>" /></b></p>
        <br/><h1>My Order</h1>
        <br/><br/>
        <!-- START OF TABLE -->
        <table>
            <tr>
                <th>Order Id</th>
                <th>Crust</th>
                <th>Extra Cheese</th>
                <th>Topping</th>
                <th>Quantity</th>
            </tr>

```

```

        <c:forEach items="${pizzas}" var="pizza">
            <tr>
                <td><c:out value="${pizza.orderid}" /></td>
                <td><c:out value="${pizza.crust}" /></td>
                <td><c:out value="${pizza.extracheese}" /></td>
                <td><c:out value="${pizza.topping}" /></td>
                <td><c:out value="${pizza.quantity}" /></td>
            </tr>
        </c:forEach>
    </table>
    <!-- END OF TABLE -->
    <p><a href="OrderController?action=insert"><b>Add Pizza</b></a></p>
    </div>
    <div class="clear"></div>
</div>
<!--////////////////////////Footer-->
</body></html>

```

map.jsp

```

<%@ page language="java" contentType="text/html; charset=ISO-8859-1"
    pageEncoding="ISO-8859-1"%>
<!DOCTYPE html PUBLIC "-//W3C//DTD HTML 4.01 Transitional//EN"
    "http://www.w3.org/TR/html4/loose.dtd">
<html>
<body>
<h1>Our Location</h1>
<div id="map" style="width:400px;height:400px;background:blue"></div>
<script>
function myMap() {
    var mapOptions = {
        center: new google.maps.LatLng(2.31056, 102.43111),
        zoom: 20,
        mapTypeId: google.maps.MapTypeId.HYBRID
    }
    var map = new google.maps.Map(document.getElementById("map"), mapOptions);
}
</script>
<script
src="https://maps.googleapis.com/maps/api/js?key=AIzaSyArWzkmhXCpVENDe88LeFd1
eOV7ok2PJtc&callback=myMap"></script>
</body>
</html>

```

OUTPUT

login.jsp & logout.jsp

📍 Jasin 📞 06-26401111 ✉️ jasinpizza@gmail.com

LOGIN

Submit

Reset

Don't have an account? [Register Here](#)

Copyright 2017

register.jsp

📍 Jasin 📞 06-26401111 ✉️ jasinpizza@gmail.com

REGISTER ACCOUNT

Submit

Reset

invalidAccount.jsp & invalidLogin.jsp

 Jasin  06-26401111  jasinpizza@gmail.com

You are either not a registered user

OR

You entered wrong user name OR password.


Login Here

index.jsp

Jasin 06-26401111 jasinpizza@gmail.com

HOME MENU MY ORDER MY ACCOUNT LOGOUT


NEW PIZZA



NO IDEA WHAT TO COOK? CRAVING FOR PIZZA?

VIEW MENU


NEW SIDE ORDER



NEED SIDE ORDER TO EAT WITH PIZZA?

VIEW MENU

NEW DRINK



HOT OR COLD? WE HAVE WHAT YOU NEEDED

VIEW MENU

Activate Windows
Go to Settings to activate Windows.

OUR LOCATION

[menu.jsp](#)

Pizza



Side Order



Drinks



listOrder.jsp

📍 Jasin

☎ 06-26401111

✉ jasinpizza@gmail.com

HOME MENU MY ORDER MY ACCOUNT LOGOUT

Welcome h@y.c

My Order

Order Id	Crust	Extra Cheese	Topping	Quantity
1	Thin Crust	Yes	Chicken	5
2	Cheese Burst	No	Chicken	6
3	Classic	No	Chicken	6
4	Melaka Crust	Yes	Mushroom	6

Add Pizza

order.jsp

📍 Jasin

☎ 06-26401111

✉ jasinpizza@gmail.com

HOME MENU MY ORDER MY ACCOUNT

Welcome h@y.c

ADD NEW ORDER

Crust

Classic ▾

Extra Cheese:

☐ Yes ☐ No

Topping:

☐ Beef ☐ Chicken ☐ Mushroom ☐ Pineapple

Quantity:

Submit

Reset

[viewAccount.jsp](#)

Jasin

06-26401111

jasinpizza@gmail.com

HOME

MENU

Welcome **h@y.c**

My Account

Email: h@y.c

Firstname: Nurul Hasanah

Lastname: Zakaria

Address: Rawang

Phone: 0126946428

Update Account

[updateAccount.jsp](#)

UPDATE ACCOUNT

h@y.c

Nurul Hasanah

Zakaria

Rawang

0126946428

Submit

Reset

map.jsp

Our Location

