

Quiz navigation



Show one page at a time

Finish review

Question **1**

Correct

Marked out of 3.00

Flag question

Status	Finished
Started	Monday, 23 December 2024, 5:33 PM
Completed	Saturday, 26 October 2024, 12:59 PM
Duration	58 days 4 hours

Write a program to read two integer values and print true if both the numbers end with the same digit, otherwise print false. Example: If 698 and 768 are given, program should print true as they both end with 8. Sample Input 1 25 53 Sample Output 1 false Sample Input 2 27 77 Sample Output 2 true

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main()
3 {
4     int a,b;
5     scanf("%d %d",&a,&b);
6     if (a%10 == b%10)
7         printf("true\n");
8     else
9         printf("false\n");
10    return 0;
11 }
```

	Input	Expected	Got	
✓	25 53	false	false	✓
✓	27 77	true	true	✓

Passed all tests! ✓

Question **2**

Correct

Marked out of 5.00

Flag question

Objective

In this challenge, we're getting started with conditional statements.

Task

Given an integer, *n*, perform the following conditional actions:

- If *n* is odd, print Weird
- If *n* is even and in the inclusive range of 2 to 5, print **Not Weird**
- If *n* is even and in the inclusive range of 6 to 20, print **Weird**
- If *n* is even and greater than 20, print **Not Weird**

Complete the stub code provided in your editor to print whether or not *n* is weird.

Input Format

A single line containing a positive integer, *n*.

Constraints

- $1 \leq n \leq 100$

Output Format

Print Weird if the number is weird; otherwise, print Not Weird.

Sample Input 0

3

Sample Output 0

Weird

Sample Input 1

24

Sample Output 1

Not Weird

Explanation

Sample Case 0: $n = 3$

n is odd and odd numbers are weird, so we print *Weird*.

Sample Case 1: $n = 24$

$n > 20$ and n is even, so it isn't weird. Thus, we print *Not Weird*.

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main()
3 {
4     int n;
5     scanf("%d",&n);
6     if (n%2!=0)
7         printf("Weird\n");
8     else
9
10        if(n>=2 && n<=5)
11            printf("Not Weird");
12        else if (n>=6&& n<=20)
13            printf("Weird");
14        else if (n>20)
15            printf("Not Weird");
16
17    return 0;
18
19
20 }
```

	Input	Expected	Got	
✓	3	Weird	Weird	✓
✓	24	Not Weird	Not Weird	✓

Passed all tests! ✓

Question 3

Correct

Marked out of 7.00

Flag question

Three numbers form a Pythagorean triple if the sum of squares of two numbers is equal to the square of the third. For example, 3, 5 and 4 form a Pythagorean triple, since $3^2 + 4^2 = 25 = 5^2$ You are given three integers, a, b, and c. They need not be given in increasing order. If they form a Pythagorean triple, then print "yes", otherwise, print "no". Please note that the output message is in small letters. Sample Input 1 3 5 4 Sample Output 1 yes Sample Input 2 5 8 2 Sample Output 2 no

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main ()
3 {
4     int a,b,c;
5     scanf ("%d %d %d",&a,&b,&c);
6     if (a>b && a>c)
7     {
8         if (a*a == b*b + c*c)
9             printf("yes\n");
10        else
11            printf ("no\n");
12    }
13    else if (b>a && b>c)
14    {
15        if(b*b == a*a+c*c)
16            printf("yes\n");
17        else
18            printf("no\n");
19    }
20    }
21    else
22    {
23        if(c*c == a*a+b*b)
24            printf ("yes\n");
25        else
26            printf("no\n");
27    }
28    return 0;
29 }
```

	Input	Expected	Got	
✓	3 5 4	yes	yes	✓
✓	5 8 2	no	no	✓

Passed all tests! ✓