

WEEK-2

Date:25-06-2025

List of programs:

1. Write a C program to search an element in the given list using recursive Linear Search technique.
2. Write a C program to search an element in the given list using non-recursive Linear Search technique.
3. Write a C program to search an element in the given sorted list using recursive Binary Search technique.
4. Write a C program to search an element in the given sorted list using recursive Binary Search technique.

- 1. Aim:** To write a C program to search an element in the given list using recursive Linear Search technique.


Program:

```
#include<stdio.h>

int LinearSearch(int arr[],int size,int key,int index)
{
    if(index>=size)
        return -1;
    if(arr[index]==key)
        return index;
    return LinearSearch(arr,size,key,index+1);
}

int main()
{
    int arr[]={5,3,8,4,2};
    int size=sizeof(arr)/sizeof(arr[0]);
    int key=4;
    int result=LinearSearch(arr,size,key,0);
```

```
if(result!=-1)
    printf("element found at index = %d\n",result);
else
    printf("element not found in the list\n");
return 0;
}
```

Output:A screenshot of a code execution environment showing the output of a program. The output consists of two lines: "element found at index = 3" and "=== Code Execution Successful ===".

```
element found at index = 3

=== Code Execution Successful ===
```

2. **Aim:** To Write a C program to search an element in the given list using non-recursive Linear Search technique.

Program:

```
#include<stdio.h>

int LinearSearch(int arr[],int size,int key)
{
    int i;
    for(i=0;i<size;i++)
    {
        if(arr[i]==key)
        {
            return i;
        }
    }
    return -1;
}

int main()
{
    int arr[]={5,3,8,4,2};
    int size=sizeof(arr)/sizeof(arr[0]);
    int key=2;
    int result=LinearSearch(arr,size,key);
    if(result!=-1)
        printf("element found at index = %d\n",result);
    else
        printf("element not found in the list\n");
    return 0;
}
```

```
}
```

Output:

```
element found at index = 4
```

```
=== Code Execution Successful ===
```

3. **Aim:** Write a C program to search an element in the given sorted list using recursive Binary Search technique.

Program:

```
#include<stdio.h>

int BinarySearch(int arr[],int left,int right,int x)
{
    if(right>=left)
    {
        int mid=(left+right)/2;
        if(arr[mid]==x)
            return mid;
        if (arr[mid]>x)
            return BinarySearch(arr,left,mid-1,x);
        return BinarySearch(arr,mid+1,right,x);
    }
    return -1;
}

int main()
{
    int arr[]={2,3,4,10,40};
    int n=sizeof(arr)/sizeof(arr[0]);
    int x=4;
    int result=BinarySearch(arr,0,n-1,x);
    if(result!=-1)
        printf("element found at index = %d\n",result);
    else
        printf("element not found in the list\n");
}
```

```
return 0;  
}
```

Output:

```
element found at index = 2
```

```
=== Code Execution Successful ===
```

4. **Aim:** Write a C program to search an element in the given sorted list using non-recursive Binary Search technique.


Program:

```
#include<stdio.h>

int BinarySearch(int arr[],int size,int target)
{
    int left=0;
    int right=size-1;
    while(left<=right)
    {
        int mid=(left+right)/2;
        if(arr[mid]==target)
            return mid;
        if (arr[mid]<target)
            left=mid+1;
        else
            right=mid-1;
    }
    return -1;
}

int main()
{
    int arr[]={2,3,4,10,40};
    int size=sizeof(arr)/sizeof(arr[0]);
    int target=4;
    int result=BinarySearch(arr,size,target);
    if(result!=-1)
```

```
        printf("element found at index = %d\n",result);  
    else  
        printf("element not found in the list\n");  
    return 0;  
}
```

Output:

```
element found at index = 3
```

```
=== Code Execution Successful ===
```


Inferences:

- Linear search is a method of checking each element of the array sequentially until the element is found or the list ends.
- Recursive linear search is simple to implement and works on unsorted array.
- Non-recursive linear search use a simple loop to scan through the array.
- In this non-recursive linear search No recursion overhead but still **$O(n)$** time complexity.
- Binary search is a method Works only on **sorted arrays**. Repeatedly divide the array into halves and check the middle element.
- Recursive binary search has time complexity **$O(\log n)$** that is much faster than linear search and has clear recursive structure.
- Non recursive binary search is implemented using a **while loop** (iterative approach).
- No recursion overhead (stack saving) and still **$O(\log n)$** and efficient.