

WEEK-7

Date:06-08-2025

List of programs:

1. Write a C program to insert a node at the beginning in a Double linked list.
2. Write a C program to insert a node at the end in a Double linked list.
3. Write a C program to insert a node after a given node(middle case) in a Double linked list.
4. Write a C program to delete a node at the beginning in a Double linked list.
5. Write a C program to delete a node at the end in a Double linked list
6. Write a C program to delete a node after a given node(middle case) in a Double linked list.

1. Aim: To write a C program to insert a node at the beginning in a Double linked list.

Program:

```
#include<stdio.h>

#include<stdlib.h>

struct node
{
    int data;
    struct node *next;
    struct node *prev;
};

struct node *head,*temp,*new,*last=NULL;

struct node *getnode(int x)
{
    struct node *temp=(struct node*)malloc(sizeof(struct node));


    temp->data=x;

    temp->next=NULL;
```

```
temp->prev=NULL;
return temp;
}
void insert_begin(int x)
{
new=getnode(x);
if(head==NULL)
    head=last=new;
else
{
new->next=head;
head->prev=new;
head=new;
}
}
void display()
{
if(head==NULL)
{
printf("list empty\n");
}
else
{
temp=head;
while(temp!=NULL)
{
printf("%d->",temp->data);
temp=temp->next;
```

```
}  
  
}  
  
printf("null\n");  
  
}  
  
int main()  
{  
    int n,i,x;  
  
    printf("enter the number of node:");  
  
    scanf("%d",&n);  
  
    for(i=0;i<n;i++)  
    {  
  
        printf("enter the data in %d node:",i+1);  
  
        scanf("%d",&x);  
  
        new=getnode(x);  
  
        if(head==NULL)  
        {  
  
            head=new;  
  
        }  
  
        else  
        {  
  
            temp=head;  
  
            while(temp->next!=NULL)  
            {  
  
                temp=temp->next;  
  
            }  
  
            temp->next=new;  
  
            new->prev=temp;  
  
            last=new;  
        }  
    }  
}
```

```
}  
  
}  
  
printf("enter the data to insert at beginning");  
scanf("%d",&x);  
  
printf("the list after inserting at beginning\n");  
insert_begin(x);  
  
display();  
  
return 0;  
  
}
```

Output:

```
enter the number of node:4  
enter the data in 1 node:13  
enter the data in 2 node:26  
enter the data in 3 node:39  
enter the data in 4 node:42  
enter the data to insert at beginning3  
the list after inserting at beginning  
3->13->26->39->42->null
```

```
=== Code Execution Successful ===
```

2. **Aim:** Write a C program to insert a node at the end in a Double linked list.

Program:

```
#include<stdio.h>

#include<stdlib.h>

struct node
{
    int data;
    struct node *next;
    struct node *prev;
};

struct node *head,*temp,*new,*last;

struct node *getnode(int x)
{
    struct node *temp=(struct node*)malloc(sizeof(struct node));
    temp->data=x;
    temp->next=NULL;
    temp->prev=NULL;
    return temp;
}

void insert_end(int x)
{
    new=getnode(x);
    if(head==NULL)
        head=last=new;
    else
```


```
{  
temp=head;  
while(temp->next!=NULL)  
{  
temp=temp->next;  
}  
last=temp;  
last->next=new;  
new->prev=last;  
last=new;  
}  
}  
  
void display()  
{  
if(head==NULL)  
{  
printf("list empty\n");  
}  
else  
{  
temp=head;  
while(temp!=NULL)  
{  
printf("%d->",temp->data);  
temp=temp->next;  
}  
}  
printf("null\n");
```

```
}

int main()
{
    int n,i,x;

    printf("enter the number of node:");
    scanf("%d",&n);
    for(i=0;i<n;i++)
    {
        printf("enter the data in %d node:",i+1);
        scanf("%d",&x);
        new=getnode(x);
        if(head==NULL)
        {
            head=last=new;
        }
        else
        {
            temp=head;
            while(temp->next!=NULL)
            {
                temp=temp->next;
            }
            temp->next=new;
            new->prev=temp;
            last=new;
            last->next=NULL;
        }
    }
}
```

```
printf("enter the data to insert at end:");  
scanf("%d",&x);  
printf("the list after inserting at end:\n");  
insert_end(x);  
display();  
return 0;  
}
```

Output:

```
enter the number of node:5  
enter the data in 1 node:14  
enter the data in 2 node:28  
enter the data in 3 node:42  
enter the data in 4 node:56  
enter the data in 5 node:70  
enter the data to insert at end:84  
the list after inserting at end:  
14->28->42->56->70->84->null  
  
=== Code Execution Successful ===
```


3. **Aim:** Write a C program to insert a node after a given node(middle case) in a Double linked list.

Program:

```
#include<stdio.h>
#include<stdlib.h>

struct node
{
    int data;
    struct node *next;
    struct node *prev;
};

struct node *head,*temp,*new,*last=NULL;

struct node *getnode(int x)
{
    struct node *temp=(struct node*)malloc(sizeof(struct node));
    temp->data=x;
    temp->next=NULL;
    temp->prev=NULL;
    return temp;
}

void insert_middle(int x,int val)
{
    new=getnode(x);
    if(head==NULL)
        head=last=new;
```

```
else if(last->data==val)
{
    last->next=new;
    new->prev=last;
    last=new;
}
else
{
    temp=head;
    while(temp->data!=val&&temp!=NULL)
    {
        temp=temp->next;
    }
    new->next=temp->next;
    (temp->next)->prev=new;
    temp->next=new;
    new->prev=temp;
}
}

void display()
{
    if(head==NULL)
    {
        printf("list empty\n");
    }
    else
    {
        temp=head;
```

```
while(temp!=NULL)
{
    printf("%d->",temp->data);
    temp=temp->next;
}
}
printf("null\n");
}

int main()
{
    int n,i,x,val;
    printf("enter the number of node:");
    scanf("%d",&n);
    for(i=0;i<n;i++)
    {
        printf("enter the data in %d node:",i+1);
        scanf("%d",&x);
        new=getnode(x);
        if(head==NULL)
        {
            head=last=new;
        }
        else
        {
            temp=head;
            while(temp->next!=NULL)
            {
                temp=temp->next;
```

```
}  
  
temp->next=new;  
new->prev=temp;  
last=new;  
last->next=NULL;  
  
}  
  
printf("enter the value of node after which you want to insert:\n");  
scanf("%d",&val);  
  
printf("enter the data to insert at end:");  
scanf("%d",&x);  
  
printf("the list after inserting at end:\n");  
insert_middle(x,val);  
  
display();  
  
return 0;  
  
}
```

Output:

```
enter the number of node:5  
enter the data in 1 node:15  
enter the data in 2 node:30  
enter the data in 3 node:45  
enter the data in 4 node:60  
enter the data in 5 node:75  
enter the value of node after which you want to insert:  
45  
enter the data to insert at end:55  
the list after inserting at end:  
15->30->45->55->60->75->null  
  
=== Code Execution Successful ===
```

4. Aim: To write a C program to delete a node at the beginning in a Double linked list.

Program:

```
#include<stdio.h>
#include<stdlib.h>

struct node
{
    int data;
    struct node *next;
    struct node *prev;
};

struct node *head,*temp,*new,*last;

struct node *getnode(int x)
{
    struct node *temp=(struct node*)malloc(sizeof(struct node));
    temp->data=x;
    temp->next=NULL;
    temp->prev=NULL;
    return temp;
}

void delete_begin()
{
    if(head==NULL)
    {
        printf("list is empty");
    }
}
```

```
}  
  
else if(head->next==NULL)  
{  
    temp=head;  
    head=last=NULL;  
    free(temp);  
}  
  
else  
{  
    temp=head;  
    head=head->next;  
    head->prev=NULL;  
    free(temp);  
}  
  
}  
  
void display()  
{  
    if(head==NULL)  
    {  
        printf("list empty\n");  
    }  
  
    else  
    {  
        temp=head;  
        while(temp!=NULL)  
        {  
            printf("%d->",temp->data);  
            temp=temp->next;
```

```
}  
  
}  
  
printf("null\n");  
  
}  
  
int main()  
{  
    int n,i,x;  
  
    printf("enter the number of node:");  
  
    scanf("%d",&n);  
  
    for(i=0;i<n;i++)  
    {  
  
        printf("enter the data in %d node:",i+1);  
  
        scanf("%d",&x);  
  
        new=getnode(x);  
  
        if(head==NULL)  
        {  
  
            head=last=new;  
  
        }  
  
        else  
        {  
  
            temp=head;  
  
            while(temp->next!=NULL)  
            {  
  
                temp=temp->next;  
  
            }  
  
            temp->next=new;  
  
            new->prev=temp;  
  
            last=new;  
        }  
    }  
}
```

```
last->next=NULL;

}

}


printf("the list after deleting at begin:\n");

delete_begin();

display();

return 0;

}
```

Output:

```
enter the number of node:5
enter the data in 1 node:16
enter the data in 2 node:32
enter the data in 3 node:48
enter the data in 4 node:64
enter the data in 5 node:80
the list after deleting at begin:
32->48->64->80->null

=== Code Execution Successful ===
```


5. **Aim:** Write a C program to delete a node at the end in a Double linked list.

Program:

```
#include<stdio.h>

#include<stdlib.h>

struct node
{
    int data;

    struct node *next;

    struct node *prev;
};

struct node *head,*temp,*new,*last=NULL;

struct node *getnode(int x)
{
    struct node *temp=(struct node*)malloc(sizeof(struct node));

    temp->data=x;

    temp->next=NULL;

    temp->prev=NULL;
}


void delete_end()
{
    if(head==NULL)
    {
        printf("list is empty");
    }

    else if(head->next==NULL)
```

```
{  
    temp=head;  
    head=last=NULL;  
    free(temp);  
}  
  
else  
  
{  
    temp=head;  
    while(temp->next!=NULL)  
    {  
        temp=temp->next;  
    }  
    temp=last;  
    last=last->prev;  
    last->next=NULL;  
    free(temp);  
}  
  
void display()  
{  
    if(head==NULL)  
    {  
        printf("list empty\n");  
    }  
    else  
    {  
        temp=head;  
        while(temp!=NULL)
```

```
{  
    printf("%d->",temp->data);  
    temp=temp->next;  
}  
  
}  
  
printf("null\n");  
}  
  
int main()  
{  
    int n,i,x;  
  
    printf("enter the number of node:");  
    scanf("%d",&n);  
    for(i=0;i<n;i++)  
    {  
        printf("enter the data in %d node:",i+1);  
        scanf("%d",&x);  
        new=getnode(x);  
        if(head==NULL)  
        {  
            head=last=new;  
        }  
        else  
        {  
            temp=head;  
            while(temp->next!=NULL)  
            {  
                temp=temp->next;  
            }  
        }  
    }  
}
```

```
temp->next=new;
new->prev=temp;
last->next=NULL;
}
}
printf("the list after deleting at end:\n");
delete_end();
display();
return 0;
}
```

Output:

```
enter no.of nodes:5
enter data value in 1 node:10
enter data value in 2 node:20
enter data value in 3 node:30
enter data value in 4 node:40
enter data value in 5 node:50
The list after creation:
10->20->30->40->50->head
The list after deletion at end:
10->20->30->40->head

=== Code Execution Successful ===
```

6. Aim: Write a C program to delete a node after a given node(middle case) in a Double linked list.

Program:

```
#include<stdio.h>
#include<stdlib.h>

struct node
{
    int data;
    struct node *next;
    struct node *prev;
};

struct node *head,*temp,*new,*last=NULL;

struct node *getnode(int x)
{
    struct node *temp=(struct node*)malloc(sizeof(struct node));
    temp->data=x;
    temp->next=NULL;
    temp->prev=NULL;
}

void delete_middle(int val)
{
    if(head==NULL)
    {
        printf("list is empty");
    }
}
```

```
else if(head->next==NULL)
{
    temp=head;
    head=last=NULL;
    free(temp);
}
else
{
    temp=head;
    while(temp!=NULL&&temp->data!=val)
    {
        temp=temp->next;
    }
    if(temp==NULL)
    {
        printf("node with value %d not found \n",val);
    }
    (temp->prev)->next=temp->next;
    (temp->next)->prev=temp->prev;
    free(temp);
}
}


void display()
{
    if(head==NULL)
    {
        printf("list empty\n");
    }
}
```

```
else
{
temp=head;
while(temp!=NULL)
{
printf("%d->",temp->data);
temp=temp->next;
}
}
printf("null\n");
}
int main()
{
int n,i,x,val;
printf("enter the number of node:");
scanf("%d",&n);
for(i=0;i<n;i++)
{
printf("enter the data in %d node:",i+1);
scanf("%d",&x);
new=getnode(x);
if(head==NULL)
{
head=last=new;
}
else
{
temp=head;
```

```
while(temp->next!=NULL)
{
temp=temp->next;
}
temp->next=new;
new->prev=temp;
last=new;
last->next=NULL;
}
}

printf("enter the value to delete at middle:\n");
scanf("%d",&val);

printf("the list after deleting at middle:\n");
delete_middle(val);
display();
return 0;
}
```

Output:A screenshot of a terminal window with a dark background and light-colored text. It shows the output of a C program. The user enters 5 for the number of nodes, then enters data values 17, 34, 51, 68, and 85 for nodes 1 through 5 respectively. Then, the user enters 51 as the value to delete from the middle. The program outputs the resulting linked list: 17->34->68->85->null. At the bottom, it says '=== Code Execution Successful ==='.

```
enter the number of node:5
enter the data in 1 node:17
enter the data in 2 node:34
enter the data in 3 node:51
enter the data in 4 node:68
enter the data in 5 node:85
enter the value to delete at middle:
51
the list after deleting at middle:
17->34->68->85->null

=== Code Execution Successful ===
```


Inferences:

- Each node contains **three fields** → `data`, `prev` pointer, and `next` pointer.
- Traversal is possible in **both directions** (forward and backward).
- **Insertion and deletion** are easier compared to singly list (can be done from both ends efficiently).
- **More memory required** per node (extra `prev` pointer).
- Searching is still **$O(n)$** in worst case.
- **Head node's `prev` = NULL** and **last node's `next` = NULL**.
- Losing head pointer still causes list inaccessibility, but tail pointer helps in reverse traversals.
- Better suited for applications where **bidirectional traversal** is required (like undo/redo in editors, navigation systems).
- Compared to singly linked list, it provides **more flexibility**, but at the cost of **extra memory** and **slightly more complex operations**.