PROGRAM 10

Aim: Write a program to implement OR logic functions.

Code:

```python
import numpy as np
x=np.array([[1,1],[1,0],[0,1],[0,0]])
t=np.array([[1],[1],[1],[0]])
w=np.array([[0],[0]])
theta=1
yin=np.zeros(shape=(4,1))
y=np.zeros(shape=(4,1))
yin=np.dot(x,w)
i=0
found=0
while(found==0):
        i=0
        yin=np.dot(x,w)
        #print(yin)
        while(i<4):
        if yin[i]>=theta:
                y[i]=1
                i=i+1
         else:
                y[i]=0
                i=i+1
   #print("y",y)
   #print("t",t)
        if (y==t).all():
        print("MODEL IS TRAINED ")
        print("\nOutput : \n",y)
        print("\nweights : ",w,"\n")
        print("theta : ",theta)
        found=1
         else:
         print("MODEL IS NOT TRAINED")
        w=np.zeros(shape=(0,0))
        theta=int(input("Enter New Theta : "))
        for k in range(int(2)):
                w1=int(input("Enter Weight : "))
                w=np.append(w,w1)
```

PROGRAM 10

OUTPUT:

```python
import numpy as np
x=np.array([[1,1],[1,0],[0,1],[0,0]])
t=np.array([[1],[1],[1],[0]])
w=np.array([[0],[0]])
theta=1
yin=np.zeros(shape=(4,1))
y=np.zeros(shape=(4,1))
yin=np.dot(x,w)
i=0
found=0
while(found==0):
    i=0
    yin=np.dot(x,w)
    print(yin)
    while(i<4):
        if yin[i]>=theta:
            y[i]=1
            i=i+1

            #if(i==4):
                #break
        else:
            y[i]=0
            i=i+1
    print("y",y)
    print("t",t)
    if (y==t).all():
        print("MODEL IS TRAINED ")
        print("\nOutput : \n",y)
        print("\nweights : ",w,"\n")
        print("theta : ",theta)
        found=1
    else:
        print("MODEL IS NOT TRAINED")
        w=np.zeros(shape=(0,0))
        theta=int(input("Enter New Theta : "))
        for k in range(int(2)):
            w1=int(input("Enter Weight : "))
            w=np.append(w,w1)
```

```
Enter New Theta : 1

Enter Weight : 1

Enter Weight : 1
[2. 1. 1. 0.]
y [[1.]
 [1.]
 [1.]
 [0.]]
t [[1]
 [1]
 [1]
 [0]]
MODEL IS TRAINED
```