

Strings I

String property

The [.length](#) property is used to return the length of the string.

```
"Nice!".length;  
//5
```

```
.toLowerCase()
```

```
"BLUE".toLowerCase(); // "blue";
```

```
.toUpperCase()
```

```
"red".toUpperCase(); // "RED";
```

parentheses () on function calls are required. `.length` is a property that is already pre-computed; therefore, it does not need parentheses.

You can access a specific character in a string by using the square brackets syntax []

You have to provide the **index** of the character that you'd like to access, starting from 0

```
console.log(language[1]); // "a"
```

Combining it with length

```
const language = "JavaScript";
```

```
language[ language.length - 2 ]; // "p" because it's the second to last character from "JavaScript"
```

The .at(index) method

The `.at()` method allows you to read a character at an index (which can also be negative).

```
const language = "JavaScript";  
language.at(0); // "J"  
language.at(1); // "a"  
language.at(-1); // "t"  
language.at(-2); // "p"
```

Substring signature

```
someString.substring(indexStart, indexEnd)
```

- `indexStart`: the position of the first character you'd like to **include**
- `indexEnd`: the position of the first character you'd like to **ignore**

```
const language = "JavaScript";  
language.substring(1, 4); //"ava"
```

```
"Hello" + "World" //"HelloWorld"
```

`+=` operator

```
let name = "Sam";  
name += " Blue";  
console.log(name); // "Sam Blue"
```

Your first template string

The only difference is that template strings start and end with a backtick ``` character

Multiline strings

```
let text = `This is a multiline  
string that  
just works!`
```

Interpolation

Template strings support interpolation! This means you could write a variable in your string, and get its value. The syntax is straightforward, you wrap your variable name with a dollar sign and curly braces. Let's take an example where we have a variable `language` with a value of `JavaScript`

```
let language = "JavaScript";  
`I am learning ${language}`; //"I am learning JavaScript";
```

Show previous notes