Script-Controlled ACL

Restrict Record Access Based on Field Value

Phase 6 - Documentation

Purpose: Prepare technical and user documentation for the completed project. This phase documents how a Script-Controlled Access Control List (ACL) restricts record access according to a selected field value.

Section Details

Project Documentation	Document the objective, requirements, design, implementation, testing, and results. The project uses a script-controlled ACL to evaluate a record field value and determine whether the current user is allowed to access the record.
Configuration Documentation	Record the important ACL components, including the table and field being protected, ACL type and operation, role or user criteria, condition, script logic, and expected allow/deny behavior. Document how the field value is evaluated by the ACL script.
User Guide	Explain how a user accesses the protected records and how access is determined by the configured field value. Describe the expected result when the field value satisfies the access rule and when it does not.
Evidence	Include relevant screenshots of the ACL configuration, script/condition, protected records, successful access, denied access, and testing results. Evidence should show that record access changes according to the configured field value.

Project Documentation

Objective: Implement a Script-Controlled ACL that restricts access to records based on the value stored in a specified record field.

Requirements: Identify the protected table and field, define the access rule, configure the appropriate ACL, implement the script condition, and verify both permitted and restricted access scenarios.

Design: When a user attempts to access a protected record, the ACL evaluates the configured field value and applies the access rule. The result determines whether the record can be accessed.

Implementation: Configure the ACL and its script so that access is granted only when the record's field value satisfies the defined rule. Otherwise, access is restricted.

Testing: Test records with field values that should permit access and records with field values that should restrict access. Confirm that the ACL produces the expected result for each case.

Results: The completed configuration demonstrates field-based record access control through a scripted ACL, with the final behavior verified using appropriate test records.

Configuration Documentation

• Protected table and record type

• Field used as the access-control value

• ACL operation (for example, read or write)

• Applicable roles, users, or conditions

• Script-controlled access logic

• Expected allow/deny behavior for each relevant field value

• Test records used to validate the configuration

User Guide

Open the application or module containing the protected records.

Select or open a record that is controlled by the ACL.

The system evaluates the configured field value against the ACL rule.

If the field value satisfies the access condition, the user can access the record.

If the field value does not satisfy the condition, access is restricted according to the ACL.

Evidence

• Screenshot of the ACL record and its configuration

• Screenshot of the script or scripted condition used by the ACL

• Screenshot of a record with a field value that permits access

• Screenshot showing restricted/denied access for a non-matching field value

• Screenshots or notes from testing different field values

• Final evidence demonstrating the completed access-control behavior

Project Note: This phase document is prepared for organizing the TN Skills project evidence and can be supplemented with your actual screenshots, ACL configuration details, field names, scripts, and testing results.