

Document title
query-multi
Date
2022-10-25
Author
Tamás Bordi
Contact
tbordi@aitia.ai

Document type SD
Version 4.4.0
Status
RELEASE
Page 1 (10)

query-multi

Service Description

Abstract

This document provides service description for the query-multi service.





Version **4.4.0** Status **RELEASE** Page **2 (10)**

Contents

ARROWHEAD

1	Ove	rview	3
	1.1	How This Service Is Meant to Be Used	4
	1.2	Important Delimitations	4
	1.3	Access policy	4
2	Serv	vice Interface	5
	2.1	interface HTTP/TLS/JSON	5
3	Info	rmation Model	6
	3.1	struct ServiceQueryFormList	6
	3.2	struct ServiceQueryResultList	7
	3.3	Primitives	8
4	Refe	erences	9
5	Rev	ision History	10
	5.1	Amendments	10
	5.2	Quality Assurance	10



Document title query-multi Date 2022-10-25

Version 4.4.0 Status RELEASE Page 3 (10)

1 Overview

This document describes the **query-multi** service, which enables autonomous service look up for multiple services by one request, therefore it is an integral part of the implementation of service discovery requirements in Service Registry Mandatory Core System. Examples of this interaction is a core system that needs the available information for services that fulfill certain requirements. The look up process itself is exactly the same as in case of the *query* service.

The rest of this document is organized as follows. In Section 2, we describe the abstract message functions provided by the service. In Section 3, we end the document by presenting the data types used by the mentioned functions.



Document title query-multi Date 2022-10-25

Version
4.4.0
Status
RELEASE
Page
4 (10)

1.1 How This Service Is Meant to Be Used

The given core system is required to submit a list of service query forms, in which the requirements for each systems are defined.

1.2 Important Delimitations

The query data must meet the following criteria:

- Service definition can contain maximum 63 character of letters (english alphabet), numbers and dash (-), and has to start with a letter (also cannot ends with dash).
- Interface names have to follow the Protocol-SecurityType-MimeType format.
- Security types could be only NOT_SECURE, CERTIFICATE or TOKEN .

1.3 Access policy

Available only for the following core systems: Authorizationt, Orchestrator, Certificate Authority, Choreographer, Device Registry, Event Handler, HawkBit Configuration Manager, MSCV, Plant Description Engine, QoS-Monitor, System Registry



Version 4.4.0 Status RELEASE Page 5 (10)

2 Service Interface

This section describes the interfaces to the service. The **query-multi** service is used to looking for multiple services. A service could contain various metadata as well as a physical endpoint. The various parameters are representing the necessary system and service input information. In particular, each subsection names an interface, an input type and an output type, in that order. The input type is named inside parentheses, while the output type is preceded by a colon. Input and output types are only denoted when accepted or returned, respectively, by the interface in question. All abstract data types named in this section are defined in Section 3.

The following interfaces are available.

2.1 interface HTTP/TLS/JSON (ServiceQueryForm) : ServiceQueryResult

Profile ype	Туре	Version
Transfer protocol	HTTP	1.1
Data encryption	TLS	1.3
Encoding	JSON	RFC 8259 [1]
Compression	N/A	-

Table 1: HTTP/TLS/JSON communication details.



Version 4.4.0 Status RELEASE Page 6 (10)

3 Information Model

Here, all data objects that can be part of the **query-multi** service provides to the hosting System are listed in alphabetic order. Note that each subsection, which describes one type of object, begins with the *struct* keyword, which is used to denote a collection of named fields, each with its own data type. As a complement to the explicitly defined types in this section, there is also a list of implicit primitive types in Section 3.3, which are used to represent things like hashes and identifiers.

3.1 struct ServiceQueryFormList

Field	Туре	Mandatory	Description
forms	Array <object></object>	yes	List of service requirements form.

3.1.1 struct forms

Field	Туре	Mandatory	Description
interfaceRequirements	Array <interface></interface>	no	Names of the required interfaces. If specified at least one of the interfaces must match for having result(s).
maxVersionRequirement	Number	no	Required maximum version of the service. If specified version must be equals or lower or having result(s). Ignored if versionRequirement is specified.
metadataRequirements	Metadata	no	Service metadata requirements. If specified the whole content of the map must match for having result(s)
minVersionRequirement	Number	no	Required minimum version of the service. If specified version must be equals or higher or having result(s). Ignored if versionRequirement is specified.
pingProviders	Boolean	no	Whether or not the provider should be pinged. If <i>true</i> only the responding providers will comply.
securityRequirements	Array <securetype></securetype>	no	Types of the required security levels. If specified at least one of the types must match for having result(s).
serviceDefinitionRequirement	Name	yes	Identifier of the service.
versionRequirement	Number	no	Required version of the service. If specified version must match for having result(s)

3.1.2 struct Metadata

A JSON Object which maps String key-value pairs



Version 4.4.0 Status RELEASE Page 7 (10)

3.2 struct ServiceQueryResultList

Field	Туре	Description
results	Array <object></object>	List of service query results

3.2.3 struct results

Field Type		Description	
serviceQueryData Array <serviceregistryresponse></serviceregistryresponse>		List of service instance results	
		Number of service instances not included by serviceQueryData due to the specified filters.	

3.2.4 struct ServiceRegistryResponse

Field	Туре	Description	
createdAt	DateTime	Service instance record was created at this UTC timestamp.	
endOfValidity	DateTime	Service is available until this UTC timestamp.	
id	Number	Identifier of the service instance	
interfaces	Array <object></object>	List of interfaces the service supports.	
provider	Object	Descriptor of the provider system record.	
secure	SecureType	Type of security the service uses.	
serviceDefinitionResponse	Object	Descriptor of the serviceDefinition record.	
serviceUri	URI	URI of the service.	
metadata	Metadata	Service metadata	
updatedAt	DateTime	Service instance record was modified at this UTC timestamp.	
version	Version	Version of the service.	

3.2.5 struct interfaces

Field	Туре	Description
createdAt DateTime		Interface instance record was created at this UTC timestamp.
id	Number	Identifier of the interface instance
interfaceName	Interface	Specified name of the interface.
updatedAt	DateTime	Interface instance record was modified at this UTC timestamp.



Version 4.4.0 Status RELEASE Page 8 (10)

3.2.6 struct provider

Field	Туре	Description	
address String		Network address.	
authenticationInfo	String	Public key of the client certificate.	
createdAt DateTime		System instance record was created at this UTC timestamp.	
id	Number	Identifier of the system instance	
metadata Metadata		Metadata	
port	PortNumber	Port of the system.	
systemName	Name	Name of the system.	
updatedAt	DateTime	System instance record was modified at this UTC timestamp.	

3.2.7 struct serviceDefinition

Field	Туре	Description
createdAt DateTime		Service definition instance record was created at this UTC timestamp.
id	Number	Identifier of the service definition instance
serviceDefinition	Name	Name of the service definition.
updatedAt	DateTime	Service definition instance record was modified at this UTC timestamp.

3.3 Primitives

Types and structures mentioned throughout this document that are assumed to be available to implementations of this service. The concrete interpretations of each of these types and structures must be provided by any IDD document claiming to implement this service.



Document title query-multi 2022-10-25

Version **4.4.0** Status **RELEASE** Page **9 (10)**

Туре	Description		
Address	A string representation of the address		
Boolean	One out of true or false.		
DateTime	Pinpoints a specific moment in time.		
Object	Set of primitives and possible further objects.		
Interface	Any suitable type chosen by the implementor of service		
List <a>	An array of a known number of items, each having type A.		
Name	A string identifier that is intended to be both human and machine-readable.		
Number	Decimal number		
SecureType	Any suitable type chosen by the implementor of service		
Version Specifies a service version.			

4 References

ARROWHEAD

[1] T. Bray, "The JavaScript Object Notation (JSON) Data Interchange Format," RFC 8259, Dec. 2017. [Online]. Available: https://rfc-editor.org/rfc/rfc8259.txt



Version 4.4.0 Status RELEASE Page 10 (10)

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	YYYY-MM-DD	4.4.0		Xxx Yyy

5.2 Quality Assurance

No.	Date	Version	Approved by
1	YYYY-MM-DD	4.4.0	