

query

Service Description

Abstract

This document provides service description for the **query** service.

Contents

1 Overview	3
1.1 How This Service Is Meant to Be Used	4
1.2 Important Delimitations	4
1.3 Access policy	4
2 Service Interface	5
2.1 interface HTTP/TLS/JSON	5
3 Information Model	6
3.1 struct ServiceQueryForm	6
3.2 struct ServiceQueryResult	7
3.3 Primitives	8
4 References	9
5 Revision History	10
5.1 Amendments	10
5.2 Quality Assurance	10

1 Overview

This document describes the **query** service, which enables autonomous service look up, therefore it is an integral part of the implementation of service discovery requirements in Service Registry Mandatory Core System. Examples of this interaction is a system that has the capability to consume some kind of public core service. In order the system will be aware, where and how the service could be consumed, it needs query the service details from Service Registry Core System.

The rest of this document is organized as follows. In Section 2, we describe the abstract message functions provided by the service. In Section 3, we end the document by presenting the data types used by the mentioned functions.

1.1 How This Service Is Meant to Be Used

The given system is required to being aware how to consume the **query** service from Service Registry Core System in order to look for the other public core services such as orchestration from the Orchestrator Core System.

1.2 Important Delimitations

The query data must meet the following criteria:

- Service definition can contain maximum 63 character of letters (english alphabet), numbers and dash (-), and has to start with a letter (also cannot ends with dash).
- Interface names have to follow the `Protocol-SecurityType-MimeType` format.
- Security types could be only `NOT_SECURE`, `CERTIFICATE` or `TOKEN` .

1.3 Access policy

Available for anyone within the local cloud, but in case of application systems, the system is allowed to query only for public core services. Other Core Systems are allowed to query only for their own services.

Exception: Translator Supporting Core Sytem is allowed to register other services too.

2 Service Interface

This section describes the interfaces to the service. The **query** service is used for looking for services. A service could contain various metadata as well as a physical endpoint. The various parameters are representing the necessary system and service input information. In particular, each subsection names an interface, an input type and an output type, in that order. The input type is named inside parentheses, while the output type is preceded by a colon. Input and output types are only denoted when accepted or returned, respectively, by the interface in question. All abstract data types named in this section are defined in Section 3.

The following interfaces are available.

2.1 interface **HTTP/TLS/JSON (ServiceQueryForm) : ServiceQueryResult**

Profile type	Type	Version
Transfer protocol	HTTP	1.1
Data encryption	TLS	1.3
Encoding	JSON	RFC 8259 [1]
Compression	N/A	-

Table 1: HTTP/TLS/JSON communication details.

3 Information Model

Here, all data objects that can be part of the **query** service provides to the hosting System are listed in alphabetic order. Note that each subsection, which describes one type of object, begins with the *struct* keyword, which is used to denote a collection of named fields, each with its own data type. As a complement to the explicitly defined types in this section, there is also a list of implicit primitive types in Section 3.3, which are used to represent things like hashes and identifiers.

3.1 struct ServiceQueryForm

Field	Type	Mandatory	Description
interfaceRequirements	Array<Interface>	no	Names of the required interfaces. If specified at least one of the interfaces must match for having result(s).
maxVersionRequirement	Number	no	Required maximum version of the service. If specified version must be equals or lower or having result(s). Ignored if <i>versionRequirement</i> is specified.
metadataRequirements	Metadata	no	Service metadata requirements. If specified the whole content of the map must match for having result(s)
minVersionRequirement	Number	no	Required minimum version of the service. If specified version must be equals or higher or having result(s). Ignored if <i>versionRequirement</i> is specified.
pingProviders	Boolean	no	Whether or not the provider should be pinged. If <i>true</i> only the responding providers will comply.
securityRequirements	Array<SecureType>	no	Types of the required security levels. If specified at least one of the types must match for having result(s).
serviceDefinitionRequirement	Name	yes	Identifier of the service.
versionRequirement	Number	no	Required version of the service. If specified version must match for having result(s)

3.1.1 struct Metadata

A JSON Object which maps String key-value pairs

3.2 struct **ServiceQueryResult**

Field	Type	Description
serviceQueryData	Array<ServiceRegistryResponse>	List of service instance results
unfilteredHits	Number	Number of service instances not included by <i>serviceQueryData</i> due to the specified filters.

3.2.2 struct **ServiceRegistryResponse**

Field	Type	Description
createdAt	DateTime	Service instance record was created at this UTC timestamp.
endOfValidity	DateTime	Service is available until this UTC timestamp.
id	Number	Identifier of the service instance
interfaces	Array<Object>	List of interfaces the service supports.
provider	Object	Descriptor of the provider system record.
secure	SecureType	Type of security the service uses.
serviceDefinitionResponse	Object	Descriptor of the serviceDefinition record.
serviceUri	URI	URI of the service.
metadata	Metadata	Service metadata
updatedAt	DateTime	Service instance record was modified at this UTC timestamp.
version	Version	Version of the service.

3.2.3 struct **interfaces**

Field	Type	Description
createdAt	DateTime	Interface instance record was created at this UTC timestamp.
id	Number	Identifier of the interface instance
interfaceName	Interface	Specified name of the interface.
updatedAt	DateTime	Interface instance record was modified at this UTC timestamp.

3.2.4 struct **provider**

Field	Type	Description
address	String	Network address.
authenticationInfo	String	Public key of the client certificate.
createdAt	DateTime	System instance record was created at this UTC timestamp.
id	Number	Identifier of the system instance
metadata	Metadata	Metadata
port	PortNumber	Port of the system.
systemName	Name	Name of the system.
updatedAt	DateTime	System instance record was modified at this UTC timestamp.

3.2.5 struct **serviceDefinition**

Field	Type	Description
createdAt	DateTime	Service definition instance record was created at this UTC timestamp.
id	Number	Identifier of the service definition instance
serviceDefinition	Name	Name of the service definition.
updatedAt	DateTime	Service definition instance record was modified at this UTC timestamp.

3.3 Primitives

Types and structures mentioned throughout this document that are assumed to be available to implementations of this service. The concrete interpretations of each of these types and structures must be provided by any IDD document claiming to implement this service.

Type	Description
Address	A string representation of the address
Boolean	One out of <code>true</code> or <code>false</code> .
DateTime	Pinpoints a specific moment in time.
Object	Set of primitives and possible further objects.
Interface	Any suitable type chosen by the implementor of service
List<A>	An <i>array</i> of a known number of items, each having type A.
Name	A string identifier that is intended to be both human and machine-readable.
Number	Decimal number
SecureType	Any suitable type chosen by the implementor of service
Version	Specifies a service version.

4 References

- [1] T. Bray, "The JavaScript Object Notation (JSON) Data Interchange Format," RFC 8259, Dec. 2017. [Online]. Available: <https://rfc-editor.org/rfc/rfc8259.txt>



ARROWHEAD

Document title
query
Date
2022-10-21

Version
4.4.0
Status
RELEASE
Page
10 (10)

5 Revision History

5.1 Amendments

No.	Date	Version	Subject of Amendments	Author
1	YYYY-MM-DD	4.4.0		Xxx Yyy

5.2 Quality Assurance

No.	Date	Version	Approved by
1	YYYY-MM-DD	4.4.0	