

Aitor Rodriguez Gallardo

- `<address>`: It's used for representing the contact information of a person or an organization.
- `<article>`: This tag specifies independent, self-contained content.
- `<aside>`: This tag defines some content aside from the content it is placed in.
- `<audio>`: This tag is used to embed sound content in a document, such as music or the other audio streams.
- `<blockquote>`: This tag specifies a section that is quoted from another source.
- `<code>`: This tag is used to define a piece of computer code. The content inside is displayed in the browser's default monospace font.
- ``: This tag defines text that has been deleted from a document. Browsers will usually strike a line through deleted text.
- `<footer>`: defines a footer for a document or section. This tag typically contains:
 - authorship information
 - copyright information
 - contact information
 - sitemap
 - back to top links
 - related documents
- `<header>`: The `<header>` element represents a container for introductory content or a set of navigational links.
- `<h1>` to `<h6>`: These tags are used to define HTML headings. The `h1` tag defines the most important heading, while the `h6` tag defines the least important heading.
- `<main>`: This tag specifies the main content of a document. The content inside the `<main>` element should be unique to the document. It should not contain any content that is repeated across documents such as sidebars, navigation links, copyright information, site logos, and search forms.
- `<menu>`: This tag is used for context menus, toolbars and for listing form controls and commands.
- `<nav>`: This tag defines a set of navigation links.
- `<section>`: This tag defines a section in a document.
- `<table>`: This tag defines an HTML table. An HTML table consists of one `<table>` element and one or more `<tr>`, `<th>`, and `<td>` elements.
- `<tbody>`: This tag is used to group the body content in an HTML table. The `<tbody>` element is used in conjunction with the `<thead>` and `<tfoot>` elements to specify each part of a table (body, header, footer).

Aitor Rodriguez Gallardo

- `<thead>`: This tag is used to group header content in an HTML table. The `<thead>` element is used in conjunction with the `<tbody>` and `<tfoot>` elements to specify each part of a table (header, body, footer).