

The background is a dark blue grid with various glowing icons and data visualizations. At the top, a laptop screen displays a line graph and a bar chart. Below it, a smartphone screen shows a weather forecast for Wednesday, 18th, with a temperature of 21°C and light rain. To the left of the phone is a Wi-Fi icon, and to the right is a camera icon. At the bottom, there are icons for a speech bubble and a cloud. The main title is centered over the phone screen.

Asynchronous Programming and Collections in Dart

A Comprehensive Guide


Introduction

Asynchronous Programming:

- Asynchronous programming is crucial for responsive apps.
- Dart offers powerful async features like Futures and Streams.

Collections in Dart:


- Collections are essential for managing data.
- Dart supports various collections like lists, sets, maps, and queues.



Asynchronous Programming in Dart

Futures

- Represent an asynchronous operation that eventually completes.
- Handle the result of the operation with `.then` or `await`.
- Use `await` to wait for the result to be available.



Streams

- Represent sequence of data elements received asynchronously.
- Listen to the stream of data using methods like `listen`.
- Use `async` for loop to iterate over the stream elements.

Example of Future

1. Asynchronous Function:

- Fetch User Age() is an asynchronous function that will eventually return an integer (user's age).
- It uses the async keyword to handle time-consuming operations without blocking the code's flow.

2. Simulating a Network Request:

- `await Future.delayed(Duration(seconds: 2))` creates a 2-second delay, acting as a placeholder for a network request.
- The `await` keyword pauses the function's execution until the delay (or actual network request) completes.

```
1 Future<int> fetchUserAge() async {  
2   await Future.delayed(Duration(seconds: 2));  
3   return 30;  
4  
5 }  
6 void main() {  
7   fetchUserAge()  
8     .then((age) => print("The user's age is : $age"));  
9  
10 }
```

Console

The user's age is : 30

Example of Stream

1. Creating a Stream:

- `Stream<int> counterStream = Stream<int>.periodic(Duration(seconds: 1), (x) => x);`
- Creates a Stream called counterStream that emits an integer every second.
- `Stream<int>` specifies that the Stream produces integer values.

2. Asynchronously Iterating over the Stream:

- `await for (int value in counterStream) { ... }`
- Uses an await for loop to iterate over the elements of the Stream asynchronously.
- `await for` pauses execution until the next value is available from the Stream.

```
1
2
3
4 Stream<int> counterStream = Stream<int>.periodic(Duration(seconds: 1), (x) => x);
5
6 void main() async {
7   await for (int value in counterStream) {
8     print(value); // Prints 0, 1, 2, 3, ...
9   }
10 }
11
```

Full-screen Snip

Run

Console

0
1
2
3
4
5
6
7

Async and Await

1.async:

- Used to **mark a function** as asynchronous. This means the function might take some time to complete because it may be waiting for an external event, like a network request or user input.
- When an async function is called, it immediately returns a Future object that represents the eventual result of the function.

```
1 Future<String> fetchName() async {  
2   // Simulate waiting for a network request  
3   await Future.delayed(Duration(seconds: 3));  
4   return "John Doe";  
5 }  
6  
7 void main() async {  
8   String name = await fetchName(); // Execution pauses here until fetchName() returns  
9   print("Welcome to the Pet World, $name!"); // Prints after 3 seconds  
10 }  
11
```

Console

```
Welcome to the Pet World, John Doe!
```

2. await:

- Used **within an async function** to **pause the execution** of the function until the awaited value is ready.
- The awaited value can be anything that represents an asynchronous operation, such as another Future or a stream.
- While the awaited value is being retrieved, the rest of the code in the async function **doesn't wait**.

Collections in Dart

- Like any other programming languages dart doesn't support arrays
- Dart collections can be used as data structures like an array.
- A collection is an object that represents a group of objects called elements.
- Iterables are a kind of collection.
- A collection can be empty, or it can contain many elements.
- Depending on the purpose, collections can have different structures and implementations.

Dart collections can be basically classified as:

- List
- Set
- Map
- Queue

Lists

Lists

- Lists are ordered collections of elements that can be accessed by index.
- The List class provides methods for adding, removing, and searching for elements.

List in dart can be classified as:

- Fixed Length List
- Growable List

List in dart can be classified as:

- **Fixed Length List**
- In Fixed Length List the list's length cannot be changed at run-time.
- These list's are defined with a specific length.

```
var li2 = List.filled(5, 0);  
li2[3] = 6;  
li2[0] = 1;  
print(li2);
```

Console

```
[1, 0, 0, 6, 0]
```

• Growable List

- **Growable List**

- In Growable List the list's length can be changed at run time.
- The following example shows how to create a list of 3 elements and another example which creates a zero-length list using the empty List() constructor.
- The add() function in the List class is used to dynamically add elements to the list.

```
1 void main(List<String> args) {  
2   var li = [1, 'kkk', 330];  
3   print(li);  
4  
5   var li1 = [];  
6   li1.add("one");  
7   li1.add("TWO");  
8   print(li1);  
9 }  
10
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL SQL CONSOLE COMMENTS

[Running] dart "e:\jithin\mine2\zeerong\lib\main.dart"
[1, kkk, 330]
[one, TWO]

[Done] exited with code=0 in 2.287 seconds

Set

- Set represents a collection of objects in which each object can occur only once.
- The dart :core library provides the Set class to implement the same.
- Must be useful when the program doesn't want a object to be added twice.

```
1 void main(List<String> args) {  
2     Set<int> specialNumbers = Set();  
3  
4     specialNumbers.add(3);  
5     print(specialNumbers);  
6  
7     specialNumbers.add(6);  
8     print(specialNumbers);  
9 }  
10
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL SQL CONS

```
[Running] dart "e:\jithin\mine2\zeerong\lib\n  
{3}  
{3, 6}  
  
[Done] exited with code=0 in 3.325 seconds
```


Maps

Maps

- Maps are collections of key-value pairs.
- The Map class provides methods for associating keys with values and retrieving values by key.

Maps can be declared in two ways :

- **Using Map Literals**
- **Using a Map constructor**



Maps can be declared in two ways :

Using Map Literal

- Just like we declare list using *var* keyword, we can also use *var* for declaring Maps.
- The main difference between declaration is, for declaring list we use [](square brackets), but to declare maps we have to use {}(curly braces).
- for declaring list use []
- for declaring map use { }

```
Run | Debug
4 void main() {
5     var details = {'Username': 'tom', 'Password': 'pass@123'};
6     print(details);
7 }
8
```

PROBLEMS 2 OUTPUT DEBUG CONSOLE TERMINAL

```
{Username: tom, Password: pass@123}
Exited
```

Using Map Constructor

Using Map Constructor

- For declaring Map we can also use Map() constructor.
- It's just which way you like.
- There nothing wrong if you declare map using standard method.

```
1  import 'package:queue/queue.dart' as queue;
2
   Run | Debug
3  void main() {
4      var myMap = Map();
5      print("***** Before adding data in Map *****");
6      print(myMap);
7
8      // Adding value to Map
9      myMap["id"] = "jay";
10     myMap["password"] = "1234";
11     myMap["country"] = "India";
12     print("***** After adding data in Map *****");
13     print(myMap);
14 }
15
```

PROBLEMS 10 OUTPUT DEBUG CONSOLE TERMINAL

```
***** Before adding data in Map *****
{}
***** After adding data in Map *****
{id: jay, password: 1234, country: India}
Exited
```


Queue

- A Queue is a collection that can be manipulated at both ends.
- Queues are useful when you want to build a first-in, first-out (FIFO) collection.
- The values are removed / read in the order of their insertion.
- The add() function can be used to insert values to the queue.
- This function inserts the value specified to the end of the queue.

```
1 // ignore_for_file: unused_local_variable
2
3 import 'dart:collection';
4
5 Run | Debug | Profile
6 void main(List<String> args) {
7   final queue = Queue<int>(); // ListQueue() by default
8   print(queue.runtimeType); // ListQueue
9
10  // Adding items to queue
11  queue.addAll([1, 2, 3]);
12  queue.addFirst(0);
13  queue.addLast(10);
14  print(queue); // {0, 1, 2, 3, 10}
15
16  // Removing items from queue
17  queue.removeFirst();
18  queue.removeLast();
19  print(queue); // {1, 2, 3}
20 }
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL SQL CONSOLE COMMENTS

```
[Running] dart "e:\jithin\mine2\zeerong\lib\main.dart"
ListQueue<int>
{0, 1, 2, 3, 10}
{1, 2, 3}
```

```
[Done] exited with code=0 in 1.729 seconds
```

Generics in Dart

- Generics allow you to write code that is reusable and type-safe.
- Generic types are represented by type parameters that are declared with angle brackets (<>).
- Generic classes and methods can be used with different types by specifying the type arguments.



Effective Dart: Best Practices and Style Guide

- Write clean, readable, and maintainable code.
- Follow consistent naming conventions.
- Use comments to explain complex code.
- Test your code thoroughly.





```
2
3 import 'dart:collection';
4
5 void main() {
6   Queue queue = new Queue();
7   print("Default implementation ${queue.runtimeType}");
8   queue.addAll([10, 12, 13, 14]);
9   for (var no in queue) {
10    print(no);
11  }
12 }
13
```

PROBLEMS 4 OUTPUT DEBUG CONSOLE TERMINAL

```
Default implementation ListQueue<dynamic>
10
12
13
14
Exited
```

Advanced Data Structures in Dart



Trees

- Trees are hierarchical data structures that consist of nodes connected by edges.
- Dart provides the Tree class for representing and manipulating trees.

Graphs

- Graphs are collections of nodes connected by edges.
- Dart provides the Graph class for representing and manipulating graphs.

Performance Optimization in Dart

- Identify and eliminate performance bottlenecks.
- Use efficient data structures and algorithms.
- Optimize code for the target platform.



Advanced Dart Features and Techniques

- Mixins: Reuse code across classes.
- Extensions: Add functionality to existing classes without modifying their source code.
- Metaprogramming: Manipulate code at runtime for powerful capabilities.




```
1 // Define a mixin
2 mixin LoggingMixin {
3     void logMessage(String message) {
4         print('Log: $message');
5     }
6 }
7
8 // Class using the mixin with if-else statement
9 class MyClass with LoggingMixin {
10     void performAction(bool shouldLog) {
11         if (shouldLog) {
12             logMessage('Action performed');
13         } else {
14             print('Action performed without logging');
15         }
16     }
17 }
18
19 void main() {
20     // Example usage
21     MyClass myObject = MyClass();
22
23     // Case 1: Logging enabled
24     myObject.performAction(true);
25
26     // Case 2: Logging disabled
27     myObject.performAction(false);
28 }
29
```

▶ Run

Console

Log: Action performed
Action performed without logging

Documentation

In this example:

- We have a Logging Mixin, mixin that provides a log Message method.
- The My Class, class uses the mixin with the with keyword.
- The perform Action method in My Class takes a Boolean parameter should Log and uses an if-else statement to conditionally call the log Message method based on the value of should Log.
- In the main function, we create an instance of My Class and demonstrate two cases, one with logging enabled and one with logging disabled.

Concurrency and Multi-Threading in Dart

- Understand the concepts of threads and isolates.
- Use the isolate library for creating and managing isolates.
- Use the Future class for synchronizing concurrent operations.



Conclusion

- Asynchronous programming and collections are essential tools for Dart developers.
- Dart provides a rich set of features for asynchronous programming and collections.
- By following best practices and using advanced techniques, you can write high-quality Dart code.

