```sql
select * from Coffee_sales

-------sales by coffee type-----

select coffee_name,
       sum(money) as total_revenue
from coffee_sales
group by coffee_name
order by total_revenue desc;

---sales by hour_of_day------

select hour_of_day,
       sum(money) as total_revenue
from coffee_sales
GROUP BY hour_of_day
order by 1 desc

---sales by time of day------

select time_of_Day,
       SUM(money) AS total_revenue
from coffee_sales
group by Time_Of_Day
order by 1 desc

----sales by weekday-----
select weekday,
       sum(money) as total_revenue
from Coffee_sales
group by Weekday
order by 1 desc

----sales by month-----

select Month_name,
       sum(money) as total_revenue
from Coffee_sales
group by Month_name
order by 2 desc

-----PAYMENT METHOD BREAKDOWN----

SELECT cash_type,
       count(*) as num_transactions,
       sum(money) as total_revenue
from coffee_sales
Group by cash_type

```

```sql

-----Daily revenue-----
select Date As sales_date,
       sum(money) As total_revenue
from coffee_sales
group by Date
order by sales_date

-----monthly revenue-----
select month_name,
       sum(money) as monthly_revenue
from Coffee_sales
group by Month_name
order by 1 asc

select * from Coffee_sales

-----to get total sales for americano in febraury----
select sum(money) as total_sales
from coffee_sales
where coffee_name = 'Americano' and Month_name = 'feb'
group by money
order by 1 desc


-----to get total sales of coffee sold in february-----

select coffee_name, sum(money) as Total_sales
from coffee_sales
where coffee_name in ('latte', 'cappuccino', 'americano', 'americano with milk', 'cartado') and Month_name = 'feb'
group by coffee_name
order by 2 desc

-----TO GET THE TOP 2 SELLING COFFEE TYPE----

SELECT MAX(coffee_name) AS TOP_SELLING_COFFEE,sum(MONEY) AS Total_sales
from Coffee_sales
where coffee_name NOT IN (select max(coffee_name) from Coffee_sales)
group by coffee_name
order by 2 DESC

----TO GET THE BOTTOM SELLING COFFEE-----

SELECT MIN(Coffee_name) as bottom_selling_coffee, sum(money) as total_sales
from Coffee_sales
where coffee_name  not in (select min(coffee_name) from Coffee_sales)
group by coffee_name
```

```
 97 order by 2 asc
 98
 99 ----to get number of orders per hour_of_day in sep-----
100
101 select coffee_name as coffee, sum(hour_of_day) as number_of_orders
102 from Coffee_sales
103 where coffee_name in ('Americano', 'latte', 'americano with milk','
      cocoa', 'espresso', 'hot chocolate', 'cappucino', 'cortado')
104 and Month_name = 'sep'
105 group by coffee_name
106 order by 1 asc
107
108 select * from Coffee_sales
109
110 -----number of morning order in feb-----
111
112 select coffee_name as coffee, sum(hour_of_day) as number_of_orders
113 from Coffee_sales
114 where coffee_name in ('Americano', 'latte', 'americano with milk',
      'cappucino', 'cocoa', 'hot chocolate', 'espresso', 'cortado')
115 and Month_name = 'feb' and Time_of_Day = 'Morning'
116 group by coffee_name
117 order by 2 desc
118
119 select coffee_name as coffee, sum(hour_of_day) as number_of_orders
120 from Coffee_sales
121 where coffee_name in ('Americano', 'latte', 'americano with milk',
      'cappucino', 'cocoa', 'hot chocolate', 'espresso', 'cortado')
122 and Month_name = 'feb' and Time_of_Day = 'afternoon'
123 group by coffee_name
124 order by 2 desc
125
126 select coffee_name as coffee, sum(hour_of_day) as number_of_orders
127 from Coffee_sales
128 where coffee_name in ('Americano', 'latte', 'americano with milk',
      'cappucino', 'cocoa', 'hot chocolate', 'espresso', 'cortado')
129 and Month_name = 'feb' and Time_of_Day = 'night'
130 group by coffee_name
131 order by 2 desc
132
133 ----total order in feb in ---
134
135 select coffee_name as coffee, sum(hour_of_day) as number_of_orders
136 from Coffee_sales
137 where coffee_name in ('Americano', 'latte', 'americano with milk',
      'cappucino', 'cocoa', 'hot chocolate', 'espresso', 'cortado')
138 and Month_name = 'feb'
139 group by coffee_name
140 order by 1 asc
```

```sql

----number of morning orders in march------

select coffee_name as coffee, sum(hour_of_day) as number_of_orders
from Coffee_sales
where coffee_name in ('Americano', 'latte', 'americano with milk',
  'cappucino', 'cocoa', 'hot chocolate', 'espresso', 'cortado')
and Month_name = 'Mar' and Time_of_Day = 'Morning'
group by coffee_name
order by 1 asc

---number of afternoon orders in march-----

select coffee_name as coffee, sum(hour_of_day) as number_of_orders
from Coffee_sales
where coffee_name in ('Americano', 'latte', 'americano with milk',
  'cappucino', 'cocoa', 'hot chocolate', 'espresso', 'cortado')
and Month_name = 'feb' and Time_of_Day = 'afternoon'
group by coffee_name
order by 1 asc

-----Number of night orders in march-----

select coffee_name as coffee, sum(hour_of_day) as number_of_orders
from Coffee_sales
where coffee_name in ('Americano', 'latte', 'americano with milk',
  'cappucino', 'cocoa', 'hot chocolate', 'espresso', 'cortado')
and Month_name = 'mar' and Time_of_Day = 'night'
group by coffee_name
order by 2 asc

----total order in march-----
select coffee_name as coffee, sum(hour_of_day) as number_of_orders
from Coffee_sales
where coffee_name in ('Americano', 'latte', 'americano with milk',
  'cappucino', 'cocoa', 'hot chocolate', 'espresso', 'cortado')
and Month_name = 'mar'
group by coffee_name
order by 2 asc

select * from Coffee_sales

-----to get the number of morning orders of coffee in may---

select coffee_name as coffee, sum(hour_of_day) as number_of_orders
from Coffee_sales
where coffee_name in ('Americano', 'latte', 'americano with milk',
  'cappucino', 'cocoa', 'hot chocolate', 'espresso', 'cortado')
```

```sql
and Month_name = 'may' and Time_of_Day = 'Morning'
group by coffee_name
order by 2 desc

select coffee_name as coffee, sum(hour_of_day) as number_of_orders
from Coffee_sales
where coffee_name in ('Americano', 'latte', 'americano with milk',
  'cappucino', 'cocoa', 'hot chocolate', 'espresso', 'cortado')
and Month_name = 'may' and Time_of_Day = 'afternoon'
group by coffee_name
order by 2 desc

select coffee_name as coffee, sum(hour_of_day) as number_of_orders
from Coffee_sales
where coffee_name in ('Americano', 'latte', 'americano with milk',
  'cappucino', 'cocoa', 'hot chocolate', 'espresso', 'cortado')
and Month_name = 'may' and Time_of_Day = 'night'
group by coffee_name
order by 2 desc

----total orders in may----
select coffee_name as coffee, sum(hour_of_day) as number_of_orders
from Coffee_sales
where coffee_name in ('Americano', 'latte', 'americano with milk',
  'cappucino', 'cocoa', 'hot chocolate', 'espresso', 'cortado')
and Month_name = 'may'
group by coffee_name
order by 2 desc

----number of coffee orders by time of day in june----

select coffee_name as coffee, sum(hour_of_day) as number_of_orders
from Coffee_sales
where coffee_name in ('Americano', 'latte', 'americano with milk',
  'cappucino', 'cocoa', 'hot chocolate', 'espresso', 'cortado')
and Month_name = 'jun' and Time_of_Day = 'Morning'
group by coffee_name
order by 2 desc

select coffee_name as coffee, sum(hour_of_day) as number_of_orders
from Coffee_sales
where coffee_name in ('Americano', 'latte', 'americano with milk',
  'cappucino', 'cocoa', 'hot chocolate', 'espresso', 'cortado')
and Month_name = 'jun' and Time_of_Day = 'afternoon'
group by coffee_name
order by 2 desc

select coffee_name as coffee, sum(hour_of_day) as number_of_orders
from Coffee_sales
```

```sql
where coffee_name in ('Americano', 'latte', 'americano with milk',
  'cappucino', 'cocoa', 'hot chocolate', 'espresso', 'cortado')
and Month_name = 'jun' and Time_of_Day = 'night'
group by coffee_name
order by 2 desc

select coffee_name as coffee, sum(hour_of_day) as number_of_orders
from Coffee_sales
where coffee_name in ('Americano', 'latte', 'americano with milk',
  'cappucino', 'cocoa', 'hot chocolate', 'espresso', 'cortado')
and Month_name = 'jun'
group by coffee_name
order by 2 desc

-----number of coffee orders by time of day in july-----

select coffee_name as coffee, sum(hour_of_day) as number_of_orders
from Coffee_sales
where coffee_name in ('Americano', 'latte', 'americano with milk',
  'cappucino', 'cocoa', 'hot chocolate', 'espresso', 'cortado')
and Month_name = 'jul' and Time_of_Day = 'Morning'
group by coffee_name
order by 2 desc


select coffee_name as coffee, sum(hour_of_day) as number_of_orders
from Coffee_sales
where coffee_name in ('Americano', 'latte', 'americano with milk',
  'cappucino', 'cocoa', 'hot chocolate', 'espresso', 'cortado')
and Month_name = 'jul' and Time_of_Day = 'afternoon'
group by coffee_name
order by 2 desc

select coffee_name as coffee, sum(hour_of_day) as number_of_orders
from Coffee_sales
where coffee_name in ('Americano', 'latte', 'americano with milk',
  'cappucino', 'cocoa', 'hot chocolate', 'espresso', 'cortado')
and Month_name = 'jul' and Time_of_Day = 'night'
group by coffee_name
order by 2 desc

select coffee_name as coffee, sum(hour_of_day) as number_of_orders
from Coffee_sales
where coffee_name in ('Americano', 'latte', 'americano with milk',
  'cappucino', 'cocoa', 'hot chocolate', 'espresso', 'cortado')
and Month_name = 'jul'
group by coffee_name
order by 2 desc

```

272
273
274